

Package ‘diffloop’

April 12, 2022

Type Package

Title Identifying differential DNA loops from chromatin topology data

Version 1.22.0

Date 2018-04-17

Maintainer Caleb Lareau <caleblareau@g.harvard.edu>

Author Caleb Lareau [aut, cre], Martin Aryee [aut]

Description A suite of tools for subsetting, visualizing, annotating, and statistically analyzing the results of one or more ChIA-PET experiments or other assays that infer chromatin loops.

Imports methods, GenomicRanges, foreach, plyr, dplyr, reshape2, ggplot2, matrixStats, Sushi, edgeR, locfit, statmod, biomaRt, GenomeInfoDb, S4Vectors, IRanges, grDevices, graphics, stats, utils, Biobase, readr, data.table, rtracklayer, pbapply, limma

License MIT + file LICENSE

URL <https://github.com/aryeelab/diffloop>

BugReports <https://github.com/aryeelab/diffloop/issues>

LazyData TRUE

Suggests DESeq2, diffloopdata, ggrepel, knitr, rmarkdown, testthat

VignetteBuilder knitr

RoxygenNote 5.0.1

Collate 'diffloop.R' 'diffloop-class.R' 'data.R' 'core.R'
'pipeline_io.R' 'loopFunctions.R' 'sugar.R' 'union.R'
'annotation.R' 'assoc.R' 'colData.R' 'mangoFunctions.R'
'plotting.R' 'ruan.R'

biocViews Preprocessing, QualityControl, Visualization, DataImport, DataRepresentation, GO

NeedsCompilation no

git_url <https://git.bioconductor.org/packages/diffloop>

git_branch RELEASE_3_14

git_last_commit 684b6b0

git_last_commit_date 2021-10-26

Date/Publication 2022-04-12

R topics documented:

addchr	3
annotateAnchors	4
annotateAnchors.bed	5
annotateAnchors.bigwig	6
annotateLoops	7
annotateLoops.dge	8
bedToGRanges	9
calcLDSizeFactors	10
callCCDs	10
computeBoundaryScores	11
diffloop	12
dim,loops-method	13
featureTest	13
filterLoops	14
filterSpanningLoops	15
geneinfo	16
getHumanGenes	16
getHumanTSS	17
getMouseGenes	18
getMouseTSS	19
head,loops-method	20
human.genes	20
interchromosomal	21
intrachromosomal	22
keepCTCFloops	22
keepEPloops	23
loopAssoc	24
loopDistancePlot	25
loopGenes	26
loopMetrics	27
loopPlot	27
loops-class	29
loops.small	29
loopsMake	30
loopsMake.mango	31
loopsSubset	32
loopWidth	33
mangoCorrection	34
manyLoopPlots	35
mergeAnchors	36
numAnchors	37

numLoops	37
padGRanges	38
pcaPlot	39
plotTopLoops	40
quickAssoc	41
quickAssocVoom	42
removeRegion	43
removeSelfLoops	43
rmchr	44
sampleNames,loops-method	45
slidingWindowTest	46
splitSamples	47
subsetLoops	47
subsetRegion	48
subsetRegionAB	49
summary,loops-method	50
tail,loops-method	51
topLoops	52
union,loops,loops-method	53
updateLDGroups	54
[,loops,numeric,numeric,missing-method	54
Index	56

addchr	<i>Add 'chr' to GRanges seqnames</i>
--------	--------------------------------------

Description

addchr takes a loops object or GRanges object and simply adds 'chr' to seqnames

Usage

```
addchr(dlo)
```

```
## S4 method for signature 'loops'
addchr(dlo)
```

```
## S4 method for signature 'GRanges'
addchr(dlo)
```

Arguments

dlo A loops object or GRanges object

Details

Often times, performing functions on GRanges objects can go awry if the seqnames are systematically different. A common example of this is when some GRanges objects has the format of 'chr1' while the other has '1'. We can add 'chr' to the first object

Value

An identical loops object or GRanges object 'chr' added

Examples

```
library(GenomicRanges)
regA <- GRanges(c('1'), ranges=IRanges(c(36200000), c(36300000)))
addchr(regA)
regA
rmchr(regA)
regA
```

annotateAnchors	<i>Add meta data column to anchors based on GRanges</i>
-----------------	---

Description

annotateAnchors adds a logical variable to meta data columns in the anchors based on a GRanges object of features' genomic coordinates

Usage

```
annotateAnchors(dlo, features, featureName, maxgap)

## S4 method for signature 'loops,GRanges,character,missing'
annotateAnchors(dlo, features,
  featureName, maxgap = 1000)

## S4 method for signature 'loops,GRanges,character,numeric'
annotateAnchors(dlo, features,
  featureName, maxgap)
```

Arguments

dlo	A loops object whose anchors will be annotated
features	A Granges object corresponding to locations of interest
featureName	A string that will be the mcol name in anchors
maxgap	A value of max permissible gap between a feature and anchor

Details

This function adds column of TRUE/FALSE values on the loops object anchors whether a feature is observed nearby in features. The name of this column that will be in the anchors GRanges object is specified by a user defined string featureName. Gap tolerance between a feature and an anchor is specified by maxgap, where the default is 1,000bp.

Value

A loops object with new meta data column in anchors

Examples

```
# Annotate whether anchors are near a gene body; within 1kb
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
gb <-getHumanGenes()
loops.small <- annotateAnchors(loops.small,gb,'nearGeneBody')

# Adding close to gene bodies with no gap tolerance
loops.small <- annotateAnchors(loops.small,gb,'inGeneBody',0)
```

annotateAnchors.bed *Add meta data column to anchors based on bedgraph scores*

Description

annotateAnchors.bed adds a numeric variable to meta data columns in the anchors slot based on a user-specified .bed file where the fourth column is a numeric score.

Usage

```
annotateAnchors.bed(dlo, file, FUN = mean, pad = 0)

## S4 method for signature 'ANY'
annotateAnchors.bed(dlo, file, FUN = mean, pad = 0)
```

Arguments

- dlo A loops object whose anchors will be annotated
- file A string pointing to the bed file of interest
- FUN A function used to combine multiple values observed in a single anchor; default is mean
- pad An integer value of to pad the anchors of the loops object; default is 0

Details

This function adds a meta data column to anchors of the specified loops object. All values from the .bed file that overlap with the each anchor are handled by the FUN (default is to average them) to produce a single value added to the mcols of the anchors.

Value

A loops object with new numeric meta data column in anchors

Examples

```
# Annotate whether anchors are near a gene body; within 1kb
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
gb <-getHumanGenes()
loops.small <- annotateAnchors(loops.small,gb,'nearGeneBody')
```

annotateAnchors.bigwig

Add meta data column to anchors based on .bigwig

Description

annotateAnchors.bigwig adds a numeric variable to meta data columns in the anchors slot based on a user-specified .bigwig file.

Usage

```
annotateAnchors.bigwig(dlo, file, FUN = mean, pad = 0)
```

```
## S4 method for signature 'ANY'
annotateAnchors.bigwig(dlo, file, FUN = mean, pad = 0)
```

Arguments

dlo	A loops object whose anchors will be annotated
file	A file corresponding to the bigwig of interest
FUN	A function used to combine multiple values observed in a single anchor; default is mean
pad	An integer value of to pad the anchors of the loops object; default is 0

Details

This function adds a meta data column to anchors of the specified loops object. All values from the .bigwig file that overlap with the each anchor are handled by the FUN (default is to average them) to produce a single value added to the mcols of the anchors.

Value

A loops object with new numeric meta data column in anchors

Examples

```
# Annotate whether anchors are near a gene body; within 1kb
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
gb <-getHumanGenes()
loops.small <- annotateAnchors(loops.small,gb,'nearGeneBody')
```

annotateLoops *Annotate loops as Enhancer-Promoter or CTCF-CTCF*

Description

annotateLoops adds a column to the rowData slot of a loops object categorizing loops as either e-p (enhancer-promoter), p-p (promoter-promoter), e-e (enhancer-enhancer), ctcf (CTCF-CTCF) or none (no biological annotation).

Usage

```
annotateLoops(lto, ctcf, enhancer, promoter)

## S4 method for signature 'loops,GRanges,GRanges,GRanges'
annotateLoops(lto, ctcf, enhancer,
               promoter)

## S4 method for signature 'loops,missing,GRanges,GRanges'
annotateLoops(lto, ctcf, enhancer,
               promoter)
```

Arguments

- lto A loops object whose loops will be annotated
- ctcf GRanges object corresponding to locations of CTCF peaks
- enhancer GRanges object corresponding to locations of enhancer peaks
- promoter GRanges object corresponding to locations of promoter regions

Details

Function annotates loops where both anchors are near CTCF peaks or where one anchor is near an enhancer and the other near a promoter. Consider using functions addchr, rmchr, bedToGRanges, and padGRanges when setting up the 3 GRanges inputs. Provide a blank GRanges objects to ignore classification for one set.

Value

A loops object with an additional row 'loop.type' in the rowData slot

Examples

```
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
ctcf_j <- system.file('extdata','Jurkat_CTCF_chr1.narrowPeak',package='diffloop')
ctcf <- rmchr(padGRanges(bedToGRanges(ctcf_j), pad = 1000))
h3k27ac_j <- system.file('extdata','Jurkat_H3K27ac_chr1.narrowPeak',package='diffloop')
h3k27ac <- rmchr(padGRanges(bedToGRanges(h3k27ac_j), pad = 1000))
promoter <- padGRanges(getHumanTSS(c('1')), pad = 1000)
# annotated_small <- annotateLoops(loops.small, ctcf, h3k27ac, promoter)
```

annotateLoops.dge *Annotate enhancer-promoter loops with differential gene expression*

Description

annotateLoops.dge adds columns to the rowData slot of a loops object that shows summary statistics corresponding TSS of a gene name based on the genes.tss rowData column. This function should be used following the keepEPloops function.

Usage

```
annotateLoops.dge(lto, deseq_res, multiple = FALSE)

## S4 method for signature 'ANY'
annotateLoops.dge(lto, deseq_res, multiple = FALSE)
```

Arguments

lto	A loops object whose loops will be annotated
deseq_res	A data.frame
multiple	Annotate loops with multiple TSS? Default = FALSE

Details

This function links enhancer-promoter loops and differential gene expression results. The rownames of the deseq_res slots should correspond to the gene names in the genes.tss column of the rowData slot of the loops object. The function returns a loops object if multiple is specified as FALSE which is the case by default. Otherwise, if multiple is TRUE, then this function returns a data frame since each loop may have more than one TSS. One can reproduce this dataframe quickly when multiple = FALSE using the summary() function on the returned loops object.

Value

A loops object if multiple = FALSE or data frame if multiple = TRUE

Examples

```
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
h3k27ac_j <- system.file('extdata','Jurkat_H3K27ac_chr1.narrowPeak',package='diffloop')
h3k27ac <- rmchr(padGRanges.bedToGRanges(h3k27ac_j), pad = 1000)
promoter <- padGRanges(getHumanTSS(c('1')), pad = 1000)
#small.ep <- keepEPloops(loops.small, h3k27ac, promoter)
#ADD SOMETHING HERE.
```

bedToGRanges	<i>Read a file and make a GRanges object</i>
--------------	--

Description

bedToGRanges takes a string corresponding to a file and creates a GRanges object, retaining meta-data

Usage

```
bedToGRanges(file)

## S4 method for signature 'character'
bedToGRanges(file)
```

Arguments

file A string specifying .bed file location

Details

Useful function to read in a .bed file to create a GRanges object where the meta-data is preserved.
Useful for later functions like annotateAnchors

Value

A GRanges object

Examples

```
#Read in CTCF Jurkat peaks in
ctcf_j <- system.file('extdata','Jurkat_CTCF_chr1.narrowPeak',package = 'diffloop')
ctcf <- bedToGRanges(ctcf_j)
```

calcLDSizeFactors *Compute normalizing factors for each sample*

Description

calcLDSizeFactors takes a loops object computes size factors based for each sample

Usage

```
calcLDSizeFactors(dlo)

## S4 method for signature 'loops'
calcLDSizeFactors(dlo)
```

Arguments

dlo A loops object with unnormalized size factors

Details

This function updates the loops object with new sizeFactor values for each sample in the colData slot using a method identical to that employed in DESeq2.

Value

A loops object with new size factors in colData

Examples

```
# Computing normalizing factors from the full ChIA-PET Data
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
loops.small <- calcLDSizeFactors(loops.small)
```

callCCDs *Compute Chromatin Contact Domains (CCDs)*

Description

callCCDs determines regions

Usage

```
callCCDs(lo, petWeights = FALSE, lowCoveragePercentile = 0.05)

## S4 method for signature 'ANY'
callCCDs(lo, petWeights = FALSE,
         lowCoveragePercentile = 0.05)
```

Arguments

lo A loops object
petWeights Boolean to weight loop coverage by number of PETs. Default = FALSE
lowCoveragePercentile
 Percentile of low coverage to be dropped. Default = 0.05

Details

This function returns a GRanges object of regions determined to be Chromatin Contact Domains as defined in the Tang et al. 2015 paper from the Ruan group. Users can choose to weight the loops by the total number PETs (across all samples) or not and what percent. For details of this method, see page 12 of the supplement of PMID:26686651. Make sure there are only loops within a chromosome before calling this.

Value

A GRanges object of called Chromatin Contact domains

Examples

```

rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
#lo <- subsetLoops(loops.small, c(1,2,5,6,7,8,9,27,69))
#ccd <- callCCDs(lo, petWeights = TRUE, lowCoveragePercentile = 0.5)

```

computeBoundaryScores *Compute boundary scores for genomic loci in between anchors*

Description

computeBoundaryScores determines the boundary scores corresponding to the Genomic region either in between pairs of anchors. To achieve this, the number of PETs for a set of samples (default is all = 0) is summed over a window (default 1MB) on the left (A) and the right (B) of gap. Thus sum of the number of PETs in these windows is divided by the number of PETs that span the two loci, plus 1 (C). A larger value corresponds to a stronger boundary.

Usage

```

computeBoundaryScores(dlo, samples = 0, windowSize = 5e+05)

## S4 method for signature 'loops'
computeBoundaryScores(dlo, samples = 0,
  windowSize = 5e+05)

```

Arguments

dlo A loops object
samples = 0 Vector indexing which samples should be used. 0 is all
windowSize = 500000 BP length on left and right of putative boundary to define A/B

Details

Warning: this function is slow; there is a progress bar outputted to give an anticipated runtime.

Value

A GRanges object with genomic loci and boundary scores in the mcols

Examples

```

# Return the width for loops
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
# BS <- computeBoundaryScores(loops.small, samples = 0, windowSize = 500000)

```

diffloop

diffloop: A package for differential DNA loop calling from ChIA-PET data

Description

The diffloop package contains a suite of tools and S4 data objects to efficiently facilitate the analysis of ChIA-PET datasets. Key features include differential loop calling, visualization of looping in regions, quality-control metrics, and principal component analysis across experiments.

diffloop classes

Three classes mostly comprise the methodology in diffloop. First, loops is a basic structure that contains one or more ChIA-PET experiments, loopfit links an edgeR fit to a loops and currently has little functionality except for generating another loops object where per-loop summary statistics are added.

dim,loops-method *See dimensions of loops object*

Description

See dimensions of loops object

Usage

```
## S4 method for signature 'loops'
dim(x)
```

Arguments

x A loops object

Value

A data.frame of dimensions of the loops object, including number of anchors, interactions, samples, and column data attributes

featureTest *Combined association test for all loops in a defined region*

Description

featureTest takes a loops and genomic coordinates of regions and computes combined significance metrics for each region using the Simes procedure

Usage

```
featureTest(x, features)

## S4 method for signature 'loops,GRanges'
featureTest(x, features)
```

Arguments

x A loops object
 features A GRanges object defining regions for a combined test

Details

This function returns a data.frame sorted by FDR of each region. Assumes the region name is specified in the GRanges object with id column. Each feature is a one row in the GRanges object. The combined significance measure per feature is computed via the Simes method for intrachromosomal loops where at least one anchor from the loop overlaps with the region of interest.

Value

A data.frame sorted by FDR

Examples

```
# Human genes chromosome 1 regional association
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
# assoc <- loopAssoc(loops.small, coef = 2)
# Gene based association
# sw_jn <- featureTest(assoc, getHumanGenes(c('1')))
```

 filterLoops

Filter loops

Description

filterLoops filters out loops that aren't wide, aren't prevalent within samples or prevalent between samples

Usage

```
filterLoops(dlo, width = 0, nreplicates = 0, nsamples = 1)

## S4 method for signature 'ANY'
filterLoops(dlo, width = 0, nreplicates = 0, nsamples = 1)
```

Arguments

dlo	A loops object
width	Minimum loop width
nreplicates	Minimum number of counts per loop
nsamples	Minimum number of samples per loop per counts

Details

Function that restricts loops in a loops object. width specifies the minimum width between anchors. Default is zero. nreplicates restricts loops to at least this specified amount of counts is present in at least one sample. Instead of nreplicates being present in only one sample, nsamples specifies how many individual samples that a loop must have nreplicates in to be included after filtering.

Value

A loops object

Examples

```
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
# Restrict loops to > 5kb width
filtered.jp1 <- filterLoops(loops.small, 5000, 0, 0)
# Restrict loops to > 5kb width and have >= 3 replicates in >= 1 sample
filtered.jp2 <- filterLoops(loops.small, 5000, 3, 1)
# Restrict loops to > 10kb width and have >= 3 replicates in >= 2 samples
filtered.jp3 <- filterLoops(loops.small, 10000, 3, 2)
```

filterSpanningLoops *Retain loops spanning some genomic feature*

Description

filterSpanningLoops returns a loops object where the ends of the anchors completely span one or more genomic feature (e.g. boundary)

Usage

```
filterSpanningLoops(dlo, gf)

## S4 method for signature 'loops,GRanges'
filterSpanningLoops(dlo, gf)
```

Arguments

dlo	A loops object
gf	A GRanges object of features

Details

Rather than a simple overlap, the function by default requires a genomic locus to be completely contiguous

Value

An loops object

Examples

```
# Return the width for loops
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
w <- loopWidth(loops.small)
```

geneinfo	<i>Human/mouse exon locations</i>
----------	-----------------------------------

Description

A dataframe used for plotting annotation for human and mouse. Each loaded .rda has the same variable called "geneinfo" (so don't co-load these), but the files differ by an m or h

Usage

```
geneinfo
```

Format

A GRanges object

chrom Chromosomes without "chr"

start exon start location

stop exon end location

gene Gene Name

score dummy column there for sushi

strand +1 or -1 to indicate side of DNA ...

Value

A data.frame

Source

biomaRt July 2015 stable build

getHumanGenes	<i>Get protein coding gene regions</i>
---------------	--

Description

getHumanGenes returns a GRanges object of all protein coding genes genome-wide or within specified chromosomes. Annotation is from regions from hg19/Gr37 and protein coding genes.

Usage

```
getHumanGenes(chr, cache = TRUE)

## S4 method for signature 'missing'
getHumanGenes(chr, cache = TRUE)

## S4 method for signature 'character'
getHumanGenes(chr, cache = TRUE)
```

Arguments

chr	A vector of chromosomes
cache	logic variable (default = TRUE) to use genes from July.2015 freeze

Details

This function returns a GRanges object with the coordinates and gene IDs of all protein coding genes either genome-wide (by default) or specified within a particular chromosome.

Value

A GRanges object

Examples

```
# Grab all protein coding gene locations genome-wide
pc.genes <- getHumanGenes()
# Grab all protein coding gene loctions on chromosome 1
chr1 <- getHumanGenes(c('1'))
```

getHumanTSS

Get Human Transcription Start Sites

Description

getHumanTSS returns a GRanges object of all transcription start sites for humans. Regions from hg19/Gr37 for protein coding regions.

Usage

```
getHumanTSS(chr)

## S4 method for signature 'missing'
getHumanTSS(chr)

## S4 method for signature 'character'
getHumanTSS(chr)
```

Arguments

chr Specifies what chromosomes are desired for the TSS#'

Details

This function returns a GRanges object with the coordinates and gene TSS. The start and end of the IRanges slot will be the same number, so consider using the padGRanges function after calling this function.

Value

A GRanges object

Examples

```
# Grab all transition start sites genome-wide
human.TSS <- getHumanTSS()
```

getMouseGenes *Get protein coding gene regions*

Description

getMouseGenes returns a GRanges object of all protein coding genes genome-wide or within specified chromosomes. Annotation is from regions from mm9 and protein coding genes.

Usage

```
getMouseGenes(chr)

## S4 method for signature 'missing'
getMouseGenes(chr)

## S4 method for signature 'character'
getMouseGenes(chr)
```

Arguments

chr A vector of chromosomes

Details

This function returns a GRanges object with the coordinates and gene IDs of all protein coding genes either genome-wide (by default) or specified within a particular chromosome.

Value

A GRanges object

Examples

```
# Grab all protein coding gene locations genome-wide
pc.genes <- getMouseGenes()
# Grab all protein coding gene loctions on chromosome 1
chr1 <- getHumanGenes(c('1'))
```

`getMouseTSS`*Get Mouse Transcription Start Sites*

Description

getMouseTSS returns a GRanges object of all transcription start sites for humans. Regions from mm9 for protein coding regions.

Usage

```
getMouseTSS(chr)

## S4 method for signature 'missing'
getMouseTSS(chr)

## S4 method for signature 'character'
getMouseTSS(chr)
```

Arguments

chr Specifies what chromosomes are desired for the TSS#

Details

This function returns a GRanges object with the coordinates and gene TSS. The start and end of the IRanges slot will be the same number, so consider using the padGRanges function after calling this function.

Value

A GRanges object

Examples

```
# Grab all transition start sites genome-wide
mouse.TSS <- getMouseTSS()
```

head, loops-method *Extract first part of loops object*

Description

Extract first part of loops object

Usage

```
## S4 method for signature 'loops'
head(x, n = 6, ...)
```

Arguments

x	A loops object
n	Number of lines to view
...	Other non-essential params

Value

A loops object

human.genes *Human protein coding genes*

Description

A GRanges object with the human protein-coding genes

Usage

```
human.genes
```

Format

A GRanges object

seqnames Chromosomes without "chr"

ranges start/end loci

strand not specified (*' everywhere)

id Gene Name ...

Value

A GRanges object

Source

biomaRt July 2015 stable build

interchromosomal *Loops between chromosomes*

Description

interchromosomal restricts loops to those where anchors are observed on different chromosomes

Usage

```
interchromosomal(dlo)

## S4 method for signature 'loops'
interchromosomal(dlo)
```

Arguments

dlo A loops object

Details

This function subsets the loops object into only those loops that have anchors on different chromosomes

Value

A loops object with all loops on different chromosomes

Examples

```
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)

# Compute number of interactions on same chromosome
dim(intrachromosomal(loops.small))
samechromo <- intrachromosomal(loops.small)

# Compute number of interactions on same chromosome
# dim(interchromosomal(loops.small))
# This will throw an error since the toy only has intrachromosomal loops
```

intrachromosomal *Loops within chromosomes*

Description

intrachromosomal restricts interactions to those where anchors are observed on the same chromosomes

Usage

```
intrachromosomal(dlo)

## S4 method for signature 'loops'
intrachromosomal(dlo)
```

Arguments

dlo A loops object

Details

This function subsets the loops object into only those interactions that have both anchors on the same chromosome

Value

A loops object where all loops are on the same chromosome.

Examples

```
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)

# Compute number of interactions on same chromosome
dim(intrachromosomal(loops.small))
samechromo <- intrachromosomal(loops.small)
```

keepCTCFloops *Keep CTCF loops*

Description

keepCTCFloops returns loops that are nearby CTCF peaks as determined by some external data in a GRanges object

Usage

```
keepCTCFloops(lto, ctcf)

## S4 method for signature 'loops,GRanges'
keepCTCFloops(lto, ctcf)
```

Arguments

lto	A loops object whose loops will be annotated
ctcf	GRanges object corresponding to locations of CTCF peaks

Details

This function works similar to the `annotateLoops` function but returns only CTCF loops that are defined in this function. However, loops in `annotateLoops` may have a different annotation based on their priority scheme. For example, an e-p loop from `annotateLoops` may be returned as a CTCF loop by this function if the loop had both annotations. These peaks don't necessarily need to be CTCF peaks, so using a GRanges object with enhancers or promoters to determine e-e loops and p-p loops could also be used in this function

Value

A loops object with all loops having both anchors in the GRanges region

Examples

```
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
ctcf_j <- system.file('extdata','Jurkat_CTCF_chr1.narrowPeak',package='diffloop')
ctcf <- rmchr(padGRanges(bedToGRanges(ctcf_j), pad = 1000))
# small.ctcf <- keepCTCFloops(loops.small, ctcf)
```

keepEPloops	<i>Keep enhancer-promoter loops</i>
-------------	-------------------------------------

Description

`keepEPloops` adds a column to the `rowData` slot of a loops object that shows the corresponding TSS of a gene name based on the promoter GRanges. The loops object is then subsetted and returns only loops that are enhancer-promoter.

Usage

```
keepEPloops(lto, enhancer, promoter)

## S4 method for signature 'loops,GRanges,GRanges'
keepEPloops(lto, enhancer, promoter)
```

Arguments

lto	A loops object whose loops will be annotated
enhancer	GRanges object corresponding to locations of enhancer peaks
promoter	GRanges object corresponding to locations of promoter regions

Details

This function works similar to the `annotateLoops` function but returns only enhancer-promoter loops that are defined in this function. Additionally, this function returns the gene name(s) of the nearby transcription start sites in a comma-separated list if there are multiple. These gene names are defined by the promoter GRanges `mcol` slot.

Value

A loops object with an additional row `'loop.type'` in the `rowData` slot in addition to the `gene.tss` (which has the gene name) and the `anchor.tss` which shows the anchor(s) near the promoter region for the gene.

Examples

```
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
h3k27ac_j <- system.file('extdata','Jurkat_H3K27ac_chr1.narrowPeak',package='diffloop')
h3k27ac <- rmchr(padGRanges(bedToGRanges(h3k27ac_j), pad = 1000))
promoter <- padGRanges(getHumanTSS(c('1')), pad = 1000)
# small.ep <- keepEPloops(loops.small, h3k27ac, promoter)
```

loopAssoc

Generalized differential Loop Calling

Description

`loopAssoc` takes a loops object and prepares it for the returns another loops object with summary statistics per-loop in the `rowData`

Usage

```
loopAssoc(y, method = "edgeR", design = NULL, coef = NULL,
          contrast = NULL)

## S4 method for signature 'loops'
loopAssoc(y, method = "edgeR", design = NULL,
          coef = NULL, contrast = NULL)
```


Arguments

y	A loops object for association
method	Specifies association; either "Voom" or "edgeR"
design	A design matrix of the samples; required for "Voom"
coef	A vector for the coefficient of GLM. See edgeR manual
contrast	A vector for the contrast. See edgeR manual

Details

By the default, we generate is to generate a design matrix from loops@colData\$groups. Currently, 'edgeR' and 'Voom' are the two supported association methods, but new association tests may be added in later developments.

Value

A loops object

Examples

```
# Differential loop fit
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
# assoc <- loopAssoc(loops.small, coef = 2)
```

loopDistancePlot	<i>Visualize proportion of loops at distances</i>
------------------	---

Description

loopDistancePlot takes a loops object plots the individual samples based on the proportion of PET counts at various distances

Usage

```
loopDistancePlot(dlo)

## S4 method for signature 'loops'
loopDistancePlot(dlo)
```

Arguments

dlo	A loops object
-----	----------------

Details

Distances for the loops are taken from the rowData slot.

Value

A ggplot2 plot

Examples

```
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
p1 <- loopDistancePlot(loops.small)
```

loopGenes

Determine genes contained within loops

Description

loopGenes determines all gene bodies partially or fully contained in a loop.

Usage

```
loopGenes(dlo, genesGR)

## S4 method for signature 'loops,GRanges'
loopGenes(dlo, genesGR)

## S4 method for signature 'loops,missing'
loopGenes(dlo, genesGR)
```

Arguments

dlo A loops object
genesGR A GRanges object of genes in first mcol.

Details

Function that annotates all loops. If there are multiple, the function returns a comma separated list. Adds a "loopGenes" column to the rowData slot. If the genesGR is left blank, diffloop will use protein coding genes for human from hg19.

Value

A matrix of comma separated gene names

Examples

```
# Determine the genes housed in the loops from our example
genes <- getHumanGenes()
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
loops.small <- loopGenes(loops.small,genes)
```

`loopMetrics`*Types of loops*

Description

`loopMetrics` counts number of loops for each sample and returns whether they are single, self, unique, or none

Usage

```
loopMetrics(dlo)

## S4 method for signature 'loops'
loopMetrics(dlo)
```

Arguments

`dlo` A loops object

Details

This function shows the number of loops for each sample based on four types. Single refers to having only one anchor for a the loop whereas none has no unique anchors. If using the `loopsMake` pipeline, only self and unique loops will be observed when running this function

Value

A data.frame

Examples

```
# Return loop metrics for number of each type for each sample
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
loopMetrics(loops.small)
```

`loopPlot`*Visualize looping*

Description

`loopPlot` takes a loops object and a GRanges object and shows all loops in region (where both anchors are present)

Usage

```
loopPlot(x, y, organism = "h", geneinfo = "NA", colorLoops = TRUE,
         cache = TRUE, showAnchorWidths = FALSE, maxCounts = -1)

## S4 method for signature 'loops,GRanges'
loopPlot(x, y, organism = "h", geneinfo = "NA",
         colorLoops = TRUE, cache = TRUE, showAnchorWidths = FALSE,
         maxCounts = -1)
```

Arguments

x	A loops object
y	A GRanges object containing region of interest
organism	'h' for human or 'm' for mouse supported
geneinfo	A data.frame manually specifying annotation (see Examples)
colorLoops	Differentiates loops based on loop.type in loops object
cache	logic variable (default = TRUE) to use gene annotation from July.2015 freeze
showAnchorWidths	Display the width of the anchor on the plot? Default = FALSE
maxCounts	Number of counts associated with thickest loop. Default is largest count in region displayed

Details

Basic plot function shows the looping in each sample. The intensity of the color is proportional to the number of counts observed for the particular loop relative to the other loops in the entire plot. If colorLoops is specified at TRUE, then the x object must be loops and it must have a loop.type column which can be generated from the annotateLoops function. Blue loops are CTCF loops; black are none; red are enhancer-promoter loops; orange are promoter-promoter loops; and purple are enhancer-enhancer loops. Plots use hg19 and mm9 annotation by default.

Value

A plot object

Examples

```
# Print loops in region chr1:36000000-36300000
library(GenomicRanges)
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
regA <- GRanges(c('1'),IRanges(start=c(36000000),end=c(36300000)))
plot1 <- loopPlot(loops.small, regA)
#Example of \code{geneinfo} table
geneinfo <- data.frame(1,359345,359681,'RP5-8572K21.15','.','-1)
names(geneinfo) <- c('chrom','start','stop','gene','strand')
```

loops-class	<i>A class to represent ChIA-PET interaction data and annotations</i>
-------------	---

Description

A class to represent ChIA-PET interaction data and annotations

Slots

anchors A GRanges object describing loop anchor locations
interactions A matrix. Each row is an interaction between two anchors
counts A matrix with the number paired-end reads per loop per sample
colData A data.frame with features (columns) for each sample (rows)
rowData A data.frame with features (columns) for each loop (rows)

loops.small	<i>chr1:36000000-36300000 loops</i>
-------------	-------------------------------------

Description

A loops object containing unique 108 loops with 27 anchors for 6 samples and corresponding colData/rowData

Usage

```
loops.small
```

Format

A small loops object

anchors GRanges object of anchor locations

loops indexes of interactions

samples Two replicates each of jurkat, naive, and primed cells

colData Groups identifying cell type and unnormalized sizeFactors

rowData Base initialization with only loopWidth values ...

Value

A loops object

Source

```
subsetRegion(loops,GRanges(c('1'),IRanges(c(36000000),c(36300000))))
```

`loopsMake`*Read preprocessed ChIA-PET data from dnalooop*

Description

loopsMake reads in a data directory created by the dnalooop preprocessing pipeline and returns a loops object

Usage

```
loopsMake(beddir, samples = NA, mergegap = 0, type = "all")
```

```
## S4 method for signature 'ANY'  
loopsMake(beddir, samples = NA, mergegap = 0,  
  type = "all")
```

Arguments

beddir	A string. The preprocessed data directory
samples	A character vector. Optional list of samples to read in
mergegap	An integer value of the radius to merge anchors; default 0
type	Specificies 'intra', 'inter', or 'all' looping. Default 'all'

Details

This function reads in preprocessed ChIA-PET data produced by the dnalooop preprocessing pipeline. The samples argument specifies which samples are read. If samples is not specified all samples will be read. The type option restricts loops whether they are on the same 'intra' or different 'inter' chormosome. Default is 'all'.

IMPORTANT: Assumes the delimiter is a space, not a tab on the files.

Value

A loops object

Examples

```
# Reading in all samples, no mergegap, all loops  
bd<- system.file('extdata', 'esc_jurkat', package='diffloopdata')  
# loops <- loopsMake(bd) #standard call  
  
# Reading in a subset of samples, 1kb mergegap, only intrachromosomal  
# looping  
samples <- c('naive_esc_1', 'naive_esc_2')  
# naive.intra <- loopsMake(bd, samples, 1000, 'inter')
```

loopsMake.mango	<i>Read preprocessed ChIA-PET data from mango</i>
-----------------	---

Description

loopsMake.mango reads in a data directory created by the mango preprocessing pipeline and returns a loops object

Usage

```
loopsMake.mango(beddir, samples = NA, mergegap = 500, ext = "all")
```

```
## S4 method for signature 'ANY'
```

```
loopsMake.mango(beddir, samples = NA, mergegap = 500,  
  ext = "all")
```

Arguments

beddir	A string. The preprocessed data directory; Required
samples	A character vector. Optional list of samples to read in
mergegap	An integer value of the radius to merge anchors; default 500
ext	Specificies 'all' or 'fdr' file format; default 'all'

Details

This function reads in preprocessed ChIA-PET data produced by the mango preprocessing pipeline. The samples argument specifies which samples are read. If samples is not specified all samples will be read. The ext specifies which type of file to look for, either all or fdr, with all being the default. Under the default, all samples with the extension .fdr.mango will be processed. Finally, the FDR parameter (default = 1) specifies the minimum threshold for loops to be added to the greater loops object. Currently, we do not support importing the verbose output, so the verbose parameter when executing mango should be set to FALSE or the user will have to parse the file before reading into diffloop using awk, cut, or something similar.

Value

A loops object where 'chr' is removed from the anchors.

Examples

```
# UPDATE THIS  
bd<- system.file('extdata', 'esc_jurkat', package='diffloopdata')
```

loopsSubset	<i>Subset two difloop objects</i>
-------------	-----------------------------------

Description

loopsSubset takes the interactions and anchors present in dlo1 and uses the counts and samples from dlo2.

Usage

```
loopsSubset(dlo1, dlo2)

## S4 method for signature 'loops,loops'
loopsSubset(dlo1, dlo2)
```

Arguments

dlo1	A loops object
dlo2	A loops object

Details

This function plays nice with union to ensure counts are correct after taking the union of two loops objects. The subset function simply returns the anchors and interactions of dlo1 and the counts and colData of dlo2.

Value

A loops object

Examples

```
# divide and recombine samples
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
naive <- loops.small[,1:2]
primed <- loops.small[,3:4]
np <- union(naive, primed)
# Subset from full to get correct counts
c.np <- loopsSubset(np, loops.small)
```

loopWidth	<i>Loop widths</i>
-----------	--------------------

Description

loopWidth returns the width of a loop, which is defined as the distance between the anchors containing a loop

Usage

```
loopWidth(dlo)

## S4 method for signature 'loops'
loopWidth(dlo)
```

Arguments

dlo A loops object

Details

This function returns a positive integer value of the number of basepairs that separate two loops. If they are on separate chromosomes, it still returns a value, but it will be non-sensical, so consider subsetting to only intrachromosomal loops. Also, self-loops will return a positive number that is the inter-anchor width. These loops should be handled using the removeSelfLoops() function.

Value

An integer vector

Examples

```
# Return the width for loops
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
w <- loopWidth(loops.small)
```

mangoCorrection	<i>Perform mango bias correction</i>
-----------------	--------------------------------------

Description

mangoCorrection takes a loops object and filters loops based on the binomial model used in the mango ChIA-PET pipeline.

Usage

```
mangoCorrection(lo, FDR = 1, PValue = 1, nbins = 10)

## S4 method for signature 'ANY'
mangoCorrection(lo, FDR = 1, PValue = 1, nbins = 10)
```

Arguments

lo	A loops object.
FDR	Minimum FDR value for loop to be included; default 1
PValue	Minimum p0value for loop to be included; default 1
nbins	Number of bins for mango computation

Details

This function processes ChIA-PET data in a loops object and filters loops that may be biased due to proximity or low PET counts as previously described by the mango pipeline. PET and anchor counts are aggregated across all samples to compute statistical significance. Consider using a larger number of bins (e.g. 30) for a larger data object when possible.

Value

A loops object where loops are filtered using mango bias correction

Examples

```
rda <- paste(system.file("rda", package = "diffloop"), "loops.small.rda", sep = "/")
load(rda)
loops.small <- removeSelfLoops(loops.small)
loops.small.mango <- mangoCorrection(loops.small, PValue = 0.05)
```

manyLoopPlots	<i>Plot several loop regions</i>
---------------	----------------------------------

Description

manyLoopPlots takes a loops object and creates a time-stamped .pdf file with loop plots (one per page) of all regions specified in the GRanges object.

Usage

```
manyLoopPlots(x, y, organism = "h", geneinfo = "NA", colorLoops = FALSE,
  cache = TRUE, maxCounts = -1, showAnchorWidths = FALSE)
```

```
## S4 method for signature 'loops,GRanges'
manyLoopPlots(x, y, organism = "h",
  geneinfo = "NA", colorLoops = FALSE, cache = TRUE, maxCounts = -1,
  showAnchorWidths = FALSE)
```

Arguments

x	loops object
y	GRanges object with many regions to be visualized
organism	'h' for human or 'm' for mouse supported
geneinfo	A data.frame manually specifying annotation (see Examples)
colorLoops	Differentiates loops based on loop.type in loops object
cache	logic variable (default = TRUE) to use gene annotation from July.2015 freeze
maxCounts	Number of counts associated with thickest loop. Default is largest count in region displayed
showAnchorWidths	Display the width of the anchor on the plot? Default = FALSE

Details

Each plot will show one region sequentially that is supplied in the GRanges object.

Value

Prints a time stamped .pdf file of top loops

Examples

```
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
jpn.u <- removeSelfLoops(loops.small)
assoc <- loopAssoc(jpn.u, coef = 2)
#manyLoopPlots(assoc, regs) #define regs as multiple GRanges
```

mergeAnchors	<i>Combine nearby anchors into one peak</i>
--------------	---

Description

mergeAnchors combines anchors that are within a user-defined radius

Usage

```
mergeAnchors(dlo, mergegap, selfloops = FALSE)
```

```
## S4 method for signature 'loops,numeric,missing'
mergeAnchors(dlo, mergegap,
  selfloops = FALSE)
```

```
## S4 method for signature 'loops,numeric,logical'
mergeAnchors(dlo, mergegap,
  selfloops = FALSE)
```

Arguments

dlo	A loops object whose anchors will be merged
mergegap	An integer value of the bp between anchors to be merged
selfloops	A logical value to either retain (T) or remove (F) resulting self-loops after merging anchors

Details

This function takes a loops object and combines nearby anchors, up to a distance specified by the mergegap. This likely will cause self loops to form (loop where the left and right anchor are the same), which can either be removed (by default) or retained with selfloops

Value

A loops object

Examples

```
# Merge anchors within 1kb of each other, keeping self loops
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
m1kb <- mergeAnchors(loops.small, 1000, FALSE)
```

```
# Merge anchors within 1kb of each other, removing self loops by default
m1kb_unique <- mergeAnchors(loops.small, 1000)
```

numAnchors	<i>Get number of anchors in each sample</i>
------------	---

Description

numAnchors takes a loops object and summarizes the number of anchors that support all the interactions (count ≥ 1) in the object

Usage

```
numAnchors(x)

## S4 method for signature 'loops'
numAnchors(x)
```

Arguments

x A loops object to be summarized

Details

This function returns a data.frame where the column names specify the sample in the original loops object and the only row shows the number of anchors used to support that sample

Value

A data.frame of each sample and the number of anchors

Examples

```
# Show number of anchors each sample is supported by
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
numAnchors(loops.small)
```

numLoops	<i>Per-sample loop quantities</i>
----------	-----------------------------------

Description

numLoops counts number of loops for each sample based on the index of nloops and returns a data.frame

Usage

```
numLoops(dlo, nloops = 1:10)

## S4 method for signature 'loops,numeric'
numLoops(dlo, nloops = 1:10)

## S4 method for signature 'loops,missing'
numLoops(dlo, nloops = 1:10)
```

Arguments

```
dlo          A loops object
nloops      A numeric vector of counts to be considered
```

Details

This function shows the number of unique loops with at least `nloops` in counts. Can be used to quickly visualize relative sequencing depth between samples

Value

A data.frame

Examples

```
# Determine what samples have loops with 1-20 counts
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
nLoops <- numLoops(loops.small, 1:20)

# Determine what samples loops with 1-10 counts by default
nLoops <- numLoops(loops.small)
```

padGRanges

Pad a GRanges object

Description

padGRanges takes a GRanges object and adds or subtracts distance based on user-defined input. Upstream and downstream consider strand information when available. Specify only either pad or upstream/downstream when using

Usage

```
padGRanges(gro, upstream = 0, downstream = 0, pad = 0)

## S4 method for signature 'GRanges'
padGRanges(gro, upstream = 0, downstream = 0, pad = 0)
```

Arguments

gro	A granges object
upstream	Distance in BP added upstream
downstream	Distance in BP added downstream
pad	Distance in BP added

Value

A GRanges object with adjusted start and end values

Examples

```
#Read in CTCF Jurkat peaks in
ctcf_j <- system.file('extdata', 'Jurkat_CTCF_chr1.narrowPeak', package = 'diffloop')
ctcf <- bedToGRanges(ctcf_j)
ctcf.pad <- padGRanges(ctcf, pad = 1000)
```

pcaPlot

Visualize sample relationships

Description

pcaPlot takes a loops object plots the individual samples based on the principal components of the loop counts matrix

Usage

```
pcaPlot(dlo)
```

```
## S4 method for signature 'loops'
pcaPlot(dlo)
```

Arguments

dlo	A loops object
-----	----------------

Details

Groups for the principal component plots are derived from colData and the normalizing factors are also taken from colData. While some loops objects may have non-informative groups or size factors, they should always be present.

Value

A ggplot2 plot

Examples

```
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
p1 <- pcaPlot(loops.small)
```

plotTopLoops *Plot the most significant loops*

Description

plotTopLoops takes a loops object and creates a time-stamped .pdf file with loop plots (one per page) of the top loops.

Usage

```
plotTopLoops(lto, n = 0, PValue = 1, FDR = 1, organism = "h",
             colorLoops = FALSE)
```

```
## S4 method for signature 'loops'
plotTopLoops(lto, n = 0, PValue = 1, FDR = 1,
             organism = "h", colorLoops = FALSE)
```

Arguments

lto	loops object
n	number of loops to print (can remain 0 to specify from other parameters) determined by PValue
PValue	Maximum pvalue threshold for loop inclusion when printing loop plot
FDR	False discovery rate threshold for inclusion
organism	Either 'm' for mouse or 'h' for human.
colorLoops	Default FALSE; specify true if rowData slot contains loop.type from annotateLoops to visualize plots with varying colors for CTCF looping and enhancer-promoter looping

Details

Each plot will show the region +/- 1 loopwidth of the loop with annotation specified for either human or mouse. Assumes columns Pvalue and FDR are specified in the loops object. We recommend removing self loops before using this function (and in reality, before any association testing was called.)

Value

Prints a time stamped .pdf file of top loops

Examples

```
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
jpn.u <- removeSelfLoops(loops.small)
assoc <- loopAssoc(jpn.u,coef = 2)
plotTopLoops(assoc, n=2)
```

quickAssoc

Perform quick differential loop calling

Description

quickAssoc takes a loops object and performs a basic edgeR association on the counts matrix and groups from colData

Usage

```
quickAssoc(y)

## S4 method for signature 'loops'
quickAssoc(y)
```

Arguments

y A loops object for association

Details

This function returns the output of fitting an edgeR model using the groups defined in colData for the specific loops object. The factor normalization is based on the edgeR model. For quick association, the number of groups is restricted to two. If a more complex group structure exists, consider using the loopAssoc function.

Value

A loops object

Examples

```
# Differential loop calling between naive and primed
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
np <- loops.small[,1:4]
assoc_np <- quickAssoc(np)
```

quickAssocVoom	<i>Perform quick differential loop calling</i>
----------------	--

Description

quickAssocVoom takes a loops object and performs a basic voom association on the counts matrix and groups from colData

Usage

```
quickAssocVoom(y)

## S4 method for signature 'loops'
quickAssocVoom(y)
```

Arguments

y A loops object for association

Details

This function returns the output of fitting a voom model using the groups defined in colData for the specific loops object. The factor normalization is based on the voom model. For quick association, the number of groups is restricted to two. If a more complex group structure exists, consider using the loopAssoc function.

Value

A loops object

Examples

```
# Differential loop calling between naive and primed
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
np <- loops.small[,1:4]
assoc_np_voom <- quickAssocVoom(np)
```

removeRegion	<i>Remove region from loops object</i>
--------------	--

Description

removeRegion takes a loops object and a GRanges object and returns a loops object where neither anchors map inside the GRanges coordinates.

Usage

```
removeRegion(dlo, region)

## S4 method for signature 'loops,GRanges'
removeRegion(dlo, region)
```

Arguments

dlo	A loops object to be subsetted
region	A GRanges object containing region of interest

Value

A loops object with no anchors touching the region given

Examples

```
# Remove region chr1:36000000-36100000
library(GenomicRanges)
regA <- GRanges(c('1'), IRanges(c(36000000), c(36100000)))
rda <- paste(system.file('rda', package='diffloop'), 'loops.small.rda', sep='/')
load(rda)
# Get rid of loop if either anchor touches that region
restricted <- removeRegion(loops.small, regA)
```

removeSelfLoops	<i>Remove self loops</i>
-----------------	--------------------------

Description

removeSelfLoops removes instances where a loop is observed between the same anchor

Usage

```
removeSelfLoops(dlo)

## S4 method for signature 'loops'
removeSelfLoops(dlo)
```

Arguments

dlo A loops object

Details

This function removes loops from the interactions slot that reference the same index of the anchors slot.

Value

A loops object

Examples

```
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
jpn_unique <- removeSelfLoops(loops.small)
```

rmchr

Remove 'chr' from GRanges seqnames

Description

rmchr takes a loops object or GRanges object and simply removes the 'chr' from seqnames, if is present

Usage

```
rmchr(dlo)
```

```
## S4 method for signature 'loops'
rmchr(dlo)
```

```
## S4 method for signature 'GRanges'
rmchr(dlo)
```

Arguments

dlo A loops object or GRanges object

Details

Often times, performing functions on GRanges objects can go awry if the seqnames are systematically different. A common example of this is when some GRanges objects has the format of 'chr1' while the other has '1'. We can remove 'chr' from the first object

Value

An identical loops/GRanges object except 'chr' removed

Examples

```
library(GenomicRanges)
regA <- GRanges(c('1'),IRanges(c(36200000),c(36300000)))
addchr(regA)
regA
rmchr(regA)
regA
```

sampleNames,loops-method

Grab/Update Sample Names

Description

sampleNames takes a loops object returns the names of the samples in the structure. One can also update the names using set replace.

Usage

```
## S4 method for signature 'loops'
sampleNames(object)

## S4 replacement method for signature 'loops,ANY'
sampleNames(object) <- value
```

Arguments

object	A loops object
value	New names when using set replace

Details

The examples show both accession and updating sample names.

Value

Vector of sample names

Examples

```
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
sampleNames(loops.small)
nnames <- c('one', 'two', 'three', 'four', 'five', 'six')
sampleNames(loops.small) <- nnames
```

slidingWindowTest *Combined association test for all loops in a defined region*

Description

slidingWindowTest takes a loops object and integer values of the association window and the distance between consecutive windows.

Usage

```
slidingWindowTest(x, window, step)
```

```
## S4 method for signature 'loops,numeric,numeric'  
slidingWindowTest(x, window, step)
```

Arguments

x	A loops object with PValue column (from association testing)
window	The length a window will be for combined association
step	The size that the window will shift for each association

Details

This function returns a data.frame sorted by FDR of each region. The engine loops over each chromosome and defines the first window at the left-most loop and slides the window right until no more loops are present in x. Each region is determined from a sliding window of fixed length. The combined significance measure per feature is computed via the Simes method for intrachromosomal loops where at least one anchor from the loop overlaps with the region. Requires PValue column in the rowData slot.

Value

A data.frame sorted by FDR

Examples

```
# Sliding window test 100kb at a time between naive and jurkat  
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')  
load(rda)  
# assoc_jn <- loopAssoc(loops.small, coef = 2)  
# sw_jn <- slidingWindowTest(assoc_jn, 100000, 100000)
```

splitSamples	<i>Split samples into their own loops object</i>
--------------	--

Description

splitSamples takes a loops object and returns a list of loops objects where each sample populates its own loops object

Usage

```
splitSamples(dlo)

## S4 method for signature 'loops'
splitSamples(dlo)
```

Arguments

dlo A loops object

Details

This function splits the colData and counts slots for each sample but makes copies of the anchors, interactions, and rowdata

Value

A list of loops objects with one sample per index.

Examples

```
# Updating groups from all 'group1' to meaningful designations
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
split <- splitSamples(loops.small)
```

subsetLoops	<i>Subset loops</i>
-------------	---------------------

Description

subsetLoops restricts the loops and counts matrix to only those specified by idxa, either numerically or logically

Usage

```
subsetLoops(dlo, idxa)

## S4 method for signature 'loops,logical'
subsetLoops(dlo, idxa)

## S4 method for signature 'loops,numeric'
subsetLoops(dlo, idxa)
```

Arguments

dlo	A loops object
idxa	A numeric vector or logical vector

Details

This function returns a loops object where the loops are retained only if they meet a logical criteria or are included in the numeric vector of `idxa`. Only the anchors that reference a loop in the subsetted loops object are retained.

Value

A loops object

Examples

```
# Return the first 10 loops
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
#' ten <- subsetLoops(loops.small, 1:10)

# Subset loops with widths greater than 10000
big <- subsetLoops(loops.small, loopWidth(loops.small) >= 10000)
```

subsetRegion

Extract region from loops object

Description

subsetRegion takes a loops object and a GRanges object and returns a loops object where both anchors map inside the GRanges coordinates by default. Once can specify where only one anchor is in the region instead.

Usage

```
subsetRegion(dlo, region, nanchors)

## S4 method for signature 'loops,GRanges,numeric'
subsetRegion(dlo, region, nanchors)

## S4 method for signature 'loops,GRanges,missing'
subsetRegion(dlo, region, nanchors)
```

Arguments

dlo	A loops object to be subsetted
region	A GRanges object containing region of interest
nanchors	Number of anchors to be contained in GRanges object. Default 2

Details

By default, nanchors = 2, meaning both anchors need to be in the region for the loop to be preserved when extracting. However, by specifying a numeric 1, interactions with either the left or right anchor will be extracted. Loops with both anchors in the region will be excluded (exclusive or). To get an inclusive or, take the union of subsetting both with 1 and 2.

Value

A loops object

Examples

```
# Grab region chr1:36000000-36100000
library(GenomicRanges)
regA <- GRanges(c('1'),IRanges(c(36000000),c(36100000)))
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
# Both anchors in region
loops.small.two <- subsetRegion(loops.small, regA)
#Only one anchor in region
loops.small.one <- subsetRegion(loops.small, regA, 1)
#Either one or two anchors in region
loops.small.both <- union(loops.small.one, loops.small.two)
```

subsetRegionAB

Retain loops that have anchors in two specified regions

Description

subsetRegionAB returns a loops object where one anchor maps to regionA and the other maps to region B

Usage

```
subsetRegionAB(dlo, regionA, regionB)

## S4 method for signature 'loops,GRanges,GRanges'
subsetRegionAB(dlo, regionA, regionB)
```

Arguments

dlo	A loops object
regionA	A GRanges object
regionB	A GRanges object

Value

A loops object

Examples

```
# Return the width for loops
library(GenomicRanges)
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
regA <- GRanges(c('1'),IRanges(c(36000000),c(36100000)))
regB <- GRanges(c('1'),IRanges(c(36200000),c(36300000)))
splits <- subsetRegionAB(loops.small, regA, regB)
```

summary,loops-method *Link the anchors and interactions back together*

Description

summary takes a loops object and breaks the loop data structure resulting in a data.frame.

Usage

```
## S4 method for signature 'loops'
summary(object)
```

Arguments

object	A loops object to be summarized
--------	---------------------------------

Details

This function returns a `data.frame` where the left and right anchors are visualized together along with the loop width, individual counts, and any anchor meta-data that has been annotated into the anchors `GRanges` object as well as any `rowData` variable. Finally, the `region` column contains the coordinates that readily facilitates visualization of loop in UCSC or `DNALandscapeR` by padding the loop by 25kb on either side.

Value

A `data.frame`

Examples

```
# Summarizing the first ten loops in \code{loops.small}
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
summarydf <- summary(loops.small[1:10,])
# Summarizing the loops and significance results between naive and primed
summarylt <- summary(quickAssoc(loops.small[,1:4])[1:10,])
```

tail,loops-method *Extract last part of loops object*

Description

Extract last part of loops object

Usage

```
## S4 method for signature 'loops'
tail(x, n = 6, ...)
```

Arguments

x	A loops object
n	Number of lines to view
...	Other non-essential params

Value

A loops object

topLoops

Grab top loops

Description

topLoops takes a loops object and performs basic filtering for FDR or PValue

Usage

```
topLoops(dlo, FDR, PValue)

## S4 method for signature 'loops,numeric,numeric'
topLoops(dlo, FDR, PValue)

## S4 method for signature 'loops,numeric,missing'
topLoops(dlo, FDR, PValue)

## S4 method for signature 'loops,missing,numeric'
topLoops(dlo, FDR, PValue)
```

Arguments

dlo	A loops object
FDR	Maximum threshold for False Discovery Rate; default = 1
PValue	Maximum threshold for P-value; default = 1

Details

This function returns a subsetting loops object where all loops meet the significance threshold specified by the parameters in the function call.

Value

A loops object subsetting by specified parameters

Examples

```
# Differential loop calling between naive and primed
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
np <- loops.small[,1:4]
assoc_np <- quickAssoc(np)
top_np <- topLoops(assoc_np, FDR = 0.3)
```

union,loops,loops-method

Combine two loops objects

Description

union combines two loops objects' interactions and anchors and populates the colData matrix where available

Usage

```
## S4 method for signature 'loops,loops'  
union(x, y)
```

Arguments

x	A loops object
y	A loops object

Details

This function returns a single loops object that has all the anchors and interactions contained in the two loops objects that were part of the input. However, when the two objects have different samples, the counts matrix will contain missing values (e.g. when loop counts in x are not in y, those values are unknown). While the number of interactions, colData, and anchors should be correct, we need to correct the counts using a subsetting function. The row data gets re-initialized here to only the loop widths

Value

A loops object

Examples

```
# divide and recombine samples  
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')  
load(rda)  
naive <- loops.small[,1:2]  
primed <- loops.small[,3:4]  
np <- union(naive, primed)  
# Subset from full to get correct counts  
c.np <- loopsSubset(np, loops.small)
```

updateLDGroups *Update groups in colData for loops object*

Description

updateLDGroups changes the groups column in colData for a loops object

Usage

```
updateLDGroups(dlo, groups)
```

```
## S4 method for signature 'loops'
updateLDGroups(dlo, groups)
```

Arguments

dlo A loops object
 groups A character vector. Lists the groups each sample belongs in

Details

This function updates the groups column in colData for a loops object. Make sure that the length of groups the number of samples in colData!

Value

A loops object with new groups in colData

Examples

```
# Updating groups from all 'group1' to meaningful designations
rda<-paste(system.file('rda',package='diffloop'),'loops.small.rda',sep='/')
load(rda)
celltypes <- c('naive1','naive1','primed2','primed2','jurkat3','jurkat3')
loops.small <- updateLDGroups(loops.small, celltypes)
```

[,loops,numeric,numeric,missing-method
Extract parts of a loops object

Description

Extract parts of a loops object

Usage

```
## S4 method for signature 'loops,numeric,numeric,missing'  
x[i, j, drop]
```

```
## S4 method for signature 'loops,missing,numeric,missing'  
x[i, j, drop]
```

```
## S4 method for signature 'loops,numeric,missing,missing'  
x[i, j, drop]
```

Arguments

x	A loops object for subsetting
i	Loops to be subsetted
j	Samples to be subsetted
drop	Other non-essential parameters needed for sub

Value

A loops object

Index

- * **datasets**
 - geneinfo, [16](#)
 - human.genes, [20](#)
 - loops.small, [29](#)
- [, loops, missing, numeric, missing-method
 - ([, loops, numeric, numeric, missing-method), [54](#)
- [, loops, numeric, missing, missing-method
 - ([, loops, numeric, numeric, missing-method), [54](#)
- [, loops, numeric, numeric, missing-method,
 - [54](#)
- addchr, [3](#)
- addchr, GRanges-method (addchr), [3](#)
- addchr, loops-method (addchr), [3](#)
- annotateAnchors, [4](#)
- annotateAnchors, loops, GRanges, character, missing-method
 - (annotateAnchors), [4](#)
- annotateAnchors, loops, GRanges, character, numeric-method
 - (annotateAnchors), [4](#)
- annotateAnchors.bed, [5](#)
- annotateAnchors.bed, ANY-method
 - (annotateAnchors.bed), [5](#)
- annotateAnchors.bigwig, [6](#)
- annotateAnchors.bigwig, ANY-method
 - (annotateAnchors.bigwig), [6](#)
- annotateLoops, [7](#)
- annotateLoops, loops, GRanges, GRanges, GRanges-method
 - (annotateLoops), [7](#)
- annotateLoops, loops, missing, GRanges, GRanges-method
 - (annotateLoops), [7](#)
- annotateLoops.dge, [8](#)
- annotateLoops.dge, ANY-method
 - (annotateLoops.dge), [8](#)
- bedToGRanges, [9](#)
- bedToGRanges, character-method
 - (bedToGRanges), [9](#)
- calcLDSizeFactors, [10](#)
- calcLDSizeFactors, loops-method
 - (calcLDSizeFactors), [10](#)
- callCCDs, [10](#)
- callCCDs, ANY-method (callCCDs), [10](#)
- computeBoundaryScores, [11](#)
- computeBoundaryScores, loops-method
 - (computeBoundaryScores), [11](#)
- diffloop, [12](#)
- diffloop-package (diffloop), [12](#)
- dim, loops-method, [13](#)
- featureTest, [13](#)
- featureTest, loops, GRanges-method
 - (featureTest), [13](#)
- filterLoops, [14](#)
- filterLoops, ANY-method (filterLoops), [14](#)
- filterSpanningLoops, [15](#)
- filterSpanningLoops, loops, GRanges-method
 - (filterSpanningLoops), [15](#)
- geneinfo, [16](#)
- getHumanGenes, [16](#)
- getHumanGenes, character-method
 - (getHumanGenes), [16](#)
- getHumanGenes, missing-method
 - (getHumanGenes), [16](#)
- getHumanTSS, [17](#)
- getHumanTSS, character-method
 - (getHumanTSS), [17](#)
- getHumanTSS, missing-method
 - (getHumanTSS), [17](#)
- getMouseGenes, [18](#)
- getMouseGenes, character-method
 - (getMouseGenes), [18](#)
- getMouseGenes, missing-method
 - (getMouseGenes), [18](#)
- getMouseTSS, [19](#)
- getMouseTSS, character-method
 - (getMouseTSS), [19](#)

- getMouseTSS,missing-method
(getMouseTSS), 19
- head, loops-method, 20
- human.genes, 20
- interchromosomal, 21
- interchromosomal, loops-method
(interchromosomal), 21
- intrachromosomal, 22
- intrachromosomal, loops-method
(intrachromosomal), 22
- keepCTCFloops, 22
- keepCTCFloops, loops, GRanges-method
(keepCTCFloops), 22
- keepEPloops, 23
- keepEPloops, loops, GRanges, GRanges-method
(keepEPloops), 23
- loopAssoc, 24
- loopAssoc, loops-method (loopAssoc), 24
- loopDistancePlot, 25
- loopDistancePlot, loops-method
(loopDistancePlot), 25
- loopGenes, 26
- loopGenes, loops, GRanges-method
(loopGenes), 26
- loopGenes, loops, missing-method
(loopGenes), 26
- loopMetrics, 27
- loopMetrics, loops-method (loopMetrics),
27
- loopPlot, 27
- loopPlot, loops, GRanges-method
(loopPlot), 27
- loops (loops-class), 29
- loops-class, 29
- loops.small, 29
- loopsMake, 30
- loopsMake, ANY-method (loopsMake), 30
- loopsMake.mango, 31
- loopsMake.mango, ANY-method
(loopsMake.mango), 31
- loopsSubset, 32
- loopsSubset, loops, loops-method
(loopsSubset), 32
- loopWidth, 33
- loopWidth, loops-method (loopWidth), 33
- mangoCorrection, 34
- mangoCorrection, ANY-method
(mangoCorrection), 34
- manyLoopPlots, 35
- manyLoopPlots, loops, GRanges-method
(manyLoopPlots), 35
- mergeAnchors, 36
- mergeAnchors, loops, numeric, logical-method
(mergeAnchors), 36
- mergeAnchors, loops, numeric, missing-method
(mergeAnchors), 36
- numAnchors, 37
- numAnchors, loops-method (numAnchors), 37
- numLoops, 37
- numLoops, loops, missing-method
(numLoops), 37
- numLoops, loops, numeric-method
(numLoops), 37
- padGRanges, 38
- padGRanges, GRanges-method (padGRanges),
38
- pcaPlot, 39
- pcaPlot, loops-method (pcaPlot), 39
- plotTopLoops, 40
- plotTopLoops, loops-method
(plotTopLoops), 40
- quickAssoc, 41
- quickAssoc, loops-method (quickAssoc), 41
- quickAssocVoom, 42
- quickAssocVoom, loops-method
(quickAssocVoom), 42
- removeRegion, 43
- removeRegion, loops, GRanges-method
(removeRegion), 43
- removeSelfLoops, 43
- removeSelfLoops, loops-method
(removeSelfLoops), 43
- rmchr, 44
- rmchr, GRanges-method (rmchr), 44
- rmchr, loops-method (rmchr), 44
- sampleNames, loops-method, 45
- sampleNames<-, loops, ANY-method
(sampleNames, loops-method), 45
- slidingWindowTest, 46

slidingWindowTest, loops, numeric, numeric-method
 (slidingWindowTest), 46

splitSamples, 47

splitSamples, loops-method
 (splitSamples), 47

subsetLoops, 47

subsetLoops, loops, logical-method
 (subsetLoops), 47

subsetLoops, loops, numeric-method
 (subsetLoops), 47

subsetRegion, 48

subsetRegion, loops, GRanges, missing-method
 (subsetRegion), 48

subsetRegion, loops, GRanges, numeric-method
 (subsetRegion), 48

subsetRegionAB, 49

subsetRegionAB, loops, GRanges, GRanges-method
 (subsetRegionAB), 49

summary, loops-method, 50

tail, loops-method, 51

topLoops, 52

topLoops, loops, missing, numeric-method
 (topLoops), 52

topLoops, loops, numeric, missing-method
 (topLoops), 52

topLoops, loops, numeric, numeric-method
 (topLoops), 52

union, loops, loops-method, 53

updateLDGroups, 54

updateLDGroups, loops-method
 (updateLDGroups), 54