

Package ‘MSstatsPTM’

October 18, 2022

Type Package

Title Statistical Characterization of Post-translational Modifications

Version 1.6.0

Date 2021-11-08

Description MSstatsPTM provides general statistical methods for quantitative characterization of post-translational modifications (PTMs). Supports DDA, DIA, and tandem mass tag (TMT) labeling. Typically, the analysis involves the quantification of PTM sites (i.e., modified residues) and their corresponding proteins, as well as the integration of the quantification results. MSstatsPTM provides functions for summarization, estimation of PTM site abundance, and detection of changes in PTMs across experimental conditions.

License Artistic-2.0

Depends R (>= 4.0)

Imports dplyr, gridExtra, stringr, stats, ggplot2, grDevices,
MSstatsTMT, MSstatsConvert, MSstats, data.table, Rcpp,
Biostrings, checkmate, ggrepel

Suggests BiocStyle, knitr, rmarkdown, tinytest, covr

LazyData true

LinkingTo Rcpp

VignetteBuilder knitr

biocViews ImmunoOncology, MassSpectrometry, Proteomics, Software,
DifferentialExpression, OneChannel, TwoChannel, Normalization,
QualityControl

BugReports <https://github.com/Vitek-Lab/MSstatsPTM/issues>

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.2

git_url <https://git.bioconductor.org/packages/MSstatsPTM>

git_branch RELEASE_3_15

git_last_commit e7a3639

git_last_commit_date 2022-04-26

Date/Publication 2022-10-18

Author Devon Kohler [aut, cre],
 Tsung-Heng Tsai [aut],
 Ting Huang [aut],
 Mateusz Staniak [aut],
 Meena Choi [aut],
 Olga Vitek [aut]

Maintainer Devon Kohler <kohler.d@northeastern.edu>

R topics documented:

| | |
|---|-----------|
| annotSite | 2 |
| dataProcessPlotsPTM | 3 |
| dataSummarizationPTM | 5 |
| dataSummarizationPTM_TMT | 8 |
| groupComparisonPlotsPTM | 10 |
| groupComparisonPTM | 12 |
| locateMod | 14 |
| locatePTM | 14 |
| MaxQtoMSstatsPTMFormat | 15 |
| MSstatsPTM | 17 |
| ProgenesistoMSstatsPTMFormat | 17 |
| raw.input | 19 |
| raw.input.tmt | 20 |
| SpectronauttoMSstatsPTMFormat | 21 |
| summary.data | 23 |
| summary.data.tmt | 24 |
| tidyFasta | 25 |
| Index | 26 |

annotSite

Annotate modification site

Description

annotSite annotates modified sites as their residues and locations.

Usage

```
annotSite(aaIndex, residue, lenIndex = NULL)
```

Arguments

| | |
|----------|---|
| aaIndex | An integer vector. Location of the sites. |
| residue | A string vector. Amino acid residue. |
| lenIndex | An integer. Default is NULL |

Value

A string.

Examples

```
annotSite(10, "K")  
annotSite(10, "K", 3L)
```

dataProcessPlotsPTM *Visualization for explanatory data analysis*

Description

To illustrate the quantitative data and quality control of MS runs, dataProcessPlotsPTM takes the quantitative data from dataSummarizationPTM or dataSummarizationPTM_TMT to plot the following : (1) profile plot (specify "ProfilePlot" in option type), to identify the potential sources of variation for each protein; (2) quality control plot (specify "QCPlot" in option type), to evaluate the systematic bias between MS runs.

Usage

```
dataProcessPlotsPTM(  
  data,  
  type = "PROFILEPLOT",  
  ylimUp = FALSE,  
  ylimDown = FALSE,  
  x.axis.size = 10,  
  y.axis.size = 10,  
  text.size = 4,  
  text.angle = 90,  
  legend.size = 7,  
  dot.size.profile = 2,  
  ncol.guide = 5,  
  width = 10,  
  height = 12,  
  ptm.title = "All PTMs",  
  protein.title = "All Proteins",  
  which.PTM = "all",  
  which.Protein = NULL,
```

```

    originalPlot = TRUE,
    summaryPlot = TRUE,
    address = ""
)

```

Arguments

| | |
|------------------|--|
| data | name of the list with PTM and (optionally) Protein data, which can be the output of the MSstatsPTM <code>dataSummarizationPTM</code> or <code>dataSummarizationPTM_TMT</code> functions. |
| type | choice of visualization. "ProfilePlot" represents profile plot of log intensities across MS runs. "QCPlot" represents box plots of log intensities across channels and MS runs. |
| ylimUp | upper limit for y-axis in the log scale. FALSE(Default) for Profile Plot and QC Plot uses the upper limit as rounded off maximum of $\log_2(\text{intensities})$ after normalization + 3.. |
| ylimDown | lower limit for y-axis in the log scale. FALSE(Default) for Profile Plot and QC Plot uses 0.. |
| x.axis.size | size of x-axis labeling for "Run" and "channel" in Profile Plot and QC Plot. |
| y.axis.size | size of y-axis labels. Default is 10. |
| text.size | size of labels represented each condition at the top of Profile plot and QC plot. Default is 4. |
| text.angle | angle of labels represented each condition at the top of Profile plot and QC plot. Default is 0. |
| legend.size | size of legend above Profile plot. Default is 7. |
| dot.size.profile | size of dots in Profile plot. Default is 2. |
| ncol.guide | number of columns for legends at the top of plot. Default is 5. |
| width | width of the saved pdf file. Default is 10. |
| height | height of the saved pdf file. Default is 10. |
| ptm.title | title of overall PTM QC plot |
| protein.title | title of overall Protein QC plot |
| which.PTM | PTM list to draw plots. List can be names of PTMs or order numbers of PTMs. Default is "all", which generates all plots for each protein. For QC plot, "allonly" will generate one QC plot with all proteins. |
| which.Protein | List of proteins to plot. Will plot all PTMs associated with listed Proteins. Default is NULL which will default to which.PTM. |
| originalPlot | TRUE(default) draws original profile plots, without normalization. |
| summaryPlot | TRUE(default) draws profile plots with protein summarization for each channel and MS run. |
| address | the name of folder that will store the results. Default folder is the current working directory. The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default |

name of "ProfilePlot.pdf" or "QCplot.pdf". The command address can help to specify where to store the file as well as how to modify the beginning of the file name. If address=FALSE, plot will be not saved as pdf file but showed in window.

Value

plot or pdf

Examples

```
# QCPlot
dataProcessPlotsPTM(summary.data,
                    type = 'QCPLLOT',
                    which.PTM = "allonly",
                    address = FALSE)

#ProfilePlot
dataProcessPlotsPTM(summary.data,
                    type = 'PROFILEPLOT',
                    which.PTM = "Q9UQ80_K376",
                    address = FALSE)
```

dataSummarizationPTM *Process MS PTM and global protein data*

Description

Utilizes functionality from MSstats to clean, summarize, and normalize PTM and protein level data. Imputes missing values, protein and PTM level summarization from peptide level quantification. Applies global median normalization on peptide level data and normalizes between runs.

Usage

```
dataSummarizationPTM(
  data,
  logTrans = 2,
  normalization = "equalizeMedians",
  normalization.PTM = "equalizeMedians",
  nameStandards = NULL,
  nameStandards.PTM = NULL,
  featureSubset = "all",
  featureSubset.PTM = "all",
  remove_uninformative_feature_outlier = FALSE,
  remove_uninformative_feature_outlier.PTM = FALSE,
  min_feature_count = 2,
  min_feature_count.PTM = 1,
  n_top_feature = 3,
```

```

n_top_feature.PTM = 3,
summaryMethod = "TMP",
equalFeatureVar = TRUE,
censoredInt = "NA",
MBimpute = TRUE,
MBimpute.PTM = TRUE,
remove50missing = FALSE,
fix_missing = NULL,
maxQuantileforCensored = 0.999,
use_log_file = TRUE,
append = TRUE,
verbose = TRUE,
log_file_path = NULL,
base = "MSstatsPTM_log_"
)

```

Arguments

| | |
|--------------------------------|--|
| <code>data</code> | name of the list with PTM and (optionally) Protein data.tables, which can be the output of the MSstatsPTM converter functions |
| <code>logTrans</code> | logarithm transformation with base 2(default) or 10 |
| <code>normalization</code> | normalization for the protein level dataset, to remove systematic bias between MS runs. There are three different normalizations supported. 'equalizeMedians'(default) represents constant normalization (equalizing the medians) based on reference signals is performed. 'quantile' represents quantile normalization based on reference signals is performed. 'globalStandards' represents normalization with global standards proteins. FALSE represents no normalization is performed |
| <code>normalization.PTM</code> | normalization for PTM level dataset. Default is "equalizeMedians" Can be adjusted to any of the options described above. |
| <code>nameStandards</code> | vector of global standard peptide names for protein dataset. only for normalization with global standard peptides. |
| <code>nameStandards.PTM</code> | Same as above for PTM dataset. "all"(default) uses all features that the data set has. "top3" uses top 3 features which have highest average of log2(intensity) across runs. "topN" uses top N features which has highest average of log2(intensity) across runs. It needs the input for n_top_feature option. "highQuality" flags uninformative feature and outliers |
| <code>featureSubset</code> | "all" (default) uses all features that the data set has. "top3" uses top 3 features which have highest average of log-intensity across runs. "topN" uses top N features which has highest average of log-intensity across runs. It needs the input for n_top_feature option. "highQuality" flags uninformative feature and outliers. |
| <code>featureSubset.PTM</code> | For PTM dataset only. Options same as above. |

| | |
|--|--|
| remove_uninformative_feature_outlier | For protein dataset only. It only works after users used featureSubset="highQuality" in dataProcess. TRUE allows to remove 1) the features are flagged in the column, feature_quality="Uninformative" which are features with bad quality, 2) outliers that are flagged in the column, is_outlier=TRUE, for run-level summarization. FALSE (default) uses all features and intensities for run-level summarization. |
| remove_uninformative_feature_outlier.PTM | For PTM dataset only. Options same as above. |
| min_feature_count | optional. Only required if featureSubset = "highQuality". Defines a minimum number of informative features a protein needs to be considered in the feature selection algorithm. |
| min_feature_count.PTM | For PTM dataset only. Options the same as above. Default is 1 due to low average feature count for PTMs. |
| n_top_feature | For protein dataset only. The number of top features for featureSubset='topN'. Default is 3, which means to use top 3 features. |
| n_top_feature.PTM | For PTM dataset only. Options same as above. |
| summaryMethod | "TMP"(default) means Tukey's median polish, which is robust estimation method. "linear" uses linear mixed model. |
| equalFeatureVar | only for summaryMethod="linear". default is TRUE. Logical variable for whether the model should account for heterogeneous variation among intensities from different features. Default is TRUE, which assume equal variance among intensities from features. FALSE means that we cannot assume equal variance among intensities from features, then we will account for heterogeneous variation from different features. |
| censoredInt | Missing values are censored or at random. 'NA' (default) assumes that all 'NA's in 'Intensity' column are censored. '0' uses zero intensities as censored intensity. In this case, NA intensities are missing at random. The output from Skyline should use '0'. Null assumes that all NA intensities are randomly missing. |
| MBimpute | For protein dataset only. only for summaryMethod="TMP" and censoredInt='NA' or '0'. TRUE (default) imputes 'NA' or '0' (depending on censoredInt option) by Accelerated failure model. FALSE uses the values assigned by cutoffCensored. |
| MBimpute.PTM | For PTM dataset only. Options same as above. |
| remove50missing | only for summaryMethod="TMP". TRUE removes the runs which have more than 50% missing values. FALSE is default. |
| fix_missing | Default is Null. Optional, same as the 'fix_missing' parameter in MSstatsConvert::MSstatsBalancedDesign function |
| maxQuantileforCensored | Maximum quantile for deciding censored missing values. default is 0.999 |
| use_log_file | logical. If TRUE, information about data processing will be saved to a file. |

| | |
|---------------|---|
| append | logical. If TRUE, information about data processing will be added to an existing log file. |
| verbose | logical. If TRUE, information about data processing will be printed to the console. |
| log_file_path | character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If append = TRUE, has to be a valid path to a file. |
| base | start of the file name. |

Value

list of summarized PTM and Protein results. These results contain the reformatted input to the summarization function, as well as run-level summarization results.

Examples

```
head(raw.input$PTM)
head(raw.input$PROTEIN)

quant.lf.msstatsptm <- dataSummarizationPTM(raw.input, verbose = FALSE)
head(quant.lf.msstatsptm$PTM$ProteinLevelData)
```

dataSummarizationPTM_TMT

Process MS PTM and global protein data produced via tandem mass tag labeling

Description

Utilizes functionality from MSstatsTMT to clean, summarize, and normalize PTM and protein level data. Imputes missing values, protein and PTM level summarization from peptide level quantification. Applies global median normalization on peptide level data and normalizes between runs.

Usage

```
dataSummarizationPTM_TMT(
  data,
  method = "msstats",
  global_norm = TRUE,
  global_norm.PTM = TRUE,
  reference_norm = TRUE,
  reference_norm.PTM = TRUE,
  remove_norm_channel = TRUE,
  remove_empty_channel = TRUE,
  MBimpute = TRUE,
  MBimpute.PTM = TRUE,
  maxQuantileforCensored = NULL,
```



```

    use_log_file = TRUE,
    append = FALSE,
    verbose = TRUE,
    log_file_path = NULL
  )

```

Arguments

| | |
|------------------------|---|
| data | Name of the output of MSstatsPTM converter function or peptide-level quantified data from other tools. It should be a list containing one or two data tables, named PTM and PROTEIN for modified and unmodified datasets. The list must at least contain the PTM dataset. The data should have columns ProteinName, PeptideSequence, Charge, PSM, Mixture, TechRepMixture, Run, Channel, Condition, BioReplicate, Intensity |
| method | Four different summarization methods to protein-level can be performed : "msstats"(default), "MedianPolish", "Median", "LogSum". |
| global_norm | Global median normalization on for unmodified peptide level data (equalizing the medians across all the channels and MS runs). Default is TRUE. It will be performed before protein-level summarization. |
| global_norm.PTM | Same as above for modified peptide level data. Default is TRUE. |
| reference_norm | Reference channel based normalization between MS runs on unmodified protein level data. TRUE(default) needs at least one reference channel in each MS run, annotated by 'Norm' in Condition column. It will be performed after protein-level summarization. FALSE will not perform this normalization step. If data only has one run, then reference_norm=FALSE. |
| reference_norm.PTM | Same as above for modified peptide level data. Default is TRUE. |
| remove_norm_channel | TRUE(default) removes 'Norm' channels from protein level data. |
| remove_empty_channel | TRUE(default) removes 'Empty' channels from protein level data. |
| MBimpute | only for method="msstats". TRUE (default) imputes missing values by Accelerated failure model. FALSE uses minimum value to impute the missing value for each peptide precursor ion. |
| MBimpute.PTM | Same as above for modified peptide level data. Default is TRUE |
| maxQuantileforCensored | We assume missing values are censored. maxQuantileforCensored is Maximum quantile for deciding censored missing value, for instance, 0.999. Default is Null. |
| use_log_file | logical. If TRUE, information about data processing will be saved to a file. |
| append | logical. If TRUE, information about data processing will be added to an existing log file. |
| verbose | logical. If TRUE, information about data processing will be printed to the console. |

`log_file_path` character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If `append = TRUE`, has to be a valid path to a file.

Value

list of two `data.tables`

Examples

```
head(raw.input.tmt$PTM)
head(raw.input.tmt$PROTEIN)

quant.tmt.msstatsptm <- dataSummarizationPTM_TMT(raw.input.tmt,
                                                method = "msstats",
                                                verbose = FALSE)

head(quant.tmt.msstatsptm$PTM$ProteinLevelData)
```

groupComparisonPlotsPTM

Visualization for model-based analysis and summarization

Description

To analyze the results of modeling changes in abundance of modified peptides and overall protein, `groupComparisonPlotsPTM` takes as input the results of the `groupComparisonPTM` function. It assesses the results of three models: unadjusted PTM, adjusted PTM, and overall protein. To assess the results of the model, the following visualizations can be created: (1) `VolcanoPlot` (specify "VolcanoPlot" in option `type`), to plot peptides or proteins and their significance for each model. (2) `Heatmap` (specify "Heatmap" in option `type`), to evaluate the fold change between conditions and peptides/proteins

Usage

```
groupComparisonPlotsPTM(
  data = data,
  type,
  sig = 0.05,
  FCcutoff = FALSE,
  logBase.pvalue = 10,
  ylimUp = FALSE,
  ylimDown = FALSE,
  xlimUp = FALSE,
  x.axis.size = 10,
  y.axis.size = 10,
  dot.size = 3,
  text.size = 4,
  text.angle = 0,
```

```

legend.size = 13,
ProteinName = TRUE,
colorkey = TRUE,
numProtein = 50,
width = 10,
height = 10,
which.Comparison = "all",
which.PTM = "all",
address = ""
)

```

Arguments

| | |
|----------------|---|
| data | name of the list with models, which can be the output of the MSstatsPTM groupComparisonPTM function |
| type | choice of visualization, one of VolcanoPlot or Heatmap |
| sig | FDR cutoff for the adjusted p-values in heatmap and volcano plot. level of significance for comparison plot. 100(1-sig)% confidence interval will be drawn. sig=0.05 is default. |
| FCcutoff | For volcano plot or heatmap, whether involve fold change cutoff or not. FALSE (default) means no fold change cutoff is applied for significance analysis. FC-cutoff = specific value means specific fold change cutoff is applied. |
| logBase.pvalue | for volcano plot or heatmap, (-) logarithm transformation of adjusted p-value with base 2 or 10(default). |
| ylimUp | for all three plots, upper limit for y-axis. FALSE (default) for volcano plot/heatmap use maximum of -log2 (adjusted p-value) or -log10 (adjusted p-value). FALSE (default) for comparison plot uses maximum of log-fold change + CI. |
| ylimDown | for all three plots, lower limit for y-axis. FALSE (default) for volcano plot/heatmap use minimum of -log2 (adjusted p-value) or -log10 (adjusted p-value). FALSE (default) for comparison plot uses minimum of log-fold change - CI. |
| xlimUp | for Volcano plot, the limit for x-axis. FALSE (default) for use maximum for absolute value of log-fold change or 3 as default if maximum for absolute value of log-fold change is less than 3. |
| x.axis.size | size of axes labels, e.g. name of the comparisons in heatmap, and in comparison plot. Default is 10. |
| y.axis.size | size of axes labels, e.g. name of targeted proteins in heatmap. Default is 10. |
| dot.size | size of dots in volcano plot and comparison plot. Default is 3. |
| text.size | size of ProteinName label in the graph for Volcano Plot. Default is 4. |
| text.angle | angle of x-axis labels represented each comparison at the bottom of graph in comparison plot. Default is 0. |
| legend.size | size of legend for color at the bottom of volcano plot. Default is 7. |
| ProteinName | for volcano plot only, whether display protein names or not. TRUE (default) means protein names, which are significant, are displayed next to the points. FALSE means no protein names are displayed. |

| | |
|------------------|---|
| colorkey | TRUE(default) shows colorkey. |
| numProtein | The number of proteins which will be presented in each heatmap. Default is 50. |
| width | width of the saved file. Default is 10. |
| height | height of the saved file. Default is 10. |
| which.Comparison | list of comparisons to draw plots. List can be labels of comparisons or order numbers of comparisons from levels(data\$Label), such as levels(testResultMultiComparisons\$Comparison). Default is "all", which generates all plots for each protein. |
| which.PTM | Protein list to draw comparison plots. List can be names of Proteins or order numbers of Proteins from levels(testResultMultiComparisons\$ComparisonResult\$Protein). Default is "all", which generates all comparison plots for each protein. |
| address | the name of folder that will store the results. Default folder is the current working directory. The other assigned folder has to be existed under the current working directory. An output pdf file is automatically created with the default name of "VolcanoPlot.pdf" or "Heatmap.pdf". The command address can help to specify where to store the file as well as how to modify the beginning of the file name. If address=FALSE, plot will be not saved as pdf file but showed in window |

Value

plot or pdf

Examples

```
model.lf.msstatsptm <- groupComparisonPTM(summary.data,
                                         data.type = "LabelFree")
groupComparisonPlotsPTM(data = model.lf.msstatsptm,
                        type = "VolcanoPlot",
                        FCcutoff= 2,
                        logBase.pvalue = 2,
                        address=FALSE)
```

groupComparisonPTM *Model PTM and/or protein data and make adjustments if needed*

Description

Takes summarized PTM and protein data from proteinSummarization. If protein data is unavailable, PTM data only can be passed into the function. Including protein data allows for adjusting PTM Fold Change by the change in protein abundance without modification. MSstatsContrastMatrix

Usage

```
groupComparisonPTM(
  data,
  data.type,
  contrast.matrix = "pairwise",
  moderated = FALSE,
  adj.method = "BH",
  log_base = 2,
  use_log_file = TRUE,
  append = FALSE,
  verbose = TRUE,
  log_file_path = NULL,
  base = "MSstatsPTM_log_"
)
```

Arguments

| | |
|-----------------|---|
| data | list of summarized datasets. Output of MSstatsPTM summarization function dataSummarizationPTM or dataSummarizationPTM_TMT depending on acquisition type. |
| data.type | string indicating experimental acquisition type. "TMT" is used for TMT labeled experiments. For all other experiments (Label Free/ DDA/ DIA) use "Label-Free". |
| contrast.matrix | comparison between conditions of interests. Default models full pairwise comparison between all conditions |
| moderated | For TMT experiments only. TRUE will moderate t statistic; FALSE (default) uses ordinary t statistic. Default is FALSE. |
| adj.method | For TMT experiemnts only. Adjusted method for multiple comparison. "BH" is default. "BH" is used for all other experiment types |
| log_base | For non-TMT experiments only. The base of the logarithm used in summarization. |
| use_log_file | logical. If TRUE, information about data processing will be saved to a file. |
| append | logical. If TRUE, information about data processing will be added to an existing log file. |
| verbose | logical. If TRUE, information about data processing will be printed to the console. |
| log_file_path | character. Path to a file to which information about data processing will be saved. If not provided, such a file will be created automatically. If append = TRUE, has to be a valid path to a file. |
| base | start of the file name. |

Value

list of modeling results. Includes PTM, PROTEIN, and ADJUSTED data.tables with their corresponding model results.

Examples

```
model.lf.msstatsptm <- groupComparisonPTM(summary.data,
                                           data.type = "LabelFree",
                                           verbose = FALSE)
```

| | |
|-----------|---|
| locateMod | <i>Locate modified sites with a peptide</i> |
|-----------|---|

Description

locateMod locates modified sites with a peptide.

Usage

```
locateMod(peptide, aaStart, residueSymbol)
```

Arguments

| | |
|---------------|--|
| peptide | A string. Peptide sequence. |
| aaStart | An integer. Starting index of the peptide. |
| residueSymbol | A string. Modification residue and denoted symbol. |

Value

A string.

Examples

```
locateMod("P*EP*TIDE", 3, "\\*")
```

| | |
|-----------|---|
| locatePTM | <i>Annotate modified sites with associated peptides</i> |
|-----------|---|

Description

PTMlocate annotates modified sites with associated peptides.

Usage

```
locatePTM(peptide, uniprot, fasta, modResidue, modSymbol, rmConfound = FALSE)
```

Arguments

| | |
|------------|---|
| peptide | A string vector of peptide sequences. The peptide sequence does not include its preceding and following AAs. |
| uniprot | A string vector of Uniprot identifiers of the peptides' originating proteins. UniProtKB entry isoform sequence is used. |
| fasta | A data.table with FASTA information. Output of tidyFasta. |
| modResidue | A string. Modifiable amino acid residues. |
| modSymbol | A string. Symbol of a modified site. |
| rmConfound | A logical. TRUE removes confounded unmodified sites, FALSE otherwise. Default is FALSE. |

Value

A data frame with three columns: uniprot_iso, peptide, site.

Examples

```
fasta <- tidyFasta(system.file("extdata", "013297.fasta", package="MSstatsPTM"))
locatePTM("DRVSYIHNDSC*TR", "013297", fasta, "C", "\\*")
```

MaxQtoMSstatsPTMFormat

Convert output of TMT labeled MaxQuant experiment into MSstatsPTM format

Description

Takes as input TMT experiments from MaxQ and converts the data into the format needed for MSstatsPTM. Requires only the modified file from MaxQ (for example Phospho(STY)Sites) and an annotation file for PTM data. To adjust modified peptides for changes in global protein level, unmodified TMT experimental data must also be returned.

Usage

```
MaxQtoMSstatsPTMFormat(
  sites.data,
  annotation.ptm,
  evidence = NULL,
  proteinGroups = NULL,
  annotation.prot = NULL,
  mod.num = "Single",
  TMT.keyword = "TMT",
  ptm.keyword = "phos",
  which.proteinid.ptm = "Protein",
  which.proteinid.protein = "Leading.razor.protein",
  removeMpeptides = FALSE
)
```

Arguments

| | |
|--------------------------------------|---|
| <code>sites.data</code> | modified peptide output from MaxQuant. For example, a phosphorylation experiment would require the Phospho(STY)Sites.txt file |
| <code>annotation.ptm</code> | data frame annotation file for the ptm level data. Contains column Run, Fraction, TechRepMixture, Mixture, Channel, BioReplicate, Condition. |
| <code>evidence</code> | for global protein dataset. name of 'evidence.txt' data, which includes feature-level data. |
| <code>proteinGroups</code> | for global protein dataset, name of 'proteinGroups.txt' data. |
| <code>annotation.prot</code> | data frame annotation file for the protein level data. Contains column Run, Fraction, TechRepMixture, Mixture, Channel, BioReplicate, Condition. |
| <code>mod.num</code> | For modified peptide dataset. The number modifications per peptide to be used. If "Single", only peptides with one modification will be used. Otherwise "Total" can be selected which does not cap the number of modifications per peptide. "Single" is the default. Selecting "Total" may confound the effect of different modifications. |
| <code>TMT.keyword</code> | the sub-name of columns in sites.data file. Default is TMT. This corresponds to the columns in the format <code>Reporter.intensity.corrected.1.TMT1phos___1</code> . Specifically, this parameter indicates the first section of the string TMT1phos (Before the mixture number). If TMT is present in the string, set this value to TMT. Else if TMT is not there (ie string is in the format 1phos) leave this parameter as an empty string (""). |
| <code>ptm.keyword</code> | the sub-name of columns in the sites.data file. Default is phos. This corresponds to the columns in the format <code>Reporter.intensity.corrected.1.TMT1phos___1</code> . Specifically, this parameter indicates the second section of the string TMT1phos (After the mixture number). If the string is present, set this parameter. Else if this part of the string is empty (ie string is in the format TMT1) leave this parameter as an empty string (""). |
| <code>which.proteinid.ptm</code> | For PTM dataset, which column to use for protein name. Use 'Proteins' (default) column for protein name. 'Leading.proteins' or 'Leading.razor.protein' or 'Gene.names' can be used instead to get the protein ID with single protein. However, those can potentially have the shared peptides. |
| <code>which.proteinid.protein</code> | For Protein dataset, which column to use for protein name. Same options as above. |
| <code>removeMpeptides</code> | If Oxidation (M) modifications should be removed. Default is TRUE. |

Value

a list of two data.tables named 'PTM' and 'PROTEIN' in the format required by MSstatsPTM.

Examples

```
head(raw.input.tmt$PTM)
```



```
head(raw.input.tmt$PROTEIN)
```

| | |
|------------|---|
| MSstatsPTM | <i>MSstatsPTM: A package for detecting differentially abundant post translational modifications (PTM) in shotgun mass spectrometry-based proteomic experiments.</i> |
|------------|---|

Description

A set of tools for detecting differentially abundant PTMs and proteins in shotgun mass spectrometry-based proteomic experiments. The package can handle a variety of acquisition types, including label free, DDA, DIA, and TMT. The package includes tools to convert raw data from different spectral processing tools, summarize feature intensities, and fit a linear mixed effects model. Additionally the package includes functionality to plot a variety of data visualizations.

functions

- [MaxQtoMSstatsPTMFormat](#) : Generates MSstatsPTM required input format for TMT MaxQuant outputs.
- [ProgenesitoMSstatsPTMFormat](#) : Generates MSstatsPTM required input format for non-TMT Proteoviz outputs.
- [SpectronauttoMSstatsPTMFormat](#) : Generates MSstatsPTM required input format for non-TMT Spectronaut outputs.
- [dataSummarizationPTM](#) : Summarizes PSM level quantification to peptide (modification) and protein level quantification. For use in non-TMT analysis
- [dataSummarizationPTM_TMT](#) : Summarizes PSM level quantification to peptide (modification) and protein level quantification. For use in TMT analysis.
- [dataProcessPlotsPTM](#) : Visualization for explanatory data analysis. Specifically gives ability to plot Profile and Quality Control plots.
- [groupComparisonPTM](#) : Tests for significant changes in PTM and protein abundance across conditions. Adjusts PTM fold change for changes in protein abundance.
- [groupComparisonPlotsPTM](#) : Visualization for model-based analysis and summarization

ProgenesitoMSstatsPTMFormat

Converts non-TMT Progenesis output into the format needed for MSstatsPTM

Description

Converts non-TMT Progenesis output into the format needed for MSstatsPTM

Usage

```
ProgenesisMSstatsPTMFormat(
  ptm_input,
  annotation,
  global_protein_input = FALSE,
  fasta_path = FALSE,
  useUniquePeptide = TRUE,
  summaryforMultipleRows = max,
  removeFewMeasurements = TRUE,
  removeOxidationMpeptides = FALSE,
  removeProtein_with1Peptide = FALSE,
  mod.num = "Single"
)
```

Arguments

| | |
|----------------------------|---|
| ptm_input | name of Progenesis output with modified peptides, which is wide-format. 'Accession', 'Sequence', 'Modification', 'Charge' and one column for each run are required |
| annotation | name of 'annotation.txt' or 'annotation.csv' data which includes Condition, BioReplicate, Run, and Type (PTM or Protein) information. It will be matched with the column name of input for MS runs. Please note PTM and global Protein run names are often different, which is why an additional Type column indicating Protein or PTM is required. |
| global_protein_input | name of Progenesis output with unmodified peptides, which is wide-format. 'Accession', 'Sequence', 'Modification', 'Charge' and one column for each run are required |
| fasta_path | string containing path to the corresponding fasta file for the modified peptide dataset. |
| useUniquePeptide | TRUE(default) removes peptides that are assigned for more than one proteins. We assume to use unique peptide for each protein. |
| summaryforMultipleRows | max(default) or sum - when there are multiple measurements for certain feature and certain run, use highest or sum of multiple intensities. |
| removeFewMeasurements | TRUE (default) will remove the features that have 1 or 2 measurements across runs. |
| removeOxidationMpeptides | TRUE will remove the modified peptides including 'Oxidation (M)' sequence. FALSE is default. |
| removeProtein_with1Peptide | TRUE will remove the proteins which have only 1 peptide and charge. FALSE is default. |

mod.num For modified peptide dataset, must be one of Single or Total. The default is Single. The number modifications per peptide to be used. If "Single", only peptides with one modification will be used. Otherwise "Total" includes peptides with more than one modification. Selecting "Total" may confound the effect of different modifications.

Value

a list of two data.tables named 'PTM' and 'PROTEIN' in the format required by MSstatsPTM.

Examples

```
# Example annotation file
annotation <- data.frame('Condition' = c('Control', 'Control', 'Control',
    'Treatment', 'Treatment', 'Treatment'),
    'BioReplicate' = c(1,2,3,4,5,6),
    'Run' = c('prot_run_1', 'prot_run_2', 'prot_run_3',
    'phos_run_1', 'phos_run_2', 'phos_run_3'),
    'Type' = c("Protein", "Protein", "Protein", "PTM",
    "PTM", "PTM"))

# The output should be in the following format.
head(raw.input$PTM)
head(raw.input$PROTEIN)
```

raw.input

Example of input PTM dataset for LabelFree/DDA/DIA experiments.

Description

It can be the output of MSstatsPTM converter ProgenesisistoMSstatsPTMFormat or other MSstats converter functions (Please see MSstatsPTM_LabelFree_Workflow vignette). The dataset is formatted as a list with two data.tables named PTM and PROTEIN. In each data.table the variables are as follows:

Usage

```
raw.input
```

Format

A list of two data.tables named PTM and PROTEIN with 1745 and 478 rows respectively.

Details

#'

ProteinName : Name of protein with modification site mapped in with an underscore. ie "Protein_4_Y474"

- PeptideSequence
- Condition : Condition (ex. Healthy, Cancer, Time0)
- BioReplicate : Unique ID for biological subject.
- Run : MS run ID.
- Intensity
- PrecursorCharge
- FragmentIon
- ProductCharge
- IsotopeLabelType

Examples

```
head(raw.input$PTM)
head(raw.input$PROTEIN)
```

raw.input.tmt

Example of input PTM dataset for TMT experiments.

Description

It can be the output of MSstatsPTM converter MaxQtoMSstatsPTMFormat or other MSstatsTMT converter functions (Please see MSstatsPTM_TMT_Workflow vignette). The dataset is formatted as a list with two data.tables named PTM and PROTEIN. In each data.table the variables are as follows:

Usage

```
raw.input.tmt
```

Format

A list of two data.tables named PTM and PROTEIN with 1716 and 29221 rows respectively.

Details

- ProteinName : Name of protein with modification site mapped in with an underscore. ie "Protein_4_Y474"
- PeptideSequence
- Charge
- PSM
- Mixture : Mixture of samples labeled with different TMT reagents, which can be analyzed in a single mass spectrometry experiment. If the channel doesn't have sample, please add 'Empty' under Condition. \item TechRepMixture : Technical replicate of one mixture. One mixture may have multiple technical replicates. \item Mixture' = 1, 2 are the two technical replicates of one mixture, then they should match with same Mixture' value. \item Run : MS run ID. \item Channel : Labeling information (126, ... 131). \item BioReplicate under BioReplicate.
- Intensity

Examples

```
head(raw.input.tmt$PTM)
head(raw.input.tmt$PROTEIN)
```

SpectronauttoMSstatsPTMFormat

Converts raw PTM MS data from Spectronaut into the format needed for MSstatsPTM.

Description

Takes as an input both raw PTM and global protein outputs from Spectronaut.

Usage

```
SpectronauttoMSstatsPTMFormat(
  PTM.data,
  fasta,
  Protein.data = NULL,
  annotation = NULL,
  intensity = "PeakArea",
  filter_with_Qvalue = TRUE,
  qvalue_cutoff = 0.01,
  useUniquePeptide = TRUE,
  removeFewMeasurements = TRUE,
  removeProtein_with1Feature = FALSE,
  removeNonUniqueProteins = TRUE,
  modificationLabel = "Phospho",
  removeiRT = TRUE,
```

```

summaryforMultipleRows = max,
which.Conditions = "all"
)

```

Arguments

PTM.data name of PTM Spectronaut output, which is long-format.

fasta A string of path to a FASTA file, used to match PTM peptides.

Protein.data name of Global Protein Spectronaut output, which is long-format.

annotation name of 'annotation.txt' data which includes Condition, BioReplicate, Run. If annotation is already complete in Spectronaut, use annotation=NULL (default). It will use the annotation information from input.

intensity 'PeakArea' (default) uses not normalized peak area. 'NormalizedPeakArea' uses peak area normalized by Spectronaut

filter_with_Qvalue TRUE (default) will filter out the intensities that have greater than `qvalue_cutoff` in EG.Qvalue column. Those intensities will be replaced with zero and will be considered as censored missing values for imputation purpose.

qvalue_cutoff Cutoff for EG.Qvalue. default is 0.01.

useUniquePeptide TRUE (default) removes peptides that are assigned for more than one proteins. We assume to use unique peptide for each protein.

removeFewMeasurements TRUE (default) will remove the features that have 1 or 2 measurements across runs.

removeProtein_with1Feature TRUE will remove the proteins which have only 1 feature, which is the combination of peptide, precursor charge, fragment and charge. FALSE is default.

removeNonUniqueProteins TRUE will remove proteins that were not uniquely identified. IE if the protein column contains multiple proteins separated by ";". TRUE is default

modificationLabel String of modification name. Default is 'Phospho'.

removeiRT TRUE will remove proteins that contain iRT. True is default

summaryforMultipleRows max (default) or sum - when there are multiple measurements for certain feature and certain run, use highest or sum of multiple intensities.

which.Conditions list of conditions to format into MSstatsPTM format. If "all" all conditions will be used. Default is "all".

Value

a list of two data.tables named 'PTM' and 'PROTEIN' in the format required by MSstatsPTM.

Examples

```
# The output should be in the following format.
head(raw.input$PTM)
head(raw.input$PROTEIN)
```

| | |
|--------------|--|
| summary.data | <i>Example of output from dataSummarizationPTM function for non-TMT data</i> |
|--------------|--|

Description

It is made from `raw.input`. It is the output of `dataSummarizationPTM` function from `MSstatsPTM`. It should include a list with two names `PTM` and `PROTEIN`. Each of these list values is also a list with two names `ProteinLevelData` and `FeatureLevelData`, which correspond to two `data.tables`. The columns in these two `data.tables` are listed below. The variables are as follows:

- `FeatureLevelData` :
 - `PROTEIN` : Protein ID with modification site mapped in. Ex. `Protein_1002_S836`
 - `PEPTIDE` : Full peptide with charge
 - `TRANSITION`: Charge
 - `FEATURE` : Combination of Protein, Peptide, and Transition Columns
 - `LABEL` :
 - `GROUP` : Condition (ex. Healthy, Cancer, Time0)
 - `RUN` : Unique ID for technical replicate of one TMT mixture.
 - `SUBJECT` : Unique ID for biological subject.
 - `FRACTION` : Unique Fraction ID
 - `originalRUN` : Run name
 - `censored` :
 - `INTENSITY` : Unique ID for TMT mixture.
 - `ABUNDANCE` : Unique ID for TMT mixture.
 - `newABUNDANCE` : Unique ID for TMT mixture.
 - `predicted` : Unique ID for TMT mixture.
- `ProteinLevelData` :
 - `RUN` : MS run ID
 - `Protein` : Protein ID with modification site mapped in. Ex. `Protein_1002_S836`
 - `LogIntensities`: Protein-level summarized abundance
 - `originalRUN` : Labeling information (126, ... 131)
 - `GROUP` : Condition (ex. Healthy, Cancer, Time0)
 - `SUBJECT` : Unique ID for biological subject.
 - `TotalGroupMeasurements` : Unique ID for technical replicate of one TMT mixture.
 - `NumMeasuredFeature` : Unique ID for TMT mixture.
 - `MissingPercentage` : Unique ID for TMT mixture.
 - `more50missing` : Unique ID for TMT mixture.
 - `NumImputedFeature` : Unique ID for TMT mixture.

Usage

```
summary.data
```

Format

A list of two lists with four data.tables.

Examples

```
head(summary.data)
```

| | |
|------------------|--|
| summary.data.tmt | <i>Example of output from dataSummarizationPTM_TMT function for TMT data</i> |
|------------------|--|

Description

It is made from [raw.input.tmt](#). It is the output of dataSummarizationPTM_TMT function from MSstatsPTM. It should include a list with two names PTM and PROTEIN. Each of these list values is also a list with two names ProteinLevelData and FeatureLevelData, which correspond to two data.tables. The columns in these two data.tables are listed below. The variables are as follows:

- FeatureLevelData :
 - ProteinName : MS run ID
 - PSM : Protein ID with modification site mapped in. Ex. Protein_1002_S836
 - censored: Protein-level summarized abundance
 - predicted : Labeling information (126, ... 131)
 - log2Intensity : Condition (ex. Healthy, Cancer, Time0)
 - Run : Unique ID for biological subject.
 - Channel : Unique ID for technical replicate of one TMT mixture.
 - BioReplicate : Unique ID for TMT mixture.
 - Condition : Unique ID for TMT mixture.
 - Mixture : Unique ID for TMT mixture.
 - TechRepMixture : Unique ID for TMT mixture.
 - PeptideSequence : Unique ID for TMT mixture.
 - Charge : Unique ID for TMT mixture.
- ProteinLevelData :
 - Mixture : MS run ID
 - TechRepMixture : Protein ID with modification site mapped in. Ex. Protein_1002_S836
 - Run: Protein-level summarized abundance
 - Channel : Labeling information (126, ... 131)
 - Protein : Condition (ex. Healthy, Cancer, Time0)
 - Abundance : Unique ID for biological subject.
 - BioReplicate : Unique ID for technical replicate of one TMT mixture.
 - Condition : Unique ID for TMT mixture.

Usage

```
summary.data.tmt
```

Format

A list of two lists with four data.tables.

Examples

```
head(summary.data.tmt)
```

tidyFasta

Read and tidy a FASTA file

Description

tidyFasta reads and tidys FASTA file. Use this function as the first step in identifying modification sites.

Usage

```
tidyFasta(path)
```

Arguments

path A string of path to a FASTA file.

Value

A data.table with columns named header, sequence, uniprot_ac, uniprot_iso, entry_name.

Examples

```
tidyFasta(system.file("extdata", "013297.fasta", package="MSstatsPTM"))
```

Index

* datasets

- raw.input, [19](#)
- raw.input.tmt, [20](#)
- summary.data, [23](#)
- summary.data.tmt, [24](#)

annotSite, [2](#)

dataProcessPlotsPTM, [3](#), [17](#)
dataSummarizationPTM, [4](#), [5](#), [13](#), [17](#)
dataSummarizationPTM_TMT, [4](#), [8](#), [13](#), [17](#)

groupComparisonPlotsPTM, [10](#), [17](#)
groupComparisonPTM, [11](#), [12](#), [17](#)

locateMod, [14](#)
locatePTM, [14](#)

MaxQtoMSstatsPTMFormat, [15](#), [17](#)
MSstatsPTM, [17](#)

ProgenesistoMSstatsPTMFormat, [17](#), [17](#)

raw.input, [19](#), [23](#)
raw.input.tmt, [20](#), [24](#)

SpectronauttoMSstatsPTMFormat, [17](#), [21](#)
summary.data, [23](#)
summary.data.tmt, [24](#)

tidyFasta, [25](#)