

Package ‘myvariant’

September 24, 2025

Type Package

Title Accesses MyVariant.info variant query and annotation services

Version 1.39.1

Date 2025-07-22

Author Adam Mark

Maintainer Adam Mark, Chunlei Wu <cwu@scripps.edu>

Description MyVariant.info is a comprehensive aggregation of variant annotation resources. myvariant is a wrapper for querying MyVariant.info services

License Artistic-2.0

Depends R (>= 3.2.1), VariantAnnotation

Imports httr, jsonlite, S4Vectors, Hmisc, plyr, magrittr, Seqinfo, GenomeInfoDb

Suggests BiocStyle

biocViews VariantAnnotation, Annotation, GenomicVariation

NeedsCompilation no

git_url <https://git.bioconductor.org/packages/myvariant>

git_branch devel

git_last_commit 236c7a9

git_last_commit_date 2025-07-22

Repository Bioconductor 3.22

Date/Publication 2025-09-23

Contents

formatHgvs	2
formatSingleHgvs	2
getVariant	3
getVariants	4
metadata	5
MyVariant	6
myvariant	6
MyVariant-class	7
queryVariant	8
queryVariants	9

Index**10**

formatHgvs	<i>Get all HGVS IDs from Vcf object.</i>
------------	--

Description

Read in a Vcf object created by [readVcf](#) to extract all HGVS IDs for querying MyVariant.info.

Usage

```
formatHgvs(vcf, variant_type = c("snp", "insertion", "deletion"))
```

Arguments

vcf	Vcf object created by readVcf .
variant_type	Type of variant HGVS IDs to retrieve from Vcf object. Default c("snp", "insertion", "deletion")

Value

vector

References

<https://myvariant.info> <http://www.hgvs.org/mutnomen/recs-DNA.html>

See Also

[formatSingleHgvs](#)

Examples

```
## return HGVS IDs for all snps in a Vcf
file.path <- system.file("extdata", "db SNP_mini.vcf", package="myvariant")
vcf <- readVcf(file.path, genome="hg19")
hgvs <- formatHgvs(vcf, variant_type="snp")
```

formatSingleHgvs	<i>Get Hgvs HGVS ID from chromosome, position, reference and alternate alleles.</i>
------------------	---

Description

Create a single HGVS ID for a variant from chromosome, position, reference and alternate alleles.

Usage

```
formatSingleHgvs(chrom, pos, ref, alt, mutant_type=FALSE)
```

Arguments

chrom	Chromosome.
pos	Position of the variant on the reference genome (hg19).
ref	Reference allele.
alt	Alternate allele.
mutant_type	Logical indicating whether to return the type of mutation along with the HGVS ID.

Value

returns a string

References

<https://myvariant.info> <http://www.hgvs.org/mutnomen/recs-DNA.html>

See Also

[formatHgvs](#)

Examples

```
## return HGVS ID for a variant
formatSingleHgvs(1, 35367, "G", "A")
```

getVariant

Return the variant object for the given HGVS id.

Description

This is a wrapper for GET query of `"/variant/<hgvsid>"` service.

Usage

```
getVariant(hgvsid, fields=NULL,
           ..., return.as=c("records", "text"), myvariant)
```

Arguments

hgvsid	HGVS id
fields	Fields to return, a list of a comma-sep string. If fields=="all", all available fields are returned.
...	
return.as	"records" (list), "text" (JSON).
myvariant	A MyVariant object that describes how to connect to data resources. See MyVariant-class . If missing, default object will be used that accesses the main MyVariant.info portal. Default is recommended.

Value

returns a variant object containing the queried annotations

References

http://docs.myvariant.info/en/latest/doc/variant_annotation_service.html#get-request <http://docs.myvariant.info/en/latest/parameters>

See Also

[getVariants](#) [queryVariant](#) [queryVariants](#)

Examples

```
## return the variant object for the given HGVS id
getVariant("chr7:g.55241707G>T")

## customize fields
getVariant("chr7:g.55241707G>T",
          fields=c("dbnsfp.cadd.phred", "dbnsfp.polyphen2"),
          return.as="text")
```

getVariants

Return the list of variant objects for the given list of HGVS ids.

Description

This is a wrapper for POST query of `"/variant"` service.

Usage

```
getVariants(hgvsids, fields=NULL, verbose=NULL, ...,
            return.as=c("DataFrame", "records", "text"), myvariant)
```

Arguments

hgvsids	A vector, list, or comm-sep string HGVS ids
fields	A vector of fields to return. If <code>fields=="all"</code> , all available fields are returned.
verbose	A logical turning on or off process status messages. Default = TRUE.
...	
return.as	"DataFrame" (default), "records" (list), "text" (JSON).
myvariant	A MyVariant object that describes how to connect to data resources. See MyVariant-class . If missing, default object will be used that accesses the main MyVariant.info portal. Default is recommended.

Value

returns a variant object (DataFrame, list, or JSON text) containing the queried annotations

References

http://docs.myvariant.info/en/latest/doc/variant_annotation_service.html#batch-queries-via-post http://docs.myvariant.info/en/latest/doc/variant_annotation_service.html#batch-queries-via-post

See Also

[getVariants](#) [queryVariant](#) [queryVariants](#)

Examples

```
## given a list of HGVS ids
vars <- c('chr1:g.866422C>T',
'chr1:g.876664G>A',
'chr1:g.69635G>C',
'chr1:g.69869T>A',
'chr1:g.881918G>A',
'chr1:g.865625G>A',
'chr1:g.879368C>A',
'chr1:g.889226C>T',
'chr1:g.879492C>G',
'chr1:g.879423T>G',
'chr1:g.881602C>T',
'chr1:g.879115C>G',
'chr1:g.69892T>C',
'chr1:g.879381C>T',
'chr1:g.878330C>G')

## Return the list of variant object for the given list of HGVS ids.
df <- getVariants(vars, fields="dbsnp, welllderly")
```

metadata	<i>metadata</i>
----------	-----------------

Description

Get metadata for MyVariant.info services.

Usage

```
metadata(x, ...)
```

Arguments

- x MyVariant object
- ... MyVariant object slot parameters

Value

returns the metadata including available databases and number of documents.

References

<http://myvariant.info/v1/metadata>

Examples

```
## Get metadata
myvariant<-MyVariant()
metadata(myvariant)
```

MyVariant	<i>MyVariant</i>
-----------	------------------

Description

Construct a MyVariant object.

Usage

```
MyVariant(...)
```

Arguments

... See help page for MyVariant-class

Value

MyVariant object

Examples

```
MyVariant()
```

myvariant	<i>Access MyVariant.info variant annotation services</i>
-----------	--

Description

MyVariant.Info provides REST web services to query/retrieve variant annotations. myvariant is an easy-to-use R wrapper to access MyVariant.info services.

Details

Package:	myvariant
Type:	Package
Version:	0.99.0
Date:	2014-12-18
License:	Artistic-2.0
Depends:	httr jsonlite Hmisc

Author(s)

Adam Mark

Maintainer: Adam Mark <adammark@scripps.edu>

References<https://github.com/Network-of-BioThings/myvariant.info/wiki>

MyVariant-class	Class "MyVariant"
-----------------	-------------------

Description

R Client to access MyVariant.Info annotation services

Objects from the Class

Objects can be created by calls of the form `MyVariant(base.url="http://myvariant.info/v1", delay=1, step=1000, version=version, verbose=TRUE, debug=FALSE)`.

Slots

`base.url`: "http://myvariant.info/v1". Object of class "character"
`delay`: Sleep time between batch retrieval. Object of class "numeric"
`step`: Batch limit. Object of class "numeric"
`version`: httr package version. Object of class "character"
`verbose`: Object of class "logical"
`debug`: Object of class "logical"

Methods

`getVariant(hgvsid, fields=NULL, ..., return.as=c("records", "text"))`: Return the variant object for the given hgvsid
`getVariants(hgvsids, fields=NULL, ..., return.as=c("DataFrame", "records", "text"))`: Return the list of variant object for the given list of hgvsids.
`queryVariant(q, fields=NULL, ..., return.as=c("DataFrame", "records", "text"))`: Return the query result.
`queryVariants(qterms, scopes=NULL, fields=NULL, ..., return.as=c("DataFrame", "records", "text"), r`
 Return the batch query result.

Author(s)

Adam Mark

References<https://github.com/Network-of-BioThings/myvariant.info/wiki>**Examples**

```
showClass("MyVariant")
```

queryVariant	<i>Return the query result.</i>
--------------	---------------------------------

Description

This is a wrapper for GET query of "/query?q=<query>" service.

Usage

```
queryVariant(q, ..., return.as=c("DataFrame", "records", "text"),
             myvariant)
```

Arguments

q	query term(s).
...	Commonly queried fields include fields, size as well as several other fields. View available fields by calling ?metadata.
return.as	"DataFrame" (default), "records" (list), or "text" (JSON).
myvariant	A MyVariant object that describes how to connect to data resources. See MyVariant-class . If missing, default object will be used that accesses the main MyVariant.info portal. Default is recommended.

Value

returns a variant object (DataFrame, list, or JSON text) containing the queried annotations

References

http://docs.myvariant.info/en/latest/doc/variant_query_service.html#get-request <http://docs.myvariant.info/en/latest/doc/syntax>

See Also

[queryVariants](#) [getVariant](#) [getVariants](#)

Examples

```
## return the query result
queryVariant("dbnsfp.variantname:BRCA2")

queryVariant("chr1:1-1000000")
```

queryVariants	<i>Return the batch query result.</i>
---------------	---------------------------------------

Description

This is a wrapper for POST query of "/query" service.

Usage

```
queryVariants(qterms, scopes=NULL, ...,
              return.as=c("DataFrame", "records", "text"),
              myvariant)
```

Arguments

qterms	A vector or list, or string of comma-separated query terms
scopes	Type of types of identifiers, either a list or a comma-separated fields to specify type of input qterms.
...	Commonly queried fields include fields, size as well as several other fields. returnall returns a list of all related data including duplicated and missing qterms. False by default. View available fields by calling ?metadata.
return.as	"DataFrame" (default), "records" (list), "text" (JSON).
myvariant	A MyVariant object that describes how to connect to data resources. See MyVariant-class . If missing, default object will be used that accesses the main MyVariant.info portal. Default is recommended.

Value

returns a variant object (DataFrame, list, or JSON text) containing the queried annotations

References

http://docs.myvariant.info/en/latest/doc/variant_query_service.html#batch-queries-via-post <http://docs.myvariant.info/en/>

See Also

[queryVariant](#) [getVariant](#) [getVariants](#)

Examples

```
## return the batch query result
```

Index

* **classes**

MyVariant-class, [7](#)

* **package**

myvariant, [6](#)

formatHgvs, [2](#), [3](#)

formatSingleHgvs, [2](#), [2](#)

getVariant, [3](#), [8](#), [9](#)

getVariant,missing-method (getVariant),
[3](#)

getVariant,MyVariant-method
(getVariant), [3](#)

getVariants, [4](#), [4](#), [5](#), [8](#), [9](#)

getVariants,missing-method
(getVariants), [4](#)

getVariants,MyVariant-method
(getVariants), [4](#)

metadata, [5](#)

metadata,MyVariant-method (metadata), [5](#)

MyVariant, [6](#)

myvariant, [6](#)

MyVariant-class, [7](#)

queryVariant, [4](#), [5](#), [8](#), [9](#)

queryVariant,missing-method
(queryVariant), [8](#)

queryVariant,MyVariant-method
(queryVariant), [8](#)

queryVariants, [4](#), [5](#), [8](#), [9](#)

queryVariants,missing-method
(queryVariants), [9](#)

queryVariants,MyVariant-method
(queryVariants), [9](#)

readVcf, [2](#)