

Package ‘ANF’

November 14, 2025

Type Package

Title Affinity Network Fusion for Complex Patient Clustering

Version 1.33.0

Author Tianle Ma, Aidong Zhang

Maintainer Tianle Ma <tianlema@buffalo.edu>

Description This package is used for complex patient clustering by integrating multi-omic data through affinity network fusion.

License GPL-3

VignetteBuilder knitr

Imports igraph, Biobase, survival, MASS, stats, RColorBrewer

Suggests ExperimentHub, SNFtool, knitr, rmarkdown, testthat

biocViews Clustering, GraphAndNetwork, Network

RoxygenNote 6.0.1

git_url <https://git.bioconductor.org/packages/ANF>

git_branch devel

git_last_commit 9a47e06

git_last_commit_date 2025-10-29

Repository Bioconductor 3.23

Date/Publication 2025-11-14

Contents

affinity_matrix	2
ANF	2
eval_clu	3
kNN_graph	4
pod	5
spectral_clustering	6
Index	7

affinity_matrix	<i>Generate a symmetric affinity matrix based on a distance matrix using 'local' Gaussian kernel</i>
-----------------	--

Description

Generate a symmetric affinity matrix based on a distance matrix using 'local' Gaussian kernel

Usage

```
affinity_matrix(D, k, alpha = 1/6, beta = 1/6)
```

Arguments

D	distance matrix (need to be a square and non-negative matrix)
k	the number of k-nearest neighbors
alpha	coefficient for local diameters. Default value: 1/6. This default value should work for most cases.
beta	coefficient for pair-wise distance. Default value: 1/6. This default value should work for most cases.

Value

an affinity matrix

Examples

```
D = matrix(runif(400), nrow=20)
A = affinity_matrix(D, 5)
```

ANF	<i>Fuse affinity networks (i.e., matrices) through one-step or two-step random walk</i>
-----	---

Description

Fuse affinity networks (i.e., matrices) through one-step or two-step random walk

Usage

```
ANF(Wall, K = 20, weight = NULL, type = c("two-step", "one-step"),
    alpha = c(1, 1, 0, 0, 0, 0, 0, 0), verbose = FALSE)
```

Arguments

Wall	a list of affinity matrices of the same shape.
K	the number of k nearest neighbors for function kNN_graph
weight	a list of non-negative real numbers (which will be normalized internally so that it sums to 1) that one-to-one correspond to the affinity matrices included in 'Wall'. If not set, internally uniform weights are assigned to all affinity matrices in 'Wall'.
type	choose one of the two options: perform "one-step" random walk, or "two-step" random walk on the list of affinity matrices in 'Wall' to generate a fused affinity matrix. Default: "two-step" random walk
alpha	a list of eight non-negative real numbers (which will be normalized internally to make it sums to 1). Only used when "two-step" (default value of 'type') random walk is used. 'alpha' is the weights for eight terms in the "two-step" random walk formula (check research paper for more explanations about the terms). Default value: (1, 1, 0, 0, 0, 0, 0, 0), i.e., only use the first two terms (since they are most effective in practice).
verbose	logical(1); if true, print some information

Value

a fused transition matrix (representing a fused network)

Examples

```
D1 = matrix(runif(400), nrow=20)
W1 = affinity_matrix(D1, 5)
D2 = matrix(runif(400), nrow=20)
W2 = affinity_matrix(D1, 5)
W = ANF(list(W1, W2), K=10)
```

eval_clu

Evaluate clustering result

Description

Evaluate clustering result

Usage

```
eval_clu(true_class, w = NULL, d = NULL, k = 10, num_clu = NULL,
  surv = NULL, type_L = c("rw", "sym", "unnormalized"), verbose = TRUE)
```

Arguments

true_class	A named vector of true class labels
w	affinity matrix
d	distance matrix if w is NULL, calculate w using d
k	an integer, default 10; if w is null, $w = \text{affinity_matrix}(d, k)$; otherwise unused.
num_clu	an integer; number of clusters; if NULL, set num_clu to be the number of classes using true_class
surv	a data.frame with at least two columns: time (days_to_death or days_to_last_follow_up), and censored (logical(1))
type_L	(parameter passed to spectral_clustering: 'type') choose one of three versions of graph Laplacian: "unnormalized": unnormalized graph Laplacian matrix ($L = D - W$); "rw": normalization closely related to random walk ($L = I - D^{-1} * W$); (default choice) "sym": normalized symmetric matrix ($L = I - D^{-0.5} * W * D^{-0.5}$) For more information: https://www.cs.cmu.edu/~aarti/Class/10701/readings/Luxburg06_TR.pdf
verbose	logical(1); if true, print some information

Value

a named list of size 3: "w": affinity matrix used for spectral_clustering; "clu.res": a named vector of calculated "NMI" (normalized mutual information), "ARI" (Adjusted Rand Index), and " $-\log_{10}(p)$ " of log rank test of survival distributions of patient clusters; "labels": a numeric vector as class labels

Examples

```
library(MASS)
true.class = rep(c(1,2), each=100)
feature.mat1 = mvrnorm(100, rep(0, 20), diag(runif(20,0.2,2)))
feature.mat2 = mvrnorm(100, rep(0.5, 20), diag(runif(20,0.2,2)))
feature1 = rbind(feature.mat1, feature.mat2)
d = dist(feature1)
d = as.matrix(d)
A = affinity_matrix(d, 10)
res = eval_clu(true_class=true.class, w=A)
```

kNN_graph	<i>Calculate k-nearest-neighbor graph from affinity matrix and normalize it as transition matrix</i>
-----------	--

Description

Calculate k-nearest-neighbor graph from affinity matrix and normalize it as transition matrix

Usage

```
kNN_graph(W, K)
```

Arguments

W	affinity matrix (its elements are non-negative real numbers)
K	the number of k nearest neighbors

Value

a transition matrix of the same shape as W

Examples

```
D = matrix(runif(400),20)
W = affinity_matrix(D, 5)
S = kNN_graph(W, 5)
```

 pod

Finding optimal discrete solutions for spectral clustering

Description

Finding optimal discrete solutions for spectral clustering

Usage

```
pod(Y, verbose = FALSE)
```

Arguments

Y	a matrix with N rows and K columns, with N being the number of objects (e.g., patients), K being the number of clusters. The K columns of ‘Y’ should correspond to the first k eigenvectors of graph Laplacian matrix (of affinity matrix) corresponding to the k smallest eigenvalues
verbose	logical(1); if true, print some information

Value

class assignment matrix with the same shape as Y (i.e., N x K). Each row contains all zeros except one 1. For instance, if $X_{ij} = 1$, then object (eg, patient) i belongs to cluster j.

References

Stella, X. Yu, and Jianbo Shi. "Multiclass spectral clustering." ICCV. IEEE, 2003.

Examples

```

D = matrix(runif(400),20)
A = affinity_matrix(D, 5)
d = rowSums(A)
L = diag(d) - A
# `NL` is graph Laplacian of affinity matrix `A`
NL = diag(1/d) %*% L
e = eigen(NL)
# Here we select eigenvectors corresponding to three smallest eigenvalues
Y = Re(e$vectors[,-1:-17])
X = pod(Y)

```

spectral_clustering	<i>spectral_clustering</i>
---------------------	----------------------------

Description

spectral_clustering

Usage

```

spectral_clustering(A, k, type = c("rw", "sym", "unnormalized"),
  verbose = FALSE)

```

Arguments

A	affinity matrix
k	the number of clusters
type	choose one of three versions of graph Laplacian: "unnormalized": unnormalized graph Laplacian matrix ($L = D - W$); "rw": normalization closely related to random walk ($L = I - D^{-1} * W$); (default choice) "sym": normalized symmetric matrix ($L = I - D^{-0.5} * W * D^{-0.5}$) For more information: https://www.cs.cmu.edu/~aarti/Class/1070
verbose	logical(1); if true, print user-friendly information

Value

a numeric vector as class labels

Examples

```

D = matrix(runif(400), nrow = 20)
A = affinity_matrix(D, 5)
labels = spectral_clustering(A, k=2)

```

Index

affinity_matrix, [2](#)

ANF, [2](#)

eval_clu, [3](#)

kNN_graph, [4](#)

pod, [5](#)

spectral_clustering, [6](#)