

Package ‘CCPlotR’

April 26, 2026

Title Plots For Visualising Cell-Cell Interactions

Version 1.9.1

Description CCPlotR is an R package for visualising results from tools that predict cell-cell interactions from single-cell RNA-seq data. These plots are generic and can be used to visualise results from multiple tools such as Liana, CellPhoneDB, NATMI etc.

Imports plyr, tidyr, dplyr, ggplot2, forcats, ggraph, igraph, scatterpie, circlize, ComplexHeatmap, tibble, grid, stringr, ggtext, ggh4x, patchwork, RColorBrewer, scales, viridis, grDevices, graphics, stats, methods

URL <https://github.com/Sarah145/CCPlotR>

BugReports <https://github.com/Sarah145/CCPlotR/issues>

License MIT + file LICENSE

Encoding UTF-8

LazyData false

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Suggests knitr, rmarkdown, BiocStyle, testthat (>= 3.0.0)

VignetteBuilder knitr

biocViews SingleCell, Network, Visualization, CellBiology, SystemsBiology

Config/testthat/edition 3

git_url <https://git.bioconductor.org/packages/CCPlotR>

git_branch devel

git_last_commit 6e010b7

git_last_commit_date 2026-03-16

Repository Bioconductor 3.24

Date/Publication 2026-04-26

Author Sarah Ennis [aut, cre] (ORCID: <<https://orcid.org/0000-0001-6100-8573>>),
Pilib Ó Broin [aut],
Eva Szegezdi [aut]

Maintainer Sarah Ennis <ennissarah94@gmail.com>

Contents

| | |
|-------------------------|---|
| cc_arrow | 2 |
| cc_circos | 3 |
| cc_dotplot | 4 |
| cc_heatmap | 5 |
| cc_network | 5 |
| cc_sigmoid | 6 |
| geom_sigmoid | 7 |
| paletteMartin | 8 |
| StatSigmoid | 8 |
| toy_data | 9 |
| toy_exp | 9 |

| | |
|--------------|-----------|
| Index | 11 |
|--------------|-----------|

| | |
|----------|-----------------------------------|
| cc_arrow | <i>Paired Arrow Plot Function</i> |
|----------|-----------------------------------|

Description

This function plots interactions between a pair of cell types

Usage

```
cc_arrow(
  cc_df,
  cell_types = NULL,
  option = "A",
  n_top_ints = 15,
  exp_df = NULL,
  colours = setNames(paletteMartin(n = 2), cell_types),
  palette = "BuPu"
)
```

Arguments

| | |
|------------|---|
| cc_df | A dataframe with columns 'source', 'target', 'ligand', 'receptor' and 'score'. See toy_data for example. |
| cell_types | A vector of which two cell types to plot. |
| option | Either 'A' or 'B'. Option A will plot the top n_top_ints interactions between cell_types and their scores. Option B will plot the top n_top_ints interactions between cell_types, their scores and the expression of the ligand/receptor genes in the sender/receiver cell types. |
| n_top_ints | The number of top interactions to plot. |
| exp_df | A dataframe containing the mean expression values for each ligand/receptor in each cell type. See toy_exp for an example. Only required for option B. |
| colours | A named vector of colours for each cell type. Default is paletteMartin(), a colourblind-friendly palette. Only used for option A. |
| palette | Which colour palette to use to show the mean expression. Should be one of the RColorBrewer sequential palettes. Only used for option B. |

Value

Returns a plot generated with the ggplot2 package

Examples

```
data(toy_data, toy_exp, package = 'CCPlotR')
cc_arrow(toy_data, cell_types = c("B", "CD8 T"), colours = c(`B` = "hotpink", `CD8 T` = "orange"))
cc_arrow(toy_data,
  cell_types = c("NK", "CD8 T"), option = "B", exp_df = toy_exp,
  n_top_ints = 10, palette = "OrRd"
)
```

cc_circos

*Circos Plot Function***Description**

This function creates a circos plot

Usage

```
cc_circos(
  cc_df,
  option = "A",
  n_top_ints = 15,
  exp_df = NULL,
  cell_cols = NULL,
  palette = "BuPu",
  cex = 1,
  show_legend = TRUE,
  scale = FALSE,
  ...
)
```

Arguments

| | |
|------------|---|
| cc_df | A dataframe with columns 'source', 'target', 'ligand', 'receptor' and 'score'. See toy_data for example. |
| option | Either 'A', 'B' or 'C'. Option A will plot the number of interactions between pairs of cell types, option B will plot the top n_top_ints interactions and their scores. Option C will plot the top n_top_ints interactions, their scores and the mean expression of the ligands/receptors in the sending/receiver cell types. |
| n_top_ints | The number of top interactions to plot. Only required for options B and C. |
| exp_df | A dataframe containing the mean expression values for each ligand/receptor in each cell type. See toy_exp for an example. Only required for option C. |
| cell_cols | A named vector of colours for each cell type. Default uses paletteMartin(), a colourblind-friendly palette. |
| palette | Which colour palette to use to show the mean expression. Should be one of the RColorBrewer sequential palettes. |

| | |
|-------------|--|
| cex | Determines text size |
| show_legend | TRUE or FALSE - whether to add legend or not. Only required for options B and C. |
| scale | TRUE or FALSE - whether to scale each sector to same width. Only required for options B and C. |
| ... | Additional parameters passed to chordDiagram function. |

Value

Returns a chord diagram generated by the circlize R package

Examples

```
data(toy_data, toy_exp, package = 'CCPlotR')
cc_circos(toy_data)
cc_circos(toy_data, option = "B", n_top_ints = 10, cex = 0.5)
cc_circos(toy_data,
  option = "C", n_top_ints = 15, exp_df = toy_exp,
  cell_cols = c(`B` = "hotpink", `NK` = "orange", `CD8 T` = "cornflowerblue"),
  palette = "PuRd", cex = 0.5
)
```

cc_dotplot

Dotplot Function

Description

This function plots a dotplot

Usage

```
cc_dotplot(cc_df, option = "A", n_top_ints = 30)
```

Arguments

| | |
|------------|---|
| cc_df | A dataframe with columns 'source', 'target', 'ligand', 'receptor' and 'score'. See toy_data for example. |
| option | Either 'A', 'B', 'CellPhoneDB' or 'Liana'. Option A will plot the number of interactions between pairs of cell types, option B will plot the top n_top_ints interactions and their scores. The 'CellPhoneDB' and 'Liana' options will generate a dotplot in the style of these popular tools. |
| n_top_ints | The number of top interactions to plot. Only required for option B. |

Value

Returns a plot generated with the ggplot2 package

Examples

```
data(toy_data, package = 'CCPlotR')
cc_dotplot(toy_data)
cc_dotplot(toy_data, option = "B", n_top_ints = 10)
cc_dotplot(toy_data, option = "Liana", n_top_ints = 15)
```

| | |
|------------|-------------------------|
| cc_heatmap | <i>Heatmap Function</i> |
|------------|-------------------------|

Description

This plots a heatmap

Usage

```
cc_heatmap(cc_df, option = "A", n_top_ints = 30)
```

Arguments

| | |
|------------|--|
| cc_df | A dataframe with columns 'source', 'target', 'ligand', 'receptor' and 'score'. See <code>toy_data</code> for example. |
| option | Either 'A', 'B', 'CellPhoneDB' or 'Liana'. Option A will plot the number of interactions between pairs of cell types, option B will plot the top <code>n_top_ints</code> interactions and their scores. The 'CellPhoneDB' and 'Liana' options will generate a heatmap in the style of these popular tools. |
| n_top_ints | The number of top interactions to plot. Only required for option B. |

Value

Returns a plot generated with the `ggplot2` package

Examples

```
data(toy_data, package = 'CCPlotR')
cc_heatmap(toy_data)
cc_heatmap(toy_data, option = "B", n_top_ints = 10)
cc_heatmap(toy_data, option = "CellPhoneDB")
```

| | |
|------------|------------------------------|
| cc_network | <i>Network Plot Function</i> |
|------------|------------------------------|

Description

This function plots a network of representing the number of interactions between cell types

Usage

```
cc_network(  
  cc_df,  
  colours = paletteMartin(),  
  option = "A",  
  n_top_ints = 20,  
  node_size = 2.75,  
  label_size = 4,  
  layout = "kk"  
)
```

Arguments

| | |
|------------|--|
| cc_df | A dataframe with columns 'source', 'target', 'ligand', 'receptor' and 'score'. See toy_data for example. |
| colours | A vector of colours for each cell type. Default is paletteMartin(), a colourblind-friendly palette. |
| option | Either 'A' or 'B'. Option A will plot the number of interactions between pairs of cell types, option B will plot the top n_top_ints interactions and their scores. |
| n_top_ints | The number of top interactions to plot. Only required for option B. |
| node_size | Point size for nodes in option B. |
| label_size | Size for labels in option B. |
| layout | Algorithm for determining layout in option B. One of 'dh', 'drl', 'fr', 'gem', 'graphopt', 'kk', 'lgl', 'mds', 'nicely'. See iGraph layouts for more details. |

Value

Returns a plot generated with the ggplot2 package

Examples

```
data(toy_data, package = 'CCPlotR')
cc_network(toy_data)
cc_network(toy_data, colours = c("orange", "cornflowerblue", "hotpink"), option = "B")
```

cc_sigmoid

Sigmoid Plot Function

Description

This function plots interactions using the geom_sigmoid function from the ggbump R package

Usage

```
cc_sigmoid(cc_df, n_top_ints = 20, colours = paletteMartin())
```

Arguments

| | |
|------------|---|
| cc_df | A dataframe with columns 'source', 'target', 'ligand', 'receptor' and 'score'. See toy_data for example. |
| n_top_ints | The number of top interactions to plot. |
| colours | A named vector of colours for each cell type. Default is paletteMartin(), a colourblind-friendly palette. |

Value

Returns a plot generated with the ggplot2 package

Examples

```
data(toy_data, package = 'CCPlotR')
cc_sigmoid(toy_data)
cc_sigmoid(toy_data, colours = c(
  `B` = "hotpink", `CD8 T` = "orange",
  `NK` = "cornflowerblue"
), n_top_ints = 25)
```

geom_sigmoid

*geom_sigmoid This function is copied from the ggbump package***Description**

Creates a ggplot that makes a smooth rank over time. To change the smooth argument you need to put it outside of the aes of the geom. Uses the x, xend, y and yend aesthetics. Make sure each sigmoid curve is its own group.

Usage

```
geom_sigmoid(
  mapping = NULL,
  data = NULL,
  geom = "line",
  position = "identity",
  na.rm = FALSE,
  show.legend = NA,
  smooth = 8,
  direction = "x",
  inherit.aes = TRUE,
  ...
)
```

Arguments

| | |
|-------------|---|
| mapping | provide you own mapping. both x, xend, y and yend need to be numeric. |
| data | provide you own data |
| geom | xchange geom |
| position | change position |
| na.rm | remove missing values |
| show.legend | show legend in plot |
| smooth | how much smooth should the curve have? More means steeper curve. |
| direction | the character x or y depending of smoothing direction |
| inherit.aes | should the geom inherits aesthetics |
| ... | other arguments to be passed to the geom |

Value

ggplot layer

Examples

```
library(ggplot2)
df <- data.frame(x = 1:6,
  y = 5:10,
  xend = 7,
  yend = -3:2)

ggplot(df, aes(x = x, xend = xend, y = y, yend = yend, color = factor(x))) +
  geom_sigmoid()
```

paletteMartin *Discrete palette generator*

Description

Generate a palette of up to 15 colours. The colours are from the paletteMartin palette in the color-Blindness R package.

Usage

```
paletteMartin(n = 15)
```

Arguments

n Number of colours to return. Max = 15.

Value

Returns a vector of colours of length n.

Examples

```
scales::show_col(paletteMartin(n = 9))
```

StatSigmoid *This function is copied from the ggbump package*

Description

This function is copied from the ggbump package

| | |
|----------|-----------------------------|
| toy_data | <i>Toy data for CCPlotR</i> |
|----------|-----------------------------|

Description

A toy dataset of ligand-receptor interactions to demonstrate cell-cell interaction plots.

Usage

```
toy_data
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 735 rows and 5 columns.

Value

`toy_data`:

A data frame with 735 rows and 5 columns:

source Cell type expressing the ligand

target Cell type expressing the receptor

ligand Ligand

receptor Receptor

score A score for each interaction e.g. $-\log_{10}(\text{aggregate_rank})$ returned by Liana

Source

This is a modified version of the toy dataset that comes with the Liana R package.

| | |
|---------|--|
| toy_exp | <i>Toy expression data for CCPlotR</i> |
|---------|--|

Description

A dataframe showing the mean expression values for each ligand and receptor in each cell type.

Usage

```
toy_exp
```

Format

An object of class `grouped_df` (inherits from `tbl_df`, `tbl`, `data.frame`) with 477 rows and 3 columns.

Value

toy_exp:

A data frame with 477 rows and 3 columns:

cell_type Cell type

gene Ligand/receptor gene

mean_exp Mean (normalised) expression of ligand/receptor gene in cell type

Index

* datasets

StatSigmoid, 8

toy_data, 9

toy_exp, 9

cc_arrow, 2

cc_circos, 3

cc_dotplot, 4

cc_heatmap, 5

cc_network, 5

cc_sigmoid, 6

geom_sigmoid, 7

paletteMartin, 8

StatSigmoid, 8

toy_data, 9

toy_exp, 9