

Package ‘ngsReports’

September 10, 2025

Version 2.11.0

Date 2025/03/01

Title Load FastqQC reports and other NGS related files

Description This package provides methods and object classes for parsing FastQC reports and output summaries from other NGS tools into R. As well as parsing files, multiple plotting methods have been implemented for visualising the parsed data. Plots can be generated as static ggplot objects or interactive plotly objects.

URL <https://github.com/smped/ngsReports>

BugReports <https://github.com/smped/ngsReports/issues>

License LGPL-3

Encoding UTF-8

Depends R (>= 4.2.0), BiocGenerics, ggplot2 (>= 3.5.0), patchwork (>= 1.1.1), tibble (>= 1.3.1)

Imports Biostrings, checkmate, dplyr (>= 1.1.0), forcats, ggdendro, grDevices (>= 3.6.0), grid, jsonlite, lifecycle, lubridate, methods, plotly (>= 4.9.4), reshape2, rlang, rmarkdown, scales, stats, stringr, tidyr, tidyselect (>= 0.2.3), utils, zoo

LazyData true

RoxygenNote 7.3.2

Collate 'AllGenerics.R' 'validationFunctions.R' 'FastpData.R' 'FastpDataList.R' 'FastpFile.R' 'FastqcData.R' 'FastqcDataList.R' 'FastqcFile.R' 'PwfCols.R' 'S4coercion.R' 'TheoreticalGC.R' 'aaa.R' 'data.R' 'errMsg.R' 'estGcDistn.R' 'extract.R' 'fqName.R' 'fqVersion.R' 'getColours.R' 'getGC.R' 'getModule.R' 'getSummary.R' 'helpers.R' 'importNgsLogs.R' 'importSJ.R' 'isCompressed.R' 'maxAdapterContent.R' 'ngsReports-package.R' 'overRep2Fasta.R' 'path.R' 'plotAdapterContent.R' 'plotAlignmentSummary.R' 'plotAssemblyStats.R' 'plotBaseQuals.R' 'plotDupLevels.R' 'plotFastqcPCA.R' 'plotGcContent.R' 'plotInsertSize.R' 'plotKmers.R' 'plotNContent.R' 'plotOverrep.R' 'plotReadTotals.R' 'plotSeqContent.R' 'plotSeqLengthDistn.R' 'plotSeqQuals.R' 'plotSummary.R' 'pwf.R' 'readTotals.R' 'summariseOverrep.R' 'writeHtmlReport.R'

VignetteBuilder knitr

Suggests BiocStyle, Cairo, DT, knitr, pander, readr, testthat,
truncnorm

biocViews QualityControl, ReportWriting

RdMacros lifecycle

Roxygen list(markdown = TRUE)

git_url <https://git.bioconductor.org/packages/ngsReports>

git_branch devel

git_last_commit 299c66a

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-09-09

Author Stevie Pederson [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-8197-3303>>),
Christopher Ward [aut],
Thu-Hien To [aut]

Maintainer Stevie Pederson <stephen.pederson.au@gmail.com>

Contents

.addPercent	4
.emptyPlot	4
.FastpFile-class	5
.FastqcFile-class	5
.getToolName	6
.hidePWFRects	6
.makeDendro	7
.makeLabels	7
.makePwfGradient	8
.makeSidebar	9
.parseAdapterRemovalLogs	10
.parseBowtieLogs	10
.parseBuscoLogs	11
.parseCutadaptLogs	11
.parseDuplicationMetricsLogs	12
.parseFeatureCountsLogs	12
.parseFlagstatLogs	13
.parseHisat2Logs	13
.parseMacs2CallpeakLogs	14
.parseQuastLogs	14
.parseRnaseqcMetricsLogs	15
.parseSalmonLibFormatCountsLogs	15
.parseSalmonMetaInfoLogs	16
.parseStarLogs	16
.parseTrimmomaticLogs	17
.parseUmitoolsDedupLogs	17
.prepHeatmap	18
.renderDendro	18

.splitByTab	19
.updateThemeFromDots	19
estGcDistn	20
FastpData-class	21
FastpDataList-class	22
FastqcData-class	22
FastqcDataList-class	23
fqVersion, FastqcData-method	24
fqName	25
gcAvail	26
gcTheoretical	27
getColours	27
getGC	28
getModule, FastqcData-method	29
getSummary, FastqcFile-method	30
importNgsLogs	31
importSJ	32
isCompressed	33
maxAdapterContent	34
mData	35
overRep2Fasta	35
path	36
plotAdapterContent	37
plotAlignmentSummary	40
plotAssemblyStats	41
plotBaseQuals	42
plotDupLevels	45
plotFastqcPCA	48
plotGcContent	50
plotInsertSize	54
plotKmers	55
plotNContent	58
plotOverrep	61
plotReadTotals	63
plotSeqContent	65
plotSeqLengthDistn	68
plotSeqQuals	71
plotSummary	74
pwf	75
PwfCols-class	76
readTotals	77
summariseOverrep	77
TheoreticalGC-class	79
writeHtmlReport	80
[, FastqcDataList, numeric, missing-method	81

<code>.addPercent</code>	<i>Add a percentage sign</i>
--------------------------	------------------------------

Description

Add a percentage sign to the end of a string

Usage

```
.addPercent(x)
```

Arguments

<code>x</code>	Any vector
----------------	------------

Value

character vector

Examples

```
x <- 1:10  
ngsReports:::addPercent(x)
```

<code>.emptyPlot</code>	<i>Create an empty plot with supplied text</i>
-------------------------	--

Description

Create an empty plot with supplied text

Usage

```
.emptyPlot(x)
```

Details

Create plot using `theme_void` and only with the supplied text

Value

A `ggplot2` object

Examples

```
ngsReports:::emptyPlot("This is an empty plot")
```

<i>.FastpFile-class</i>	<i>The .FastpFile Object Class</i>
-------------------------	------------------------------------

Description

The *.FastpFile* Object Class defines a path to the output from the standalone tool fastp. **[Experimental]**

Arguments

x character(1) denoting a file.path

Details

This class simply refers to a fastp output file after checking for existence and validity (i.e. the correct internal structure). Underlying files are expected to be in json format

The helper function *.FastpFile()* is a simple constructor which checks validity and enables construction of other dependent classes.

Value

An object of class *.FastqcFile*

Slots

path Character vector of length 1 which contains a valid file path.

<i>.FastqcFile-class</i>	<i>The .FastqcFile Object Class</i>
--------------------------	-------------------------------------

Description

The *.FastqcFile* Object Class defines a path to the output from the standalone tool FastQC. **[Stable]**

Arguments

x character(1) denoting a file.path

Details

This class simply refers to a fastqc output file after checking for existence and validity (i.e. the correct internal structure). Underlying files can be zipped (*_fastqc.zip) or extracted directories

The helper function *.FastqcFile()* is a simple constructor which checks validity and enables construction of other dependent classes.

Value

An object of class *.FastqcFile*

Slots

path Character vector of length 1 which contains a valid file path.

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)[1]

# As this is the root structure, we can only call this
# function with an individual file
ff <- ngsReports:::.FastqcFile(fl)
```

<code>.getToolName</code>	<i>Identify tool name</i>
---------------------------	---------------------------

Description

Identify tool name for log files after reading in using readLines.

Usage

```
.getToolName(x, possTypes)
```

Arguments

x Character vector as output when readLines to a supplied log file

Details

Checks for all the required fields in the lines provided

Value

logical(1)

<code>.hidePWFRects</code>	<i>Hide PWF tooltips from line plots</i>
----------------------------	--

Description

Hide tooltips from PWF rectangles in line plots

Usage

```
.hidePWFRects(x)
```

Arguments

x plotlyObject\$x\$data

Value

plotlyObject\$x\$data

.makeDendro	<i>Make the dendrogram for heatmap-style plots</i>
-------------	--

Description

Set the clusters for heatmap-style interactive plots

Usage

```
.makeDendro(df, rowVal, colVal, value)
```

Arguments

df	The data frame to be clustered
rowVal	The rows to be clustered
colVal	The value which will become column names
value	The value to use for the clustering

Value

A dendrogram

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fileList <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)
cols <- c("Filename", "Position", "Illumina_Universal_Adapter")
ac <- getModule(fileList, "Adapter_Content")[cols]
ngsReports:::makeDendro(df = ac,
                        rowVal = "Filename",
                        colVal = "Position",
                        value = "Illumina_Universal_Adapter")
```

.makeLabels	<i>Perform the checks and return the labels</i>
-------------	---

Description

Checks for the presence of labels and returns defaults

Usage

```
.makeLabels(
  x,
  labels,
  pattern = "(fast|fq|bam|sam|cram).*",
  col = "Filename",
  ...
)
```

Arguments

<code>x</code>	A data.frame with a column titled "Filename"
<code>labels</code>	Named vector of labels for plotting
<code>pattern</code>	character Regular expression to remove from filenames
<code>col</code>	character Column to use for generating labels
<code>...</code>	Not used

Details

Takes a named vector of labels and checks for the correct fields. If no vector is supplied, returns the file names missing the specified pattern, which defaults to removing the suffixes fastq(.gz), fq(.gz), bam, sam or cram.

Value

Named character vector

Examples

```
f <- paste0(c("File1", "File2"), ".fastq")
df <- data.frame(Filename = f, stringsAsFactors = FALSE)
ngsReports:::makeLabels(df)
```

.makePwfGradient

Construct a gradient using PwfCols

Description

Construct a gradient using PwfCols

Usage

```
.makePwfGradient(
  vals,
  pwfCols,
  breaks = c(0, 5, 10, 100),
  passLow = TRUE,
  na.value = "white"
)
```

Arguments

<code>vals</code>	The values which need to have the scale generated
<code>pwfCols</code>	An object of class <code>PwfCols</code>
<code>breaks</code>	The breaks for the PWF bins
<code>passLow</code>	Is the PASS category at the low or high end of the numeric range
<code>na.value</code>	The colour to plot for missing values

Details

This constructs a list of arguments for passing to `scale_fill_gradientn()` using the values contained in the fill aesthetic and the supplied breaks for PASS/WARN/FAIL criteria.

Value

Returns a ggplot list

<code>.makeSidebar</code>	<i>Shortcut for making the status sidebar</i>
---------------------------	---

Description

Shortcut for making the status sidebar

Usage

```
.makeSidebar(status, key, pwfCols, usePlotly = TRUE)
```

Arguments

<code>status</code>	A data.frame with columns 'Filename' & 'Status'
<code>key</code>	A vector of values corresponding to the Filename column
<code>pwfCols</code>	An object of class <code>PwfCols</code>
<code>usePlotly</code>	If TRUE, output is a plotly panel

Value

if `usePlotly = TRUE`, a plotly object. The sidebar for an interactive plot showing PASS/WARN/FAIL status for each file. If `usePlotly = FALSE` the underlying ggplot object will be returned.

`.parseAdapterRemovalLogs`*Parse data from Adapter Removal log files*

Description

Parse data from Adapter Removal log files

Usage

```
.parseAdapterRemovalLogs(data, which = 3)
```

Arguments

<code>data</code>	List of lines read using <code>readLines</code> on one or more files
<code>which</code>	which element of the log file to return. Can be 1:4, "sequences", "settings", "statistics" or "distribution"

Details

Checks for structure will have been performed

Value

tibble

`.parseBowtieLogs`*Parse data from Bowtie log files*

Description

Parse data from Bowtie log files

Usage

```
.parseBowtieLogs(data, ...)
```

Arguments

<code>data</code>	List of lines read using <code>readLines</code> on one or more files
<code>...</code>	Not used

Details

Checks for structure will have been performed

Value

data.frame

.parseBuscoLogs	<i>Parse data from BUSCO log files</i>
-----------------	--

Description

Parse data from BUSCO log files

Usage

```
.parseBuscoLogs(data, ...)
```

Arguments

data	List of lines read using readLines on one or more files
...	Not used

Details

Checks for structure will have been performed

Value

data.frame

.parseCutadaptLogs	<i>Parse data from cutadapt log files</i>
--------------------	---

Description

Parse data from cutadapt log files

Usage

```
.parseCutadaptLogs(data, which = 1)
```

Arguments

data	List of lines read using readLines on one or more files
which	which element of the log file to return. Can be summary, adapter1, adapter2, adapter3 or overview, or any integer in 1:5

Details

Checks for structure will have been performed

Value

tibble

`.parseDuplicationMetricsLogs`*Parse data from Picard duplicationMetrics log files*

Description

Parse data from Picard duplicationMetrics log files

Usage

```
.parseDuplicationMetricsLogs(data, which = 1)
```

Arguments

<code>data</code>	List of lines read using readLines on one or more files
<code>which</code>	which element of the log file to return. Can be 1:2, "metrics" or "histogram"

Details

Checks for structure will have been performed

Value

tibble

`.parseFeatureCountsLogs`*Parse data from featureCounts summary files*

Description

Parse data from featureCounts summary files

Usage

```
.parseFeatureCountsLogs(data, ...)
```

Arguments

<code>data</code>	List of lines read using readLines on one or more files
<code>...</code>	Not used

Details

Checks for structure will have been performed

Value

tibble

<code>.parseFlagstatLogs</code>	<i>Parse data from samtools flagstat files</i>
---------------------------------	--

Description

Parse data from samtools flagstat files

Usage

```
.parseFlagstatLogs(data, ...)
```

Arguments

<code>data</code>	List of lines read using <code>readLines</code> on one or more files
<code>...</code>	Not used

Details

Checks for structure will have been performed

Value

`data.frame`

<code>.parseHisat2Logs</code>	<i>Parse data from HISAT2 log files</i>
-------------------------------	---

Description

Parse data from HISAT2 log files

Usage

```
.parseHisat2Logs(data, ...)
```

Arguments

<code>data</code>	List of lines read using <code>readLines</code> on one or more files
<code>...</code>	Not used

Details

Checks for structure will have been performed

Value

`data.frame`

`.parseMacs2CallpeakLogs`*Parse data from macs2 callpeak log files*

Description

Parse data from macs2 callpeak log files

Usage

```
.parseMacs2CallpeakLogs(data, ...)
```

Arguments

<code>data</code>	List of lines read using <code>readLines</code> on one or more files
<code>...</code>	Not used

Details

Checks for structure will have been performed

Value

`data.frame`

`.parseQuastLogs`*Parse data from BUSCO log files*

Description

Parse data from BUSCO log files

Usage

```
.parseQuastLogs(data, ...)
```

Arguments

<code>data</code>	List of lines read using <code>readLines</code> on one or more files
<code>...</code>	Not used

Details

Checks for structure will have been performed

Value

`data.frame`

`.parseRnaseqcMetricsLogs`*Parse data from rnaseqc metrics files*

Description

Parse data from rnaseqc metrics files

Usage

```
.parseRnaseqcMetricsLogs(data, ...)
```

Arguments

<code>data</code>	List of lines read using <code>readLines</code> on one or more files
<code>...</code>	Not used

Details

Checks for structure will have been performed

Value

`data.frame`

`.parseSalmonLibFormatCountsLogs`*Parse data from salmon lib_format_counts.json files*

Description

Parse data from salmon lib_format_counts.json files

Usage

```
.parseSalmonLibFormatCountsLogs(data, ...)
```

Arguments

<code>data</code>	List of lines read using <code>readLines</code> on one or more files
<code>...</code>	Not used

Details

Checks for structure will have been performed

Value

`data.frame`

`.parseSalmonMetaInfoLogs`*Parse data from salmon meta_info.json files*

Description

Parse data from salmon meta_info.json files

Usage

```
.parseSalmonMetaInfoLogs(data, ...)
```

Arguments

<code>data</code>	List of lines read using readLines on one or more files
<code>...</code>	Not used

Details

Checks for structure will have been performed

Value

`data.frame`

`.parseStarLogs`*Parse data from STAR log files*

Description

Parse data from STAR log files

Usage

```
.parseStarLogs(data, ...)
```

Arguments

<code>data</code>	List of lines read using readLines on one or more files
<code>...</code>	Not used

Details

Checks for structure will have been performed

Value

`tibble`

`.parseTrimmomaticLogs` *Parse data from trimmomatic log files*

Description

Parse data from trimmomatic log files

Usage

```
.parseTrimmomaticLogs(data, ...)
```

Arguments

<code>data</code>	List of lines read using <code>readLines</code> on one or more files
<code>...</code>	not used

Details

Checks for structure will have been performed

Value

tibble

`.parseUmiToolsDedupLogs`
Parse data from umi_tools dedup files

Description

Parse data from umi_tools dedup files

Usage

```
.parseUmiToolsDedupLogs(data, ...)
```

Arguments

<code>data</code>	List of lines read using <code>readLines</code> on one or more files
<code>...</code>	Not used

Details

Checks for structure will have been performed

Value

`data.frame`

<code>.prepHeatmap</code>	<i>Prepare the final heatmap for plotting</i>
---------------------------	---

Description

Add dendrogram & status bar to ggplot2 heatmap

Usage

```
.prepHeatmap(x, status, segments, usePlotly, heat_w = 8, pwf, hv = NULL)
```

Arguments

<code>x</code>	a ggplot2 heatmap produced by ngsReports
<code>status</code>	a tibble with the columns Filename and Status
<code>segments</code>	a dendrogram produced during clustering of samples
<code>usePlotly</code>	logical(1)
<code>hv</code>	character vector of fields to include in hoverinfo

Value

Either a ggplot2 object assembled using patchwork, or an interactive plotly object

<code>.renderDendro</code>	<i>Set up dendrograms for interactive plots</i>
----------------------------	---

Description

A commonly used (hidden) function for setting up dendrograms for interactive plots. based on code found at <https://plot.ly/ggplot2/ggdendro-dendrograms/>

Usage

```
.renderDendro(df)
```

Arguments

<code>df</code>	A data.frame as required
-----------------	--------------------------

Details

Create plot using theme_dendro

Value

A plotly object

<code>.splitByTab</code>	<i>Split elements of a vector into a data.frame</i>
--------------------------	---

Description

Split elements of a character vector by the tab separator

Usage

```
.splitByTab(x, firstRowToNames = TRUE, tab = "\\t")
```

Arguments

<code>x</code>	A character vector
<code>firstRowToNames</code>	logical Should the first element be used for column names
<code>tab</code>	character The string used to represent the tab symbol

Details

This will split a vector into a data.frame checking that every line has the same number of separators. By default the first element will be set as the column names.

This is designed to take input from `readLines()`

Value

A data frame

Examples

```
x <- c("ColA\\tColB", "Value1\\tValue2")
ngsReports:::splitByTab(x, firstRowToNames = TRUE)
ngsReports:::splitByTab(x, firstRowToNames = FALSE)
```

<code>.updateThemeFromDots</code>	<i>Add custom theme elements from dotArgs</i>
-----------------------------------	---

Description

Add custom theme elements from dotArgs

Usage

```
.updateThemeFromDots(p, ...)
```

Arguments

<code>p</code>	ggplot object
<code>...</code>	Standard dot arguments

Value

ggplot2 object

estGcDistn

Estimate a GC Content Distribution From Sequences

Description

Generate a GC content distribution from sequences for a given read length and fragment length

Usage

```
estGcDistn(x, n = 1e+06, rl = 100, fl = 200, fragSd = 30, bins = 101, ...)
```

```
## S4 method for signature 'ANY'
```

```
estGcDistn(x, n = 1e+06, rl = 100, fl = 200, fragSd = 30, bins = 101, ...)
```

```
## S4 method for signature 'character'
```

```
estGcDistn(x, n = 1e+06, rl = 100, fl = 200, fragSd = 30, bins = 101, ...)
```

```
## S4 method for signature 'DNAStrngSet'
```

```
estGcDistn(x, n = 1e+06, rl = 100, fl = 200, fragSd = 30, bins = 101, ...)
```

Arguments

x	DNAStrngSet or path to a fasta file
n	The number of reads to sample
rl	Read Lengths to sample
fl	The mean of the fragment lengths sequenced
fragSd	The standard deviation of the fragment lengths being sequenced
bins	The number of bins to estimate
...	Not used

Details

The function takes the supplied object and returns the theoretical GC content distribution. Using a fixed read length essentially leads to a discrete distribution so the bins argument is used to define the number of bins returned. This defaults to 101 for 0 to 100% inclusive.

The returned values are obtained by interpolating the values obtained during sampling. This avoids returned distributions with gaps and jumps as would be obtained setting readLengths at values not in multiples of 100.

Based heavily on <https://github.com/mikelove/fastqcTheoreticalGC>

Value

A tibble with two columns: GC_Content and Freq denoting the proportion of GC and frequency of occurrence respectively

Examples

```
faDir <- system.file("extdata", package = "ngsReports")
faFile <- list.files(faDir, pattern = "fasta", full.names = TRUE)
df <- estGcDistn(faFile, n = 200)
```

FastpData-class

*The FastpData Object Class***Description**

The FastpData Object Class **[Experimental]**

Usage

```
FastpData(x)
```

Arguments

x Path to a single zip archive or extracted folder for a individual fastp report.

Details

This object class is the main object required for generating plots and tables. Instantiation will first check for a .json file with the correct data structure, and will then parse all the data into R as a FastpData object. Fastp modules are contained as individual slots, which can be viewed using slotNames. Sub-modules are also contained within many larger modules with modules being based on the sections within a fastp html report

Individual modules can be returned using the function `getModule()` and specifying which module/sub-module is required. See [getModule\(\)](#) for more details.

Value

An object of class FastpData

Slots

Summary Contains three submodules 1) Before_filtering, 2) After_filtering and 3) Filtering_result.

All values presented in the initial table for individual fastp reports are contained in other sections of the report

Adapters Contains a tibble with all data from this module

Duplication Contains a tibble with all duplication results

Insert_size Contains a tibble with all insert size estimates

Before_filtering, After_filtering The modules can be selected for either Read1 or Read2

paired logical(1) indicating whether the file is from paired-end sequencing

command character(1) with the executed command

version character(1) with the fastp version being used

path Path to the Fastp report

FastpDataList-class *The FastpDataList Object Class*

Description

The FastpDataList Object Class **[Stable]**

Usage

```
FastpDataList(x)
```

Arguments

x Character vector of file paths specifying paths to fastp.json.gz output

Value

An object of class FastpDataList

Slots

... this can either be a single character vector of paths to fastp files, or several instances of .Fastp-File objects

FastqcData-class *The FastqcData Object Class*

Description

The FastqcData Object Class **[Stable]**

Usage

```
FastqcData(x)
```

Arguments

x Path to a single zip archive or extracted folder for a individual FastQC report.

Details

This object class is the main object required for generating plots and tables. Instantiation will first test for a compressed file (or extracted directory) with the correct data structure, and will then parse all the data into R as a FastqcData object. FastQC modules are contained as individual slots, which can be viewed using slotNames.

Individual modules can be returned using the function `getModule()` and specifying which module is required. See [getModule\(\)](#) for more details.

Value

An object of class FastqcData

Slots

Summary Summary of PASS/WARN/FAIL status for each module

Basic_Statistics The Basic_Statistics table from the top of a FastQC html report

Per_base_sequence_quality The underlying data from the Per_base_sequence_quality module

Per_sequence_quality_scores The underlying data from the Per_sequence_quality_scores module

Per_base_sequence_content The underlying data from the Per_base_sequence_content module

Per_sequence_GC_content The underlying data from the Per_sequence_GC_content module

Per_base_N_content The underlying data from the Per_base_N_content module

Sequence_Length_Distribution The underlying data from the Sequence_Length_Distribution module

Sequence_Duplication_Levels The underlying data from the Sequence_Duplication_Levels module

Overrepresented_sequences The underlying data from the Overrepresented_sequences module

Adapter_Content The underlying data from the Adapter_Content module

Kmer_Content The underlying data from the Kmer_Content module

Total_Deduplicated_Percentage Estimate taken from the plot data for Sequence_Duplication_Levels. Only included in later versions of FastQC

version The version of FastQC used for generation of the report (if available)

path Path to the FastQC report

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)[1]

# Load the FASTQC data as a FastqcData object
fd <- FastqcData(fl)
fd
```

FastqcDataList-class *The FastqcDataList Object Class*

Description

The FastqcDataList Object Class **[Stable]**

Usage

```
FastqcDataList(x)
```

Arguments

x Character vector of file paths specifying paths to FastQC reports

Value

An object of class FastqcDataList

Slots

... this can either be a single character vector of paths to FASTQC files, or several instances of .FastqcFile objects

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)
fdl
```

fqVersion, FastqcData-method
Get the FASTQC version

Description

Get the FASTQC version used to generate the initial files

Usage

```
## S4 method for signature 'FastqcData'
fqVersion(object)

## S4 method for signature 'FastqcDataList'
fqVersion(object)

## S4 method for signature 'ANY'
fqVersion(object)
```

Arguments

object An object of class FastqcData or FastqcDataList

Value

A character vector (FastqcData), or tibble (FastqcDataList)

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)

# Get the FASTQC version
fqVersion(fdl)
```

fqName	<i>Return the Underlying Fastq File Names from Fastqc/Fastp Objects</i>
--------	---

Description

Return the Underlying Fastq File Names from Fastqc/Fastp Objects

Usage

```
fqName(object)

## S4 method for signature 'ANY'
fqName(object)

## S4 method for signature 'FastqcData'
fqName(object)

## S4 method for signature 'FastqcDataList'
fqName(object)

fqName(object) <- value

## S4 replacement method for signature 'FastqcData'
fqName(object) <- value

## S4 replacement method for signature 'FastqcDataList'
fqName(object) <- value

## S4 method for signature 'FastpData'
fqName(object)

## S4 method for signature 'FastpDataList'
fqName(object)
```

Arguments

object	An object able to extract an Fastq name from
value	Replacement value for fqName

Value

Returns the names of the Fastq files the FastQC report was generated from, without any preceding directories.

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)
fqName(fdl)

nm <- paste0(letters[seq_along(fdl)], ".fq")
fqName(fdl) <- nm
fqName(fdl)
```

gcAvail

*List Genomes or Transcriptomes with Theoretical GC Content***Description**

List available genomes or transcriptomes in a TheoreticalGC object

Usage

```
gcAvail(object, type)

## S4 method for signature 'TheoreticalGC'
gcAvail(object, type)
```

Arguments

object	An object of class TheoreticalGC
type	character indicating either Genome or Transcriptome

Details

An object of class TheoreticalGC can hold the theoretical GC content for one or more species, for either the genome or transcriptome. This function checks which species are available in the given object, for either the genome or transcriptome, as supplied to the parameter type.

Value

A tibble object

Examples

```
gcAvail(gcTheoretical, "Genome")
```

gcTheoretical	<i>Theoretical GC content</i>
---------------	-------------------------------

Description

This object contains the theoretical GC content for each provided species, for both the genome and transcriptome, where available.

Usage

```
gcTheoretical
```

Format

An object of class TheoreticalGC of length 1.

Details

The object is defined with the S4 class TheoreticalGC. Species for which information is available can be found using the command `gcAvail(gcTheoretical)` and selecting the appropriate type.

Metadata is accessible using `mData(gcTheoretical)`.

All GC content was calculated using code from <https://github.com/mikelove/fastqcTheoreticalGC> using BSgenome packages. This provides a default set of GC content data for common organisms generated using 100bp reads/fragments and 1e6 reads.

See Also

`gcAvail`

Examples

```
## Check which genomes are included
gcAvail(gcTheoretical, "Genome")

## Check which transcriptomes are included
gcAvail(gcTheoretical, "Transcriptome")
```

getColours	<i>Work with objects of class PwfCols</i>
------------	---

Description

Get and modify colours from objects of class PwfCols

Usage

```
## S4 method for signature 'PwfCols'
getColours(object)

## S4 method for signature 'PwfCols'
setColours(object, PASS, WARN, FAIL, MAX)

## S4 method for signature 'PwfCols'
setAlpha(object, alpha)
```

Arguments

object	An object of class PwfCols
PASS	The colour denoting PASS on all plots, in rgb format
WARN	The colour denoting WARN on all plots, in rgb format
FAIL	The colour denoting FAIL on all plots, in rgb format
MAX	The colour denoting the limit of values in rgb format
alpha	Numeric(1). Ranges from 0 to 1 by default, but can also be on the range 0 to 255.

Details

Use `getColours` to obtain the colours in an object of class `PwfCols`.
 These can be modified using the functions `setColours` and `setAlpha`

Value

`getColours` will return a character vector of colours corresponding to PASS/WARN/FAIL
`setColours` will return an object of class `PwfCols`
`setAlpha` will return an object of class `PwfCols`

Examples

```
getColours(pwf)

# How to add transparency
pwf2 <- setAlpha(pwf, 0.1)
getColours(pwf2)
```

getGC

Get Theoretical GC content

Description

Get the GC content data from a `TheoreticalGC` object

Usage

```
getGC(object, name, type)

## S4 method for signature 'ANY'
getGC(object, type)

## S4 method for signature 'TheoreticalGC'
getGC(object, name, type)
```

Arguments

object	An object of class Theoretical GC
name	The Name of the species in 'Gspecies' format, e.g. Hsapiens
type	The type of GC content. Can only be either "Genome" or "Transcriptome"

Value

A tibble object

Examples

```
getGC(gcTheoretical, name = "Hsapiens", type = "Genome")
```

```
getModule, FastqcData-method
```

Retrieve a given module from a Fastqc Object*

Description

Retrieve a specific module from a Fastqc* object as a data.frame

Usage

```
## S4 method for signature 'FastqcData'
getModule(object, module)

## S4 method for signature 'FastqcDataList'
getModule(object, module)

## S4 method for signature 'ANY'
getModule(object, module)

## S4 method for signature 'FastpData'
getModule(object, module)

## S4 method for signature 'FastpDataList'
getModule(object, module)
```

Arguments

object	Can be a FastqcData, fastqcDataList, or simply a character vector of paths
module	The requested module as contained in a FastQC report. Possible values are Summary, Basic_Statistics, Per_base_sequence_quality, Per_tile_sequence_quality, Per_sequence_quality_scores, Per_base_sequence_content, Per_sequence_GC_content, Per_base_N_content, Sequence_Length_Distribution, Sequence_Duplication_Levels, Overrepresented_sequences, Adapter_Content, Kmer_Content, Total_Deduplicated_Percent. Note that spelling and capitalisation is exactly as contained within a FastQC report, with the exception that spaces have been converted to underscores. Partial matching is implemented for this argument.

Details

This function will return a given module from a Fastqc* object as a data.frame. Note that each module will be it's own unique structure, although all will return a data.frame

Value

A single tibble containing module-level information from all FastQC reports contained in the Fastqc* object.

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)

# Extract the Summary module, which corresponds to the PASS/WARN/FAIL flags
getModule(fdl, "Summary")

# The Basic_Statistics module corresponds to the table at the top of each
# FastQC report
getModule(fdl, "Basic_Statistics")
```

```
getSummary,.FastqcFile-method
```

Get the summary information from Fastqc Files

Description

Read the information from the summary.txt files in each .FastqcFile

Usage

```
## S4 method for signature '.FastqcFile'
getSummary(object)

## S4 method for signature 'ANY'
```

```
getSummary(object)

## S4 method for signature 'FastqcData'
getSummary(object)

## S4 method for signature 'FastqcDataList'
getSummary(object)
```

Arguments

object Can be a FastqcData, FastqcDataList object or a vector of paths to unparsed FastQC reports.

Details

This simply extracts the summary of PASS/WARN/FAIL status for every module as defined by the tool FastQC for each supplied file.

Value

A tibble containing the PASS/WARN/FAIL status for each module, as defined in a FastQC report.

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)

# Return a tibble/tibble with the raw information
getSummary(fdl)
```

importNgsLogs	<i>Import Various NGS-related log files</i>
---------------	---

Description

[Maturing] Imports NGS-related log files such as those generated from stderr.

Usage

```
importNgsLogs(x, type = "auto", which, stripPaths = TRUE)
```

Arguments

x character. Vector of filenames. All log files must be of the same type. Duplicate file paths will be silently ignored.

type	character. The type of file being imported. Can be one of bowtie, bowtie2, hisat2, star, flagstat, featureCounts, duplicationMetrics, cutadapt, umitoolsDedup, macs2Callpeak, adapterRemoval, rnaseqMetrics, quast, salmonLibFormatCounts, salmonMetaInfo or busco. Defaults to type = "auto" which will automatically detect the file type for all implemented types.
which	Which element of the parsed object to return. Ignored in all file types except when type is set to duplicationMetrics, cutadapt or adapterRemoval. See details for possible values. To return all elements, set this value to 'all'
stripPaths	logical(1). Remove paths from the Filename column

Details

Imports one or more log files as output by tools such as: bowtie, bowtie2, featureCounts, Hisat2, STAR, salmonpicard MarkDuplicates, cutadapt, flagstat, macs2Callpeak, Adapter Removal, trimmomatic, rnaseqMetrics, quast or busco. autoDetect can be used to detect the log type by parsing the file.

The featureCounts log file corresponds to the counts.out.summary, not the main counts.out file.

Whilst most log files return a single tibble, some are more complex with multiple modules.

adapterRemoval can return one of four modules (which = 1:4). When calling by name, the possible values are sequences, settings, statistics or distribution. Partial matching is implemented.

cutadapt can return one of five modules (which = 1:5). When calling by name the possible modules are summary, adapter1, adapter2, adapter3 or overview. Note that adapter2/3 may be missing from these files depending on the nature of your data. If cutadapt log files are obtained using report=minimal, all supplied log files must be of this format and no modules can be returned.

duplicationMetrics will return either the metrics of histogram. These can be requested by setting which as 1 or 2, or naming either module.

Value

A tibble. Column names are broadly similar to the text in supplied files, but have been modified for easier handling under R naming conventions.

Examples

```
f <- c("bowtiePE.txt", "bowtieSE.txt")
bowtieLogs <- system.file("extdata", f, package = "ngsReports")
df <- importNgsLogs(bowtieLogs, type = "bowtie")
```

importSJ

Import STAR Splice Junctions

Description

Import the SJ.out.tab files produced by STAR

Usage

```
importSJ(x, stripPaths = TRUE)
```

Arguments

`x` vector of file paths to SJ.out.tab files

`stripPaths` logical(1) Remove directory prefixes from the file paths in `x`

Details

Imports one or more splice-junction output files as produced by STAR. If all are located in separated directories with identical names, be sure to set the argument `stripPaths = FALSE`

All co-ordinates are 1-based, in keeping with the STAR manual

Value

A tibble

Examples

```
sjFiles <- system.file("extdata", "SJ.out.tab", package = "ngsReports")
# Import leaving the complete file path in the column Filename
# The argument stripPaths is set as TRUE by default
df <- importSJ(sjFiles, stripPaths = FALSE)
```

isCompressed	<i>Check to see if a file is compressed</i>
--------------	---

Description

Check to see if a file, or vector of files is compressed

Usage

```
isCompressed(path, type = c("zip", "gzip"), verbose = FALSE)
```

Arguments

`path` The path to one or more files

`type` The type of compression to check for. Currently only ZIP/GZIP files have been implemented.

`verbose` logical/integer Determine the level of output to show as messages

Details

Reads the first four bytes from the local file header. If the file is a .ZIP file, this should match the magic number PK\003\004.

This function assumes that the first thing in a zip archive is the .ZIP entry with the local file header signature. ZIP files containing a self-extracting archive may not exhibit this structure and will return FALSE

Value

A logical vector

Examples

```
# Get the files included with the package
fileDir <- system.file("extdata", package = "ngsReports")
allFiles <- list.files(fileDir, pattern = "zip$", full.names = TRUE)
isCompressed(allFiles)
```

maxAdapterContent

Get the maximum Adapter Content

Description

Get the maximum Adapter Content across one or more FASTQC reports

Usage

```
maxAdapterContent(x, asPercent = TRUE)
```

Arguments

x	Can be a .FastqcFile, FastqcData, FastqcDataList or path
asPercent	logical. Format the values as percentages with the added \% symbol

Details

This will extract the Adapter_Content module from the supplied object, and provide a tibble with the final value for each file.

Value

A tibble object containing the percent of reads with each adapter type at the final position

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)

# Get the maxAdapterContent
maxAdapterContent(fdl)
```

mData	<i>Extract Metadata for TheoreticalGC objects</i>
-------	---

Description

Extract Metadata for TheoreticalGC objects

Usage

```
mData(object)

## S4 method for signature 'TheoreticalGC'
mData(object)
```

Arguments

object An object of class Theoretical GC

Value

A tibble object

Examples

```
mData(gcTheoretical)
```

overRep2Fasta	<i>Write fasta of Over-Represented sequences.</i>
---------------	---

Description

Output overrepresented sequences to disk in fasta format.

Usage

```
overRep2Fasta(x, path, n = 10, labels, noAdapters = TRUE, ...)

## S4 method for signature 'ANY'
overRep2Fasta(x, path, n = 10, labels, noAdapters = TRUE, ...)

## S4 method for signature 'FastqcData'
overRep2Fasta(x, path, n = 10, labels, noAdapters = TRUE, ...)

## S4 method for signature 'FastqcDataList'
overRep2Fasta(x, path, n = 10, labels, noAdapters = TRUE, ...)
```

Arguments

x	Can be a FastqcData or FastqcDataList
path	Path to export the fasta file to. Reverts to a default in the working directory if not supplied
n	The number of sequences to output
labels	An optional named factor of labels for the file names. All filenames must be present in the names. File extensions are dropped by default.
noAdapters	logical. Remove any sequences identified as possible adapters or primers by FastQC
...	Used to pass any alternative patterns to remove from the end of filenames

Details

Fasta will contain Filename, Possible Source, Percent of total reads

Value

Exports to a fasta file, and returns the fasta information invisibly

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)

# Export the top10 Overrepresented Sequences as a single fasta file
faOut <- file.path(tempdir(), "top10.fa")
overRep2Fasta(fdl, path = faOut)
```

path

Return the File Paths from an object

Description

Return the File Paths from an object

Usage

```
## S4 method for signature '.FastqcFile'
path(object)

## S4 method for signature 'FastqcData'
path(object)

## S4 method for signature 'FastqcDataList'
path(object)
```

```
## S4 method for signature '.FastpFile'
path(object)

## S4 method for signature 'FastpData'
path(object)

## S4 method for signature 'FastpDataList'
path(object)
```

Arguments

object An object of class .FastqcFile

Details

Obtains the file.path for objects of multiple classes

Value

A character vector of the file paths to the underlying FastQC reports

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)
path(fdl)
```

plotAdapterContent	<i>Draw an Adapter Content Plot</i>
--------------------	-------------------------------------

Description

Draw an Adapter Content Plot across one or more FASTQC reports

Usage

```
plotAdapterContent(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  ...
)

## S4 method for signature 'ANY'
plotAdapterContent(
```

```

    x,
    usePlotly = FALSE,
    labels,
    pattern = ".(fast|fq|bam).*",
    ...
)

## S4 method for signature 'FastqcData'
plotAdapterContent(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  showPwf = TRUE,
  warn = 5,
  fail = 10,
  scaleColour = NULL,
  plotlyLegend = FALSE,
  ...
)

## S4 method for signature 'FastqcDataList'
plotAdapterContent(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  showPwf = TRUE,
  warn = 5,
  fail = 10,
  plotType = c("heatmap", "line"),
  adapterType = "Total",
  cluster = FALSE,
  dendrogram = FALSE,
  heat_w = 8L,
  scaleFill = NULL,
  scaleColour = NULL,
  plotlyLegend = FALSE,
  ...
)

## S4 method for signature 'FastpData'
plotAdapterContent(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  scaleFill = NULL,
  plotlyLegend = FALSE,
  plotTheme = theme_get(),

```

```

    ...
)

## S4 method for signature 'FastpDataList'
plotAdapterContent(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  showPwf = FALSE,
  warn = 5,
  fail = 10,
  cluster = FALSE,
  dendrogram = FALSE,
  scaleFill = NULL,
  plotTheme = theme_get(),
  heat_w = 8L,
  ...
)

```

Arguments

x	Can be a FastqcData, a FastqcDataList or character vector of file paths
usePlotly	logical. Output as ggplot2 (default) or plotly object.
labels	An optional named vector of labels for the file names. All filenames must be present in the names.
pattern	regex used to trim the ends of all filenames for plotting
...	Used to pass additional attributes to theme() for FastQC objects and geoms for Fastp objects
pwfCols	Object of class <code>PwfCols()</code> containing the colours for PASS/WARN/FAIL
showPwf	logical(1) Show PASS/WARN/FAIL status as would be included in a standard FastQC report
warn, fail	The default values for warn and fail are 5 and 10 respectively (i.e. percentages)
plotlyLegend	logical(1) Show legend when choosing interactive plots. Ignored for heatmaps
plotType	character. Can only take the values <code>plotType = "heatmap"</code> or <code>plotType = "line"</code>
adapterType	A regular expression matching the adapter(s) to be plotted. To plot all adapters summed, specify <code>adapterType = "Total"</code> . This is the default behaviour.
cluster	logical default FALSE. If set to TRUE, fastqc data will be clustered using hierarchical clustering
dendrogram	logical redundant if cluster is FALSE if both cluster and dendrogram are specified as TRUE then the dendrogram will be displayed.
heat_w	Width of the heatmap relative to other plot components
scaleFill, scaleColour	<code>scale_fill*</code> and <code>scale_colour*</code> objects
plotTheme	Set theme elements by passing a theme

Details

This extracts the Adapter_Content module from the supplied object and generates a ggplot2 object, with a set of minimal defaults. The output of this function can be further modified using the standard ggplot2 methods.

When x is a single or FastqcData object line plots will always be drawn for all adapters. Otherwise, users can select line plots or heatmaps. When plotting more than one fastqc file, any undetected adapters will not be shown.

An interactive version of the plot can be made by setting usePlotly as TRUE

Value

A standard ggplot2 object, or an interactive plotly object

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)

# The default plot
plotAdapterContent(fdl)

# Also subset the reads to just the R1 files
r1 <- grepl("R1", fqName(fdl))
plotAdapterContent(fdl[r1])

# Plot just the Universal Adapter
# and change the y-axis using ggplot2::scale_y_continuous
plotAdapterContent(fdl, adapterType = "Illumina_Universal", plotType = "line") +
  facet_wrap(~Filename) +
  guides(colour = "none")

# For FastpData object, the plots are slightly different
fp <- FastpData(system.file("extdata/fastp.json.gz", package = "ngsReports"))
plotAdapterContent(fp, scaleFill = scale_fill_brewer(palette = "Set1"))
```

plotAlignmentSummary *Plot a summary of alignments*

Description

Plot a summary of alignments from a set of log files

Usage

```
plotAlignmentSummary(
  x,
  type = c("star", "bowtie", "bowtie2", "hisat2"),
```

```

    usePlotly = FALSE,
    stripPaths = TRUE,
    asPercent = FALSE,
    ...,
    fill = c("red", "yellow", "blue", rgb(0, 0.5, 1))
  )

```

Arguments

<code>x</code>	Paths to one or more alignment log files
<code>type</code>	The aligner used. Can be one of star, bowtie, bowtie2 or hisat2
<code>usePlotly</code>	logical. If TRUE an interactive plot will be generated.
<code>stripPaths</code>	logical(1). Remove paths from the Filename column
<code>asPercent</code>	Show alignments as percentages, with the alternative (FALSE) being the total number of reads If FALSE a ggplot object will be output
<code>...</code>	Used to pass additional attributes to theme() and between methods
<code>fill</code>	Colours used to fill the bars. Passed to scale_fill_manual.

Details

Loads a set of alignment log files and creates a default plot. Implemented aligners are bowtie, bowtie2, Hisat2 and STAR.

Value

A ggplot2 object, or a plotly object

Examples

```

f <- c("bowtie2PE.txt", "bowtie2SE.txt")
bowtie2Logs <- system.file("extdata", f, package = "ngsReports")
plotAlignmentSummary(bowtie2Logs, "bowtie2")

```

plotAssemblyStats	<i>Plot a summary of assembly logs</i>
-------------------	--

Description

Plot a summary of assembly stats from a set of log files

Usage

```

plotAssemblyStats(
  x,
  type = c("quast", "busco"),
  usePlotly = FALSE,
  plotType = c("bar", "paracoord"),
  ...
)

```

Arguments

x	Paths to one or more log files
type	The tool used. Can be one of quast or busco
usePlotly	logical. If TRUE an interactive plot will be generated. If FALSE a ggplot object will be output
plotType	character. Plot type to output, one of bar or paracoord.
...	Used to pass additional attributes to theme() and between methods

Details

Loads a set of assembly log files and creates a default plot. Implemented tools are quast and BUSCO. quast will plot a parralel coordinate plot of some assembly statistics BUSCO will plot a stacked barplot of completeness statistics

Value

A ggplot2 object, or a plotly object

Examples

```
#getquast log filenames
quastFiles <- system.file("extdata",
c("quast1.tsv", "quast2.tsv"), package = "ngsReports")

# The default plot
plotAssemblyStats(quastFiles)
```

plotBaseQuals	<i>Plot the Base Qualities for each file</i>
---------------	--

Description

Plot the Base Qualities for each file as separate plots

Usage

```
plotBaseQuals(x, usePlotly = FALSE, labels, pattern = ".(fast|fq|bam).*", ...)

## S4 method for signature 'ANY'
plotBaseQuals(x, usePlotly = FALSE, labels, pattern = ".(fast|fq|bam).*", ...)

## S4 method for signature 'FastqcData'
plotBaseQuals(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  warn = 25,
```

```

    fail = 20,
    boxWidth = 0.8,
    showPwf = TRUE,
    plotlyLegend = FALSE,
    ...
)

## S4 method for signature 'FastqcDataList'
plotBaseQuals(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  warn = 25,
  fail = 20,
  showPwf = TRUE,
  boxWidth = 0.8,
  plotType = c("heatmap", "boxplot"),
  plotValue = "Mean",
  cluster = FALSE,
  dendrogram = FALSE,
  nc = 2,
  heat_w = 8L,
  ...
)

## S4 method for signature 'FastpData'
plotBaseQuals(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  warn = 25,
  fail = 20,
  showPwf = FALSE,
  module = c("Before_filtering", "After_filtering"),
  reads = c("read1", "read2"),
  readsBy = c("facet", "linetype"),
  bases = c("A", "T", "C", "G", "mean"),
  scaleColour = NULL,
  plotTheme = theme_get(),
  plotlyLegend = FALSE,
  ...
)

## S4 method for signature 'FastpDataList'
plotBaseQuals(
  x,
  usePlotly = FALSE,
  labels,

```

```

pattern = ".(fast|fq|bam).*",
pwfCols,
warn = 25,
fail = 20,
showPwf = FALSE,
module = c("Before_filtering", "After_filtering"),
plotType = "heatmap",
plotValue = c("mean", "A", "T", "C", "G"),
scaleFill = NULL,
plotTheme = theme_get(),
cluster = FALSE,
dendrogram = FALSE,
heat_w = 8L,
...
)

```

Arguments

<code>x</code>	Can be a <code>FastqcData</code> , <code>FastqcDataList</code> or character vector of file paths
<code>usePlotly</code>	logical Default FALSE will render using ggplot. If TRUE plot will be rendered with plotly
<code>labels</code>	An optional named vector of labels for the file names. All filenames must be present in the names.
<code>pattern</code>	Regex to remove from the end of the Fastp report and Fastq file names
<code>...</code>	Used to pass additional attributes to <code>theme()</code> and between methods
<code>pwfCols</code>	Object of class <code>PwfCols()</code> to give colours for pass, warning, and fail values in plot
<code>warn, fail</code>	The default values for warn and fail are 30 and 20 respectively (i.e. percentages)
<code>boxWidth</code>	set the width of boxes when using a boxplot
<code>showPwf</code>	Include the Pwf status colours
<code>plotlyLegend</code>	logical(1) Show legend for interactive plots. Only called when drawing line plots
<code>plotType</code>	character Can be either "boxplot" or "heatmap"
<code>plotValue</code>	character Type of data to be presented. Can be any of the columns returned by the appropriate call to <code>getModule()</code>
<code>cluster</code>	logical default FALSE. If set to TRUE, fastqc data will be clustered using hierarchical clustering
<code>dendrogram</code>	logical redundant if cluster is FALSE if both cluster and dendrogram are specified as TRUE then the dendrogram will be displayed.
<code>nc</code>	numeric. The number of columns to create in the plot layout. Only used if drawing boxplots for multiple files in a <code>FastqcDataList</code>
<code>heat_w</code>	Relative width of any heatmap plot components
<code>module</code>	Select Before and After filtering when using a <code>FastpDataList</code>
<code>reads</code>	Create plots for read1, read2 or all when using a <code>FastpDataList</code>
<code>readsBy</code>	If paired reads are present, separate using either linetype or by facet
<code>bases</code>	Which bases to include on the plot
<code>scaleColour</code>	ggplot discrete colour scale, passed to lines
<code>plotTheme</code>	theme object
<code>scaleFill</code>	ggplot2 continuous scale. Passed to heatmap cells

Details

When acting on a `FastqcDataList`, this defaults to a heatmap using the mean `Per_base_sequence_quality` score. A set of plots which replicate those obtained through a standard FastQC html report can be obtained by setting `plotType = "boxplot"`, which uses `facet_wrap` to provide the layout as a single `ggplot` object.

When acting on a `FastqcData` object, this replicates the `Per_base_sequence_quality` plots from FastQC with no faceting.

For large datasets, subsetting by R1 or R2 reads may be helpful.

An interactive plot can be obtained by setting `usePlotly = TRUE`.

Value

A standard `ggplot2` object or an interactive `plotly` object

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)

# The default plot for multiple libraries is a heatmap
plotBaseQuals(fdl)

# The default plot for a single library is the standard boxplot
plotBaseQuals(fdl[[1]])

# FastpData objects have qualities by base
fp <- FastpData(system.file("extdata/fastp.json.gz", package = "ngsReports"))
plotBaseQuals(
  fp, plotTheme = theme(plot.title = element_text(hjust = 0.5))
)
```

plotDupLevels

Plot the combined Sequence_Duplication_Levels information

Description

Plot the `Sequence_Duplication_Levels` information for a set of FASTQC reports

Usage

```
plotDupLevels(x, usePlotly = FALSE, labels, pattern = ".(fast|fq|bam).*", ...)

## S4 method for signature 'ANY'
plotDupLevels(x, usePlotly = FALSE, labels, pattern = ".(fast|fq|bam).*", ...)

## S4 method for signature 'FastqcData'
```

```

plotDupLevels(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  warn = 20,
  fail = 50,
  showPwf = TRUE,
  plotlyLegend = FALSE,
  lineCol = c("red", "blue"),
  lineWidth = 1,
  ...
)

## S4 method for signature 'FastqcDataList'
plotDupLevels(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  warn = 20,
  fail = 50,
  showPwf = TRUE,
  plotlyLegend = FALSE,
  deduplication = c("pre", "post"),
  plotType = c("heatmap", "line"),
  cluster = FALSE,
  dendrogram = FALSE,
  heatCol = hcl.colors(50, "inferno"),
  heat_w = 8,
  ...
)

## S4 method for signature 'FastpData'
plotDupLevels(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  warn = 20,
  fail = 50,
  showPwf = FALSE,
  maxLevel = 10,
  lineCol = "red",
  barFill = "dodgerblue4",
  barCol = barFill,
  plotlyLegend = FALSE,
  plotTheme = theme_get(),
  ...
)

```

```

)

## S4 method for signature 'FastpDataList'
plotDupLevels(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  warn = 20,
  fail = 50,
  showPwf = FALSE,
  plotlyLegend = FALSE,
  plotType = c("bar", "heatmap"),
  barFill = "blue",
  barCol = "blue",
  cluster = FALSE,
  dendrogram = FALSE,
  scaleFill = NULL,
  plotTheme = theme_get(),
  heat_w = 8,
  maxLevel = 10,
  ...
)

```

Arguments

x	Can be a FastqcData, FastqcDataList or file path
usePlotly	logical Default FALSE will render using ggplot. If TRUE plot will be rendered with plotly
labels	An optional named vector of labels for the file names. All filenames must be present in the names. File extensions are dropped by default.
pattern	regex to remove from the end of fastp & fastq file names
...	Used to pass additional attributes to theme() and between methods
pwfCols	Object of class <code>PwfCols()</code> to give colours for pass, warning, and fail values in the plot
warn, fail	The default values for warn and fail are 20 and 50 respectively (i.e. percentages)
showPwf	logical(1) Show PWF rectangles in the background
plotlyLegend	logical(1) Show legend for line plots when using interactive plots
lineCol, lineWidth	Colours and width of lines drawn
deduplication	Plot Duplication levels 'pre' or 'post' deduplication. Can only take values "pre" and "post"
plotType	Choose between "heatmap" and "line"
cluster	logical default FALSE. If set to TRUE, fastqc data will be clustered using hierarchical clustering
dendrogram	logical Plot will automatically be clustered if TRUE.
heatCol	Colour palette used for the heatmap

heat_w	Relative width of the heatmap relative to other plot components
maxLevel	The maximum duplication level to plot. Beyond this level, all values will be summed
barFill, barCol	Colours for bars when calling geom_col()
plotTheme	theme object. Applied after a call to theme_bw()
scaleFill	Discrete scale used to fill heatmap cells

Details

This extracts the Sequence_Duplication_Levels from the supplied object and generates a ggplot2 object, with a set of minimal defaults. For multiple reports, this defaults to a heatmap with block sizes proportional to the percentage of reads belonging to that duplication category.

If setting usePlotly = FALSE, the output of this function can be further modified using standard ggplot2 syntax. If setting usePlotly = TRUE an interactive plotly object will be produced.

Value

A standard ggplot2 or plotly object

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)

# Draw the default plot for a single file
plotDupLevels(fdl[[1]])

plotDupLevels(fdl)
```

plotFastqcPCA

Draw a PCA plot for Fast QC modules

Description

Draw a PCA plot for Fast QC modules across multiple samples **[Experimental]**

Usage

```
plotFastqcPCA(
  x,
  module = "Per_sequence_GC_content",
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  sz = 4,
  groups,
```

```

    ...
)

## S4 method for signature 'ANY'
plotFastqcPCA(
  x,
  module = "Per_sequence_GC_content",
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  sz = 4,
  groups,
  ...
)

## S4 method for signature 'character'
plotFastqcPCA(
  x,
  module = "Per_sequence_GC_content",
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  sz = 4,
  groups,
  ...
)

## S4 method for signature 'FastqcDataList'
plotFastqcPCA(
  x,
  module = "Per_sequence_GC_content",
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  sz = 4,
  groups,
  pc = c(1, 2),
  ...
)

```

Arguments

x	Can be a FastqcDataList or character vector of file paths
module	character vector containing the desired FastQC module (eg. c("Per_base_sequence_quality", "Per_base_sequence_content"))
usePlotly	logical. Output as ggplot2 (default) or plotly object.
labels	An optional named vector of labels for the file names. All file names must be present in the names of the vector.
pattern	Regex to remove from the end of any filenames
sz	The size of the text labels

groups	Optional factor of the same length as x. If provided, the plot will be coloured using this factor as the defined groups. Ellipses will also be added to the final plot.
...	Used to pass additional attributes to theme() and between methods
pc	The two components to be plotted

Details

This carries out PCA on a single FastQC module and plots the output using either ggplot or plotly. Current modules for PCA are Per_base_sequence_quality, Per_sequence_quality_scores, Per_sequence_GC_content, Per_base_sequence_content, and Sequence_Length_Distribution.

If a factor is provided in the groups argument, this will be applied to the plotting colours and ellipses will be drawn using these groups. Only the labels will be plotted using geom_text()

Value

A standard ggplot2 object, or an interactive plotly object

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)
grp <- as.factor(gsub(".*(R[12]).*", "\\1", fqName(fdl)))
plotFastqcPCA(fdl, module = "Per_sequence_GC_content", groups = grp)
```

plotGcContent

Plot the Per Sequence GC Content

Description

Plot the Per Sequence GC Content for a set of FASTQC files

Usage

```
plotGcContent(x, usePlotly = FALSE, labels, pattern = ".(fast|fq|bam).*", ...)

## S4 method for signature 'ANY'
plotGcContent(x, usePlotly = FALSE, labels, pattern = ".(fast|fq|bam).*", ...)

## S4 method for signature 'FastqcData'
plotGcContent(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
```

```

    theoreticalGC = TRUE,
    gcType = c("Genome", "Transcriptome"),
    species = "Hsapiens",
    GObject,
    plotlyLegend = FALSE,
    Fastafilename,
    n = 1e+06,
    counts = FALSE,
    scaleColour = NULL,
    lineCols = c("red3", "black"),
    linetype = 1,
    linewidth = 0.5,
    ...
)

## S4 method for signature 'FastqcDataList'
plotGcContent(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  theoreticalGC = TRUE,
  gcType = c("Genome", "Transcriptome"),
  species = "Hsapiens",
  GObject,
  Fastafilename,
  n = 1e+06,
  plotType = c("heatmap", "line", "cdf"),
  cluster = FALSE,
  dendrogram = FALSE,
  heat_w = 8,
  pwfCols,
  showPwf = TRUE,
  scaleFill = NULL,
  scaleColour = NULL,
  plotlyLegend = FALSE,
  lineCols = RColorBrewer::brewer.pal(12, "Paired"),
  linetype = 1,
  linewidth = 0.5,
  ...
)

## S4 method for signature 'FastpData'
plotGcContent(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  theoreticalGC = TRUE,
  gcType = c("Genome", "Transcriptome"),
  species = "Hsapiens",
  GObject,

```

```

    Fastafile,
    n = 1e+06,
    plotType = "bar",
    scaleFill = NULL,
    plotlyLegend = FALSE,
    plotTheme = theme_get(),
    ...
)

## S4 method for signature 'FastpDataList'
plotGcContent(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  theoreticalGC = TRUE,
  gcType = c("Genome", "Transcriptome"),
  species = "Hsapiens",
  GCobject,
  Fastafile,
  n = 1e+06,
  plotType = "bar",
  scaleFill = NULL,
  plotTheme = theme_get(),
  plotlyLegend = FALSE,
  ...
)

```

Arguments

<code>x</code>	Can be a <code>FastqcData</code> , <code>FastqcDataList</code> or character vector of file paths
<code>usePlotly</code>	logical Default FALSE will render using ggplot. If TRUE plot will be rendered with plotly
<code>labels</code>	An optional named vector of labels for the file names.
<code>pattern</code>	Pattern to remove from the end of filenames
<code>...</code>	Used to pass various potting parameters to themes and geoms.
<code>theoreticalGC</code>	logical default is FALSE to give the true GC content, set to TRUE to normalize values of <code>GC_Content</code> by the theoretical values using <code>gcTheoretical()</code> . species must be specified. For <code>Fastqc*</code> objects, the entire distributions will be used, whereas for the <code>Fastp*</code> objects, only the expected mean value is shown as a horizontal line
<code>gcType</code>	character Select type of data to normalize GC content against. Accepts either "Genome" (default) or "Transcriptome".
<code>species</code>	character if <code>gcTheory</code> is TRUE it must be accompanied by a species. Species currently supported can be obtained using <code>mData(gcTheoretical)</code>
<code>GCobject</code>	an object of class <code>GCTheoretical</code> . Defaults to the <code>gcTheoretical</code> object supplied with the package
<code>plotlyLegend</code>	logical(1) Show legend on interactive line plots
<code>Fastafile</code>	a fasta file contains DNA sequences to generate theoretical GC content
<code>n</code>	number of simulated reads to generate theoretical GC content from <code>Fastafile</code>

counts	logical. Plot the counts from each file if counts = TRUE, otherwise frequencies will be plotted. Ignored if calling the function on a FastqcDataList.
scaleColour	ggplot2 scale for line colours
lineCols, linetype, linewidth	Line colour type and width for observed and theoretical GC lines
plotType	Takes values "line", "heatmap" or "cdf"
cluster	logical default FALSE. If set to TRUE, fastqc data will be clustered using hierarchical clustering
dendrogram	logical redundant if cluster is FALSE if both cluster and dendrogram are specified as TRUE then the dendrogram will be displayed.
heat_w	Relative width of any heatmap plot components
pwfCols	Object of class <code>PwfCols()</code> to give colours for pass, warning, and fail values in plot
showPwf	logical(1) Show Pwf Status on the plot
scaleFill	ggplot2 scale for filling heatmap cells or bars
plotTheme	<code>theme</code> object

Details

Makes plots for GC_Content. When applied to a single FastqcData object a simple line plot will be drawn, with Theoretical GC content overlaid if desired.

When applied to multiple FastQC reports, the density at each GC content bin can be shown as a heatmap by setting `theoreticalGC = FALSE`. By default the difference in observed and expected theoretical GC is shown. Species and genome/transcriptome should also be set if utilising the theoretical GC content.

As an alternative to a heatmap, a series of overlaid distributions can be shown by setting `plotType = "line"`.

Can produce a static ggplot2 object or an interactive plotly object.

Value

A ggplot2 or plotly object

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
f1 <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(f1)

# The default plot for a FastqcDataList
plotGcContent(fdl)

# Plot a single FastqcData object
plotGcContent(fdl[[1]])
```

plotInsertSize	<i>Plot Insert Size Distributions</i>
----------------	---------------------------------------

Description

Plot the insert size distribution from one of Fastp reports

Usage

```
plotInsertSize(x, usePlotly = FALSE, labels, pattern = ".(fast|fq|bam).*", ...)
```

```
## S4 method for signature 'FastpData'
```

```
plotInsertSize(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  plotType = c("histogram", "cumulative"),
  counts = FALSE,
  plotTheme = theme_get(),
  expand.x = 0.01,
  expand.y = c(0, 0.05),
  ...
)
```

```
## S4 method for signature 'FastpDataList'
```

```
plotInsertSize(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  plotType = c("heatmap", "line", "cumulative"),
  plotTheme = theme_get(),
  scaleFill = NULL,
  scaleColour = NULL,
  cluster = FALSE,
  dendrogram = FALSE,
  heat_w = 8,
  ...
)
```

Arguments

x	A FastpData or FastpDataList object
usePlotly	logical. Generate an interactive plot using plotly
labels	An optional named vector of labels for the file names. All file names must be present in the names of the vector.
pattern	Regex to remove from the end of any filenames
...	Passed to geom* functions during plotting

plotType	Determine the plot type. Options vary with the input structure
counts	logical(1) Plot read counts, or percentages (default)
plotTheme	a theme object
expand.x, expand.y	Axis expansions
scaleFill	Continuous scale used to fill heatmap cells. Defaults to the "inferno" palette
scaleColour	Discrete scale for adding line colours
cluster	logical default FALSE. If set to TRUE, data will be clustered using hierarchical clustering
dendrogram	logical redundant if cluster is FALSE if both cluster and dendrogram are specified as TRUE the dendrogram will be displayed.
heat_w	Width of the heatmap relative to other plot components

Details

Takes a Fastp or a set of Fastp reports and plot insert size distributions. Plots can be drawn as cumulative totals or the default histograms for a single report, and as boxplots or heatmaps for a set of reports

Value

A ggplot or plotly object

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastp.json.gz", full.names = TRUE)
fp <- FastpData(fl)
plotInsertSize(
  fp, counts = TRUE, fill = "steelblue4",
  plotTheme = theme(plot.title = element_text(hjust = 0.5))
)
plotInsertSize(fp, plotType = "cumulative")
```

plotKmers

Plot Overrepresented Kmers

Description

Plot Overrepresented Kmers

Usage

```

plotKmers(x, usePlotly = FALSE, labels, pattern = ".(fast|fq|bam).*", ...)

## S4 method for signature 'ANY'
plotKmers(x, usePlotly = FALSE, labels, pattern = ".(fast|fq|bam).*", ...)

## S4 method for signature 'FastqcData'
plotKmers(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  n = 6,
  linewidth = 0.5,
  plotlyLegend = FALSE,
  scaleColour = NULL,
  pal = c("red", "blue", "green", "black", "magenta", "yellow"),
  ...
)

## S4 method for signature 'FastqcDataList'
plotKmers(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  cluster = FALSE,
  dendrogram = FALSE,
  pwfCols,
  showPwf = TRUE,
  scaleFill = NULL,
  heatCol = hcl.colors(50, "inferno"),
  heat_w = 8,
  ...
)

## S4 method for signature 'FastpData'
plotKmers(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  module = c("Before_filtering", "After_filtering"),
  reads = c("read1", "read2"),
  readsBy = c("facet", "mean", "diff"),
  trans = "log2",
  scaleFill = NULL,
  plotTheme = theme_get(),
  plotlyLegend = FALSE,
  ...
)

```

Arguments

x	Can be a FastqcData, FastqcDataList or file paths
usePlotly	logical Default FALSE will render using ggplot. If TRUE plot will be rendered with plotly
labels	An optional named vector of labels for the file names. All filenames must be present in the names.
pattern	regex to drop from the end of filenames
...	Used to pass parameters to theme for FastqcData objects and to geoms for FastpData objects
n	numeric. The number of Kmers to show.
linewidth	Passed to geom_line()
plotlyLegend	Show legend for interactive plots
pal	The colour palette. If the vector supplied is less than n, grDevices::colorRampPalette() will be used
cluster	logical default FALSE. If set to TRUE, fastqc data will be clustered using hierarchical clustering
dendrogram	logical redundant if cluster is FALSE if both cluster and dendrogram are specified as TRUE then the dendrogram will be displayed.
pwfCols	Object of class PwfCols() to give colours for pass, warning, and fail values in the plot
showPwf	Show the PASS/WARN/FAIL status
scaleFill, scaleColour	ggplot2 scales to be used for colour palettes
heatCol	Colour palette used for the heatmap. Default is inferno from the viridis set of palettes
heat_w	Relative width of any heatmap plot components
module	The module to obtain data from when using a FastpData object
reads	Either read1 or read2. Only used when using a FastpData object
readsBy	Strategy for visualising both read1 and read2. Can be set to show each set of reads by facet, or within the same plot taking the mean of the enrichment above mean, or the difference in the enrichment above mean
trans	Function for transforming the count/mean ratio. Set as NULL to use the ratio without transformation
plotTheme	theme object

Details

As the Kmer Content module present in FastQC reports is relatively uninformative, and omitted by default in later versions of FastQC, these are rudimentary plots.

Plots for FastqcData objects replicate those contained in a FastQC report, whilst the heatmap generated from FastqcDataList objects simply show the location and abundance of over-represented Kmers.

Value

A standard ggplot2 object or an interactive plotly object

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)
plotKmers(fdl[[1]])

# Use a FastpData object
fl <- system.file("extdata", "fastp.json.gz", package = "ngsReports")
fp <- FastpData(fl)
plotKmers(fp, size = 2)
plotKmers(
  fp, reads = "read1", size = 2, trans = NULL,
  scaleFill = scale_fill_gradient(low = "white", high = "black")
)
```

plotNContent

Draw an N Content Plot

Description

Draw an N Content Plot across one or more FastQC reports

Usage

```
plotNContent(x, usePlotly = FALSE, labels, pattern = ".(fast|fq|bam).*", ...)

## S4 method for signature 'ANY'
plotNContent(x, usePlotly = FALSE, labels, pattern = ".(fast|fq|bam).*", ...)

## S4 method for signature 'FastqcData'
plotNContent(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  warn = 5,
  fail = 20,
  showPwf = TRUE,
  ...,
  lineCol = "red"
)

## S4 method for signature 'FastqcDataList'
plotNContent(
  x,
  usePlotly = FALSE,
  labels,
```

```

    pattern = ".(fast|fq|bam).*",
    pwfCols,
    warn = 5,
    fail = 20,
    showPwf = TRUE,
    cluster = FALSE,
    dendrogram = FALSE,
    heat_w = 8,
    scaleFill = NULL,
    ...
)

## S4 method for signature 'FastpData'
plotNContent(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  module = c("Before_filtering", "After_filtering"),
  moduleBy = c("facet", "colour", "linetype"),
  reads = c("read1", "read2"),
  readsBy = c("facet", "colour", "linetype"),
  scaleColour = NULL,
  scaleLine = NULL,
  plotTheme = theme_get(),
  plotlyLegend = FALSE,
  ...
)

## S4 method for signature 'FastpDataList'
plotNContent(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  module = c("Before_filtering", "After_filtering"),
  reads = c("read1", "read2"),
  scaleFill = NULL,
  plotTheme = theme_get(),
  cluster = FALSE,
  dendrogram = FALSE,
  heat_w = 8,
  ...
)

```

Arguments

<code>x</code>	Can be a <code>FastqcData</code> , <code>FastqcDataList</code> or file paths
<code>usePlotly</code>	logical. Output as <code>ggplot2</code> (default) or <code>plotly</code> object.
<code>labels</code>	An optional named vector of labels for the file names. All filenames must be present in the names.
<code>pattern</code>	Regex used to trim the end of filenames

...	Used to pass additional attributes to theme() for FastqcData objects and to geom* calls for FastpData-based objects
pwfCols	Object of class <code>PwfCols()</code> containing the colours for PASS/WARN/FAIL
warn, fail	The default values for warn and fail are 5 and 10 respectively (i.e. percentages)
showPwf	logical(1) Show the PASS/WARN/FAIL status
lineCol	Line colours
cluster	logical default FALSE. If set to TRUE, fastqc data will be clustered using hierarchical clustering
dendrogram	logical redundant if cluster is FALSE if both cluster and dendrogram are specified as TRUE then the dendrogram will be displayed.
heat_w	Relative width of any heatmap plot components
scaleFill, scaleColour, scaleLine	ggplot2 scale objects
module	Used for Fastp* structures to show results before or after filtering
moduleBy, readsBy	How to show each module or set of reads on the plot
reads	Show plots for read1, read2 or both.
plotTheme	<code>theme</code> object
plotlyLegend	logical(1) Show legend on interactive plots

Details

This extracts the N_Content from the supplied object and generates a ggplot2 object, with a set of minimal defaults. The output of this function can be further modified using the standard ggplot2 methods.

When x is a single FastqcData object line plots will always be drawn for all Ns. Otherwise, users can select line plots or heatmaps.

Value

A standard ggplot2 object, or an interactive plotly object

Examples

```
## Using a Fastp Data object
fl <- system.file("extdata/fastp.json.gz", package = "ngsReports")
fp <- FastpData(fl)
plotNContent(fp)
plotNContent(
  fp, pattern = "_001.+",
  moduleBy = "colour", scaleColour = scale_colour_brewer(palette = "Set1"),
  plotTheme = theme(
    legend.position = 'inside', legend.position.inside = c(0.99, 0.99),
    legend.justification = c(1, 1), plot.title = element_text(hjust = 0.5)
  )
)
```

`plotOverrep`*Plot a summary of Over-represented Sequences*

Description

Plot a summary of Over-represented Sequences for a set of FASTQC reports

Usage

```
plotOverrep(  
  x,  
  usePlotly = FALSE,  
  labels,  
  pattern = ".(fast|fq|bam).*",  
  pwfCols,  
  ...  
)  
  
## S4 method for signature 'ANY'  
plotOverrep(  
  x,  
  usePlotly = FALSE,  
  labels,  
  pattern = ".(fast|fq|bam).*",  
  pwfCols,  
  ...  
)  
  
## S4 method for signature 'character'  
plotOverrep(  
  x,  
  usePlotly = FALSE,  
  labels,  
  pattern = ".(fast|fq|bam).*",  
  pwfCols,  
  ...  
)  
  
## S4 method for signature 'FastqcData'  
plotOverrep(  
  x,  
  usePlotly = FALSE,  
  labels,  
  pattern = ".(fast|fq|bam).*",  
  pwfCols,  
  n = 10,  
  expand.x = c(0, 0, 0.05, 0),  
  expand.y = c(0, 0.6, 0, 0.6),  
  plotlyLegend = FALSE,  
  ...  
)
```

```
## S4 method for signature 'FastqcDataList'
plotOverrep(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  showPwf = TRUE,
  cluster = FALSE,
  dendrogram = FALSE,
  scaleFill = NULL,
  paletteName = "Set1",
  panel_w = 8,
  expand.x = c(0, 0, 0.05, 0),
  expand.y = rep(0, 4),
  ...
)
```

Arguments

x	Can be a FastqcData, FastqcDataList or file paths
usePlotly	logical Default FALSE will render using ggplot. If TRUE plot will be rendered with plotly
labels	An optional named factor of labels for the file names. All filenames must be present in the names.
pattern	Regex to remove from the end of any filenames
pwfCols	Object of class <code>PwfCols()</code> containing the colours for PASS/WARN/FAIL
...	Used to pass additional attributes to theme() and between methods
n	The number of sequences to plot from an individual file
expand.x, expand.y	Output from expansion() or numeric vectors of length 4. Passed to scale_*_continuous()
plotlyLegend	Show legend on interactive plots
showPwf	Show PASS/WARN/FAIL status on the plot
cluster	logical default FALSE. If set to TRUE, fastqc data will be clustered using hierarchical clustering
dendrogram	logical redundant if cluster is FALSE if both cluster and dendrogram are specified as TRUE then the dendrogram will be displayed.
scaleFill	ggplot scale object
paletteName	Name of the palette for colouring the possible sources of the overrepresented sequences. Must be a palette name from RColorBrewer. Ignored if specifying the scaleFill separately
panel_w	Width of main panel on output

Details

Percentages are obtained by simply summing those within a report. Any possible double counting by FastQC is ignored for the purposes of a simple approximation.

Plots generated from a FastqcData object will show the top n sequences grouped by their predicted source & coloured by whether the individual sequence would cause a WARN/FAIL.

Plots generated from a FastqcDataList group sequences by predicted source and summarise as a percentage of the total reads.

Value

A standard ggplot2 object

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)

# A brief summary across all FastQC reports
plotOverrep(fdl)
```

plotReadTotals	<i>Draw a barplot of read totals</i>
----------------	--------------------------------------

Description

Draw a barplot of read totals

Usage

```
plotReadTotals(x, usePlotly = FALSE, labels, pattern = ".(fast|fq|bam).*", ...)

## S4 method for signature 'ANY'
plotReadTotals(x, usePlotly = FALSE, labels, pattern = ".(fast|fq|bam).*", ...)

## S4 method for signature 'FastqcDataList'
plotReadTotals(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  duplicated = TRUE,
  bars = c("stacked", "adjacent"),
  vertBars = TRUE,
  divBy = 1,
  barCols = c("red", "blue"),
  expand.y = c(0, 0.02),
  plotlyLegend = FALSE,
  ...
)
```

```
## S4 method for signature 'FastpDataList'
plotReadTotals(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  adjPaired = TRUE,
  divBy = 1e+06,
  scaleFill = NULL,
  labMin = 0.05,
  status = TRUE,
  labelVJ = 0.5,
  labelFill = "white",
  plotTheme = theme_get(),
  vertBars = FALSE,
  plotlyLegend = FALSE,
  expand.y = c(0, 0.05),
  ...
)
```

Arguments

x	Can be a FastqcData, FastqcDataList or file paths
usePlotly	logical Default FALSE will render using ggplot. If TRUE plot will be rendered with plotly
labels	An optional named vector of labels for the file names. All filenames must be present in the names.
pattern	Regex used to trim the end of filenames
...	Used to pass additional attributes to theme()
duplicated	logical(1). Include deduplicated read total estimates to plot charts
bars	If duplicated = TRUE, show unique and deduplicated reads as "stacked" or "adjacent".
vertBars	logical(1) Show bars as vertical or horizontal
divBy	Scale read totals by this value. The default shows the y-axis in millions for FastpDataList objects, but does not scale FastQC objects, for the sake of backwards compatability
barCols	Colours for duplicated and unique reads.
expand.y	Passed to ggplot2::expansion for the axis showing totals
plotlyLegend	logical(1) Show legend on interactive plots
adjPaired	Scale read totals by 0.5 when paired
scaleFill	ScaleDiscrete function to be applied to the plot
labMin	Only show labels for filtering categories higher than this values as a proportion of reads. Set to any number > 1 to turn off labels
status	logical(1) Include read status in the plot
labelVJ	Relative vertical position to labels within each bar.
labelFill	Passed to geom_label
plotTheme	theme to be added to the plot

Details

Draw a barplot of read totals using the standard ggplot2 syntax. The raw data from `readTotals()` can otherwise be used to manually create a plot.

Duplication levels are based on the value shown on FASTQC reports at the top of the DeDuplicated-Totals plot, which is known to be inaccurate. As it still gives a good guide as to sequence diversity it is included as the default. This can be turned off by setting `duplicated = FALSE`.

For `FastpDataList` objects, duplication statistics are not part of the default module containing Read-Totals. However, the status of reads and the reason for being retained or filtered is, and as such these are shown instead of duplication statistics.

Value

Returns a ggplot or plotly object

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)

# Plot the Read Totals showing estimated duplicates
plotReadTotals(fdl)

# Plot the Read Totals without estimated duplicates
plotReadTotals(fdl, duplicated = FALSE)
```

plotSeqContent

Plot the per base content as a heatmap

Description

Plot the Per Base content for a set of FASTQC files.

Usage

```
plotSeqContent(x, usePlotly = FALSE, labels, pattern = ".(fast|fq|bam).*", ...)

## S4 method for signature 'ANY'
plotSeqContent(x, usePlotly = FALSE, labels, pattern = ".(fast|fq|bam).*", ...)

## S4 method for signature 'FastqcData'
plotSeqContent(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  bases = c("A", "T", "C", "G"),
```

```

    scaleColour = NULL,
    plotTheme = theme_get(),
    plotlyLegend = FALSE,
    expand.x = 0.02,
    expand.y = c(0, 0.05),
    ...
)

## S4 method for signature 'FastqcDataList'
plotSeqContent(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  showPwf = TRUE,
  plotType = c("heatmap", "line", "residuals"),
  scaleColour = NULL,
  plotTheme = theme_get(),
  cluster = FALSE,
  dendrogram = FALSE,
  heat_w = 8,
  plotlyLegend = FALSE,
  nc = 2,
  ...
)

## S4 method for signature 'FastpData'
plotSeqContent(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  module = c("Before_filtering", "After_filtering"),
  reads = c("read1", "read2"),
  readsBy = c("facet", "linetype"),
  moduleBy = c("facet", "linetype"),
  bases = c("A", "T", "C", "G", "N", "GC"),
  scaleColour = NULL,
  scaleLine = NULL,
  plotlyLegend = FALSE,
  plotTheme = theme_get(),
  expand.x = 0.02,
  expand.y = c(0, 0.05),
  ...
)

## S4 method for signature 'FastpDataList'
plotSeqContent(
  x,
  usePlotly = FALSE,
  labels,

```

```

pattern = ".(fast|fq|bam).*",
module = c("Before_filtering", "After_filtering"),
moduleBy = c("facet", "linetype"),
reads = c("read1", "read2"),
readsBy = c("facet", "linetype"),
bases = c("A", "T", "C", "G", "N", "GC"),
showPwf = FALSE,
pwfCols,
warn = 10,
fail = 20,
plotType = c("heatmap", "line", "residuals"),
plotlyLegend = FALSE,
scaleColour = NULL,
scaleLine = NULL,
plotTheme = theme_get(),
cluster = FALSE,
dendrogram = FALSE,
heat_w = 8,
expand.x = c(0.01),
expand.y = c(0, 0.05),
nc = 2,
...
)

```

Arguments

x	Can be a FastqcData, FastqcDataList or file paths
usePlotly	logical. Generate an interactive plot using plotly
labels	An optional named vector of labels for the file names. All file names must be present in the names of the vector.
pattern	Regex to remove from the end of any filenames
...	Used to pass additional attributes to plotting geoms
bases	Which bases to draw on the plot. Also becomes the default plotting order by setting these as factor levels
scaleColour	Discrete colour scale as a ggplot ScaleDiscrete object If not provided, will default to scale_colour_manual
plotTheme	theme object to be applied. Note that all plots will have theme_bw theme applied by default, as well as any additional themes supplied here
plotlyLegend	logical(1) Show legends for interactive plots. Ignored for heatmaps
expand.x, expand.y	Passed to expansion in the x- and y-axis scales respectively
pwfCols	Object of class PwfCols() to give colours for pass, warning, and fail values in plot
showPwf	Show PASS/WARN/FAIL categories as would be defined in a FastQC report
plotType	character. Type of plot to generate. Must be "line", "heatmap" or "residuals"
cluster	logical default FALSE. If set to TRUE, fastqc data will be clustered using hierarchical clustering
dendrogram	logical redundant if cluster is FALSE if both cluster and dendrogram are specified as TRUE then the dendrogram will be displayed.

heat_w	Relative width of any heatmap plot components
nc	Specify the number of columns if plotting a FastqcDataList as line plots. Passed to facet_wrap .
module	Fastp Module to show. Can only be Before/After_filtering
reads	Which set of reads to show
readsBy, moduleBy	When plotting both R1 & R2 and both modules, separate by either linetype or linetype
scaleLine	Discrete scale_linetype object. Only relevant if plotting values by linetype
warn, fail	Default values for WARN and FAIL based on FastQC reports. Only applied to heatmaps for FastpDataList objects

Details

Per base sequence content (%A, %T, %G, %C), is shown as four overlaid heatmap colours when plotting from multiple reports. The individual line plots are able to be generated by setting plotType = "line", and the layout is determined by facet_wrap from ggplot2.

Individual line plots are also generated when plotting from a single FastqcData object.

If setting usePlotly = TRUE for a large number of reports, the plot can be slow to render. An alternative may be to produce a plot of residuals for each base, produced by taking the position-specific mean for each base.

Value

A ggplot2 object or an interactive plotly object

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)

# The default plot
plotSeqContent(fdl)

fp <- FastpData(system.file("extdata/fastp.json.gz", package = "ngsReports"))
plotSeqContent(fp)
plotSeqContent(fp, moduleBy = "linetype", bases = c("A", "C", "G", "T"))
```

plotSeqLengthDistn *Plot the Sequence Length Distribution*

Description

Plot the Sequence Length Distribution across one or more FASTQC reports

Usage

```

plotSeqLengthDistn(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  ...
)

## S4 method for signature 'ANY'
plotSeqLengthDistn(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  ...
)

## S4 method for signature 'character'
plotSeqLengthDistn(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  ...
)

## S4 method for signature 'FastqcData'
plotSeqLengthDistn(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  counts = TRUE,
  plotType = c("line", "cdf"),
  expand.x = c(0, 0.2, 0, 0.2),
  plotlyLegend = FALSE,
  colour = "red",
  ...
)

## S4 method for signature 'FastqcDataList'
plotSeqLengthDistn(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  counts = FALSE,
  plotType = c("heatmap", "line", "cdf"),
  cluster = FALSE,
  dendrogram = FALSE,
  heat_w = 8,

```

```

    pwfCols,
    showPwf = TRUE,
    scaleFill = NULL,
    scaleColour = NULL,
    heatCol = hcl.colors(50, "inferno"),
    plotlyLegend = FALSE,
    ...
)

```

Arguments

<code>x</code>	Can be a <code>FastqcData</code> , <code>FastqcDataList</code> or file paths
<code>usePlotly</code>	logical. Output as <code>ggplot2</code> or <code>plotly</code> object.
<code>labels</code>	An optional named vector of labels for the file names. All filenames must be present in the names.
<code>pattern</code>	Regex to remove from the end of any filenames
<code>...</code>	Used to pass additional attributes to <code>theme()</code>
<code>counts</code>	logical Should distributions be shown as counts or frequencies (percentages)
<code>plotType</code>	character. Can only take the values <code>plotType = "heatmap"</code> <code>plotType = "line"</code> or <code>plotType = "cdf"</code>
<code>expand.x</code>	Output from <code>expansion()</code> or numeric vector of length 4. Passed to <code>scale_x_discrete</code>
<code>plotlyLegend</code>	logical(1) Show legend for interactive line plots
<code>colour</code>	Line colour
<code>cluster</code>	logical default FALSE. If set to TRUE, fastqc data will be clustered using hierarchical clustering
<code>dendrogram</code>	logical redundant if <code>cluster</code> and <code>usePlotly</code> are FALSE. If both <code>cluster</code> and <code>dendrogram</code> are specified as TRUE then the dendrogram will be displayed.
<code>heat_w</code>	Relative width of any heatmap plot components
<code>pwfCols</code>	Object of class <code>PwfCols()</code> to give colours for pass, warning, and fail values in plot
<code>showPwf</code>	logical(1) Show PASS/WARN/FAIL status
<code>scaleFill, scaleColour</code>	Optional <code>ggplot</code> scale objects
<code>heatCol</code>	The colour scheme for the heatmap

Details

This extracts the Sequence Length Distribution from the supplied object and generates a `ggplot2` object, with a set of minimal defaults. The output of this function can be further modified using the standard `ggplot2` methods.

A cdf plot can also be generated to provide guidance for minimum read length in some NGS workflows, by setting `plotType = "cdf"`. If all libraries have reads of identical lengths, these plots may be less informative.

An alternative interactive plot is available by setting the argument `usePlotly = TRUE`.

Value

A standard `ggplot2` object, or an interactive `plotly` object

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)

# Plot as a frequency plot using lines
plotSeqLengthDistn(fdl)

# Or plot the cdf
plotSeqLengthDistn(fdl, plotType = "cdf")
```

plotSeqQuals

*Plot the Per Sequence Quality Scores***Description**

Plot the Per Sequence Quality Scores for a set of FASTQC reports

Usage

```
plotSeqQuals(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  ...
)

## S4 method for signature 'ANY'
plotSeqQuals(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  ...
)

## S4 method for signature 'character'
plotSeqQuals(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  ...
)
```

```

)

## S4 method for signature 'FastqcData'
plotSeqQuals(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  showPwf = TRUE,
  counts = FALSE,
  alpha = 0.1,
  warn = 30,
  fail = 20,
  colour = "red",
  plotlyLegend = FALSE,
  ...
)

## S4 method for signature 'FastqcDataList'
plotSeqQuals(
  x,
  usePlotly = FALSE,
  labels,
  pattern = ".(fast|fq|bam).*",
  pwfCols,
  counts = FALSE,
  alpha = 0.1,
  warn = 30,
  fail = 20,
  showPwf = TRUE,
  plotType = c("heatmap", "line"),
  dendrogram = FALSE,
  cluster = FALSE,
  scaleFill = NULL,
  heatCols = hcl.colors(100, "inferno"),
  heat_w = 8,
  scaleColour = NULL,
  plotlyLegend = FALSE,
  ...
)

```

Arguments

x	Can be a FastqcData, FastqcDataList or path
usePlotly	logical Default FALSE will render using ggplot. If TRUE plot will be rendered with plotly
labels	An optional named vector of labels for the file names. All file names must be present in the names of the vector.
pattern	Regex to remove from the end of any filenames
pwfCols	Object of class <code>PwfCols()</code> containing the colours for PASS/WARN/FAIL

...	Used to pass various potting parameters to theme. Can also be used to set size and colour for box outlines.
showPwf	logical(1) Show PASS/WARN/FAIL status
counts	logical. Plot the counts from each file if counts = TRUE, otherwise the frequencies will be plotted
alpha	set alpha for line graph bounds
warn, fail	The default values for warn and fail are 5 and 10 respectively (i.e. percentages)
colour	Colour for single line plots
plotlyLegend	logical(1) Show legend for interactive line plots
plotType	character. Can only take the values plotType = "heatmap" or plotType = "line"
dendrogram	logical redundant if cluster is FALSE if both cluster and dendrogram are specified as TRUE then the dendrogram will be displayed.
cluster	logical default FALSE. If set to TRUE, fastqc data will be clustered using hierarchical clustering
scaleFill, scaleColour	ggplot2 scales
heatCols	Colour palette for the heatmap
heat_w	Relative width of any heatmap plot components

Details

Plots the distribution of average sequence quality scores across the set of files. Values can be plotted either as counts (counts = TRUE) or as frequencies (counts = FALSE).

Any faceting or scale adjustment can be performed after generation of the initial plot, using the standard methods of ggplot2 as desired.

Value

A standard ggplot2 object, or an interactive plotly object

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)

# The default plot
plotSeqQuals(fdl)

# Also subset the reads to just the R1 files
r1 <- grepl("R1", fqName(fdl))
plotSeqQuals(fdl[r1])
```

plotSummary

Plot the PASS/WARN/FAIL information

Description

Extract the PASS/WARN/FAIL summaries and plot them

Usage

```
plotSummary(  
  x,  
  usePlotly = FALSE,  
  labels,  
  pwfCols,  
  cluster = FALSE,  
  dendrogram = FALSE,  
  ...  
)  
  
## S4 method for signature 'ANY'  
plotSummary(  
  x,  
  usePlotly = FALSE,  
  labels,  
  pwfCols,  
  cluster = FALSE,  
  dendrogram = FALSE,  
  ...  
)  
  
## S4 method for signature 'character'  
plotSummary(  
  x,  
  usePlotly = FALSE,  
  labels,  
  pwfCols,  
  cluster = FALSE,  
  dendrogram = FALSE,  
  ...  
)  
  
## S4 method for signature 'FastqcDataList'  
plotSummary(  
  x,  
  usePlotly = FALSE,  
  labels,  
  pwfCols,  
  cluster = FALSE,  
  dendrogram = FALSE,  
  ...,  
  gridlineWidth = 0.2,
```

```
    gridlineCol = "grey20"
  )
```

Arguments

<code>x</code>	Can be a <code>FastqcData</code> , <code>FastqcDataList</code> or character vector of file paths
<code>usePlotly</code>	logical. Generate an interactive plot using plotly
<code>labels</code>	An optional named vector of labels for the file names. All filenames must be present in the names. File extensions are dropped by default.
<code>pwfCols</code>	Object of class <code>PwfCols()</code> containing the colours for PASS/WARN/FAIL
<code>cluster</code>	logical default FALSE. If set to TRUE, fastqc data will be clustered using hierarchical clustering
<code>dendrogram</code>	logical redundant if <code>cluster</code> is FALSE if both <code>cluster</code> and <code>dendrogram</code> are specified as TRUE then the dendrogram will be displayed.
<code>...</code>	Used to pass various potting parameters to theme.
<code>gridlineWidth, gridlineCol</code>	Passed to <code>geom_hline</code> and <code>geom_vline</code> to determine width and colour of grid-lines

Details

This uses the standard `ggplot2` syntax to create a three colour plot. The output of this function can be further modified using the standard `ggplot2` methods if required.

Value

A `ggplot2` object (`usePlotly = FALSE`) or an interactive plotly object (`usePlotly = TRUE`)

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)

# Check the overall PASS/WARN/FAIL status
plotSummary(fdl)
```

pwf

Colours for PASS/WARN/FAIL

Description

Default colours for PASS/WARN/FAIL

Usage

```
pwf
```

Format

An object of class PwfCols of length 1.

Details

pwf is an object of class PwfCols supplied with the package and used as the default colouring. Colours correspond approximately to PASS, WARN and FAIL from the FASTQC reports, with the additional colour (MAX) included to indicate an extreme FAIL. In order, these colours in the default vector are green (rgb(0, 0.8, 0)), yellow (rgb(0.9, 0.9, 0.2)), red (rgb(0.8, 0.2, 0.2)) and white (rgb(1, 1, 1))

Examples

```
# Make a pie chart showing the default colours
pie(rep(1,4), labels = names(pwf), col = getColours(pwf))
```

PwfCols-class

The PwfCols class and associated methods

Description

Define the PwfCols class and associated methods

Details

This is an object of with four colours in components named PASS, WARN, FAIL and MAX. Used to indicate these categories as defined on the standard plots from fastqc.

Value

An S4 object of class PwfCols

Slots

PASS A vector of length 1, defining the colour for PASS in rgb format. Defaults to rgb(0, 0.8, 0)

WARN A vector of length 1, defining the colour for WARN in rgb format. Defaults to rgb(0.9, 0.9, 0.2)

FAIL A vector of length 1, defining the colour for FAIL in rgb format. Defaults to rgb(0.8, 0.2, 0.2)

MAX A vector of length 1, defining the colour for an extreme FAIL or NA in rgb format. Defaults to rgb(1, 1, 1)

readTotals	<i>Get the read totals</i>
------------	----------------------------

Description

Get the read totals from one or more FASTQC reports

Usage

```
readTotals(x)
```

Arguments

x	Can be a FastqcData, FastqcDataList, FastpData, FastpDataList or file paths
---	---

Value

A tibble with the columns Filename and Total_Sequences

Examples

```
# Get the files included with the package
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)

# Load the FASTQC data as a FastqcDataList object
fdl <- FastqcDataList(fl)

# Print the read totals
readTotals(fdl)
```

summariseOverrep	<i>Summarise Overrepresented Sequences</i>
------------------	--

Description

Summarise the Overrepresented sequences found in one or more QC files

Usage

```
summariseOverrep(x, ...)

## S4 method for signature 'FastpData'
summariseOverrep(x, step = c("Before", "After"), min_count = 0, ...)

## S4 method for signature 'FastpDataList'
summariseOverrep(
  x,
  min_count = 0,
```

```

    step = c("Before", "After"),
    vals = c("count", "rate"),
    fn = c("mean", "sum", "max"),
    by = c("reads", "sequence"),
    ...
)

## S4 method for signature 'FastqcDataList'
summariseOverrep(
  x,
  min_count = 0,
  vals = c("Count", "Percentage"),
  fn = c("mean", "sum", "max"),
  pattern = ".*",
  ...
)

## S4 method for signature 'FastqcData'
summariseOverrep(
  x,
  min_count = 0,
  vals = c("Count", "Percentage"),
  fn = c("mean", "sum", "max"),
  pattern = ".*",
  by = "Filename",
  ...
)

```

Arguments

<code>x</code>	An object of a suitable class
<code>...</code>	Not used
<code>step</code>	Can be 'Before', 'After' or both to obtain data from the Before_filtering or After_filtering modules
<code>min_count</code>	Filter sequences with counts less than this value, both before and after filtering
<code>vals</code>	Values to use for creating summaries across multiple files. For FastpDataList objects these can be "count" and/or "rate", whilst for FastqcDataList objects these values can be "Count" and/or "Percentage"
<code>fn</code>	Functions to use when summarising values across multiple files
<code>by</code>	character vector of columns to summarise by. See dplyr::summarise
<code>pattern</code>	Regular expression to filter the Possible_Source column by

Details

This function prepares a useful summary of all over-represented sequences as reported by either fastp or FastQC

Value

A tibble

Tibble columns will vary between Fastp*, FastqcDataList and FastqcData objects. Calling this function on list-type objects will attempt to summarise the presence each over-represented sequence across all files.

In particular, FastqcData objects will provide the requested summary statistics across all sequences within a file

Examples

```
## For operations on a FastpData object
f <- system.file("extdata/fastp.json.gz", package = "ngsReports")
fp <- FastpData(f)
summariseOverrep(fp, min_count = 100)

## Applying the function to a FastqcDataList
packageDir <- system.file("extdata", package = "ngsReports")
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)
fdl <- FastqcDataList(fl)
summariseOverrep(fdl)

# An alternative viewpoint can be obtained using
fdl |> lapply(summariseOverrep) |> dplyr::bind_rows()
```

TheoreticalGC-class	<i>The TheoreticalGC Object Class</i>
---------------------	---------------------------------------

Description

Contains Theoretical GC content for a selection of species

Details

Estimates are able to be retained for genomic and transcriptomic sequences. Values are stored as frequencies.

Value

An object of class TheoreticalGC

Slots

Genome A data.frame containing theoretical GC content for genomic sequences

Transcriptome A data.frame containing theoretical GC content for transcriptomic sequences

mData A data.frame containing metadata about all species in the object

Examples

```
## How to form an object using your own fasta file
faDir <- system.file("extdata", package = "ngsReports")
faFile <- list.files(faDir, pattern = "fasta", full.names = TRUE)
gen_df <- estGcDistn(faFile, n = 200)
gen_df <- dplyr::rename(gen_df, Athaliana = Freq)
mData_df <-
  data.frame(Name = "Athaliana", Genome = TRUE, Transcriptome = FALSE)
tr_df <- data.frame()
myGC <- new(
  "TheoreticalGC", Genome = gen_df, Transcriptome = tr_df, mData = mData_df)
```

writeHtmlReport

Write an HTML Summary Report

Description

Compiles an HTML report using a supplied template

Usage

```
writeHtmlReport(
  fastqcDir,
  template,
  outDir,
  usePlotly = TRUE,
  species = "Hsapiens",
  gcType = c("Genome", "Transcriptome"),
  nOver = 30,
  targetsDF,
  overwrite = FALSE,
  quiet = TRUE
)
```

Arguments

fastqcDir	A directory containing zipped, or extracted FastQC reports
template	The template file which will be copied into fastqcDir
outDir	The directory to write the compiled document to
usePlotly	Generate interactive plots?
species	Species/closely related species of sequenced samples
gcType	Is the data "Transcriptomic" or "Genomic" in nature?
nOver	The maximum number of Overrepresented Sequences to show
targetsDF	A data.frame with at least two columns named Filename and Label. The file-names should match the original fastq files, and the labels should be simply alternative labels for these files for convenience.
overwrite	logical. Overwrite any previous copies of the template file in the destination directory
quiet	logical. Show or hide markdown output in the Console.

Details

This will take a user supplied template, or the file supplied with the package and create an HTML summary of all standard FASTQC plots for all files in the supplied directory.

Value

Silently returns TRUE and will output a compiled HTML file from the supplied Rmarkdown template file

Examples

```
## Not run:
packageDir <- system.file("extdata", package = "ngsReports")
fileList <- list.files(packageDir, pattern = "fastqc.zip", full.names= TRUE)
# Copy these files to tempdir() to avoid overwriting
# any files in the package directory
file.copy(fileList, tempdir(), overwrite = TRUE)
writeHtmlReport(fastqcDir = tempdir())

## End(Not run)
```

```
[,FastqcDataList,numeric,missing-method
      Extract Elements
```

Description

Extract elements from FastqcDataList Object

Usage

```
## S4 method for signature 'FastqcDataList,numeric,missing'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'FastqcDataList,character,missing'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'FastqcDataList,logical,missing'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'FastqcDataList,ANY,missing'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'FastpDataList,numeric,missing'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'FastpDataList,character,missing'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'FastpDataList,logical,missing'
x[i, j, ..., drop = TRUE]
```

```
## S4 method for signature 'FastpDataList,ANY,missing'  
x[i, j, ..., drop = TRUE]
```

Arguments

x	A FastqcDataList or FastpDataList
i	character, logical or integer vector
j	not used
...	not used
drop	not used

Details

Extract elements in a consistent manner with R conventions

Value

Will return a subset of the original object following the standard rules for subsetting objects

Examples

```
# Get the files included with the package  
packageDir <- system.file("extdata", package = "ngsReports")  
fl <- list.files(packageDir, pattern = "fastqc.zip", full.names = TRUE)  
  
# Load the FASTQC data as a FastqcDataList object  
fdl <- FastqcDataList(fl)  
  
# Subsetting using the standard methods  
fdl[1]  
fdl[[1]]
```

Index

* datasets

gcTheoretical, 27
pwf, 75

* internal

.FastpFile-class, 5
.FastqcFile-class, 5
.addPercent, 4
.emptyPlot, 4
.getToolName, 6
.hidePWFRects, 6
.makeDendro, 7
.makeLabels, 7
.makePwfGradient, 8
.makeSidebar, 9
.parseAdapterRemovalLogs, 10
.parseBowtieLogs, 10
.parseBuscoLogs, 11
.parseCutadaptLogs, 11
.parseDuplicationMetricsLogs, 12
.parseFeatureCountsLogs, 12
.parseFlagstatLogs, 13
.parseHisat2Logs, 13
.parseMacs2CallpeakLogs, 14
.parseQuastLogs, 14
.parseRnaseqcMetricsLogs, 15
.parseSalmonLibFormatCountsLogs, 15
.parseSalmonMetaInfoLogs, 16
.parseStarLogs, 16
.parseTrimmomaticLogs, 17
.parseUmitoolsDedupLogs, 17
.prepHeatmap, 18
.renderDendro, 18
.splitByTab, 19
.updateThemeFromDots, 19
.FastpFile-class, 5
.FastqcFile-class, 5
.addPercent, 4
.emptyPlot, 4
.getToolName, 6
.hidePWFRects, 6
.makeDendro, 7
.makeLabels, 7

.makePwfGradient, 8
.makeSidebar, 9
.parseAdapterRemovalLogs, 10
.parseBowtieLogs, 10
.parseBuscoLogs, 11
.parseCutadaptLogs, 11
.parseDuplicationMetricsLogs, 12
.parseFeatureCountsLogs, 12
.parseFlagstatLogs, 13
.parseHisat2Logs, 13
.parseMacs2CallpeakLogs, 14
.parseQuastLogs, 14
.parseRnaseqcMetricsLogs, 15
.parseSalmonLibFormatCountsLogs, 15
.parseSalmonMetaInfoLogs, 16
.parseStarLogs, 16
.parseTrimmomaticLogs, 17
.parseUmitoolsDedupLogs, 17
.prepHeatmap, 18
.renderDendro, 18
.splitByTab, 19
.updateThemeFromDots, 19
[,FastpDataList,ANY,missing-method
([,FastqcDataList,numeric,missing-method),
81
[,FastpDataList,character,missing-method
([,FastqcDataList,numeric,missing-method),
81
[,FastpDataList,logical,missing-method
([,FastqcDataList,numeric,missing-method),
81
[,FastpDataList,numeric,missing-method
([,FastqcDataList,numeric,missing-method),
81
[,FastqcDataList,ANY,missing-method
([,FastqcDataList,numeric,missing-method),
81
[,FastqcDataList,character,missing-method
([,FastqcDataList,numeric,missing-method),
81
[,FastqcDataList,logical,missing-method
([,FastqcDataList,numeric,missing-method),
81

- [,FastqcDataList,numeric,missing-method,
21
- dplyr::summarise, 78
- estGcDistn, 20
- estGcDistn,ANY-method (estGcDistn), 20
- estGcDistn,character-method
(estGcDistn), 20
- estGcDistn,DNAStringSet-method
(estGcDistn), 20
- expansion, 67
- facet_wrap, 68
- FastpData (FastpData-class), 21
- FastpData-class, 21
- FastpDataList (FastpDataList-class), 22
- FastpDataList-class, 22
- FastqcData (FastqcData-class), 22
- FastqcData-class, 22
- FastqcDataList (FastqcDataList-class),
23
- FastqcDataList-class, 23
- fqcVersion
(fqcVersion, FastqcData-method),
24
- fqcVersion,ANY-method
(fqcVersion, FastqcData-method),
24
- fqcVersion, FastqcData-method, 24
- fqcVersion, FastqcDataList-method
(fqcVersion, FastqcData-method),
24
- fqName, 25
- fqName,ANY-method (fqName), 25
- fqName, FastpData-method (fqName), 25
- fqName, FastpDataList-method (fqName), 25
- fqName, FastqcData-method (fqName), 25
- fqName, FastqcDataList-method (fqName),
25
- fqName<- (fqName), 25
- fqName<- , FastqcData-method (fqName), 25
- fqName<- , FastqcDataList-method
(fqName), 25
- gcAvail, 26
- gcAvail, TheoreticalGC-method (gcAvail),
26
- gcTheoretical, 27
- gcTheoretical(), 52
- geom_label, 64
- getColours, 27
- getColours, PwfCols-method (getColours),
27
- getGC, 28
- getGC,ANY-method (getGC), 28
- getGC, TheoreticalGC-method (getGC), 28
- getModule
(getModule, FastqcData-method),
29
- getModule(), 21, 22
- getModule,ANY-method
(getModule, FastqcData-method),
29
- getModule, FastpData-method
(getModule, FastqcData-method),
29
- getModule, FastpDataList-method
(getModule, FastqcData-method),
29
- getModule, FastqcData-method, 29
- getModule, FastqcDataList-method
(getModule, FastqcData-method),
29
- getSummary
(getSummary, .FastqcFile-method),
30
- getSummary, .FastqcFile-method, 30
- getSummary,ANY-method
(getSummary, .FastqcFile-method),
30
- getSummary, FastqcData-method
(getSummary, .FastqcFile-method),
30
- getSummary, FastqcDataList-method
(getSummary, .FastqcFile-method),
30
- ggplot2::expansion, 64
- importNgsLogs, 31
- importSJ, 32
- isCompressed, 33
- maxAdapterContent, 34
- mData, 35
- mData, TheoreticalGC-method (mData), 35
- overRep2Fasta, 35
- overRep2Fasta,ANY-method
(overRep2Fasta), 35
- overRep2Fasta, FastqcData-method
(overRep2Fasta), 35
- overRep2Fasta, FastqcDataList-method
(overRep2Fasta), 35
- path, 36
- path, .FastpFile-method (path), 36

- path, .FastqcFile-method (path), 36
- path, FastpData-method (path), 36
- path, FastpDataList-method (path), 36
- path, FastqcData-method (path), 36
- path, FastqcDataList-method (path), 36
- plotAdapterContent, 37
- plotAdapterContent, ANY-method (plotAdapterContent), 37
- plotAdapterContent, FastpData-method (plotAdapterContent), 37
- plotAdapterContent, FastpDataList-method (plotAdapterContent), 37
- plotAdapterContent, FastqcData-method (plotAdapterContent), 37
- plotAdapterContent, FastqcDataList-method (plotAdapterContent), 37
- plotAlignmentSummary, 40
- plotAssemblyStats, 41
- plotBaseQuals, 42
- plotBaseQuals, ANY-method (plotBaseQuals), 42
- plotBaseQuals, FastpData-method (plotBaseQuals), 42
- plotBaseQuals, FastpDataList-method (plotBaseQuals), 42
- plotBaseQuals, FastqcData-method (plotBaseQuals), 42
- plotBaseQuals, FastqcDataList-method (plotBaseQuals), 42
- plotDupLevels, 45
- plotDupLevels, ANY-method (plotDupLevels), 45
- plotDupLevels, FastpData-method (plotDupLevels), 45
- plotDupLevels, FastpDataList-method (plotDupLevels), 45
- plotDupLevels, FastqcData-method (plotDupLevels), 45
- plotDupLevels, FastqcDataList-method (plotDupLevels), 45
- plotFastqcPCA, 48
- plotFastqcPCA, ANY-method (plotFastqcPCA), 48
- plotFastqcPCA, character-method (plotFastqcPCA), 48
- plotFastqcPCA, FastqcDataList-method (plotFastqcPCA), 48
- plotGcContent, 50
- plotGcContent, ANY-method (plotGcContent), 50
- plotGcContent, FastpData-method (plotGcContent), 50
- plotGcContent, FastpDataList-method (plotGcContent), 50
- plotGcContent, FastqcData-method (plotGcContent), 50
- plotGcContent, FastqcDataList-method (plotGcContent), 50
- plotInsertSize, 54
- plotInsertSize, FastpData-method (plotInsertSize), 54
- plotInsertSize, FastpDataList-method (plotInsertSize), 54
- plotKmers, 55
- plotKmers, ANY-method (plotKmers), 55
- plotKmers, FastpData-method (plotKmers), 55
- plotKmers, FastqcData-method (plotKmers), 55
- plotKmers, FastqcDataList-method (plotKmers), 55
- plotNContent, 58
- plotNContent, ANY-method (plotNContent), 58
- plotNContent, FastpData-method (plotNContent), 58
- plotNContent, FastpDataList-method (plotNContent), 58
- plotNContent, FastqcData-method (plotNContent), 58
- plotNContent, FastqcDataList-method (plotNContent), 58
- plotOverrep, 61
- plotOverrep, ANY-method (plotOverrep), 61
- plotOverrep, character-method (plotOverrep), 61
- plotOverrep, FastqcData-method (plotOverrep), 61
- plotOverrep, FastqcDataList-method (plotOverrep), 61
- plotReadTotals, 63
- plotReadTotals, ANY-method (plotReadTotals), 63
- plotReadTotals, FastpDataList-method (plotReadTotals), 63
- plotReadTotals, FastqcDataList-method (plotReadTotals), 63
- plotSeqContent, 65
- plotSeqContent, ANY-method (plotSeqContent), 65
- plotSeqContent, FastpData-method (plotSeqContent), 65
- plotSeqContent, FastpDataList-method (plotSeqContent), 65

- plotSeqContent, FastqcData-method
(plotSeqContent), 65
- plotSeqContent, FastqcDataList-method
(plotSeqContent), 65
- plotSeqLengthDistn, 68
- plotSeqLengthDistn, ANY-method
(plotSeqLengthDistn), 68
- plotSeqLengthDistn, character-method
(plotSeqLengthDistn), 68
- plotSeqLengthDistn, FastqcData-method
(plotSeqLengthDistn), 68
- plotSeqLengthDistn, FastqcDataList-method
(plotSeqLengthDistn), 68
- plotSeqQuals, 71
- plotSeqQuals, ANY-method (plotSeqQuals),
71
- plotSeqQuals, character-method
(plotSeqQuals), 71
- plotSeqQuals, FastqcData-method
(plotSeqQuals), 71
- plotSeqQuals, FastqcDataList-method
(plotSeqQuals), 71
- plotSummary, 74
- plotSummary, ANY-method (plotSummary), 74
- plotSummary, character-method
(plotSummary), 74
- plotSummary, FastqcDataList-method
(plotSummary), 74
- pwf, 75
- PwfCols (PwfCols-class), 76
- PwfCols(), 39, 44, 47, 53, 57, 60, 62, 67, 70,
72, 75
- PwfCols-class, 76

- readTotals, 77
- readTotals(), 65

- scale_colour_manual, 67
- setAlpha (getColours), 27
- setAlpha, PwfCols-method (getColours), 27
- setColours (getColours), 27
- setColours, PwfCols-method (getColours),
27
- summariseOverrep, 77
- summariseOverrep, FastpData-method
(summariseOverrep), 77
- summariseOverrep, FastpDataList-method
(summariseOverrep), 77
- summariseOverrep, FastqcData-method
(summariseOverrep), 77
- summariseOverrep, FastqcDataList-method
(summariseOverrep), 77
- theme, 39, 44, 48, 53, 55, 57, 60, 64, 67
- theme_bw, 67
- TheoreticalGC-class, 79
- writeHtmlReport, 80