

Package ‘phosponormalizer’

January 31, 2025

Type Package

Title Compensates for the bias introduced by median normalization in

Version 1.30.0

Date 2016-11-11

Description It uses the overlap between enriched and non-enriched datasets to compensate for the bias introduced in global phosphorylation after applying median normalization.

biocViews Software, StatisticalMethod, WorkflowStep, Normalization, Proteomics

License GPL (>= 2)

Imports plyr, stats, graphics, matrixStats, methods

Suggests knitr, rmarkdown, testthat

Enhances MSnbase

Depends R (>= 4.0)

VignetteBuilder knitr

NeedsCompilation no

LazyData true

git_url <https://git.bioconductor.org/packages/phosponormalizer>

git_branch RELEASE_3_20

git_last_commit 79f78b5

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2025-01-30

Author Sohrab Saraei [aut, cre],
Tomi Suomi [ctb],
Otto Kauko [ctb],
Laura Elo [ths]

Maintainer Sohrab Saraei <sohrab.saraei@blueprintgenetics.com>

Contents

enriched.rd	2
non.enriched.rd	3
normalizePhospho	4

Index**6**

enriched.rd

*Enriched dataset***Description**

A dataset containing sequences, modifications and abundances of about 4000 peptides over 5 samples with 3 technical replicates each.

Usage

enriched.rd

Format

A data frame with 4099 rows and 17 variables, all samples are median normalized:

Sequence The sequence of the peptide

Modification The modification and its location

gcNorm.ctr12.1 Sample: Control 2 Technical Replicate: 1

gcNorm.ctr12.2 Sample: Control 2 Technical Replicate: 2

gcNorm.ctr12.3 Sample: Control 2 Technical Replicate: 3

gcNorm.ctr11.1 Sample: Control 1 Technical Replicate: 1

gcNorm.ctr11.2 Sample: Control 1 Technical Replicate: 2

gcNorm.ctr11.3 Sample: Control 1 Technical Replicate: 3

gcNorm.CIP2A.1 Sample: CIP2A Technical Replicate: 1

gcNorm.CIP2A.2 Sample: CIP2A Technical Replicate: 2

gcNorm.CIP2A.3 Sample: CIP2A Technical Replicate: 3

gcNorm.RAS.1 Sample: RAS Technical Replicate: 1

gcNorm.RAS.2 Sample: RAS Technical Replicate: 2

gcNorm.RAS.3 Sample: RAS Technical Replicate: 3

gcNorm.OA.1 Sample: OA Technical Replicate: 1

gcNorm.OA.2 Sample: OA Technical Replicate: 2

gcNorm.OA.3 Sample: OA Technical Replicate: 3 ...

Value

Example Non-enriched dataset

Source

<http://www.nature.com/articles/srep13099>

non.enriched.rd	<i>Non-enriched dataset</i>
-----------------	-----------------------------

Description

A dataset containing sequences, modifications and abundances of about 17000 peptides measured over 5 samples with 3 technical replicates each.

Usage

non.enriched.rd

Format

A data frame with 16982 rows and 17 variables, all samples are median normalized:

Sequence The sequence of the peptide

Modification The modification and its location

gcNorm.ctr12.1 Sample: Control 2 Technical Replicate: 1

gcNorm.ctr12.2 Sample: Control 2 Technical Replicate: 2

gcNorm.ctr12.3 Sample: Control 2 Technical Replicate: 3

gcNorm.ctr11.1 Sample: Control 1 Technical Replicate: 1

gcNorm.ctr11.2 Sample: Control 1 Technical Replicate: 2

gcNorm.ctr11.3 Sample: Control 1 Technical Replicate: 3

gcNorm.CIP2A.1 Sample: CIP2A Technical Replicate: 1

gcNorm.CIP2A.2 Sample: CIP2A Technical Replicate: 2

gcNorm.CIP2A.3 Sample: CIP2A Technical Replicate: 3

gcNorm.RAS.1 Sample: RAS Technical Replicate: 1

gcNorm.RAS.2 Sample: RAS Technical Replicate: 2

gcNorm.RAS.3 Sample: RAS Technical Replicate: 3

gcNorm.OA.1 Sample: OA Technical Replicate: 1

gcNorm.OA.2 Sample: OA Technical Replicate: 2

gcNorm.OA.3 Sample: OA Technical Replicate: 3 ...

Value

Example Non-enriched dataset

Source

<http://www.nature.com/articles/srep13099>

normalizePhospho *Pairwise Normalization of MS-based phosphoproteomic data*

Description

This function compensates for the bias introduced in global phosphorylation in the sample after using median normalization.

Usage

```
normalizePhospho(enriched, non.enriched, phospho = NULL,
samplesCols, modseqCols, techRep, plot.fc=NULL)
```

Arguments

enriched	The enriched data with the type data.frame or MSnSet, which should contain the sequence, modification of the sequence with their phosphorylation site and their abundances across samples
non.enriched	The non-enriched data with the type data.frame or MSnSet, which should contain the sequence, modification of the sequence with their phosphorylation site and their abundances across samples
phospho	a string that shows the term that represents phosphorylation in the modification column of the data. If it is not assigned, "Phospho" will be used as the default value
samplesCols	A data.frame with two columns, with the column names enriched and non.enriched, of type numeric or integer, which must contain the column number of samples that hold the abundances
modseqCols	A data.frame with two columns, with the names enriched and non.enriched, of type numeric or integer, which must contain the column number of samples that hold the sequence and modifications of the peptides
techRep	a factor that holds information about columns order and the technical replicates of the samples
plot.fc	This parameter if set plots the fold change distribution before and after pairwise normalization. controls and samples should be set as named vectors in a list (look at the example)

Details

It is shown that global median normalization can introduce bias in the fold change of global phosphorylation between samples. It is suggested that by taking the non-enriched data into consideration, this bias could be compensated (Kauko et al. 2015).

Value

A data.frame with the normalized values and their sequence and modification.

Author(s)

Sohrab Saraei, Tomi Suomi, Otto Kauko, Laura L. Elo

Maintainer: Sohrab Saraei <sohrab.saraei@utu.fi>

References

<http://www.nature.com/articles/srep13099>

See Also

[MSnbase](#)

Examples

```
#Specifying the column numbers of abundances in the original data.frame,  
#from both enriched and non-enriched runs  
samplesCols <- data.frame(enriched=3:17, non.enriched=3:17)  
#Specifying the column numbers of sequence and modification in the original data.frame,  
#from both enriched and non-enriched runs  
modseqCols <- data.frame(enriched = 1:2, non.enriched = 1:2)  
#The samples and their technical replicates  
techRep <- factor(x = c(1,1,1,2,2,2,3,3,3,4,4,4,5,5,5))  
#Call the function  
norm <- normalizePhospho(enriched = enriched.rd, non.enriched = non.enriched.rd,  
  samplesCols = samplesCols, modseqCols = modseqCols, techRep = techRep,  
plot.fc = list(control = c(1,2), samples = c(3,4,5)))  
head(norm)
```

Index

- * **Mass-spectrometry**
 - normalizePhospho, [4](#)
 - * **Normalization,**
 - normalizePhospho, [4](#)
 - * **Phosphoproteomics,**
 - normalizePhospho, [4](#)
 - * **datasets**
 - enriched.rd, [2](#)
 - non.enriched.rd, [3](#)
- enriched.rd, [2](#)
- non.enriched.rd, [3](#)
- normalizePhospho, [4](#)