

# ITALICS

October 5, 2010

---

analyseCGH

*GLAD analysis*

---

## Description

Glad Analysis of the genomic profile

## Usage

```
analyseCGH(data, amplicon, deletion, deltaN, forceGL, param, nbsigma, ...)
```

## Arguments

|          |  |
|----------|--|
| data     | A data frame containing SNP's intensity, chromosome and position on the genome. data must have a Chr, X and LogRatio columns |
| amplicon | see the amplicon parameter in the daglad function  |
| deletion | see the deletion parameter in the daglad function  |
| deltaN   | see the deltaN parameter in the daglad function  |
| forceGL  | see the forceGL parameter in the daglad function   |
| param    | see the param parameter in the daglad function   |
| nbsigma  | see the nbsigma parameter in the daglad function   |
| ...      | Other daglad parameters.   |

## Value

An object of class profileCGH

## Note

People interested in tools dealing with array CGH analysis and DNA copy number analysis can visit our web-page <http://bioinfo.curie.fr>.

## Author(s)

Guillem Rigail, <italics@curie.fr>.

## Source

Institut Curie, <italics@curie.fr>.

ITALICS

*Affymetrix SNP chip normalization***Description**

Normalize and analyse Affymetrix SNP array 100K and 500K set (see the vignette)

**Usage**

```
ITALICS(quartetInfo, snpInfo, confidence=0.95, iteration=2,
        formule="Smoothing+QuartetEffect+FL+I (FL^2)+I (FL^3)+GC+I (GC^2)+I (GC^3)", prc=
        amplicon=2.1, deletion=-3.5, deltaN=0.15, forceGL=c(-0.2,0.2), param=c(d=2),
```

**Arguments**

|             |   |
|-------------|---|
| quartetInfo | a data frame containing all the raw quartet intensities plus there GC content, fragment length, and Quartet effect  |
| snpInfo     | a data frame containing SNPs position along the genome and raw copy number  |
| confidence  | The confidence interval. After the last bias estimation step, quartets outside this confidence interval are flagged. The lower confidence is, the more quartets will be flagged. See also the parameter prc.  |
| iteration   | The number of iteration you d'like to do  |
| formule     | A symbolic description of the term of the model. The default value of formule means that we want correct the observed quartetLogRatio using the estimated copy number (Smoothing), the Quartet Effect, the quartet Fragment Length (FL) and the quartet GC content.   |
| prc         | prc is a frequence (between 0 and 1). After the final iteration of ITALICS, badly predicted probes are flagged (see also the parameter confidence). Only SNPs having more than prc of their probes non-flagged are kept for the final GLAD analysis. The higher prc is, the more SNPs are removed before the final GLAD analysis. |
| amplicon    | see the amplicon parameter in the daglad function   |
| deletion    | see the deletion parameter in the daglad function   |
| deltaN      | see the deltaN parameter in the daglad function   |
| forceGL     | see the forceGL parameter in the daglad function  |
| param       | see the param parameter in the daglad function  |
| nbsigma     | see the nbsigma parameter in the daglad function  |
| ...         | Other daglad parameters.  |

**Details**

The function ITALICS implements the methodology which is described in the article : ITALICS: an algorithm for normalization and DNA copy number calling for Affymetrix SNP arrays (Rigaill et al., Bioinformatics Advance Access published on February 5, 2008).

The principle of the ITALICS algorithm: ITALICS, is a normalization method that estimates both the biological and the non-relevant effects in an alternate and iterative way to accurately remove the non-relevant effects.

ITALICS deals with known systematic sources of variation such as the GC-content of the quartets, the PCR amplified fragment length and the GC-content of the PCR amplified fragment . It also takes into account the quartet effect which corresponds to the fact that some quartets systematically have a small intensity while others tend to have a high intensity. ITALICS is also able to correct spatial artifacts which sometimes arise on Affymetrix SNP arrays 100K and 500K set.

### Value

Return an object of class profileCGH

### Note

People interested in tools dealing with array CGH analysis and DNA copy number analysis can visit our web-page <http://bioinfo.curie.fr>.

### Author(s)

Guillem Rigail, <italics@curie.fr>.

### Source

Institut Curie, <italics@curie.fr>.

### Examples

```
## Not run:
## step to get the path of the HF0844_Hind.CEL file
ITALICSDataPATH <- attr(as.environment(match("package:ITALICSData",search())), "path")
filename <- paste(ITALICSDataPATH, "/data/HF0844_Hind.CEL", sep="")
quartetEffectFile <- paste(ITALICSDataPATH, "/data/Hind.QuartetEffect.csv", sep="")

## load quartet effect
quartetEffect <- read.table(quartetEffectFile, sep=";", header=TRUE)

## load annotation using the pd.mapping50k.xba24 or pd.mapping50k.hind240 or pd.mapping2
headdetails <- readCelHeader(filename[1])
pkgname <- cleanPlatformName(headdetails[["chiptype"]])
snpInfo <- getSnpInfo(pkgname)
quartet <- getQuartet(pkgname, snpInfo)

## read cel files and format data
tmpExprs <- readCelIntensities(filename, indices=quartet$fid)
quartet$quartetInfo$quartetLogRatio <- readQuartetCopyNb(tmpExprs)
quartet$quartetInfo <- addInfo(quartet, quartetEffect)
snpInfo <- fromQuartetToSnp(cIntensity="quartetLogRatio", quartetInfo=quartet$quartetInfo)

## ITALICS normalization
profilSNPHind <- ITALICS(quartet$quartetInfo, snpInfo,
  formule="Smoothing+QuartetEffect+FL+I(FL^2)+I(FL^3)+GC+I(GC^2)+I(GC^3)")

## plot the profile
data(cytoband)
plotProfile(profilSNPHind, Smoothing="Smoothing", Bkp=TRUE, cytoband = cytoband)

## End(Not run)
```

---

trainITALICS            *ITALICS training*

---

### Description

Estimation of the quartet effect based on several normal sample chips

### Usage

```
trainITALICS (dir, amplicon=2.1, deletion=-3.5, deltaN=0.15, forceGL=c(-0.2,0.2
```

### Arguments

|          |   |
|----------|---|
| dir      | The directory containing the normal sample chips. All these chips should be of the same type hind, xba, nsp or sty. Only .CEL files be considered |
| amplicon | see the amplicon parameter in the daglad function   |
| deletion | see the deletion parameter in the daglad function   |
| deltaN   | see the deltaN parameter in the daglad function   |
| forceGL  | see the forceGL parameter in the daglad function  |
| param    | see the param parameter in the daglad function  |
| nbsigma  | see the nbsigma parameter in the daglad function  |
| ...      | Other daglad parameters.  |

### Details

The ITALICS function take into account a quartet effect which is computed on a reference data set of normal women samples. The ITALICSData provide quartetEffect for the Xba, Hind, Sty and Nsp chip computed on our own reference data set.

We recommand that you use your own reference data set to compute the quartet Effect by using the trainITALICS function. ITALICS reference data should contain only woman normal samples. Furthermore we recommand that you check that none of these chip have obvious spatial artifact. To so read the cel files using the read.affybatch (form the affy package). Then use the image function on the obtain affybatch object.

### Value

a data.frame with two column fsetid and quartetEffect

### Note

People interested in tools dealing with array CGH analysis and DNA copy number analysis can visit our web-page <http://bioinfo.curie.fr>.

### Author(s)

Guillem Rigaille, <italics@curie.fr>.

### Source

Institut Curie, <italics@curie.fr>.

---

|            |  |
|------------|--|
| getConfDat | <i>Elimination of badly predicted probes</i> |
|------------|--|

---

**Description**

This function eliminate badly predicted probes using a regression table and an estimated model given by the function `getModel` or `getBestBICModelLight`. Then it computes the corrected intensity.

**Usage**

```
getConfDat(confidence, quartetInfo, model)
```

**Arguments**

|                          |  |
|--------------------------|--|
| <code>confidence</code>  | The confidence interval : 0.95   |
| <code>quartetInfo</code> | A Regression table containing the variables in the model                     |
| <code>model</code>       | The class <code>lm</code> object given by the function <code>getModel</code> |

**Value**

A data frame with the corrected intensity. Only goodly predicted probes are taken into account. SNP's with more than 8 badly predicted probes get a NA.

**Note**

People interested in tools dealing with array CGH analysis and DNA copy number analysis can visit our web-page <http://bioinfo.curie.fr>.

**Author(s)**

Guillem Rigail, <[italics@curie.fr](mailto:italics@curie.fr)>.

**Source**

Institut Curie, <[italics@curie.fr](mailto:italics@curie.fr)>.

---

|               |                   |
|---------------|-------------------|
| getCorrection | <i>Correction</i> |
|---------------|-------------------|

---

**Description**

This function computes the corrected intensity.

**Usage**

```
getCorrection(effet, model, regTab)
```

**Arguments**

|        |   |
|--------|---|
| effet  | The name of the biological effect   |
| model  | The class lm object given by the getModel function  |
| regTab | The regression table used to estimate the linear model, and containing the variables in the model |

**Note**

People interested in tools dealing with array CGH analysis and DNA copy number analysis can visit our web-page <http://bioinfo.curie.fr>.

**Author(s)**

Guillem Rigaiil, <italics@curie.fr>.

**Source**

Institut Curie, <italics@curie.fr>.

---

getEffet

*Effet*

---

**Description**

This function retrieves the estimated biological effect

**Usage**

```
getEffet(effet, model, regTab)
```

**Arguments**

|        |   |
|--------|---|
| effet  | The name of the biological effect   |
| model  | The class lm object given by the getModel function  |
| regTab | The regression table used to estimate the linear model, and containing the variables in the model |

**Note**

People interested in tools dealing with array CGH analysis and DNA copy number analysis can visit our web-page <http://bioinfo.curie.fr>.

**Author(s)**

Guillem Rigaiil, <italics@curie.fr>.

**Source**

Institut Curie, <italics@curie.fr>.

---

`getModel`*Regression Model*

---

**Description**

Computes the linear regression model and and return an object of class `lm`.

**Usage**

```
getModel(formule, response, regTab)
```

**Arguments**

|                       |  |
|-----------------------|--|
| <code>formule</code>  | A symbolic description of the term of the model. It is a string                      |
| <code>response</code> | The parameter you want to explain (the response) : the SNP "LogRatio". Y is a string |
| <code>regTab</code>   | A Regression table containing the variables in the model                             |

**Note**

People interested in tools dealing with array CGH analysis and DNA copy number analysis can visit our web-page <http://bioinfo.curie.fr>.

**Author(s)**

Guillem Rigall, <[italics@curie.fr](mailto:italics@curie.fr)>.

**Source**

Institut Curie, <[italics@curie.fr](mailto:italics@curie.fr)>.

---

`getResidu`*Correction*

---

**Description**

This function retrieves the residual values

**Usage**

```
getResidu(model)
```

**Arguments**

|                    |  |
|--------------------|--|
| <code>model</code> | The class <code>lm</code> object given by the <code>getModel</code> function |
|--------------------|--|

**Note**

People interested in tools dealing with array CGH analysis and DNA copy number analysis can visit our web-page <http://bioinfo.curie.fr>.

**Author(s)**

Guillem Rigaiil, <*italics@curie.fr*>.

**Source**

Institut Curie, <*italics@curie.fr*>.

---

addInfo

*add info to quartet annotation*

---

**Description**

This function merge information obtain from the getQuartet function and a given table

**Usage**

```
addInfo(quartet, dat)
```

**Arguments**

|         |   |
|---------|---|
| quartet | list obtain through the getQuartet Function                                       |
| dat     | a data.frame with additionnal information it must contain a fsetid and fid column |

**Value**

a data.frame similar to the quartetInfo item of quartet plus additionnal column

**Note**

People interested in tools dealing with array CGH analysis and DNA copy number analysis can visit our web-page <http://bioinfo.curie.fr>.

**Author(s)**

Guillem Rigaiil, <*italics@curie.fr*>.

**Source**

Institut Curie, <*italics@curie.fr*>.



---

fromQuartetToSnp     *Compute the copy number of each SNP from its quartets intensities*

---

### Description

This function removes the LogRatio column of the snpInfo data.frame. Then compute the copy number of each SNP having its quartet intensities. And return the snpInfo data.frame with the newly computed LogRatio.

### Usage

```
fromQuartetToSnp(quartetInfo, snpInfo, cIntensity="quartetLogRatio", nLog=1)
```

### Arguments

`quartetInfo`     A table containing the quartet intensities and other quartet information. It must have a column called : fsetid.

`snpInfo`         A table containing snp information.

`cIntensity`     A vector containing the names of the quartet information to be aggregate. For example quartetLogRatio.

`nLog`            The position of the field which will be named LogRatio in the snpInfo data.frame. For example if `cIntensity = c("a", "b")` and you want b to be considered as the LogRatio you should set `nLog=2`

### Value

return the data.frame snpInfo with additionnal columns.

### Note

People interested in tools dealing with array CGH analysis and DNA copy number analysis can visit our web-page <http://bioinfo.curie.fr>.

### Author(s)

Guillem Rigaille, <[italics@curie.fr](mailto:italics@curie.fr)>.

### Source

Institut Curie, <[italics@curie.fr](mailto:italics@curie.fr)>.

---

fromSnpToQuartet     *Function to get from snp to quartet*

---

### Description

This function put the smoothing value of each SNP in front of its corresponding quartet in the quartetInfo data.frame.

### Usage

```
fromSnpToQuartet(quartetInfo, profilSNP)
```

### Arguments

quartetInfo     a data frame containing all the quartet values plus there GC content, fragment length and GC content and Quartet effect

profilSNP       a data frame, corresponding to the profileValues argument of a profilCGH object (see GLAD)

### Value

return the data.frame quartetInfo with an additionnal column: "Smoothing" corresponding to the estimated smoothing value.

### Note

People interested in tools dealing with array CGH analysis and DNA copy number analysis can visit our web-page <http://bioinfo.curie.fr>.

### Author(s)

Guillem Rigaille, <[italics@curie.fr](mailto:italics@curie.fr)>.

### Source

Institut Curie, <[italics@curie.fr](mailto:italics@curie.fr)>.

---

getQuartet             *Function to retrieve the information of each quartet*

---

### Description

This function retrieve information of each quartet. This function use the pd.mapping50k.xba240, pd.mapping50k.hind240, pd.mapping250k.sty and pd.mapping250k.nsp package.

### Usage

```
getQuartet(pkgname, snpInfo)
```

**Arguments**

|         |   |
|---------|---|
| pkgname | the chip type pd.mapping50k.xba240, pd.mapping50k.hind240, pd.mapping250k.sty or pd.mapping250k.nsp |
| snpInfo | a data frame containing SNPs position along the genome  |

**Value**

return a list with two fields. fid : containing the position of each quartet on the CEL file. quartetInfo : a data fame containing the columns : fsetid, fid, FL (fragment length) and GC (content of the quartet)

**Note**

People interested in tools dealing with array CGH analysis and DNA copy number analysis can visit our web-page <http://bioinfo.curie.fr>.

**Author(s)**

Guillem Rigaille, <*italics@curie.fr*>.

**Source**

Institut Curie, <*italics@curie.fr*>.

---

|            |   |
|------------|---|
| getSnpInfo | <i>Function to retrieve the chromosome and the position of each SNP on a given Affymetrix SNP array</i> |
|------------|---|

---

**Description**

This function retrieve the chromosome and position in bp of each SNP of a given Affymetrix SNP array. This function use the pd.mapping50k.xba240, pd.mapping50k.hind240, pd.mapping250k.sty and pd.mapping250k.nsp package.

**Usage**

```
getSnpInfo(pkgname)
```

**Arguments**

|         |   |
|---------|---|
| pkgname | the chip type pd.mapping50k.xba240, pd.mapping50k.hind240, pd.mapping250k.sty or pd.mapping250k.nsp |
|---------|---|

**Value**

Return a data.frame with five columns : fsetid, dbsnp\_rs\_id, Chr, X and fragment\_length corresponding to the fsetid, the rs\_id, the chromosome, the position on the chromosome and the PCR amplified fragment length respectively.

**Note**

People interested in tools dealing with array CGH analysis and DNA copy number analysis can visit our web-page <http://bioinfo.curie.fr>.

**Author(s)**

Guillem Rigail, <[italics@curie.fr](mailto:italics@curie.fr)>.

**Source**

Institut Curie, <[italics@curie.fr](mailto:italics@curie.fr)>.

---

readQuartetCopyNb *Read PM probes of selected quartets and compute the quartet intensity*

---

**Description**

This function read the cel files and return the raw-value of each quartet = mean of allele A and B

**Usage**

```
readQuartetCopyNb(tmpExprs)
```

**Arguments**

`tmpExprs` A vector of the perfect match intensity of allele A and B of the quartets. This vector should be sorted in a specific order. See the example given in the help of the ITALICS function.

**Value**

return a vector with the raw-value of each quartet

**Note**

People interested in tools dealing with array CGH analysis and DNA copy number analysis can visit our web-page <http://bioinfo.curie.fr>.

**Author(s)**

Guillem Rigail, <[italics@curie.fr](mailto:italics@curie.fr)>.

**Source**

Institut Curie, <[italics@curie.fr](mailto:italics@curie.fr)>.

# Index

addInfo, 8  
analyseCGH, 1  
  
fromQuartetToSnp, 9  
fromSnpToQuartet, 10  
  
getConfDat, 5  
getCorrection, 5  
getEffet, 6  
getModel, 7  
getQuartet, 10  
getResidu, 7  
getSnpInfo, 11  
  
ITALICS, 2  
Italics (*ITALICS*), 2  
italics (*ITALICS*), 2  
  
readQuartetCopyNb, 12  
  
trainITALICS, 4  
trainItalics (*trainITALICS*), 4  
trainitalics (*trainITALICS*), 4