

Package ‘GEOmetadb’

December 16, 2025

Type Package

Title A compilation of metadata from NCBI GEO

Version 1.72.0

Date 2024-12-03

Depends R.utils, RSQLite

Suggests knitr, rmarkdown, dplyr, dbplyr, tm, wordcloud

Author Jack Zhu and Sean Davis

Maintainer Jack Zhu <zhujack@mail.nih.gov>

biocViews Infrastructure

Description The NCBI Gene Expression Omnibus (GEO) represents the largest public repository of microarray data. However, finding data of interest can be challenging using current tools. GEOmetadb is an attempt to make access to the metadata associated with samples, platforms, and datasets much more feasible. This is accomplished by parsing all the NCBI GEO metadata into a SQLite database that can be stored and queried locally. GEOmetadb is simply a thin wrapper around the SQLite database along with associated documentation. Finally, the SQLite database is updated regularly as new data is added to GEO and can be downloaded at will for the most up-to-date metadata. GEOmetadb paper: <http://bioinformatics.oxfordjournals.org/cgi/content/short/24/23/2798> .

VignetteBuilder knitr

License Artistic-2.0

git_url <https://git.bioconductor.org/packages/GEOmetadb>

git_branch RELEASE_3_22

git_last_commit b851bf6

git_last_commit_date 2025-10-29

Repository Bioconductor 3.22

Date/Publication 2025-12-15

Contents

GEOmetadb-package	2
columnDescriptions	3
geoConvert	3
getBiocPlatformMap	4
getSQLiteFile	5
Index	7

GEOmetadb-package*Query NCBI GEO metadata from a local SQLite database*

Description

The NCBI Gene Expression Omnibus (GEO) represents the largest public repository of microarray data. However, finding data of interest can be challenging using current tools. GEOmetadb is an attempt to make access to the metadata associated with samples, platforms, and datasets much more feasible. This is accomplished by parsing all the NCBI GEO metadata into a SQLite database that can be stored and queried locally. GEOmetadb is simply a thin wrapper around the SQLite database along with associated documentation. Finally, the SQLite database is updated regularly as new data is added to GEO and can be downloaded at will for the most up-to-date metadata.

Details

Package: GEOmetadb
Type: Package
Version: 1.1.5
Date: 2008-09-09
License: Artistic-2.0

Author(s)

Jack Zhu and Sean Davis

Maintainer: Jack Zhu <zhujack@mail.nih.gov>

Examples

```
## Use the demo GEOmetadb database:
if( !file.exists("GEOmetadb.sqlite") ) {
  demo_sqlfile <- getSQLiteFile(destdir = getwd(), destfile = "GEOmetadb.sqlite.gz", type = "demo")
} else {
  demo_sqlfile <- "GEOmetadb.sqlite"
}
columnDescriptions(demo_sqlfile)[1:5,]
a <- columnDescriptions(demo_sqlfile)[1:5,]
b <- geoConvert('GPL96', out_type='GSM', sqlite_db_name=demo_sqlfile)

## Download the full GEOmetadb database:
## Not run: geometadbfile <- getSQLiteFile()
```

columnDescriptions	<i>Get column descriptions for the GEOmetadb database</i>
--------------------	---

Description

Searching the GEOmetadb database requires a bit of knowledge about the structure of the database and column descriptions. This function returns those column descriptions for all columns in all tables in the database.

Usage

```
columnDescriptions(sqlite_db_name='GEOmetadb.sqlite')
```

Arguments

sqlite_db_name The filename of the GEOmetadb sqlite database file

Value

A three-column data.frame including TableName, FieldName, and Description.

Author(s)

Sean Davis <sdavis2@mail.nih.gov>

Examples

```
## Use the demo GEOmetadb database:
if( !file.exists("GEOmetadb.sqlite") ) {
  demo_sqlfile <- getSQLiteFile(destdir = getwd(), destfile = "GEOmetadb.sqlite.gz", type = "demo")
} else {
  demo_sqlfile <- "GEOmetadb.sqlite"
}
columnDescriptions(demo_sqlfile)[1:5,]

## Download the full GEOmetadb database:
## Not run: geometadbfile <- getSQLiteFile()
```

geoConvert	<i>Cross-reference between GEO data types</i>
------------	---

Description

A common task is to find all the GEO entities of one type associated with another GEO entity (eg., find all GEO samples associated with GEO platform 'GPL96'). This function provides a very fast mapping between entity types to facilitate queries of this type.

Usage

```
geoConvert(in_list, out_type = c("gse", "gpl", "gsm", "gds", "smatrix"), sqlite_db_name = "GEOmetad
```

Arguments

`in_list` Character vector of GEO entities to convert from.
`out_type` Character vector of GEO entity types to which to convert.
`sqlite_db_name` The filename of the GEOmetadb sqlite database file

Value

A list of data.frames.

Author(s)

Jack Zhu <zhujack@mail.nih.gov>

Examples

```
## Use the demo GEOmetadb database:
if( !file.exists("GEOmetadb.sqlite") ) {
  demo_sqlfile <- getSQLiteFile(destdir = getwd(), destfile = "GEOmetadb.sqlite.gz", type = "demo")
} else {
  demo_sqlfile <- "GEOmetadb.sqlite"
}
ls = geoConvert('GPL96', out_type=c("GSE", 'GSM'), sqlite_db_name=demo_sqlfile)
names(ls)
head(ls[[1]])

## Download the full GEOmetadb database:
## Not run: geometadbfile <- getSQLiteFile()
```

getBiocPlatformMap	<i>Get mappings between GPL and Bioconductor microarray annotation packages</i>
--------------------	---

Description

Query the gpl table and get GPL information of a given list of Bioconductor microarray annotation packages. Note currently the GEOmetadb does not contains all the mappings, but we are trying to construct a relative complete list.

Usage

```
getBiocPlatformMap(con, bioc='all')
```

Arguments

`con` Connection to the GEOmetadb.sqlite database
`bioc` Character vector of Bioconductor microarray annotation packages, e.g. `c('hgu133plus2','hgu95av2')`.
`'all'` returns all mappings.

Value

A six-column data.frame including GPL title, GPL accession, bioc_package, manufacturer, organism, data_row_count.

Author(s)

Jack Zhu <zhujack@mail.nih.gov>, Sean Davis <sdavis2@mail.nih.gov>

Examples

```
## Use the demo GEOmetadb database:
if( !file.exists("GEOmetadb.sqlite") ) {
  demo_sqlfile <- getSQLiteFile(destdir = getwd(), destfile = "GEOmetadb.sqlite.gz", type = "demo")
} else {
  demo_sqlfile <- "GEOmetadb.sqlite"
}

con <- dbConnect(SQLite(), demo_sqlfile)
getBiocPlatformMap(con)[1:5,]
getBiocPlatformMap(con, bioc=c('hgu133a', 'hgu95av2'))
dbDisconnect(con)

## Download the full GEOmetadb database:
## Not run: geometadbfile <- getSQLiteFile()
```

getSQLiteFile

Download and unzip the most recent GEOmetadb SQLite file

Description

This function is the standard method for downloading and unzipping the most recent GEOmetadb SQLite file from the server. Note: size of the full GEOmetadb.sqlite.gz could be over 10GB and the demo database is 25MB (use type="demo")

Usage

```
getSQLiteFile(destdir = getwd(), destfile = "GEOmetadb.sqlite.gz", type = "normal")
```

Arguments

destdir	The destination directory of the downloaded file
destfile	The filename of the downloaded file. This filename should end in ".gz" as the unzipping assumes that is the case
type	type of GEOmetadb.sqlite to download, if it is 'normal', a full database will be downloaded, otherwise a demo database will be downloaded, which is 25MB.

Value

Prints some diagnostic information to the screen.
Returns the local filename for use later.

Author(s)

Sean Davis <sdavis2@mail.nih.gov>

Examples

```
## Download the demo GEOmetadb database:
if( !file.exists("GEOmetadb.sqlite") ) {
  demo_sqlfile <- getSQLiteFile(destdir = getwd(), destfile = "GEOmetadb.sqlite.gz", type = "demo")
} else {
  demo_sqlfile <- "GEOmetadb.sqlite"
}

## Download the full GEOmetadb database:
## Not run: geometadbfile <- getSQLiteFile()
```

Index

* **package**

GEOmetadb-package, [2](#)

columnDescriptions, [3](#)

geoConvert, [3](#)

GEOmetadb (GEOmetadb-package), [2](#)

GEOmetadb-package, [2](#)

getBiocPlatformMap, [4](#)

getSQLiteFile, [5](#)