

# Package ‘PhyloProfile’

December 20, 2025

**Version** 2.3.2

**Date** 2025-11-18

**Title** PhyloProfile

## Description

PhyloProfile is a tool for exploring complex phylogenetic profiles. Phylogenetic profiles, presence/absence patterns of genes over a set of species, are commonly used to trace the functional and evolutionary history of genes across species and time. With PhyloProfile we can enrich regular phylogenetic profiles with further data like sequence/structure similarity, to make phylogenetic profiling more meaningful. Besides the interactive visualisation powered by R-Shiny, the package offers a set of further analysis features to gain insights like the gene age estimation or core gene identification.

**URL** <https://github.com/BIONF/PhyloProfile/>

**BugReports** <https://github.com/BIONF/PhyloProfile/issues>

**License** MIT + file LICENSE

**Depends** R (>= 4.5.0)

**Encoding** UTF-8

**biocViews** Software, Visualization, DataRepresentation,  
MultipleComparison, FunctionalPrediction, DimensionReduction

**Imports** ape, bioDist, BiocStyle, Biostrings, bsplus, colourpicker,  
data.table, dplyr, DT, energy, fastcluster, ggplot2, gridExtra,  
htmlwidgets, pbapply, plotly, RColorBrewer, RCurl, Rfast,  
scattermore, shiny, shinycssloaders, shinyFiles, shinyjs,  
stringr, tsne, svglite, umap, xml2, zoo, yaml

**RoxygenNote** 7.3.3

**Suggests** knitr, rmarkdown, testthat, OmaDB

**VignetteBuilder** knitr

**git\_url** <https://git.bioconductor.org/packages/PhyloProfile>

**git\_branch** devel

**git\_last\_commit** 139f3a1

**git\_last\_commit\_date** 2025-11-18

**Repository** Bioconductor 3.23

**Date/Publication** 2025-12-19

**Author** Vinh Tran [aut, cre] (ORCID: <<https://orcid.org/0000-0001-6772-7595>>),  
 Bastian Greshake Tzovaras [aut],  
 Ingo Ebersberger [aut],  
 Carla Mölbert [ctb]

**Maintainer** Vinh Tran <[tran@bio.uni-frankfurt.de](mailto:tran@bio.uni-frankfurt.de)>

## Contents

|                                                |    |
|------------------------------------------------|----|
| addDimRedTaxaColors . . . . .                  | 4  |
| addFeatureColors . . . . .                     | 5  |
| addRankDivisionPlot . . . . .                  | 6  |
| calcPresSpec . . . . .                         | 8  |
| checkColorPalette . . . . .                    | 9  |
| checkInputValidity . . . . .                   | 9  |
| checkNewick . . . . .                          | 10 |
| checkOmaID . . . . .                           | 11 |
| checkOverlapDomains . . . . .                  | 11 |
| clusterDataDend . . . . .                      | 12 |
| compareMedianTaxonGroups . . . . .             | 13 |
| compareTaxonGroups . . . . .                   | 14 |
| createArchiPlot . . . . .                      | 15 |
| createDimRedPlotData . . . . .                 | 17 |
| createGeneAgePlot . . . . .                    | 18 |
| createLongMatrix . . . . .                     | 19 |
| createPercentageDistributionData . . . . .     | 20 |
| createProfileFromOma . . . . .                 | 21 |
| createUnrootedTree . . . . .                   | 21 |
| createVarDistPlot . . . . .                    | 22 |
| createVariableDistributionData . . . . .       | 23 |
| createVariableDistributionDataSubset . . . . . | 24 |
| dataCustomizedPlot . . . . .                   | 25 |
| dataFeatureTaxGroup . . . . .                  | 26 |
| dataMainPlot . . . . .                         | 27 |
| dataVarDistTaxGroup . . . . .                  | 28 |
| dimReduction . . . . .                         | 29 |
| distributionTest . . . . .                     | 30 |
| estimateGeneAge . . . . .                      | 30 |
| fallbackUmap . . . . .                         | 32 |
| fastaParser . . . . .                          | 32 |
| featureDistTaxPlot . . . . .                   | 33 |
| filteredProfile . . . . .                      | 34 |
| filterProfileData . . . . .                    | 35 |
| finalProcessedProfile . . . . .                | 37 |
| fromInputToProfile . . . . .                   | 38 |
| fullProcessedProfile . . . . .                 | 40 |

|                                    |    |
|------------------------------------|----|
| geneAgePlotDf . . . . .            | 41 |
| generateSinglePlot . . . . .       | 42 |
| getAllDomainsOma . . . . .         | 43 |
| getAllFastaOma . . . . .           | 43 |
| getCommonAncestor . . . . .        | 44 |
| getCoreGene . . . . .              | 45 |
| getDataClustering . . . . .        | 46 |
| getDataForOneOma . . . . .         | 47 |
| getDendrogram . . . . .            | 48 |
| getDistanceMatrix . . . . .        | 49 |
| getDomainFolder . . . . .          | 50 |
| getFastaFromFasInput . . . . .     | 50 |
| getFastaFromFile . . . . .         | 51 |
| getFastaFromFolder . . . . .       | 52 |
| getIDsRank . . . . .               | 53 |
| getInputTaxaID . . . . .           | 54 |
| getInputTaxaName . . . . .         | 54 |
| getNameList . . . . .              | 55 |
| getOmaDataForOneOrtholog . . . . . | 56 |
| getOmaDomainFromURL . . . . .      | 56 |
| getOmaMembers . . . . .            | 57 |
| getQualColForVector . . . . .      | 58 |
| getSelectedFastaOma . . . . .      | 58 |
| getSelectedTaxonNames . . . . .    | 59 |
| getTaxHierarchy . . . . .          | 60 |
| getTaxonomyInfo . . . . .          | 61 |
| getTaxonomyMatrix . . . . .        | 61 |
| getTaxonomyRanks . . . . .         | 62 |
| gridArrangeSharedLegend . . . . .  | 63 |
| groupLabelDimRedData . . . . .     | 64 |
| heatmapPlotting . . . . .          | 65 |
| heatmapPlottingFast . . . . .      | 66 |
| highlightProfilePlot . . . . .     | 68 |
| id2name . . . . .                  | 69 |
| idList . . . . .                   | 70 |
| joinPlotMergeLegends . . . . .     | 71 |
| linearizeArchitecture . . . . .    | 72 |
| mainLongRaw . . . . .              | 73 |
| mainTaxonomyRank . . . . .         | 74 |
| modifyFeatureName . . . . .        | 74 |
| pairDomainPlotting . . . . .       | 75 |
| parseDomainInput . . . . .         | 77 |
| parseInfoProfile . . . . .         | 78 |
| performPCA . . . . .               | 79 |
| performUmap . . . . .              | 79 |
| plotDimRed . . . . .               | 80 |
| plotDimRed3D . . . . .             | 81 |
| ppTaxonomyMatrix . . . . .         | 82 |

|                                  |     |
|----------------------------------|-----|
| ppTree . . . . .                 | 82  |
| prepareDimRedData . . . . .      | 83  |
| processNcbiTaxonomy . . . . .    | 84  |
| processOrthoID . . . . .         | 85  |
| profileWithTaxonomy . . . . .    | 85  |
| qualitativeColours . . . . .     | 86  |
| rankIndexing . . . . .           | 87  |
| rankList . . . . .               | 87  |
| reduceProfile . . . . .          | 88  |
| resolveOverlapFeatures . . . . . | 89  |
| runPhyloProfile . . . . .        | 90  |
| singleDomainPlotting . . . . .   | 90  |
| sortDomains . . . . .            | 92  |
| sortDomainsByList . . . . .      | 93  |
| sortInputTaxa . . . . .          | 94  |
| sortTaxaFromTree . . . . .       | 95  |
| taxa2dist . . . . .              | 96  |
| taxonNamesReduced . . . . .      | 96  |
| taxonomyMatrix . . . . .         | 97  |
| taxonomyTableCreator . . . . .   | 97  |
| varDistTaxPlot . . . . .         | 98  |
| wideToLong . . . . .             | 99  |
| xmlParser . . . . .              | 100 |

## Index 101

---

|                     |                                                        |
|---------------------|--------------------------------------------------------|
| addDimRedTaxaColors | <i>Add colors for taxa in dimension reduction plot</i> |
|---------------------|--------------------------------------------------------|

---

### Description

Add colors for taxa in dimension reduction plot

### Usage

```
addDimRedTaxaColors(plotDf = NULL, colorPalette = "Set2",
  highlightTaxa = NULL)
```

### Arguments

|               |                                   |
|---------------|-----------------------------------|
| plotDf        | data for dimension reduction plot |
| colorPalette  | color palette. Default: "Set2"    |
| highlightTaxa | list of taxa to be highlighted    |

### Value

A dataframe for dimension reduction plot with an additional column for the assigned color to each taxon

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[prepareDimRedData](#), [dimReduction](#), [createDimRedPlotData](#)

**Examples**

```
rawInput <- system.file(
  "extdata", "test.main.long", package = "PhyloProfile", mustWork = TRUE
)
longDf <- createLongMatrix(rawInput)
data4dimRed <- prepareDimRedData(longDf, "phylum")
dimRedCoord <- dimReduction(data4dimRed)
plotDf <- createDimRedPlotData(dimRedCoord, data4dimRed)
PhyloProfile::addDimRedTaxaColors(plotDf, colorPalette = "Set2")
```

---

|                  |                                           |
|------------------|-------------------------------------------|
| addFeatureColors | <i>Add colors for each feature/domain</i> |
|------------------|-------------------------------------------|

---

**Description**

Add colors to features/domains of 2 domain dataframes. Users can choose to color only the shared features, unique features, all features (default) or based on feature types. Default color palette is "Paired", but it can be changed.

**Usage**

```
addFeatureColors(
  seedDf = NULL,
  orthoDf = NULL,
  colorType = "all",
  colorPalette = "Paired",
  ignoreInstanceNo = FALSE
)
```

**Arguments**

|                  |                                                                                                |
|------------------|------------------------------------------------------------------------------------------------|
| seedDf           | Domain dataframe of seed protein (protein 1)                                                   |
| orthoDf          | Domain dataframe of orthologs protein (protein 2)                                              |
| colorType        | Choose to color "all", "shared", "unique" features or color by "Feature type". Default: "all"  |
| colorPalette     | Choose between "Paired", "Set1", "Set2", "Set3", "Accent", "Dark2" for the color palette       |
| ignoreInstanceNo | Ignore number of feature instances while identifying shared or unique features. Default: FALSE |

**Value**

2 dataframes (seedDf and orthoDf) with an additional column for the assigned color to each feature instance

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
# get domain data
seedID <- "101621at6656"
domainFile <- system.file(
  "extdata", "domainFiles/101621at6656.domains",
  package = "PhyloProfile", mustWork = TRUE
)
domainDf <- parseDomainInput(seedID, domainFile, "file")
# get seedDf and orthoDf
subDf <- domainDf[
  domainDf$seedID ==
  "101621at6656#101621at6656:AGRPL@224129@0:224129_0:001955:1",]
orthoDf <- subDf[subDf$orthoID == "101621at6656:DROME@7227@1:Q9VG04",]
seedDf <- subDf[subDf$orthoID != "101621at6656:DROME@7227@1:Q9VG04",]
# add colors to features
PhyloProfile::addFeatureColors(seedDf, orthoDf)
```

---

|                     |                                                             |
|---------------------|-------------------------------------------------------------|
| addRankDivisionPlot | <i>Add taxonomy rank division lines to the heatmap plot</i> |
|---------------------|-------------------------------------------------------------|

---

**Description**

Add taxonomy rank division lines to the heatmap plot

**Usage**

```
addRankDivisionPlot(profilePlot = NULL, plotDf = NULL,
  taxDB = NULL, workingRank = NULL, superRank = NULL, xAxis = "taxa",
  font = "Arial", groupLabelSize = 14, groupLabelDist = 2,
  groupLabelAngle = 90, refLine = TRUE)
```

**Arguments**

|             |                                                               |
|-------------|---------------------------------------------------------------|
| profilePlot | initial (highlighted) profile plot                            |
| plotDf      | dataframe for plotting the heatmap phylogentic profile        |
| taxDB       | path to taxonomy database (taxonomyMatrix.txt file required!) |
| workingRank | working taxonomy rank (e.g. species)                          |
| superRank   | taxonomy rank for division lines (e.g. superkingdom)          |

|                 |                                               |
|-----------------|-----------------------------------------------|
| xAxis           | type of x-axis (either "genes" or "taxa")     |
| font            | font of text. Default = Arial                 |
| groupLabelSize  | size of rank labels                           |
| groupLabelDist  | size of the plot area for rank labels         |
| groupLabelAngle | angle of rank labels                          |
| refLine         | add vertical line to separate reference taxon |

**Value**

A profile heatmap plot with highlighted gene and/or taxon of interest as ggplot object.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[heatmapPlotting](#), [highlightProfilePlot](#), [getTaxonomyMatrix](#)

**Examples**

```
data("finalProcessedProfile", package="PhyloProfile")
plotDf <- dataMainPlot(finalProcessedProfile)
plotParameter <- list(
  "xAxis" = "taxa",
  "geneIdType" = "geneID",
  "var1ID" = "FAS_FW",
  "var2ID" = "FAS_BW",
  "midVar1" = 0.5,
  "midColorVar1" = "#FFFFFF",
  "lowColorVar1" = "#FF8C00",
  "highColorVar1" = "#4682B4",
  "midVar2" = 1,
  "midColorVar2" = "#FFFFFF",
  "lowColorVar2" = "#CB4C4E",
  "highColorVar2" = "#3E436F",
  "paraColor" = "#07D000",
  "xSize" = 8,
  "ySize" = 8,
  "legendSize" = 8,
  "mainLegend" = "top",
  "dotZoom" = 0,
  "xAngle" = 60,
  "guideline" = 0,
  "colorByGroup" = FALSE,
  "colorByOrthoID" = FALSE
)
profilePlot <- heatmapPlotting(plotDf, plotParameter)
workingRank <- "class"
```

```

superRank <- "superkingdom"
addRankDivisionPlot(
  profilePlot, plotDf, NULL, workingRank, superRank, "taxa", font = "sans"
)

```

---

calcPresSpec

*Calculate percentage of present species in each super taxon*


---

## Description

Calculate percentage of present species in each super taxon

## Usage

```
calcPresSpec(profileWithTax, taxaCount)
```

## Arguments

`profileWithTax` data frame of main PhyloProfile input together with their taxonomy info (see `?profileWithTaxonomy`)

`taxaCount` number of species occur in each supertaxon (e.g. phylum or kingdom)

## Value

A data frame with

## Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

## See Also

[profileWithTaxonomy](#) for a demo input data

## Examples

```

# NOTE: for internal testing only
library(dplyr)
data("profileWithTaxonomy", package="PhyloProfile")
taxaCount <- profileWithTaxonomy %>% dplyr::count(supertaxon)
taxaCount$n <- 1
calcPresSpec(profileWithTaxonomy, taxaCount)

```

---

|                   |                                                                       |
|-------------------|-----------------------------------------------------------------------|
| checkColorPalette | <i>Check if a color palette has enough colors for a list of items</i> |
|-------------------|-----------------------------------------------------------------------|

---

**Description**

Check if a color palette has enough colors for a list of items

**Usage**

```
checkColorPalette(items, palette = "Paired")
```

**Arguments**

|         |                               |
|---------|-------------------------------|
| items   | vector contains list of items |
| palette | name of color palette         |

**Value**

TRUE if color palette has enough colors, otherwise FALSE

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
myItems <- rep("a",3)
checkColorPalette(myItems, "Set1")
```

---

|                    |                                                                  |
|--------------------|------------------------------------------------------------------|
| checkInputValidity | <i>Check the validity of the input phylogenetic profile file</i> |
|--------------------|------------------------------------------------------------------|

---

**Description**

Check if input file has one of the following format: orthoXML, multiple FASTA, tab-delimited matrix (wide or long), or list of OMA IDs.

**Usage**

```
checkInputValidity(filein)
```

**Arguments**

|        |            |
|--------|------------|
| filein | input file |
|--------|------------|

**Value**

The format of the input file format, or type of error

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[checkOmaID](#)

**Examples**

```
filein <- system.file(
  "extdata", "test.main.wide", package = "PhyloProfile", mustWork = TRUE
)
checkInputValidity(filein)
```

---

checkNewick

*Check the validity of input newick tree*

---

**Description**

Check the validity of input newick tree

**Usage**

```
checkNewick(tree, inputTaxonID = NULL)
```

**Arguments**

|              |                                                           |
|--------------|-----------------------------------------------------------|
| tree         | input newick tree                                         |
| inputTaxonID | list of all input taxon IDs for the phylogenetic profiles |

**Value**

Possible formatting error of input tree. 0 = suitable tree for using with PhyloProfile, 1 = missing parenthesis; 2 = missing comma; 3 = tree has singleton; or a list of taxa that do not exist in the input phylogenetic profile.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[getInputTaxaID](#) for getting input taxon IDs, [ppTree](#) for an example of input tree

**Examples**

```
data("ppTree", package="PhyloProfile")
checkNewick(ppTree, c("ncbi3702", "ncbi3711", "ncbi7029"))
```

---

|            |                                            |
|------------|--------------------------------------------|
| checkOmaID | <i>Check the validity of input OMA IDs</i> |
|------------|--------------------------------------------|

---

**Description**

Check if input IDs are valid OMA IDs for OMA Browser

**Usage**

```
checkOmaID(ids)
```

**Arguments**

|     |                                 |
|-----|---------------------------------|
| ids | list of ids needs to be checked |
|-----|---------------------------------|

**Value**

List of invalid IDs (not readable for OMA)

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
### Uncomment the following line to run the function
# checkOmaID("HUMAN29398")
```

---

|                     |                                                                        |
|---------------------|------------------------------------------------------------------------|
| checkOverlapDomains | <i>Identify feature type(s) containing overlapped domains/features</i> |
|---------------------|------------------------------------------------------------------------|

---

**Description**

Identify feature type(s) containing overlapped domains/features

**Usage**

```
checkOverlapDomains(domainDf)
```

**Arguments**

|          |                        |
|----------|------------------------|
| domainDf | input domain dataframe |
|----------|------------------------|

**Value**

List of feature types that have overlapped domains

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
# get domain data
seedID <- "101621at6656"
domainFile <- system.file(
  "extdata", "domainFiles/101621at6656.domains",
  package = "PhyloProfile", mustWork = TRUE
)
domainDf <- parseDomainInput(seedID, domainFile, "file")
# get seedDf and orthoDf
subDf <- domainDf[
  domainDf$seedID ==
  "101621at6656#101621at6656:AGRPL@224129@0:224129_0:001955:1",]
orthoDf <- subDf[subDf$orthoID == "101621at6656:DROME@7227@1:Q9VG04",]
# check overlap features
PhyloProfile::checkOverlapDomains(orthoDf)
```

---

clusterDataDend

---

*Create a hclust object from the distance matrix*


---

**Description**

Create a hclust object from the distance matrix

**Usage**

```
clusterDataDend(distanceMatrix = NULL, clusterMethod = "complete")
```

**Arguments**

**distanceMatrix** calculated distance matrix as dist object

**clusterMethod** clustering method ("single", "complete", "average" for UPGMA, "mcquitty" for WPGMA, "median" for WPGMC, or "centroid" for UPGMC). Default = "complete".

**Value**

An object class hclust generated based on input distance matrix and a selected clustering method.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[getDataClustering](#), [getDistanceMatrix](#), [hclust](#)

**Examples**

```
data("finalProcessedProfile", package="PhyloProfile")
data <- finalProcessedProfile
profileType <- "binary"
profiles <- getDataClustering(
  data, profileType, var1AggregateBy, var2AggregateBy)
distMethod <- "mutualInformation"
distanceMatrix <- getDistanceMatrix(profiles, distMethod)
clusterMethod <- "complete"
clusterDataDend(as.dist(distanceMatrix), clusterMethod)
```

---

compareMedianTaxonGroups

*Compare the median values of a variable between 2 taxon groups*

---

**Description**

Given the phylogenetic profiles that contains up to 2 additional variables besides the presence/absence information of the orthologous proteins. This function will compare the median scores of those variables between 2 different taxon groups (e.g. parasitic species vs non-parasitic species), which are defined as in-group and out-group. In-group is identified by the user. Out-group contains all taxa in the input phylogenetic profiles that are not part of the in-group.

**Usage**

```
compareMedianTaxonGroups(data, inGroup, useCommonAncestor, variable,
  taxDB)
```

**Arguments**

|                   |                                                                                                                                       |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| data              | input phylogenetic profile in long format (see ?mainLongRaw and ?createLongMatrix)                                                    |
| inGroup           | ID list of in-group taxa (e.g. "ncbi1234")                                                                                            |
| useCommonAncestor | TRUE/FALSE if using all taxa that share the same common ancestor with the pre-selected in-group as the in-group taxa. Default = TRUE. |
| variable          | name of the variable that need to be compared                                                                                         |
| taxDB             | Path to the taxonomy DB files                                                                                                         |

**Value**

List of genes that have a difference in the variable's median scores between the in-group and out-group taxa and their corresponding delta-median.

**Author(s)**

Vinh Tran (tran@bio.uni-frankfurt.de)

**Examples**

```
data("mainLongRaw", package="PhyloProfile")
data <- mainLongRaw
inGroup <- c("ncbi9606", "ncbi10116")
variable <- colnames(data)[4]
compareMedianTaxonGroups(data, inGroup, TRUE, variable)
```

---

|                    |                                                               |
|--------------------|---------------------------------------------------------------|
| compareTaxonGroups | <i>Compare the score distributions between 2 taxon groups</i> |
|--------------------|---------------------------------------------------------------|

---

**Description**

Given the phylogenetic profiles that contains up to 2 additional variables besides the presence/absence information of the orthologous proteins. This function will compare the distribution of those variables between 2 different taxon groups (e.g. parasitic species vs non-parasitic species), which are defined as in-group and out-group. In-group is identified by the user. Out-group contains all taxa in the input phylogenetic profiles that are not part of the in-group.

**Usage**

```
compareTaxonGroups(data, inGroup, useCommonAncestor, variable,
  significanceLevel, taxDB)
```

**Arguments**

|                   |                                                                                                                                       |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| data              | input phylogenetic profile in long format (see ?mainLongRaw and ?createLong-Matrix)                                                   |
| inGroup           | ID list of in-group taxa (e.g. "ncbi1234")                                                                                            |
| useCommonAncestor | TRUE/FALSE if using all taxa that share the same common ancestor with the pre-selected in-group as the in-group taxa. Default = TRUE. |
| variable          | name of the variable that need to be compared                                                                                         |
| significanceLevel | significant cutoff for the statistic test (between 0 and 1). Default = 0.05.                                                          |
| taxDB             | Path to the taxonomy DB files                                                                                                         |

**Value**

list of genes that have a significant difference in the variable distributions between the in-group and out-group taxa and their corresponding p-values.

**Author(s)**

Vinh Tran (tran@bio.uni-frankfurt.de)

**Examples**

```
data("mainLongRaw", package="PhyloProfile")
data <- mainLongRaw
inGroup <- c("ncbi9606", "ncbi10116")
variable <- colnames(data)[4]
compareTaxonGroups(data, inGroup, TRUE, variable, 0.05)
```

---

createArchiPlot

---

*Create protein's domain architecture plot*


---

**Description**

Create architecture plot for both seed and orthologous protein. If domains of ortholog are missing, only architecture of seed protein will be plotted. NOTE: seed protein ID is the one being shown in the profile plot, which normally is also the orthologous group ID.

**Usage**

```
createArchiPlot(info, domainDf, labelArchiSize, titleArchiSize,
  legendArchiSize, showScore, showWeight, namePosition, firstDist,
  nameType, nameSize, segmentSize, nameColor, labelPos, colorType,
  ignoreInstanceNo, currentNCBIinfo, featureClassSort, featureClassOrder,
  colorPalette, resolveOverlap, font)
```

**Arguments**

|                 |                                                                                                                                                                                                                                                                                                                                                    |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| info            | A list contains seed and ortholog's IDs                                                                                                                                                                                                                                                                                                            |
| domainDf        | Dataframe contains domain info for the seed and ortholog. This including the seed ID, orthologs IDs, sequence lengths, feature names, start and end positions, feature weights (optional) and the status to determine if that feature is important for comparison the architecture between 2 proteins* (e.g. seed protein vs ortholog) (optional). |
| labelArchiSize  | Lable size (in px). Default = 12.                                                                                                                                                                                                                                                                                                                  |
| titleArchiSize  | Title size (in px). Default = 12.                                                                                                                                                                                                                                                                                                                  |
| legendArchiSize | Title size (in px). Default = 12.                                                                                                                                                                                                                                                                                                                  |
| showScore       | Show/hide E-values and Bit-scores. Default = NULL (hide)                                                                                                                                                                                                                                                                                           |
| showWeight      | Show/hide feature weights. Default = NULL (hide)                                                                                                                                                                                                                                                                                                   |
| namePosition    | list of positions for domain names, choose from "plot", "legend" or "axis". Default: "plot"                                                                                                                                                                                                                                                        |
| firstDist       | Distance of the first domain to plot title. Default = 0.5                                                                                                                                                                                                                                                                                          |

|                   |                                                                                                                           |
|-------------------|---------------------------------------------------------------------------------------------------------------------------|
| nameType          | Type of domain names, either "Texts" or "Labels" (default)                                                                |
| nameSize          | Size of domain names. Default = 3                                                                                         |
| segmentSize       | Height of domain segment. Default = 5                                                                                     |
| nameColor         | Color of domain names (for Texts only). Default = "black"                                                                 |
| labelPos          | Position of domain names (for Labels only). Choose from                                                                   |
| colorType         | Choose to color "all", "shared", "unique" features or color by "Feature type". Default = "all"                            |
| ignoreInstanceNo  | Ignore number of feature instances while identifying shared or unique features. Default = FALSE                           |
| currentNCBIinfo   | Dataframe of the pre-processed NCBI taxonomy data. Default = NULL (will be automatically retrieved from PhyloProfile app) |
| featureClassSort  | Choose to sort features. Default = "Yes"                                                                                  |
| featureClassOrder | vector of ordered feature classes                                                                                         |
| colorPalette      | Choose between "Paired", "Set1", "Set2", "Set3", "Accent", "Dark2" for the color pallete                                  |
| resolveOverlap    | Choose to merge non-overlapped features of a feature type into one line. Default = "Yes"                                  |
| font              | font of text. Default = Arial"                                                                                            |

**Value**

A domain plot as arrangeGrob object. Use `grid::grid.draw(plot)` to render.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[singleDomainPlotting](#), [pairDomainPlotting](#), [sortDomains](#), [parseDomainInput](#)

**Examples**

```
seedID <- "101621at6656"
orthoID <- "101621at6656|AGRPL@224129@0|224129_0:001955|1"
info <- c(seedID, orthoID)
domainFile <- system.file(
  "extdata", "domainFiles/101621at6656.domains",
  package = "PhyloProfile", mustWork = TRUE
)
domainDf <- parseDomainInput(seedID, domainFile, "file")
domainDf$feature_id_mod <- domainDf$feature_id
domainDf$feature_id_mod <- gsub("SINGLE", "LCR", domainDf$feature_id_mod)
```

```

domainDf$feature_id_mod[domainDf$feature_type == "coils"] <- "Coils"
domainDf$feature_id_mod[domainDf$feature_type == "seg"] <- "LCR"
domainDf$feature_id_mod[domainDf$feature_type == "tmhmm"] <- "TM"
plot <- createArchiPlot(info, domainDf, font = "sans")
grid::grid.draw(plot)

```

---

createDimRedPlotData    *Generate data for dimension reduction plot*

---

## Description

Generate data for dimension reduction plot

## Usage

```

createDimRedPlotData(dimRedCoord = NULL, data4dimRed = NULL,
  freqCutoff = c(0,200), excludeTaxa = "None", currentNCBIinfo = NULL)

```

## Arguments

|                 |                                                                                                          |
|-----------------|----------------------------------------------------------------------------------------------------------|
| dimRedCoord     | data contains DIM reduction coordinates (from dimReduction)                                              |
| data4dimRed     | data for dimension reduction (from prepareDimRedData())                                                  |
| freqCutoff      | gene/taxon frequency cutoff range. Any labels that are outside of this range will be assigned as [Other] |
| excludeTaxa     | hide taxa from plot. Default: "None"                                                                     |
| currentNCBIinfo | table/dataframe of the pre-processed NCBI taxonomy data (/PhyloProfile/data/preProcessedTaxonomy.txt)    |

## Value

A plot as ggplot object

## Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

## See Also

[prepareDimRedData](#), [dimReduction](#)

## Examples

```

rawInput <- system.file(
  "extdata", "test.main.long", package = "PhyloProfile", mustWork = TRUE
)
longDf <- createLongMatrix(rawInput)
data4dimRed <- prepareDimRedData(longDf, "phylum")
dimRedCoord <- dimReduction(data4dimRed)
createDimRedPlotData(dimRedCoord, data4dimRed)

```

---

|                   |                             |
|-------------------|-----------------------------|
| createGeneAgePlot | <i>Create gene age plot</i> |
|-------------------|-----------------------------|

---

**Description**

Create gene age plot

**Usage**

```
createGeneAgePlot(geneAgePlotDf, textFactor = 1, font = "Arial")
```

**Arguments**

|               |                                                                |
|---------------|----------------------------------------------------------------|
| geneAgePlotDf | data frame required for plotting gene age (see ?geneAgePlotDf) |
| textFactor    | increase factor of text size                                   |
| font          | font of text. Default = Arial"                                 |

**Value**

A gene age distribution plot as a ggplot2 object

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[estimateGeneAge](#) and [geneAgePlotDf](#)

**Examples**

```
geneAgePlotDf <- data.frame(  
  name = c("Streptophyta (Phylum)", "Bikonta", "Eukaryota (Superkingdom)"),  
  count = c(7, 1, 30),  
  percentage = c(18, 3, 79)  
)  
createGeneAgePlot(geneAgePlotDf, 1, "sans")
```

---

|                  |                                                                          |
|------------------|--------------------------------------------------------------------------|
| createLongMatrix | Create a long matrix format for all kinds of input phylogenetic profiles |
|------------------|--------------------------------------------------------------------------|

---

## Description

Create a long matrix format for all kinds of input phylogenetic profiles

## Usage

```
createLongMatrix(inputFile = NULL)
```

## Arguments

|           |                                                                                             |
|-----------|---------------------------------------------------------------------------------------------|
| inputFile | input profile file in orthoXML, multiple FASTA, tab-delimited matrix format (wide or long). |
|-----------|---------------------------------------------------------------------------------------------|

## Value

A data frame of input data in long-format containing seed gene IDs ( or orthologous group IDs), their orthologous proteins together with the corresponding taxonomy IDs and values of (up to) two additional variables.

## Author(s)

Vinh Tran [tran@bio.uni-frankfurt.de](mailto:tran@bio.uni-frankfurt.de)

## See Also

[xmlParser](#), [fastaParser](#), [wideToLong](#)

## Examples

```
inputFile <- system.file(  
  "extdata", "test.main.wide", package = "PhyloProfile", mustWork = TRUE  
)  
createLongMatrix(inputFile)
```

---

`createPercentageDistributionData`*Create data for percentage present taxa distribution*

---

## Description

Create data for percentage present taxa distribution

## Usage

```
createPercentageDistributionData(inputData = NULL, rankName = NULL,  
                                taxDB = NULL)
```

## Arguments

|                        |                                                                     |
|------------------------|---------------------------------------------------------------------|
| <code>inputData</code> | dataframe contains raw input data in long format (see ?mainLongRaw) |
| <code>rankName</code>  | name of the working taxonomy rank (e.g. "species", "family")        |
| <code>taxDB</code>     | Path to the taxonomy DB files                                       |

## Value

A dataframe for analysing the distribution of the percentage of species in the selected supertaxa, containing the seed protein IDs, percentage of their orthologs in each supertaxon and the corresponding supertaxon names.

## Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

## See Also

[mainLongRaw](#)

## Examples

```
data("mainLongRaw", package="PhyloProfile")  
createPercentageDistributionData(mainLongRaw, "class")
```

---

createProfileFromOma     *Create a phylogenetic profile from a raw OMA dataframe*

---

**Description**

Create a phylogenetic profile from a raw OMA dataframe

**Usage**

```
createProfileFromOma(finalOmaDf = NULL)
```

**Arguments**

finalOmaDf     raw OMA data for a list of proteins (see ?getDataForOneOma)

**Value**

Dataframe of the phylogenetic profiles in long format, which contains the seed protein IDs, their orthologous proteins and the corresponding taxononmy IDs of the orthologs.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[getDataForOneOma](#)

**Examples**

```
### Uncomment the following lines to run the function
# omaData <- getDataForOneOma("HUMAN29397", "OG")
# createProfileFromOma(omaData)
```

---

createUnrootedTree     *Create unrooted tree from a taxonomy matrix*

---

**Description**

Create unrooted tree from a taxonomy matrix

**Usage**

```
createUnrootedTree(df)
```

**Arguments**

df                      data frame contains taxonomy matrix used for generating tree

**Value**

A unrooted taxonomy tree as an object of class "phylo".

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[taxa2dist](#) for distance matrix generation from a taxonomy matrix, [getTaxonomyMatrix](#) for getting taxonomy matrix, [ppTaxonomyMatrix](#) for a demo taxonomy matrix data

**Examples**

```
data("ppTaxonomyMatrix", package = "PhyloProfile")
createUnrootedTree(ppTaxonomyMatrix)
```

---

createVarDistPlot              *Create distribution plot*

---

**Description**

Create distribution plot for one of the additional variable or the percentage of the species present in the supertaxa.

**Usage**

```
createVarDistPlot(data, varName = "var", varType = "var1",
  percent = c(0, 1), textSize = 12)
```

**Arguments**

|          |                                                                                                                                                        |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| data     | dataframe contains data for plotting (see ?createVariableDistributionData, ?createVariableDistributionDataSubset or ?createPercentageDistributionData) |
| varName  | name of the variable that need to be analyzed (either name of variable 1 or variable 2 or "percentage of present taxa"). Default = "var".              |
| varType  | type of variable (either "var1", "var2" or "presSpec"). Default = "var1".                                                                              |
| percent  | range of percentage cutoff (between 0 and 1). Default = c(0,1)                                                                                         |
| textSize | text size of the distribution plot (in px). Default = 12.                                                                                              |

**Value**

A distribution plot for the selected variable as a ggplot object

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[mainLongRaw](#), [createVariableDistributionData](#), [createVariableDistributionDataSubset](#), [createPercentageDistributionData](#)

**Examples**

```
data("mainLongRaw", package="PhyloProfile")
data <- createVariableDistributionData(
  mainLongRaw, c(0, 1), c(0.5, 1)
)
varName <- "Variable abc"
varType <- "var1"
percent <- c(0,1)
textSize <- 12
createVarDistPlot(
  data,
  varName,
  varType,
  percent,
  textSize
)
```

---

```
createVariableDistributionData
```

*Create data for additional variable distribution*

---

**Description**

Create data for additional variable distribution

**Usage**

```
createVariableDistributionData(inputData, var1Cutoff = c(0, 1),
  var2Cutoff = c(0, 1))
```

**Arguments**

|            |                                                                     |
|------------|---------------------------------------------------------------------|
| inputData  | dataframe contains raw input data in long format (see ?mainLongRaw) |
| var1Cutoff | min and max cutoff for var1. Default = c(0, 1).                     |
| var2Cutoff | min and max cutoff for var2. Default = c(0, 1).                     |

**Value**

A dataframe for analysing the distribution of the additional variable(s) containing the protein (ortholog) IDs and the values of their variables (var1 and var2).

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[mainLongRaw](#)

**Examples**

```
data("mainLongRaw", package="PhyloProfile")
createVariableDistributionData(
  mainLongRaw, c(0, 1), c(0.5, 1)
)
```

---

```
createVariableDistributionDataSubset
```

*Create data for additional variable distribution (for a subset data)*

---

**Description**

Create data for additional variable distribution (for a subset data)

**Usage**

```
createVariableDistributionDataSubset(fullProfileData,
  distributionData, selectedGenes, selectedTaxa)
```

**Arguments**

|                  |                                                                                                                       |
|------------------|-----------------------------------------------------------------------------------------------------------------------|
| fullProfileData  | dataframe contains the full processed profiles (see ?fullProcessedProfile, ?filterProfileData or ?fromInputToProfile) |
| distributionData | dataframe contains the full distribution data (see ?createVariableDistributionData)                                   |
| selectedGenes    | list of genes of interest. Default = "all".                                                                           |
| selectedTaxa     | list of taxa of interest Default = "all".                                                                             |

**Value**

A dataframe for analysing the distribution of the additional variable(s) for a subset of genes and/or taxa containing the protein (ortholog) IDs and the values of their variables (var1 and var2).

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[parseInfoProfile](#), [createVariableDistributionData](#), [fullProcessedProfile](#), [mainLongRaw](#)

**Examples**

```
data("fullProcessedProfile", package="PhyloProfile")
data("mainLongRaw", package="PhyloProfile")
distributionData <- createVariableDistributionData(
  mainLongRaw, c(0, 1), c(0.5, 1)
)
selectedGenes <- "100136at6656"
selectedTaxa <- c("Mammalia", "Saccharomycetes", "Insecta")
createVariableDistributionDataSubset(
  fullProcessedProfile,
  distributionData,
  selectedGenes,
  selectedTaxa
)
```

---

|                    |                                                |
|--------------------|------------------------------------------------|
| dataCustomizedPlot | <i>Create data for customized profile plot</i> |
|--------------------|------------------------------------------------|

---

**Description**

Create data for customized profile plot based on a selected list of genes and/or taxa, containing seed protein IDs (geneID), ortholog IDs (orthoID) together with their ncbi taxonomy IDs (ncbiID and abbrName), full names (fullName), indexed supertaxa (supertaxon), values for additional variables (var1, var2) and the aggregated values of those additional variables for each supertaxon (mVar1, mVar2), number of original and filtered co-orthologs in each supertaxon (paralog and paralogNew), number of species in each supertaxon (numberSpec) and the each supertaxon (presSpec).

**Usage**

```
dataCustomizedPlot(dataHeat = NULL, selectedTaxa = "all",
  selectedSeq = "all")
```

**Arguments**

|              |                                                                                                                      |
|--------------|----------------------------------------------------------------------------------------------------------------------|
| dataHeat     | a data frame contains processed profiles (see <code>?fullProcessedProfile</code> , <code>?filterProfileData</code> ) |
| selectedTaxa | selected subset of taxa. Default = "all".                                                                            |
| selectedSeq  | selected subset of genes. Default = "all".                                                                           |

**Value**

A dataframe contains data for plotting the customized profile.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[filterProfileData](#)

**Examples**

```
data("finalProcessedProfile", package="PhyloProfile")
selectedTaxa <- c("Mammalia", "Saccharomycetes", "Insecta")
selectedSeq <- "all"
dataCustomizedPlot(finalProcessedProfile, selectedTaxa, selectedSeq)
```

---

|                     |                                                             |
|---------------------|-------------------------------------------------------------|
| dataFeatureTaxGroup | <i>Create data for feature distribution comparison plot</i> |
|---------------------|-------------------------------------------------------------|

---

**Description**

Create data for plotting the distribution of the protein domain features between 2 group of taxa for a selected gene (average number of feature occurrence per protein/ortholog).

**Usage**

```
dataFeatureTaxGroup(mainDf, domainDf, inGroup, gene)
```

**Arguments**

|          |                                                                                                                                                                                                                                                                                                                                                                            |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| mainDf   | input phylogenetic profile in long format (see ?mainLongRaw and ?createLongMatrix)                                                                                                                                                                                                                                                                                         |
| domainDf | dataframe contains domain info for the seed and ortholog. This including the seed ID, orthologs IDs, sequence lengths, feature names, start and end positions, feature weights (optional) and the status to determine if that feature is important for comparison the architecture between 2 proteins* (e.g. seed protein vs ortholog) (optional). (see ?parseDomainInput) |
| inGroup  | ID list of in-group taxa (e.g. "ncbi1234")                                                                                                                                                                                                                                                                                                                                 |
| gene     | ID of gene that need to be plotted the feature distribution comparison between in- and out-group taxa.                                                                                                                                                                                                                                                                     |

**Value**

Dataframe containing all feature names, their frequencies (absolute count and the average instances per protein - IPP) in each taxon group and the corresponding taxa group type (in- or out-group).

**Author(s)**

Vinh Tran (tran@bio.uni-frankfurt.de)

**See Also**

[createLongMatrix](#), [parseDomainInput](#)

**Examples**

```
data("mainLongRaw", package="PhyloProfile")
mainDf <- mainLongRaw
gene <- "101621at6656"
inputFile <- system.file(
  "extdata", "domainFiles/101621at6656.domains",
  package = "PhyloProfile", mustWork = TRUE
)
type <- "file"
domainDf <- parseDomainInput(gene, inputFile, type)
inGroup <- c("ncbi9606", "ncbi10116")
dataFeatureTaxGroup(mainDf, domainDf, inGroup, gene)
```

---

|              |                                          |
|--------------|------------------------------------------|
| dataMainPlot | <i>Create data for main profile plot</i> |
|--------------|------------------------------------------|

---

**Description**

Create data for main profile plot

**Usage**

```
dataMainPlot(dataHeat = NULL)
```

**Arguments**

|          |                                                                                                                            |
|----------|----------------------------------------------------------------------------------------------------------------------------|
| dataHeat | a data frame contains processed profiles (see <a href="#">?fullProcessedProfile</a> , <a href="#">?filterProfileData</a> ) |
|----------|----------------------------------------------------------------------------------------------------------------------------|

**Value**

A dataframe for plotting the phylogenetic profile, containing seed protein IDs (geneID), ortholog IDs (orthoID) together with their ncbi taxonomy IDs (ncbiID and abbrName), full names (full-Name), indexed supertaxa (supertaxon), values for additional variables (var1, var2) and the aggregated values of those additional variables for each supertaxon (mVar1, mVar2), number of original and filtered co-orthologs in each supertaxon (paralog and paralogNew), number of species in each supertaxon (numberSpec) and the species that have orthologs in each supertaxon (presSpec).

**Author(s)**

Vinh Tran [tran@bio.uni-frankfurt.de](mailto:tran@bio.uni-frankfurt.de)

**See Also**

[filterProfileData](#)

**Examples**

```
data("finalProcessedProfile", package="PhyloProfile")
dataMainPlot(finalProcessedProfile)
```

---

|                     |                                                              |
|---------------------|--------------------------------------------------------------|
| dataVarDistTaxGroup | <i>Create data for variable distribution comparison plot</i> |
|---------------------|--------------------------------------------------------------|

---

**Description**

Create data for plotting the distribution comparison between 2 groups of taxa for a selected gene.

**Usage**

```
dataVarDistTaxGroup(data, inGroup, gene, variable)
```

**Arguments**

|          |                                                                                                |
|----------|------------------------------------------------------------------------------------------------|
| data     | input phylogenetic profile in long format (see ?mainLongRaw and ?createLongMatrix)             |
| inGroup  | ID list of in-group taxa (e.g. "ncbi1234")                                                     |
| gene     | ID of gene that need to be plotted the distribution comparison between in- and out-group taxa. |
| variable | var1 or c(var1, var2)                                                                          |

**Value**

Dataframe containing list of values for all available variables for the selected genes in in-group and out-group taxa (max. 3 columns).

**Author(s)**

Vinh Tran (tran@bio.uni-frankfurt.de)

**See Also**

[createLongMatrix](#)

**Examples**

```
data("mainLongRaw", package="PhyloProfile")
data <- mainLongRaw
inGroup <- c("ncbi9606", "ncbi10116")
variable <- colnames(data)[c(4, 5)]
dataVarDistTaxGroup(data, inGroup, "101621at6656", variable)
```

---

|              |                                       |
|--------------|---------------------------------------|
| dimReduction | <i>Perform dimension reduction 2D</i> |
|--------------|---------------------------------------|

---

## Description

Perform dimension reduction 2D

## Usage

```
dimReduction(data4dimRed = NULL, by = "taxa", type = "binary",
  randomSeed = 123, reductionTechnique = "umap", dimension = "2d",
  tsneIter = 1000)
```

## Arguments

|                    |                                                                       |
|--------------------|-----------------------------------------------------------------------|
| data4dimRed        | data for dimension reduction (from prepareDimRedData)                 |
| by                 | cluster data by "taxa" (default) or "genes"                           |
| type               | type of data, either "binary" (default) or "non-binary"               |
| randomSeed         | random seed. Default: 123                                             |
| reductionTechnique | dimensionality reduction technique, either "umap" (default) or "tsne" |
| dimension          | either "2d" (default) or "3d"                                         |
| tsneIter           | number of iterations for t-SNE. Default: 1000                         |

## Value

A table contains coordinates of the 2D dimension reduction

## Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

## See Also

[prepareDimRedData](#)

## Examples

```
rawInput <- system.file(
  "extdata", "test.main.long", package = "PhyloProfile", mustWork = TRUE
)
longDf <- createLongMatrix(rawInput)
data4dimRed <- prepareDimRedData(longDf, "phylum")
dimReduction(data4dimRed)
```

---

|                  |                                                      |
|------------------|------------------------------------------------------|
| distributionTest | <i>Compare the distribution of 2 numeric vectors</i> |
|------------------|------------------------------------------------------|

---

### Description

This function tests the difference between the distributions of two input numeric samples using the statistical test. First the Kolmogorov-Smirnov is used to check if 2 samples have the same distribution. If yes, Wilcoxon-Mann-Whitney will be used to compare the distribution difference.

### Usage

```
distributionTest(varIn, varOut, significanceLevel)
```

### Arguments

|                   |                                                                    |
|-------------------|--------------------------------------------------------------------|
| varIn             | first numeric vector                                               |
| varOut            | second numeric vector                                              |
| significanceLevel | significant cutoff of the Kolmogorov-Smirnov test. Default = 0.05. |

### Value

p-value of the comparison test.

### Author(s)

Carla Mölbert (carla.moelbert@gmx.de)

---

|                 |                                                                           |
|-----------------|---------------------------------------------------------------------------|
| estimateGeneAge | <i>Calculate the phylogenetic gene age from the phylogenetic profiles</i> |
|-----------------|---------------------------------------------------------------------------|

---

### Description

Calculate the phylogenetic gene age from the phylogenetic profiles

### Usage

```
estimateGeneAge(processedProfileData, taxaCount, rankName, refTaxon,
  var1C0, var2C0, percentC0, taxDB = NULL)
```

**Arguments**

|                      |                                                                                                              |
|----------------------|--------------------------------------------------------------------------------------------------------------|
| processedProfileData | dataframe contains the full processed phylogenetic profiles (see ?fullProcessedProfile or ?parseInfoProfile) |
| taxaCount            | dataframe counting present taxa in each supertaxon                                                           |
| rankName             | working taxonomy rank (e.g. "species", "genus", "family")                                                    |
| refTaxon             | reference taxon name (e.g. "Homo sapiens", "Homo" or "Hominidae")                                            |
| var1CO               | cutoff for var1. Default: c(0, 1)                                                                            |
| var2CO               | cutoff for var2. Default: c(0, 1)                                                                            |
| percentCO            | cutoff for percentage of species present in each supertaxon. Default: c(0, 1)                                |
| taxDB                | Path to the taxonomy DB files                                                                                |

**Value**

A dataframe contains estimated gene ages for the seed proteins.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[parseInfoProfile](#) for creating a full processed profile dataframe; [getNameList](#) and [getTaxonomyMatrix](#) for getting taxonomy info, [fullProcessedProfile](#) for a demo input dataframe

**Examples**

```
library(dplyr)
data("fullProcessedProfile", package="PhyloProfile")
rankName <- "class"
refTaxon <- "Mammalia"
processedProfileData <- fullProcessedProfile
taxonIDs <- levels(as.factor(processedProfileData$ncbiID))
sortedInputTaxa <- sortInputTaxa(
  taxonIDs, rankName, refTaxon, NULL, NULL
)
taxaCount <- sortedInputTaxa %>% dplyr::count(supertaxon)
var1Cutoff <- c(0, 1)
var2Cutoff <- c(0, 1)
percentCutoff <- c(0, 1)
estimateGeneAge(
  processedProfileData,
  taxaCount,
  rankName,
  refTaxon,
  var1Cutoff, var2Cutoff, percentCutoff
)
```

---

|              |                                                          |
|--------------|----------------------------------------------------------|
| fallbackUmap | <i>Fallback for UMAP in case of insufficient samples</i> |
|--------------|----------------------------------------------------------|

---

**Description**

Fallback for UMAP in case of insufficient samples

**Usage**

```
fallbackUmap(umapDt, randomSeed, dim)
```

**Arguments**

|            |                                                  |
|------------|--------------------------------------------------|
| umapDt     | data matrix for UMAP                             |
| randomSeed | random seed. Default: 123                        |
| dim        | dimension, either 2 for 2D (default) or 3 for 3D |

**Value**

A table contains coordinates UMAP reduction

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

---

|             |                                     |
|-------------|-------------------------------------|
| fastaParser | <i>Parse multi-fasta input file</i> |
|-------------|-------------------------------------|

---

**Description**

Parse multi-fasta input file

**Usage**

```
fastaParser(inputFile = NULL)
```

**Arguments**

|           |                                                                                                                                                                                                                                                             |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| inputFile | input multiple fasta file. Check extdata/test.main.fasta or <a href="https://github.com/BIONF/PhyloProfile/wiki/Input-Data#multi-fasta-format">https://github.com/BIONF/PhyloProfile/wiki/Input-Data#multi-fasta-format</a> for the supported FASTA header. |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**Value**

A data frame of input data in long-format containing seed gene IDs ( or orthologous group IDs), their orthologous proteins together with the corresponding taxonomy IDs and values of (up to) two additional variables.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
inputFile <- system.file(  
  "extdata", "test.main.fasta", package = "PhyloProfile", mustWork = TRUE  
)  
fastaParser(inputFile)
```

---

|                    |                                             |
|--------------------|---------------------------------------------|
| featureDistTaxPlot | Create feature distribution comparison plot |
|--------------------|---------------------------------------------|

---

**Description**

Create protein feature distribution plots between 2 groups of taxa for a selected gene.

**Usage**

```
featureDistTaxPlot(data, plotParameters)
```

**Arguments**

|                |                                                                                                                                                                                                                                                    |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data           | dataframe for plotting (see ?dataFeatureTaxGroup)                                                                                                                                                                                                  |
| plotParameters | plot parameters, including size of x-axis, y-axis, legend and title; position of legend ("right", "bottom" or "none"); names of in-group and out-group; flip the plot coordinate ("Yes" or "No"). NOTE: Leave blank or NULL to use default values. |

**Value**

Distribution plots as a ggplot2 object.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[dataFeatureTaxGroup](#)

**Examples**

```

data("mainLongRaw", package="PhyloProfile")
data <- mainLongRaw
gene <- "101621at6656"
inputFile <- system.file(
  "extdata", "domainFiles/101621at6656.domains",
  package = "PhyloProfile", mustWork = TRUE
)
type <- "file"
domainDf <- parseDomainInput(gene, inputFile, type)
inGroup <- c("ncbi9606", "ncbi10116")
plotDf <- dataFeatureTaxGroup(data, domainDf, inGroup, gene)
plotParameters <- list(
  "xSize" = 12,
  "ySize" = 12,
  "angle" = 15,
  "legendSize" = 12,
  "inGroupName" = "In-group",
  "outGroupName" = "Out-group",
  "flipPlot" = "No"
)
featureDistTaxPlot(plotDf, plotParameters)

```

---

filteredProfile

*An example of a filtered phylogenetic profile*


---

**Description**

An example of a filtered phylogenetic profile

**Usage**

```
data(filteredProfile)
```

**Format**

Dataframe

**Value**

A data frame with 168 rows and 20 variables:

- geneID Seed or ortholog group ID, e.g. "100136at6656"
- supertaxon Supertaxon name together with its ordered index, e.g. "1001\_Mammalia"
- ncbiID Taxon ID, e.g. "ncbi10116"
- orthoID Ortholog ID, e.g. "100136at6656|HUMAN@9606@1|Q9UNQ2|1"
- var1 First additional variable

- var2 Second additional variable
- paralog Number of co-orthologs in the current taxon
- abbrName NCBI ID of the ortholog, e.g. "ncbi9606"
- taxonID Taxon ID of the ortholog, in this case: "0"
- fullName Full taxon name of the ortholog, e.g. "Homo sapiens"
- supertaxonID Supertaxon ID (only different than ncbiID in case working with higher taxonomy rank than input's). e.g. "40674"
- rank Rank of the supertaxon, e.g. "class"
- category "cat"
- numberSpec Total number of species in each supertaxon
- taxonMod Name of supersupertaxon w/o its index, e.g. "Mammalia"
- presSpec Percentage of taxa having orthologs in each supertaxon
- presentTaxa Number of taxa that have ortho in each supertaxon
- totalTaxa Total number of taxa in each supertaxon
- mVar1 Value of the 1. variable after grouping into supertaxon
- mVar2 Value of the 2. variable after grouping into supertaxon

---

|                   |                                    |
|-------------------|------------------------------------|
| filterProfileData | <i>Filter phylogentic profiles</i> |
|-------------------|------------------------------------|

---

## Description

Create a filtered data needed for plotting or clustering phylogenetic profiles. NOTE: this function require some intermediate steps using the results from other functions. If you would like to get a full processed data from the raw input, please use the function fromInputToProfile() instead!

## Usage

```
filterProfileData(DF, taxaCount, refTaxon = NULL,
  percentCO = c(0, 1), coorthoCOMax = 9999,
  var1CO = c(0, 1), var2CO = c(0, 1), var1Rel = "protein",
  var2Rel = "protein", groupByCat = FALSE, catDt = NULL,
  var1AggregateBy = "max", var2AggregateBy = "max")
```

## Arguments

|           |                                                                                                                                                    |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| DF        | a reduced dataframe contains info for all phylogenetic profiles in the selected taxonomy rank.                                                     |
| taxaCount | dataframe counting present taxa in each supertaxon                                                                                                 |
| refTaxon  | selected reference taxon. NOTE: This taxon will not be affected by the filtering. If you want to filter all, set refTaxon <- NULL. Default = NULL. |

|                 |                                                                                                                   |
|-----------------|-------------------------------------------------------------------------------------------------------------------|
| percentC0       | min and max cutoffs for percentage of species present in a supertaxon. Default = c(0, 1).                         |
| coorthoC0Max    | maximum number of co-orthologs allowed. Default = 9999.                                                           |
| var1C0          | min and max cutoffs for var1. Default = c(0, 1).                                                                  |
| var2C0          | min and max cutoffs for var2. Default = c(0, 1).                                                                  |
| var1Rel         | relation of var1 ("protein" for protein-protein or "species" for protein-species). Default = "protein".           |
| var2Rel         | relation of var2 ("protein" for protein-protein or "species" for protein-species). Default = "protein".           |
| groupByCat      | group genes by their categories (TRUE or FALSE). Default = FALSE.                                                 |
| catDt           | dataframe contains gene categories (optional, NULL if groupByCat = FALSE or no info provided). Default = NULL.    |
| var1AggregateBy | aggregate method for VAR1 (max, min, mean or median), applied for calculating var1 of supertaxa. Default = "max". |
| var2AggregateBy | aggregate method for VAR2 (max, min, mean or median), applied for calculating var2 of supertaxa. Default = "max". |

### Value

A filtered dataframe for generating profile plot including seed gene IDs (or orthologous group IDs), their ortholog IDs and the corresponding (super)taxa, (super)taxon IDs, number of co-orthologs in each (super)taxon, values for two additional variables var1, var2, supertaxon, and the categories of seed genes (or ortholog groups).

### Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

### See Also

[parseInfoProfile](#) and [reduceProfile](#) for generating input dataframe, [fullProcessedProfile](#) for a demo full processed profile dataframe, [fromInputToProfile](#) for generating fully processed data from raw input.

### Examples

```
# NOTE: this function require some intermediate steps using the results from
# other functions. If you would like to get a full processed data from the
# raw input, please use the function fromInputToProfile() instead!
library(dplyr)
data("fullProcessedProfile", package="PhyloProfile")
rankName <- "class"
refTaxon <- "Mammalia"
percentCutoff <- c(0.0, 1.0)
coorthologCutoffMax <- 10
var1Cutoff <- c(0.75, 1.0)
```

```

var2Cutoff <- c(0.5, 1.0)
var1Relation <- "protein"
var2Relation <- "species"
groupByCat <- FALSE
catDt <- NULL
var1AggregateBy <- "max"
var2AggregateBy <- "max"
taxonIDs <- levels(as.factor(fullProcessedProfile$ncbiID))
sortedInputTaxa <- sortInputTaxa(
  taxonIDs, rankName, refTaxon, NULL, NULL
)
taxaCount <- sortedInputTaxa %>% dplyr::group_by(supertaxon) %>%
  summarise(n = n(), .groups = "drop")
filterProfileData(
  fullProcessedProfile,
  taxaCount,
  refTaxon,
  percentCutoff,
  coorthologCutoffMax,
  var1Cutoff,
  var2Cutoff,
  var1Relation,
  var2Relation,
  groupByCat,
  catDt,
  var1AggregateBy,
  var2AggregateBy
)

```

---

`finalProcessedProfile` *An example of a final processed & filtered phylogenetic profile*

---

### Description

An example of a final processed & filtered phylogenetic profile

### Usage

```
data(finalProcessedProfile)
```

### Format

Dataframe

### Value

A data frame with 88 rows and 11 variables:

- geneID Seed or ortholog group ID, e.g. "100136at6656"
- supertaxon Supertaxon name together with its ordered index, e.g. "1001\_Mammalia"

- supertaxonID Supertaxon ID (only different than ncbiID in case working with higher taxonomy rank than input's). e.g. "40674"
- var1 First additional variable
- presSpec The percentage of species presenting in each supertaxon
- category "cat"
- orthoID Ortholog ID, e.g. "100136at6656|RAT@10116@1|G3V7R8|1"
- var2 Second additional variable
- paralog Number of co-orthologs in the current taxon
- presentTaxa Number of taxa that have ortho in each supertaxon
- totalTaxa Total number of taxa in each supertaxon

---

|                    |                                                               |
|--------------------|---------------------------------------------------------------|
| fromInputToProfile | <i>Complete processing of raw input phylogenetic profiles</i> |
|--------------------|---------------------------------------------------------------|

---

## Description

Create a processed and filtered data for plotting or analysing phylogenetic profiles from raw input file (from raw input to final filtered dataframe)

## Usage

```
fromInputToProfile(rawInput, rankName, refTaxon = NULL,
  taxaTree = NULL, sortedTaxonList = NULL, var1AggregateBy = "max",
  var2AggregateBy = "max", percentCutoff = c(0, 1),
  coorthologCutoffMax = 9999, var1Cutoff = c(0, 1), var2Cutoff = c(0, 1),
  var1Relation = "protein", var2Relation = "protein", groupByCat = FALSE,
  catDt = NULL, taxDB = NULL)
```

## Arguments

|                 |                                                                                                        |
|-----------------|--------------------------------------------------------------------------------------------------------|
| rawInput        | input file (in long, wide, multi-fasta or orthoxml format)                                             |
| rankName        | taxonomy rank (e.g. "species", "phylum", ...)                                                          |
| refTaxon        | selected reference taxon name (used for sorting and will be protected from filtering). Default = NULL. |
| taxaTree        | input taxonomy tree for taxa in input profiles (optional). Default = NULL.                             |
| sortedTaxonList | list of sorted taxa (optional). Default = NULL.                                                        |
| var1AggregateBy | aggregate method for var1 (min, max, mean or median). Default = "max".                                 |
| var2AggregateBy | aggregate method for VAR2 (min, max, mean or median). Default = "max".                                 |
| percentCutoff   | min and max cutoffs for percentage of species present in a supertaxon. Default = c(0, 1).              |

|                     |                                                                                                         |
|---------------------|---------------------------------------------------------------------------------------------------------|
| coorthologCutoffMax | maximum number of co-orthologs allowed. Default = 9999.                                                 |
| var1Cutoff          | min and max cutoffs for var1. Default = c(0, 1).                                                        |
| var2Cutoff          | min and max cutoffs for var2. Default = c(0, 1).                                                        |
| var1Relation        | relation of var1 ("protein" for protein-protein or "species" for protein-species). Default = "protein". |
| var2Relation        | relation of var2 ("protein" for protein-protein or "species" for protein-species). Default = "protein". |
| groupByCat          | group genes by their categories (TRUE or FALSE). Default = FALSE.                                       |
| catDt               | dataframe contains gene categories. Default = NULL                                                      |
| taxDB               | Path to the taxonomy DB files                                                                           |

**Value**

Dataframe required for generating phylogenetic profile plot or clustering analysis. It contains seed gene IDs (or orthologous group IDs), their ortholog IDs and the corresponding (super)taxa, (super)taxon IDs, number of co-orthologs in each (super)taxon, values for two additional variables var1, var2, categories of seed genes (or ortholog groups).

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[createLongMatrix](#), [getInputTaxaID](#), [getInputTaxaName](#), [sortInputTaxa](#), [parseInfoProfile](#), [reduceProfile](#), [filterProfileData](#)

**Examples**

```

rawInput <- system.file(
  "extdata", "test.main.long", package = "PhyloProfile", mustWork = TRUE
)
rankName <- "class"
refTaxon <- "Mammalia"
taxaTree <- NULL
sortedTaxonList <- NULL
var1AggregateBy <- "max"
var2AggregateBy <- "mean"
percentCutoff <- c(0.0, 1.0)
coorthologCutoffMax <- 10
var1Cutoff <- c(0.75, 1.0)
var2Cutoff <- c(0.5, 1.0)
var1Relation <- "protein"
var2Relation <- "species"
groupByCat <- FALSE
catDt <- NULL
fromInputToProfile(
  rawInput,

```

```

    rankName,
    refTaxon,
    taxaTree,
    sortedTaxonList,
    var1AggregateBy,
    var2AggregateBy,
    percentCutoff,
    coorthologCutoffMax,
    var1Cutoff,
    var2Cutoff,
    var1Relation,
    var2Relation,
    groupByCat,
    catDt
  )

```

---

fullProcessedProfile    *An example of a fully processed phylogenetic profile*

---

### Description

An example of a fully processed phylogenetic profile

### Usage

```
data(fullProcessedProfile)
```

### Format

Dataframe

### Value

A data frame with 168 rows and 14 variables:

- supertaxon Supertaxon name together with its ordered index, e.g. "1001\_Mammalia"
- ncbiID Taxon ID, e.g. "ncbi10116"
- geneID Seed or ortholog group ID, e.g. "100136at6656"
- orthoID Ortholog ID, e.g. "100136at6656|HUMAN@9606@1|Q9UNQ2|1"
- var1 First additional variable
- var2 Second additional variable
- paralog Number of co-orthologs in the current taxon
- abbrName NCBI ID of the ortholog, e.g. "ncbi9606"
- taxonID Taxon ID of the ortholog, in this case: "0"
- fullName Full taxon name of the ortholog, e.g. "Homo sapiens"

- supertaxonID Supertaxon ID (only different than ncbiID in case working with higher taxonomy rank than input's). e.g. "40674"
- rank Rank of the supertaxon, e.g. "class"
- category "cat"
- numberSpec Total number of species in each supertaxon

---

geneAgePlotDf

---

*Create data for plotting gene ages*


---

## Description

Create data for plotting gene ages

## Usage

```
geneAgePlotDf(geneAgeDf)
```

## Arguments

geneAgeDf      data frame containing estimated gene ages for seed proteins

## Value

A dataframe for plotting gene age plot containing the absolute number and percentage of genes for each calculated evolutionary ages and the corresponding position for writing those number on the plot.

## Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

## See Also

[estimateGeneAge](#)

## Examples

```
geneAgeDf <- data.frame(
  geneID = c("100136at6656", "100265at6656", "101621at6656", "103479at6656"),
  cath = c("0000001", "0000011", "0000001", "0000011"),
  age = c("07_LUCA", "06_Eukaryota", "07_LUCA", "06_Eukaryota")
)
geneAgePlotDf(geneAgeDf)
```

---

|                    |                                          |
|--------------------|------------------------------------------|
| generateSinglePlot | Create a single violin distribution plot |
|--------------------|------------------------------------------|

---

**Description**

Create a single violin distribution plot

**Usage**

```
generateSinglePlot(plotDf, parameters, variable)
```

**Arguments**

|            |                                                                                                                                                                                                                                             |
|------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| plotDf     | dataframe for plotting containing values for each variable in in-group and out-group.                                                                                                                                                       |
| parameters | plot parameters, including size of x-axis, y-axis, legend and title; position of legend ("right", "bottom" or "none"); mean/median point; names of in-group and out-group; and plot title. NOTE: Leave blank or NULL to use default values. |
| variable   | name of variable that need to be plotted (one of the column names of input dataframe plotDf).                                                                                                                                               |

**Value**

A violin plot as a ggplot object.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
data("mainLongRaw", package="PhyloProfile")
data <- mainLongRaw
inGroup <- c("ncbi9606", "ncbi10116")
varNames <- colnames(data)[c(4, 5)]
plotDf <- dataVarDistTaxGroup(data, inGroup, "101621at6656", varNames)
plotParameters <- list(
  "xSize" = 12,
  "ySize" = 12,
  "titleSize" = 15,
  "legendSize" = 12,
  "legendPosition" = "right",
  "mValue" = "mean",
  "inGroupName" = "In-group",
  "outGroupName" = "Out-group",
  "title" = "101621at6656"
)
generateSinglePlot(plotDf, plotParameters, colnames(plotDf)[1])
```

---

|                  |                                                             |
|------------------|-------------------------------------------------------------|
| getAllDomainsOma | Create domain annotation dataframe from a raw OMA dataframe |
|------------------|-------------------------------------------------------------|

---

### Description

Create domain annotation dataframe from a raw OMA dataframe

### Usage

```
getAllDomainsOma(finalOmaDf = NULL)
```

### Arguments

finalOmaDf      raw OMA data for a list of proteins (see ?getDataForOneOma)

### Value

Dataframe of the domain annotation used for PhyloProfile, which contains seed IDs, ortholog IDs, ortholog lengths, annotated features, start and end positions of those features.

### Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

### See Also

[getDataForOneOma](#)

### Examples

```
### Uncomment the following line to run the function
# omaData <- getDataForOneOma("HUMAN29397", "OG")
# getAllDomainsOma(omaData)
```

---

|                |                                                  |
|----------------|--------------------------------------------------|
| getAllFastaOma | Get all fasta sequences from a raw OMA dataframe |
|----------------|--------------------------------------------------|

---

### Description

Get all fasta sequences from a raw OMA dataframe

### Usage

```
getAllFastaOma(finalOmaDf = NULL)
```

**Arguments**

finalOmaDf      raw OMA data for a list of proteins (see ?getDataForOneOma)

**Value**

A list contains all protein sequences in fasta format.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[getDataForOneOma](#)

**Examples**

```
### Uncomment the following line to run the function
# omaData <- getDataForOneOma("HUMAN29397", "OG")
# getAllFastaOma(omaData)
```

---

|                   |                                                  |
|-------------------|--------------------------------------------------|
| getCommonAncestor | <i>Get all taxa that share a common ancestor</i> |
|-------------------|--------------------------------------------------|

---

**Description**

Identify the common ancestor for a selected taxa and return a list of all taxa that have that common ancestor from an large input taxa set.

**Usage**

```
getCommonAncestor(inputTaxa = NULL, inGroup = NULL, taxDB = NULL)
```

**Arguments**

|           |                                                                                    |
|-----------|------------------------------------------------------------------------------------|
| inputTaxa | ID list of all input taxa (e.g. "ncbi12345")                                       |
| inGroup   | ID list of selected taxa used for identify the common ancestor (e.g.: "ncbi55555") |
| taxDB     | Path to the taxonomy DB files                                                      |

**Value**

A list containing the taxonomy rank and name of the common ancestor, together with a dataframe storing the full taxonomy info of all taxa that share that corresponding common ancestor.

**Author(s)**

Vinh Tran (tran@bio.uni-frankfurt.de)

**Examples**

```
inputTaxa <- c("ncbi34740", "ncbi9606", "ncbi374847", "ncbi123851",
  "ncbi5664", "ncbi189518", "ncbi418459", "ncbi10116", "ncbi284812",
  "ncbi35128", "ncbi7070")
inGroup <- c("ncbi9606", "ncbi10116")
getCommonAncestor(inputTaxa, inGroup)
```

---

|             |                                                        |
|-------------|--------------------------------------------------------|
| getCoreGene | <i>Identify core genes for a list of selected taxa</i> |
|-------------|--------------------------------------------------------|

---

**Description**

Identify core genes for a list of selected (super)taxa. The identified core genes must be present in at least a certain proportion of species in each selected (super)taxon (identified via percentCutoff) and that criteria must be fulfilled for a certain percentage of selected taxa or all of them (determined via coreCoverage).

**Usage**

```
getCoreGene(rankName, taxaCore, profileDt, taxaCount,
  var1Cutoff = c(0, 1), var2Cutoff = c(0, 1), percentCutoff = c(0, 1),
  coreCoverage = 100, taxDB = NULL)
```

**Arguments**

|               |                                                                                                               |
|---------------|---------------------------------------------------------------------------------------------------------------|
| rankName      | working taxonomy rank (e.g. "species", "genus", "family")                                                     |
| taxaCore      | list of selected taxon names                                                                                  |
| profileDt     | dataframe contains the full processed phylogenetic profiles (see ?fullProcessed-Profile or ?parseInfoProfile) |
| taxaCount     | dataframe counting present taxa in each supertaxon                                                            |
| var1Cutoff    | cutoff for var1. Default = c(0, 1).                                                                           |
| var2Cutoff    | cutoff for var2. Default = c(0, 1).                                                                           |
| percentCutoff | cutoff for percentage of species present in each supertaxon. Default = c(0, 1).                               |
| coreCoverage  | the least percentage of selected taxa should be considered. Default = 1.                                      |
| taxDB         | Path to the taxonomy DB files                                                                                 |

**Value**

A list of identified core genes.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[parseInfoProfile](#) for creating a full processed profile dataframe

**Examples**

```
library(dplyr)
data("fullProcessedProfile", package="PhyloProfile")
rankName <- "class"
refTaxon <- "Mammalia"
taxaCore <- c("Mammalia", "Saccharomycetes", "Insecta")
profileDt <- fullProcessedProfile
taxonIDs <- levels(as.factor(fullProcessedProfile$ncbiID))
sortedInputTaxa <- sortInputTaxa(
  taxonIDs, rankName, refTaxon, NULL, NULL
)
taxaCount <- sortedInputTaxa %>% dplyr::count(supertaxon)
var1Cutoff <- c(0.75, 1.0)
var2Cutoff <- c(0.75, 1.0)
percentCutoff <- c(0.0, 1.0)
coreCoverage <- 100
getCoreGene(
  rankName,
  taxaCore,
  profileDt,
  taxaCount,
  var1Cutoff, var2Cutoff,
  percentCutoff, coreCoverage
)
```

---

getDataClustering

*Get data for calculating distance matrix from phylogenetic profiles*

---

**Description**

Get data for calculating distance matrix from phylogenetic profiles

**Usage**

```
getDataClustering(data, profileType = "binary", var1AggBy = "max",
  var2AggBy = "max")
```

**Arguments**

|             |                                                                                                                                                                                                                                                                                           |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data        | a data frame contains processed and filtered profiles (see <code>?fullProcessedProfile</code> and <code>?filterProfileData</code> , <code>?fromInputToProfile</code> )                                                                                                                    |
| profileType | type of data used for calculating the distance matrix. Either "binary" (consider only the presence/absence status of orthlogs), "orthoID" (consider ortholog IDs as values for clustering), "var1"/"var2" for taking values of the additional variables into account. Default = "binary". |

var1AggBy            aggregate method for VAR1 (min, max, mean or median). Default = "max".  
var2AggBy            aggregate method for VAR2 (min, max, mean or median). Default = "max".

**Value**

A wide dataframe contains values for calculating distance matrix.

**Author(s)**

Carla Mölbert (carla.moelbert@gmx.de), Vinh Tran (tran@bio.uni-frankfurt.de)

**See Also**

[fromInputToProfile](#)

**Examples**

```
data("finalProcessedProfile", package="PhyloProfile")  
data <- finalProcessedProfile  
profileType <- "binary"  
var1AggregateBy <- "max"  
var2AggregateBy <- "mean"  
getDataClustering(data, profileType, var1AggregateBy, var2AggregateBy)
```

---

|                  |                                                           |
|------------------|-----------------------------------------------------------|
| getDataForOneOma | <i>Get OMA info for a query protein and its orthologs</i> |
|------------------|-----------------------------------------------------------|

---

**Description**

Get taxonomy IDs, sequences, length and annotations for an OMA orthologous group (or OMA HOG).

**Usage**

```
getDataForOneOma(seedID = NULL, orthoType = "OG")
```

**Arguments**

seedID                OMA protein ID  
orthoType             type of OMA orthologs ("OG" or "HOG"). Default = "OG".

**Value**

Data frame contains info for all sequences of the input OMA group (or HOG). That info contains the protein IDs, taxonomy IDs, sequences, lengths, domain annotations (tab delimited) and the corresponding seed ID.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
### Uncomment the following line to run the function
# getDataForOneOma("HUMAN29397", "OG")
```

---

|               |                             |
|---------------|-----------------------------|
| getDendrogram | <i>Plot dendrogram tree</i> |
|---------------|-----------------------------|

---

**Description**

Plot dendrogram tree

**Usage**

```
getDendrogram(dd = NULL)
```

**Arguments**

dd                      dendrogram object (see ?clusterDataDend)

**Value**

A dendrogram plot for the genes in the input phylogenetic profiles.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[clusterDataDend](#)

**Examples**

```
data("finalProcessedProfile", package="PhyloProfile")
data <- finalProcessedProfile
profileType <- "binary"
profiles <- getDataClustering(
  data, profileType, var1AggregateBy, var2AggregateBy)
distMethod <- "mutualInformation"
distanceMatrix <- getDistanceMatrix(profiles, distMethod)
clusterMethod <- "complete"
dd <- clusterDataDend(as.dist(distanceMatrix), clusterMethod)
getDendrogram(dd)
```

---

|                   |                                      |
|-------------------|--------------------------------------|
| getDistanceMatrix | <i>Calculate the distance matrix</i> |
|-------------------|--------------------------------------|

---

## Description

Calculate the distance matrix

## Usage

```
getDistanceMatrix(profiles = NULL, method = "mutualInformation")
```

## Arguments

|          |                                                                                                                                                                                                                                                                    |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| profiles | dataframe contains profile data for distance calculating (see ?getDataClustering)                                                                                                                                                                                  |
| method   | distance calculation method ("euclidean", "maximum", "manhattan", "canberra", "binary", "distanceCorrelation", "mutualInformation" or "pearson" for binary data; "distanceCorrelation" or "mutualInformation" for non-binary data). Default = "mutualInformation". |

## Value

A calculated distance matrix for input phylogenetic profiles.

## Author(s)

Carla Mölbert (carla.moelbert@gmx.de), Vinh Tran (tran@bio.uni-frankfurt.de)

## See Also

[getDataClustering](#)

## Examples

```
data("finalProcessedProfile", package="PhyloProfile")
data <- finalProcessedProfile
profileType <- "binary"
profiles <- getDataClustering(
  data, profileType, var1AggregateBy, var2AggregateBy)
method <- "mutualInformation"
getDistanceMatrix(profiles, method)
```

---

|                 |                                                         |
|-----------------|---------------------------------------------------------|
| getDomainFolder | <i>Get domain file from a folder for a seed protein</i> |
|-----------------|---------------------------------------------------------|

---

**Description**

Get domain file from a folder for a seed protein

**Usage**

```
getDomainFolder(seed, domainPath)
```

**Arguments**

|            |                       |
|------------|-----------------------|
| seed       | seed protein ID       |
| domainPath | path to domain folder |

**Value**

Domain file and its complete directory path for the selected protein.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
domainPath <- paste0(
  path.package("PhyloProfile", quiet = FALSE), "/extdata/domainFiles"
)
PhyloProfile::getDomainFolder("101621at6656", domainPath)
```

---

|                      |                                                                       |
|----------------------|-----------------------------------------------------------------------|
| getFastaFromFasInput | <i>Get fasta sequences from main input file in multi-fasta format</i> |
|----------------------|-----------------------------------------------------------------------|

---

**Description**

Get fasta sequences from main input file in multi-fasta format

**Usage**

```
getFastaFromFasInput(seqIDs = NULL, file = NULL)
```

**Arguments**

|        |                                                                                                       |
|--------|-------------------------------------------------------------------------------------------------------|
| seqIDs | list of sequences IDs. Set seqIDs = "all" if you want to get all fasta sequences from the input file. |
| file   | raw phylogenetic profile input file in multi-fasta format.                                            |

**Value**

A dataframe with one column contains sequences in fasta format.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
file <- system.file(
  "extdata", "test.main.fasta",
  package = "PhyloProfile", mustWork = TRUE
)
getFastaFromFasInput("all", file)
```

---

getFastaFromFile

*Get fasta sequences from main input file in multi-fasta format*


---

**Description**

Get fasta sequences from main input file in multi-fasta format

**Usage**

```
getFastaFromFile(seqIDs = NULL, concatFasta = NULL)
```

**Arguments**

|             |                                                                                                                          |
|-------------|--------------------------------------------------------------------------------------------------------------------------|
| seqIDs      | list of sequences IDs. Set seqIDs = "all" if you want to get all fasta sequences from the concatenated input fasta file. |
| concatFasta | input concatenated fasta file.                                                                                           |

**Value**

A dataframe with one column contains sequences in fasta format.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
concatFasta <- system.file(
  "extdata", "fastaFiles/concatenatedFile.fa",
  package = "PhyloProfile", mustWork = TRUE
)
getFastaFromFasInput("all", concatFasta)
```

---

|                    |                            |
|--------------------|----------------------------|
| getFastaFromFolder | <i>Get fasta sequences</i> |
|--------------------|----------------------------|

---

## Description

Get fasta sequences for the input phylogenetic profiles.

## Usage

```
getFastaFromFolder(seqIDs = NULL, path = NULL, dirFormat = NULL,
  fileExt = NULL, idFormat = NULL)
```

## Arguments

|           |                                                                                                                     |
|-----------|---------------------------------------------------------------------------------------------------------------------|
| seqIDs    | list of sequences IDs.                                                                                              |
| path      | path to fasta folder.                                                                                               |
| dirFormat | directory format (either 1 for "path/speciesID.fa*" or 2 for "path/speciesID/speciesID.fa*")                        |
| fileExt   | fasta file extension ("fa", "fasta", "fas" or "txt")                                                                |
| idFormat  | fasta header format (1 for ">speciesID:seqID", 2 for ">speciesID@seqID", 3 for ">speciesID seqID" or 4 for "seqID") |

## Value

A dataframe with one column contains sequences in fasta format.

## Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

## See Also

[mainLongRaw](#)

## Examples

```
seqIDs <- "RAT@10116@1|D3ZUE4"
path <- system.file(
  "extdata", "fastaFiles", package = "PhyloProfile", mustWork = TRUE
)
dirFormat <- 1
fileExt <- "fa"
idFormat <- 3
getFastaFromFolder(seqIDs, path, dirFormat, fileExt, idFormat)
```

---

|            |                                             |
|------------|---------------------------------------------|
| getIDsRank | <i>Get taxonomy info for a list of taxa</i> |
|------------|---------------------------------------------|

---

## Description

Get NCBI taxonomy IDs, ranks and names for an input taxon list.

## Usage

```
getIDsRank(inputTaxa = NULL, currentNCBIinfo = NULL)
```

## Arguments

inputTaxa            NCBI ID list of input taxa.

currentNCBIinfo

table/dataframe of the pre-processed NCBI taxonomy data (/PhyloProfile/data/preProcessedTaxonomy.txt)

## Value

A list of 3 dataframes: idList, rankList and reducedInfoList. The "rankList" contains taxon names and all taxonomy ranks of the input taxa including also the noranks from the input rank to the taxonomy root. The "idList" contains input taxon IDs, taxon names, all the ranks from current rank to the taxonomy root together with their IDs (with the format "id#rank"). The reducedInfoList is a subset of preProcessedTaxonomy.txt file, containing the NCBI IDs, taxon fullnames, their current rank and their direct parent ID.

## Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

## Examples

```
inputTaxa <- c("272557", "176299")
ncbiFilein <- system.file(
  "extdata", "data/preProcessedTaxonomy.txt",
  package = "PhyloProfile", mustWork = TRUE
)
currentNCBIinfo <- as.data.frame(data.table::fread(ncbiFilein))
getIDsRank(inputTaxa, currentNCBIinfo)
```

---

|                |                                                      |
|----------------|------------------------------------------------------|
| getInputTaxaID | <i>Get ID list of input taxa from the main input</i> |
|----------------|------------------------------------------------------|

---

**Description**

Get ID list of input taxa from the main input

**Usage**

```
getInputTaxaID(rawProfile = NULL)
```

**Arguments**

rawProfile      A dataframe of input phylogenetic profile in long format

**Value**

List of all input taxon IDs (e.g. ncbi1234). Default = NULL.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[createLongMatrix](#), [mainLongRaw](#)

**Examples**

```
data("mainLongRaw", package="PhyloProfile")
getInputTaxaID(mainLongRaw)
```

---

|                  |                                                         |
|------------------|---------------------------------------------------------|
| getInputTaxaName | <i>Get NCBI taxon names for a selected list of taxa</i> |
|------------------|---------------------------------------------------------|

---

**Description**

Get NCBI taxon names from "PhyloProfile/data/taxonNamesReduced.txt" for a list of input taxa

**Usage**

```
getInputTaxaName(rankName, taxonIDs = NULL, taxDB = NULL)
```

**Arguments**

|          |                                                   |
|----------|---------------------------------------------------|
| rankName | taxonomy rank (e.g. "species", "phylum", ...)     |
| taxonIDs | list of taxon IDs (e.g. ncbi1234). Default = NULL |
| taxDB    | Path to the taxonomy DB files                     |

**Value**

Data frame contains a list of full names, taxonomy ranks and parent IDs for the input taxa.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[getInputTaxaID](#) for getting input taxon IDs, [getNameList](#) for getting the full taxon name list

**Examples**

```
taxonIDs <- c("ncbi9606", "ncbi10116")
getInputTaxaName("species", taxonIDs)
```

---

getNameList

*Get list of pre-installed NCBI taxon names*

---

**Description**

Get all NCBI taxon names from "PhyloProfile/data/taxonNamesReduced.txt"

**Usage**

```
getNameList(taxDB = NULL)
```

**Arguments**

|       |                               |
|-------|-------------------------------|
| taxDB | Path to the taxonomy DB files |
|-------|-------------------------------|

**Value**

List of taxon IDs, their full names, taxonomy ranks and parent IDs obtained from "PhyloProfile/data/taxonNamesReduced.txt"

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
getNameList()
```

---

```
getOmaDataForOneOrtholog
```

*Get taxonomy ID, sequence and annotation for one OMA protein*

---

### Description

Get taxonomy ID, sequence and annotation for one OMA protein

### Usage

```
getOmaDataForOneOrtholog(id = NULL)
```

### Arguments

|    |                       |
|----|-----------------------|
| id | oma ID of one protein |
|----|-----------------------|

### Value

Data frame contains the input protein ID with its taxonomy ID, sequence, length and domain annotations (tab delimited) for input OMA protein

### Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

### Examples

```
### Uncomment the following line to run the function
# getOmaDataForOneOrtholog("HUMAN29397")
```

---

```
getOmaDomainFromURL
```

*Get domain annotation from OMA Browser*

---

### Description

Get domain annotation from OMA Browser based on a URL or a raw data frame contains annotation info from OMA

### Usage

```
getOmaDomainFromURL(domainURL = NULL)
```

### Arguments

|           |                                                                                                       |
|-----------|-------------------------------------------------------------------------------------------------------|
| domainURL | URL address for domain annotation of ONE OMA id or a raw data frame contains annotation info from OMA |
|-----------|-------------------------------------------------------------------------------------------------------|

**Value**

Data frame contains feature names with their start and end positions

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
### Uncomment the following line to run the function
# getOmaDomainFromURL("https://omabrowser.org/api/protein/7916808/domains/")
```

---

getOmaMembers

*Get OMA members*

---

**Description**

Get OMA ortholog group, OMA HOG or OMA pair's members for a seed protein from OMA Browser.

**Usage**

```
getOmaMembers(id = NULL, orthoType = "OG")
```

**Arguments**

|           |                                                                                                                                     |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------|
| id        | ID of the seed protein (OMA or UniProt ID)                                                                                          |
| orthoType | type of OMA orthologs: either "HOG", "OG" (orthologous group) or "PAIR" (orthologous pair - CURRENTLY NOT WORKING). Default = "OG". |

**Value**

List of OMA orthologs for an input seed protein.

**Author(s)**

Carla Mölbert carla.moelbert@gmx.de

**Examples**

```
### Uncomment the following line to run the function
# getOmaMembers("HUMAN29397", "OG")
```

---

|                     |                                      |
|---------------------|--------------------------------------|
| getQualColForVector | <i>Get color for a list of items</i> |
|---------------------|--------------------------------------|

---

**Description**

Get color for a list of items

**Usage**

```
getQualColForVector(x = NULL)
```

**Arguments**

|   |            |
|---|------------|
| x | input list |
|---|------------|

**Value**

list of colors for each element (same elements will have the same color)

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[qualitativeColours](#)

**Examples**

```
items <- c("a", "b", "c")
getQualColForVector(items)
```

---

|                     |                                                              |
|---------------------|--------------------------------------------------------------|
| getSelectedFastaOma | <i>Get selected fasta sequences from a raw OMA dataframe</i> |
|---------------------|--------------------------------------------------------------|

---

**Description**

Get selected fasta sequences from a raw OMA dataframe

**Usage**

```
getSelectedFastaOma(finalOmaDf = NULL, seqID = NULL)
```

**Arguments**

|            |                                                             |
|------------|-------------------------------------------------------------|
| finalOmaDf | raw OMA data for a list of proteins (see ?getDataForOneOma) |
| seqID      | OMA ID of selected protein                                  |

**Value**

Required protein sequence in fasta format.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[getDataForOneOma](#)

**Examples**

```
### Uncomment the following line to run the function
# omaData <- getDataForOneOma("HUMAN29397", "OG")
# getSelectedFastaOma(omaData, "HUMAN29397")
```

---

getSelectedTaxonNames *Get a subset of input taxa based on a selected taxonomy rank*

---

**Description**

Get a subset of taxon ncbi IDs and names from an input list of taxa based on a selected supertaxon (identified by its taxonomy rank and supertaxon name or supertaxon ID).

**Usage**

```
getSelectedTaxonNames(inputTaxonIDs = NULL, rank = NULL,
  higherRank = NULL, higherID = NULL, higherName = NULL, taxDB = NULL)
```

**Arguments**

|               |                                                                                                               |
|---------------|---------------------------------------------------------------------------------------------------------------|
| inputTaxonIDs | list of input taxon IDs (e.g. c("10116", "122586"))                                                           |
| rank          | taxonomy rank of input taxa (e.g. "species")                                                                  |
| higherRank    | selected taxonomy rank (e.g. "phylum")                                                                        |
| higherID      | supertaxon ID (e.g. 7711). NOTE: either supertaxon ID or name is required, not necessary to give both         |
| higherName    | supertaxon name (e.g. "Chordata"). NOTE: either supertaxon ID or name is required, not necessary to give both |
| taxDB         | Path to the taxonomy DB files                                                                                 |

**Value**

A data frame contains ncbi IDs and names of taxa from the input taxon list that belong to the selected supertaxon.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
inputTaxonIDs <- c("10116", "122586", "123851", "13616", "188937", "189518",
"208964", "224129", "224324", "237631", "243230")
rank <- "species"
higherRank <- "phylum"
higherID <- 7711
getSelectedTaxonNames(inputTaxonIDs, rank, higherRank, higherID, NULL)
higherName <- "Chordata"
getSelectedTaxonNames(inputTaxonIDs, rank, higherRank, NULL, higherName, NULL)
```

---

getTaxHierarchy

*Get taxonomy hierarchy for a list of taxon IDs*


---

**Description**

Get NCBI taxonomy hierarchy and URLs for an input taxon list.

**Usage**

```
getTaxHierarchy(inputTaxa = NULL, currentNCBIinfo = NULL)
```

**Arguments**

inputTaxa            NCBI ID list of input taxa.

currentNCBIinfo

table/dataframe of the pre-processed NCBI taxonomy data (/PhyloProfile/data/preProcessedTaxonomy.txt)

**Value**

A list of dataframes containing taxonomy hierarchy and its URL to NCBI database for input taxon IDs

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
inputTaxa <- c("272557", "176299")
ncbiFilein <- system.file(
  "extdata", "data/preProcessedTaxonomy.txt",
  package = "PhyloProfile", mustWork = TRUE
)
currentNCBIinfo <- as.data.frame(data.table::fread(ncbiFilein))
PhyloProfile::getTaxHierarchy(inputTaxa, currentNCBIinfo)
```

---

|                 |                                                   |
|-----------------|---------------------------------------------------|
| getTaxonomyInfo | <i>Get taxonomy info for a list of input taxa</i> |
|-----------------|---------------------------------------------------|

---

**Description**

Get taxonomy info for a list of input taxa

**Usage**

```
getTaxonomyInfo(inputTaxa = NULL, currentNCBIinfo = NULL)
```

**Arguments**

|                 |                                                                                                       |
|-----------------|-------------------------------------------------------------------------------------------------------|
| inputTaxa       | NCBI taxonomy IDs of input taxa.                                                                      |
| currentNCBIinfo | table/dataframe of the pre-processed NCBI taxonomy data (/PhyloProfile/data/preProcessedTaxonomy.txt) |

**Value**

A list of NCBI taxonomy info for input taxa, including the taxonomy IDs, full scientific names, taxonomy ranks and the parent IDs.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
inputTaxa <- c("272557", "176299")
ncbiFilein <- system.file(
  "extdata", "data/preProcessedTaxonomy.txt",
  package = "PhyloProfile", mustWork = TRUE
)
currentNCBIinfo <- as.data.frame(data.table::fread(ncbiFilein))
getTaxonomyInfo(inputTaxa, currentNCBIinfo)
```

---

|                   |                            |
|-------------------|----------------------------|
| getTaxonomyMatrix | <i>Get taxonomy matrix</i> |
|-------------------|----------------------------|

---

**Description**

Get the (full or subset) taxonomy matrix from "data/taxonomyMatrix.txt" based on an input taxon list

**Usage**

```
getTaxonomyMatrix(taxDB = NULL, subsetTaxaCheck = FALSE, taxonIDs = NULL)
```

**Arguments**

taxDB                    Path to the taxonomy DB files

subsetTaxaCheck        TRUE/FALSE subset taxonomy matrix based on input taxon IDs. Default = FALSE

taxonIDs                list of input taxon IDs (e.g. ncbi1234). Default = NULL

**Value**

Data frame contains the (subset of) taxonomy matrix for list of input taxa.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
# get full pre-installed taxonomy matrix
getTaxonomyMatrix()
# get taxonomy matrix for a list of taxon IDs
taxonIDs <- c("ncbi9606", "ncbi10116")
getTaxonomyMatrix(NULL, TRUE, taxonIDs)
```

---

|                  |                                                         |
|------------------|---------------------------------------------------------|
| getTaxonomyRanks | <i>Create a list containing all main taxanomy ranks</i> |
|------------------|---------------------------------------------------------|

---

**Description**

Create a list containing all main taxanomy ranks

**Usage**

```
getTaxonomyRanks()
```

**Value**

A list of all main ranks (from strain to superkingdom)

**Author(s)**

Carla Mölbert (carla.moelbert@gmx.de)

**Examples**

```
getTaxonomyRanks()
```

---

`gridArrangeSharedLegend`*Plot Multiple Graphs with Shared Legend in a Grid*

---

**Description**

Plot Multiple Graphs with Shared Legend in a Grid

**Usage**

```
gridArrangeSharedLegend(..., ncol = length(list(...)), nrow = 1,  
  position = c("bottom", "right"), title = NA, titleSize = 12)
```

**Arguments**

|                        |                                 |
|------------------------|---------------------------------|
| <code>...</code>       | Plots to be arranged in grid    |
| <code>ncol</code>      | Number of columns in grid       |
| <code>nrow</code>      | Number of rows in grid          |
| <code>position</code>  | Grid position (bottom or right) |
| <code>title</code>     | Title of grid                   |
| <code>titleSize</code> | Size of grid title              |

**Value**

Grid of plots with common legend

**Note**

adapted from <https://rdrr.io/github/PhilBoileau/CLSAR/src/R/gridArrangeSharedLegend.R>

**Author(s)**

Phil Boileau, <philippe.boileau@rimuhc.ca>

**Examples**

```
## Not run:  
data("mainLongRaw", package="PhyloProfile")  
data <- mainLongRaw  
inGroup <- c("ncbi9606", "ncbi10116")  
varNames <- colnames(data)[c(4, 5)]  
plotDf <- dataVarDistTaxGroup(data, inGroup, "101621at6656", varNames)  
plotParameters <- list(  
  "xSize" = 12,  
  "ySize" = 12,  
  "titleSize" = 15,  
  "legendSize" = 12,
```

```

    "legendPosition" = "right",
    "mValue" = "mean",
    "inGroupName" = "In-group",
    "outGroupName" = "Out-group",
    "title" = "101621at6656"
  )
plotVar1 <- generateSinglePlot(plotDf, plotParameters, colnames(plotDf)[1])
plotVar2 <- generateSinglePlot(plotDf, plotParameters, colnames(plotDf)[2])
g <- gridArrangeSharedLegend(
  plotVar1, plotVar2,
  position = plotParameters$legendPosition,
  title = plotParameters$title,
  size = plotParameters$titleSize
)

## End(Not run)

```

---

|                      |                                                                                             |
|----------------------|---------------------------------------------------------------------------------------------|
| groupLabelDimRedData | <i>Reduce the number of labels for DIM reduction plot based on the gene/taxon frequency</i> |
|----------------------|---------------------------------------------------------------------------------------------|

---

## Description

Reduce the number of labels for DIM reduction plot based on the gene/taxon frequency

## Usage

```
groupLabelDimRedData(data4dimRed = NULL, freqCutoff = c(0,200))
```

## Arguments

|             |                                                                                                          |
|-------------|----------------------------------------------------------------------------------------------------------|
| data4dimRed | data for dimension reduction (from prepareDimRedData)                                                    |
| freqCutoff  | gene/taxon frequency cutoff range. Any labels that are outside of this range will be assigned as [Other] |

## Value

A dataframe similar to input data4dimRed, but with modified Label column, where less frequent labels are grouped together as "Other"

## Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

## See Also

[prepareDimRedData](#)

## Examples

```
rawInput <- system.file(
  "extdata", "test.main.long", package = "PhyloProfile", mustWork = TRUE
)
longDf <- createLongMatrix(rawInput)
data4dimRed <- prepareDimRedData(longDf, "phylum")
groupLabelDimRedData(data4dimRed, freqCutoff = c(3,5))
```

---

|                 |                                    |
|-----------------|------------------------------------|
| heatmapPlotting | <i>Create profile heatmap plot</i> |
|-----------------|------------------------------------|

---

## Description

Create profile heatmap plot

## Usage

```
heatmapPlotting(data = NULL, parm = NULL)
```

## Arguments

|      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data | dataframe for plotting the heatmap phylogentic profile (either full or subset profiles)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| parm | plot parameters, including (1) type of x-axis "taxa" or "genes" - default = "taxa"; (2) display gene IDs (default) or gene names; (3+4) names of 2 variables var1ID and var2ID - default = "var1" & "var2"; (5+6) mid value and color for mid value of var1 - default is 0.5 and #FFFFFF; (7) color for lowest var1 - default = "#FF8C00"; (8) color for highest var1 - default = "#4682B4"; (9+10) mid value and color for mid value of var2 - default is 1 and #FFFFFF; (11) color for lowest var2 - default = "#FFFFFF", (12) color for highest var2 - default = "#F0E68C", (13) color of co-orthologs - default = "#07D000"; (14+15+16) text sizes for x, y axis and legend - default = 9 for each; (17) legend position "top", "bottom", "right", "left" or "none" - default = "top"; (18) zoom ratio of the co-ortholog dots from -1 to 3 - default = 0; (19) angle of x-axis from 0 to 90 - default = 60; (20) show/hide separate line for reference taxon 1/0 - default = 0; (21) enable/disable coloring gene categories TRUE/FALSE - default = FALSE; (22) enable/disable coloring duplicated ortholog IDs TRUE/FALSE - default=FALSE). NOTE: Leave blank or NULL to use default values. |

## Value

A profile heatmap plot as a ggplot object.

## Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[dataMainPlot](#), [dataCustomizedPlot](#)

**Examples**

```
data("finalProcessedProfile", package="PhyloProfile")
plotDf <- dataMainPlot(finalProcessedProfile)
plotParameter <- list(
  "xAxis" = "taxa",
  "geneIdType" = "geneID",
  "var1ID" = "FAS_FW",
  "var2ID" = "FAS_BW",
  "midVar1" = 0.5,
  "midColorVar1" = "#FFFFFF",
  "lowColorVar1" = "#FF8C00",
  "highColorVar1" = "#4682B4",
  "midVar2" = 1,
  "midColorVar2" = "#FFFFFF",
  "lowColorVar2" = "#CB4C4E",
  "highColorVar2" = "#3E436F",
  "paraColor" = "#07D000",
  "xSize" = 8,
  "ySize" = 8,
  "legendSize" = 8,
  "mainLegend" = "top",
  "dotZoom" = 0,
  "xAngle" = 60,
  "guideline" = 0,
  "colorByGroup" = FALSE,
  "catColors" = NULL,
  "colorByOrthoID" = FALSE
)

heatmapPlotting(plotDf, plotParameter)
```

---

heatmapPlottingFast      *Create profile heatmap plot using scattermore*

---

**Description**

Create profile heatmap plot using scattermore

**Usage**

```
heatmapPlottingFast(data = NULL, parm = NULL)
```

**Arguments**

|      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data | dataframe for plotting the heatmap phylogentic profile (either full or subset profiles)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| parm | plot parameters, including (1) type of x-axis "taxa" or "genes" - default = "taxa"; (2) display gene IDs (default) or gene names; (3+4) names of 2 variables var1ID and var2ID - default = "var1" & "var2"; (5+6) mid value and color for mid value of var1 - default is 0.5 and #FFFFFF; (7) color for lowest var1 - default = "#FF8C00"; (8) color for highest var1 - default = "#4682B4"; (9+10) mid value and color for mid value of var2 - default is 1 and #FFFFFF; (11) color for lowest var2 - default = "#FFFFFF", (12) color for highest var2 - default = "#F0E68C", (13) color of co-orthologs - default = "#07D000"; (14+15+16) text sizes for x, y axis and legend - default = 9 for each; (17) legend position "top", "bottom", "right", "left" or "none" - default = "top"; (18) zoom ratio of the co-ortholog dots from -1 to 3 - default = 0; (19) color dots based on either "var1" or "var2". NOTE: Leave blank or NULL to use default values. |

**Value**

A profile heatmap plot as a ggplot object.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[dataMainPlot](#), [dataCustomizedPlot](#)

**Examples**

```
data("finalProcessedProfile", package="PhyloProfile")
plotDf <- dataMainPlot(finalProcessedProfile)
plotParameter <- list(
  "xAxis" = "taxa",
  "geneIdType" = "geneID",
  "var1ID" = "FAS_FW",
  "var2ID" = "FAS_BW",
  "midVar1" = 0.5,
  "midColorVar1" = "#FFFFFF",
  "lowColorVar1" = "#FF8C00",
  "highColorVar1" = "#4682B4",
  "midVar2" = 1,
  "midColorVar2" = "#FFFFFF",
  "lowColorVar2" = "#CB4C4E",
  "highColorVar2" = "#3E436F",
  "paraColor" = "#07D000",
  "xSize" = 8,
  "ySize" = 8,
  "legendSize" = 8,
  "mainLegend" = "top",
```

```

    "dotZoom" = 0,
    "colorVar" = "var1"
  )

heatmapPlottingFast(plotDf, plotParameter)

```

---

highlightProfilePlot    *Highlight gene and/or taxon of interest on the phylogenetic profile plot*

---

### Description

Highlight gene and/or taxon of interest on the phylogenetic profile plot

### Usage

```

highlightProfilePlot(profilePlot = NULL, plotDf = NULL,
  taxonHighlight = "none", workingRank = "none", geneHighlight = NULL,
  taxDB = NULL, xAxis = "taxa")

```

### Arguments

|                |                                                          |
|----------------|----------------------------------------------------------|
| profilePlot    | initial (highlighted) profile plot                       |
| plotDf         | dataframe for plotting the heatmap phylogentic profile   |
| taxonHighlight | taxon of interst. Default = "none".                      |
| workingRank    | working taxonomy rank (needed only for highlight taxon). |
| geneHighlight  | gene of interest. Default = NULL.                        |
| taxDB          | Path to the taxonomy DB files                            |
| xAxis          | type of x-axis (either "genes" or "taxa")                |

### Value

A profile heatmap plot with highlighted gene and/or taxon of interest as ggplot object.

### Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

### See Also

[dataMainPlot](#), [dataCustomizedPlot](#), [heatmapPlotting](#)

## Examples

```
data("finalProcessedProfile", package="PhyloProfile")
plotDf <- dataMainPlot(finalProcessedProfile)
plotParameter <- list(
  "xAxis" = "taxa",
  "geneIdType" = "geneID",
  "var1ID" = "FAS_FW",
  "var2ID" = "FAS_BW",
  "midVar1" = 0.5,
  "midColorVar1" = "#FFFFFF",
  "lowColorVar1" = "#FF8C00",
  "highColorVar1" = "#4682B4",
  "midVar2" = 1,
  "midColorVar2" = "#FFFFFF",
  "lowColorVar2" = "#CB4C4E",
  "highColorVar2" = "#3E436F",
  "paraColor" = "#07D000",
  "xSize" = 8,
  "ySize" = 8,
  "legendSize" = 8,
  "mainLegend" = "top",
  "dotZoom" = 0,
  "xAngle" = 60,
  "guideline" = 0,
  "colorByGroup" = FALSE,
  "colorByOrthoID" = FALSE
)
profilePlot <- heatmapPlotting(plotDf, plotParameter)
taxonHighlight <- "none"
workingRank <- "class"
geneHighlight <- "100265at6656"
highlightProfilePlot(
  profilePlot, plotDf, taxonHighlight, workingRank, geneHighlight,
  NULL, plotParameter$xAxis
)
```

---

id2name

*Get taxon names for a list of taxon IDs*


---

## Description

Get taxon names for a list of taxon IDs

## Usage

```
id2name(idList = NULL, currentNCBIinfo = NULL)
```

**Arguments**

idList                    list of taxonomy IDs  
 currentNCBIinfo        table/dataframe of the pre-processed NCBI taxonomy data (/PhyloProfile/data/preProcessedTaxonomy.txt)

**Value**

A dataframe contains input taxon IDs and their full names.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
ncbiFilein <- system.file(
  "extdata", "data/preProcessedTaxonomy.txt",
  package = "PhyloProfile", mustWork = TRUE
)
currentNCBIinfo <- as.data.frame(data.table::fread(ncbiFilein))
idList <- c("9606", "5207", "40674", "4751")
id2name(idList, currentNCBIinfo)
```

---

|        |                                                |
|--------|------------------------------------------------|
| idList | <i>NCBI ID list for experimental data sets</i> |
|--------|------------------------------------------------|

---

**Description**

Data frame, in which each row contains the complete taxonomy ranks from the lowest systematic level (strain/species) upto the taxonomy root and the corresponding IDs for one taxon in the experimental data sets.

**Usage**

```
data(idList)
```

**Format**

Dataframe

**Value**

A data frame with up to 41 columns and 95 rows corresponding to 95 taxa in the 2 experimental data sets

---

joinPlotMergeLegends    *Join multiple plots and merge legends*

---

## Description

Join multiple plots and merge legends

## Usage

```
joinPlotMergeLegends(  
  df1 = NULL,  
  df2 = NULL,  
  plot1 = NULL,  
  plot2 = NULL,  
  position = c("bottom", "right"),  
  font = "Arial",  
  legendSize = 12  
)
```

## Arguments

|            |                                      |
|------------|--------------------------------------|
| df1        | Data frame for plot 1                |
| df2        | Data frame for plot 2                |
| plot1      | ggplot object of plot 1              |
| plot2      | ggplot object of plot 2              |
| position   | position of legend (bottom or right) |
| font       | font of text                         |
| legendSize | font size                            |

## Value

joined plots with merged legend as a grid object

## Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

## Examples

```
seed <- "101621at6656"  
ortho <- "101621at6656|AGRPL@224129@0|224129_0:001955|1"  
ortho <- gsub("\\|", ":", ortho)  
grepID <- paste(seed, "#", ortho, sep = "")  
domainFile <- system.file(  
  "extdata", "domainFiles/101621at6656.domains",  
  package = "PhyloProfile", mustWork = TRUE
```

```

)
domainDf <- parseDomainInput(seed, domainFile, "file")
domainDf$feature_id_mod <- domainDf$feature_id
subdomainDf <- domainDf[grep(grepID, domainDf$seedID), ]
subdomainDf$feature <- as.character(subdomainDf$feature)
orthoDf <- subdomainDf[subdomainDf$orthoID == ortho,]
seedDf <- subdomainDf[subdomainDf$orthoID != ortho,]
minStart <- min(subdomainDf$start)
maxEnd <- max(c(subdomainDf$end, subdomainDf$length))
# resolve overlapping domains
seedDf <- PhyloProfile:::resolveOverlapFeatures(seedDf)
orthoDf <- PhyloProfile:::resolveOverlapFeatures(orthoDf)
# add feature colors
featureColorDf <- PhyloProfile:::addFeatureColors(seedDf, orthoDf)
seedDf <- featureColorDf[[1]]
orthoDf <- featureColorDf[[2]]
# generate plots
plotSeed <- PhyloProfile:::singleDomainPlotting(
  seedDf, seed, minStart = minStart, maxEnd = maxEnd, font = "sans"
)
plotOrtho <- PhyloProfile:::singleDomainPlotting(
  orthoDf, ortho, minStart = minStart, maxEnd = maxEnd, font = "sans"
)
# merge plots
PhyloProfile:::joinPlotMergeLegends(
  seedDf, orthoDf, plotSeed, plotOrtho, "bottom", font = "sans",
  legendSize = 12)

```

---

linearizeArchitecture *Linearize PFAM/SMART annotations by best e-value/bitscore*

---

## Description

Linearize PFAM/SMART annotations by best e-value/bitscore

## Usage

```
linearizeArchitecture(domainDf = NULL, orthoID = NULL, value = "evalue")
```

## Arguments

|          |                                                                                      |
|----------|--------------------------------------------------------------------------------------|
| domainDf | input domain dataframe                                                               |
| orthoID  | ID of protein that needs to be linearized                                            |
| value    | type of values that will be used for linearized, either evalue (default) or bitscore |

## Value

Domain dataframe of the selected protein after linearization

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
demoDomainDf <- data.frame(
  orthoID = rep("protID", 4),
  start = c(1, 5, 100, 80),
  end = c(30, 40, 130, 110),
  evalue = c(0.001, 0.0005, 0.2, 0.004),
  feature_type = c(rep("pfam", 2), rep("smart", 2)),
  feature_id = c("pf1", "pf2", "sm1", "sm2")
)
linearizeArchitecture(demoDomainDf, "protID", "evalue")
```

---

mainLongRaw

*An example of a raw long input file*


---

**Description**

An example of a raw long input file

**Usage**

```
data(mainLongRaw)
```

**Format**

Dataframe

**Value**

A data frame with 168 rows and 5 variables:

- geneID Seed or ortholog group ID, e.g. "100136at6656"
- ncbiID Taxon ID, e.g. "ncbi36329"
- orthoID Ortholog ID, e.g. "100136at6656|PLAF7@36329@1|Q8ILT8|1"
- FAS\_F First additional variable
- FAS\_B Second additional variable

---

|                  |                                         |
|------------------|-----------------------------------------|
| mainTaxonomyRank | <i>Get all NCBI taxonomy rank names</i> |
|------------------|-----------------------------------------|

---

**Description**

Get all NCBI taxonomy rank names

**Usage**

```
mainTaxonomyRank()
```

**Value**

A list of all available NCBI taxonomy rank names.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
mainTaxonomyRank()
```

---

|                   |                             |
|-------------------|-----------------------------|
| modifyFeatureName | <i>Modify feature names</i> |
|-------------------|-----------------------------|

---

**Description**

Simplify feature names (e.g. TM for transmembrane domain, LCR for low complexity regions, remove tool names from domain name) and add weight to feature names (if available)

**Usage**

```
modifyFeatureName(domainDf = NULL)
```

**Arguments**

|          |                                   |
|----------|-----------------------------------|
| domainDf | domain data as a dataframe object |
|----------|-----------------------------------|

**Value**

Dataframe contains simlified domain names in yLabel column

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

## Examples

```
domainFile <- system.file(
  "extdata", "domainFiles/101621at6656.domains",
  package = "PhyloProfile", mustWork = TRUE
)
seedID <- "101621at6656"
domainDf <- parseDomainInput(seedID, domainFile, "file")
PhyloProfile::modifyFeatureName(domainDf)
```

---

|                    |                                                                  |
|--------------------|------------------------------------------------------------------|
| pairDomainPlotting | Create architecture plot for a pair of seed and ortholog protein |
|--------------------|------------------------------------------------------------------|

---

## Description

Create architecture plot for a pair of seed and ortholog protein

## Usage

```
pairDomainPlotting(seed, ortho, seedDf, orthoDf, minStart, maxEnd,
  labelSize, titleSize, legendSize, showScore, showWeight, namePosition,
  firstDist, nameType, nameSize, segmentSize, nameColor, labelPos,
  colorPalette, font)
```

## Arguments

|              |                                                                                                                                                                                                                                                                                                                    |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| seed         | Seed ID                                                                                                                                                                                                                                                                                                            |
| ortho        | Ortho ID                                                                                                                                                                                                                                                                                                           |
| seedDf       | domain dataframe for seed domains containing the seed ID, ortholog ID, sequence length, feature names, start and end positions, feature weights (optional) and the status to determine if that feature is important for comparison the architecture between 2 proteins* (e.g. seed protein vs ortholog) (optional) |
| orthoDf      | domain dataframe for ortholog domains (same format as seedDf)                                                                                                                                                                                                                                                      |
| minStart     | the smallest start position of all domains                                                                                                                                                                                                                                                                         |
| maxEnd       | the highest stop position of all domains                                                                                                                                                                                                                                                                           |
| labelSize    | label size. Default = 12                                                                                                                                                                                                                                                                                           |
| titleSize    | title size. Default = 12                                                                                                                                                                                                                                                                                           |
| legendSize   | legend size. Default = 12                                                                                                                                                                                                                                                                                          |
| showScore    | show/hide E-values and Bit-scores. Default = NULL (hide)                                                                                                                                                                                                                                                           |
| showWeight   | Show/hide feature weights. Default = NULL (hide)                                                                                                                                                                                                                                                                   |
| namePosition | list of positions for domain names, choose from "plot", "legend" or "axis". Default: "plot"                                                                                                                                                                                                                        |
| firstDist    | distance of the first domain to plot title. Default = 0.5                                                                                                                                                                                                                                                          |
| nameType     | type of domain names, either "Texts" or "Labels" (default)                                                                                                                                                                                                                                                         |

|              |                                                                                                               |
|--------------|---------------------------------------------------------------------------------------------------------------|
| nameSize     | Size of domain names. Default = 3                                                                             |
| segmentSize  | Height of domain segment. Default = 5                                                                         |
| nameColor    | color of domain names (for Texts only). Default = "black"                                                     |
| labelPos     | position of domain names (for Labels only). Choose from "Above" (default), "Below" or "Inside" the domain bar |
| colorPalette | color pallete. Default = Paired"                                                                              |
| font         | font of text. Default = Arial"                                                                                |

**Value**

Domain plot of a pair proteins as a arrangeGrob object.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[singleDomainPlotting](#), [sortDomains](#), [parseDomainInput](#)

**Examples**

```
seed <- "101621at6656"
ortho <- "101621at6656|AGRPL@224129@0|224129_0:001955|1"
ortho <- gsub("\\|", ":", ortho)
grepID <- paste(seed, "#", ortho, sep = "")
domainFile <- system.file(
  "extdata", "domainFiles/101621at6656.domains",
  package = "PhyloProfile", mustWork = TRUE
)
domainDf <- parseDomainInput(seed, domainFile, "file")
domainDf$feature_id_mod <- domainDf$feature_id
subdomainDf <- domainDf[grep(grepID, domainDf$seedID), ]
subdomainDf$feature <- as.character(subdomainDf$feature)
orthoDf <- subdomainDf[subdomainDf$orthoID == ortho, ]
seedDf <- subdomainDf[subdomainDf$orthoID != ortho, ]
minStart <- min(subdomainDf$start)
maxEnd <- max(c(subdomainDf$end, subdomainDf$length))
# resolve overlapping domains
seedDf <- PhyloProfile::resolveOverlapFeatures(seedDf)
orthoDf <- PhyloProfile::resolveOverlapFeatures(orthoDf)
# add feature colors
featureColorDf <- PhyloProfile::addFeatureColors(seedDf, orthoDf)
seedDf <- featureColorDf[[1]]
orthoDf <- featureColorDf[[2]]
# do plot
g <- PhyloProfile::pairDomainPlotting(
  seed, ortho, seedDf, orthoDf, minStart, maxEnd, font = "sans"
)
grid::grid.draw(g)
```

---

|                  |                                |
|------------------|--------------------------------|
| parseDomainInput | <i>Parse domain input file</i> |
|------------------|--------------------------------|

---

**Description**

Get all domain annotations for one seed protein IDs.

**Usage**

```
parseDomainInput(seed = NULL, inputFile = NULL, type = "file")
```

**Arguments**

|           |                                                                                   |
|-----------|-----------------------------------------------------------------------------------|
| seed      | seed protein ID                                                                   |
| inputFile | name of input file (file name or path to folder contains individual domain files) |
| type      | type of data (file" or "folder"). Default = "file".                               |

**Value**

A dataframe for protein domains including seed ID, its orthologs IDs, sequence lengths, feature names, start and end positions, feature weights (optional) and the status to determine if that feature is important for comparison the architecture between 2 proteins\* (e.g. seed protein vs ortholog) (optional).

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[getDomainFolder](#)

**Examples**

```
seed <- "101621at6656"
inputFile <- system.file(
  "extdata", "domainFiles/101621at6656.domains",
  package = "PhyloProfile", mustWork = TRUE
)
type <- "file"
parseDomainInput(seed, inputFile, type)
```

---

|                  |                                               |
|------------------|-----------------------------------------------|
| parseInfoProfile | <i>Parsing info for phylogenetic profiles</i> |
|------------------|-----------------------------------------------|

---

### Description

Creating main dataframe for the input phylogenetic profiles based on selected input taxonomy level (e.g. strain, species) and reference taxon. The output contains the number of paralogs, the max/min/mean/median of VAR1 and VAR2.

### Usage

```
parseInfoProfile(inputDf, sortedInputTaxa, taxaCount, coorthoCOMax)
```

### Arguments

|                 |                                                                 |
|-----------------|-----------------------------------------------------------------|
| inputDf         | input profiles in long format                                   |
| sortedInputTaxa | sorted taxonomy data for the input taxa (check sortInputTaxa()) |
| taxaCount       | dataframe counting present taxa in each supertaxon              |
| coorthoCOMax    | maximum number of co-orthologs allowed                          |

### Value

A dataframe contains all info for the input phylogenetic profiles. This full processed profile that is required for several profiling analyses e.g. estimation of gene age (?estimateGeneAge) or identification of core gene (?getCoreGene).

### Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

### See Also

[createLongMatrix](#), [sortInputTaxa](#), [calcPresSpec](#), [mainLongRaw](#)

### Examples

```
library(dplyr)
data("mainLongRaw", package="PhyloProfile")
taxonIDs <- getInputTaxaID(mainLongRaw)
sortedInputTaxa <- sortInputTaxa(
  taxonIDs, "class", "Mammalia", NULL, NULL
)
taxaCount <- sortedInputTaxa %>% dplyr::group_by(supertaxon) %>%
  summarise(n = n(), .groups = "drop")
coorthoCOMax <- 999
parseInfoProfile(
  mainLongRaw, sortedInputTaxa, taxaCount, coorthoCOMax
)
```

---

|            |                                       |
|------------|---------------------------------------|
| performPCA | <i>Helper function to perform PCA</i> |
|------------|---------------------------------------|

---

**Description**

Helper function to perform PCA

**Usage**

```
performPCA(pcaDt)
```

**Arguments**

|       |                     |
|-------|---------------------|
| pcaDt | data matrix for PCA |
|-------|---------------------|

**Value**

A table contains coordinates of the first 3 PCs

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

---

|             |                                             |
|-------------|---------------------------------------------|
| performUmap | <i>Helper function to handle UMAP logic</i> |
|-------------|---------------------------------------------|

---

**Description**

Helper function to handle UMAP logic

**Usage**

```
performUmap(umapDt, randomSeed = 123, dim = 2)
```

**Arguments**

|            |                                                  |
|------------|--------------------------------------------------|
| umapDt     | data matrix for UMAP                             |
| randomSeed | random seed. Default: 123                        |
| dim        | dimension, either 2 for 2D (default) or 3 for 3D |

**Value**

A table contains coordinates UMAP reduction

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

---

|            |                                        |
|------------|----------------------------------------|
| plotDimRed | <i>Create dimension reduction plot</i> |
|------------|----------------------------------------|

---

### Description

Create dimension reduction plot

### Usage

```
plotDimRed(plotDf = NULL, legendPos = "bottom",
  colorPalette = "Set2", transparent = 0, textSize = 12, font = "Arial",
  highlightTaxa = NULL, dotZoom = 0)
```

### Arguments

|               |                                             |
|---------------|---------------------------------------------|
| plotDf        | data for dimension reduction 2D plot        |
| legendPos     | position of legend. Default: "right"        |
| colorPalette  | color palette. Default: "Set2"              |
| transparent   | transparent level (from 0 to 1). Default: 0 |
| textSize      | size of axis and legend text. Default: 12   |
| font          | font of text. Default = Arial"              |
| highlightTaxa | list of taxa to be highlighted              |
| dotZoom       | dot size zooming factor. Default: 0         |

### Value

A plot as ggplot object

### Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

### See Also

[prepareDimRedData](#), [dimReduction](#), [createDimRedPlotData](#)

### Examples

```
rawInput <- system.file(
  "extdata", "test.main.long", package = "PhyloProfile", mustWork = TRUE
)
longDf <- createLongMatrix(rawInput)
data4dimRed <- prepareDimRedData(longDf, "phylum")
dimRedCoord <- dimReduction(data4dimRed)
plotDf <- createDimRedPlotData(dimRedCoord, data4dimRed)
plotDimRed(plotDf, font = "sans")
```

---

|              |                                           |
|--------------|-------------------------------------------|
| plotDimRed3D | <i>Create dimension reduction 3D plot</i> |
|--------------|-------------------------------------------|

---

## Description

Create dimension reduction 3D plot

## Usage

```
plotDimRed3D(plotDf = NULL, legendPos = "bottom",
  colorPalette = "Set2", transparent = 0, highlightTaxa = NULL,
  dotZoom = 0)
```

## Arguments

|               |                                             |
|---------------|---------------------------------------------|
| plotDf        | data for dimension reduction 3D plot        |
| legendPos     | position of legend. Default: "right"        |
| colorPalette  | color palette. Default: "Set2"              |
| transparent   | transparent level (from 0 to 1). Default: 0 |
| highlightTaxa | list of taxa to be highlighted              |
| dotZoom       | dot size zooming factor. Default: 0         |

## Value

A plot as ggplot object

## Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

## See Also

[prepareDimRedData](#), [dimReduction](#), [createDimRedPlotData](#)

## Examples

```
rawInput <- system.file(
  "extdata", "test.main.long", package = "PhyloProfile", mustWork = TRUE
)
longDf <- createLongMatrix(rawInput)
data4dimRed <- prepareDimRedData(longDf, "phylum")
dimRedCoord3d <- dimReduction(data4dimRed, dimension = "3d")
plotDf <- createDimRedPlotData(dimRedCoord3d, data4dimRed)
plotDimRed3D(plotDf)
```

---

|                  |                                        |
|------------------|----------------------------------------|
| ppTaxonomyMatrix | <i>An example of a taxonomy matrix</i> |
|------------------|----------------------------------------|

---

**Description**

An example of a taxonomy matrix

**Usage**

```
data(ppTaxonomyMatrix)
```

**Format**

Dataframe

**Value**

A data frame with 10 rows and 162 variables:

- abbrName e.g. "ncbi10090"
- ncbiID e.g. "10090"
- fullName e.g. "Mus musculus"
- strain e.g. "10090" ...

---

|        |                                                       |
|--------|-------------------------------------------------------|
| ppTree | <i>An example of a taxonomy tree in newick format</i> |
|--------|-------------------------------------------------------|

---

**Description**

An example of a taxonomy tree in newick format

**Usage**

```
data(ppTree)
```

**Format**

Dataframe

**Value**

A data frame with only one entry

- V1 tree in newick format

---

|                   |                                             |
|-------------------|---------------------------------------------|
| prepareDimRedData | <i>Prepare data for dimension reduction</i> |
|-------------------|---------------------------------------------|

---

**Description**

Prepare data for dimension reduction

**Usage**

```
prepareDimRedData(longDf = NULL, taxonRank = NULL, type = "taxa",  
  taxDB = NULL, filterVar = "both", cutoff = 0, groupLabelsBy = "taxa")
```

**Arguments**

|               |                                                                                       |
|---------------|---------------------------------------------------------------------------------------|
| longDf        | input phyloprofile file in long format                                                |
| taxonRank     | taxonomy rank for labels (e.g. "phylum")                                              |
| type          | type of clustering, either "taxa" (default) or "genes"                                |
| taxDB         | path to taxonomy database                                                             |
| filterVar     | choose variable (either "var1", "var2" or "both") to filter the data. Default: "both" |
| cutoff        | cutoff to filter data values. Default: 0                                              |
| groupLabelsBy | group labels by the number of "taxa" (default) or "genes"                             |

**Value**

A dataframe in wide format

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
rawInput <- system.file(  
  "extdata", "test.main.long", package = "PhyloProfile", mustWork = TRUE  
)  
longDf <- createLongMatrix(rawInput)  
prepareDimRedData(longDf, "phylum")
```

---

|                     |                                          |
|---------------------|------------------------------------------|
| processNcbiTaxonomy | <i>Pre-processing NCBI taxonomy data</i> |
|---------------------|------------------------------------------|

---

**Description**

Download NCBI taxonomy database and parse information that are needed for PhyloProfile, including taxon IDs, their scientific names, systematic ranks, and parent (next higher) rank IDs.

**Usage**

```
processNcbiTaxonomy()
```

**Value**

A dataframe contains NCBI taxon IDs, taxon names, taxon ranks and the next higher taxon IDs (parent's IDs) of all taxa in the NCBI taxonomy database.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
## Not run:
?processNcbiTaxonomy
preProcessedTaxonomy <- PhyloProfile::processNcbiTaxonomy()
# save to text (tab-delimited) file
write.table(
  preProcessedTaxonomy,
  file = "preProcessedTaxonomy.txt",
  col.names = TRUE,
  row.names = FALSE,
  quote = FALSE,
  sep = "\t"
)
# save to rdata file
save(
  preProcessedTaxonomy, file = "preProcessedTaxonomy.RData", compress='xz'
)

## End(Not run)
```

---

|                |                             |
|----------------|-----------------------------|
| processOrthoID | <i>Process ortholog IDs</i> |
|----------------|-----------------------------|

---

**Description**

Process ortholog IDs to identify duplicated IDs

**Usage**

```
processOrthoID(dataHeat = NULL)
```

**Arguments**

|          |                                                                                          |
|----------|------------------------------------------------------------------------------------------|
| dataHeat | a data frame contains processed profiles (see ?fullProcessedProfile, ?filterProfileData) |
|----------|------------------------------------------------------------------------------------------|

**Value**

the same dataframe as input, but the ortholog IDs are changed into <taxID:orthoID>. New column "orthoFreq" specifies if the ortholog IDs are single or duplicated

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
?processOrthoID  
data("finalProcessedProfile", package="PhyloProfile")  
processOrthoID(finalProcessedProfile)
```

---

|                     |                                                                            |
|---------------------|----------------------------------------------------------------------------|
| profileWithTaxonomy | <i>An example of a raw long input file together with the taxonomy info</i> |
|---------------------|----------------------------------------------------------------------------|

---

**Description**

An example of a raw long input file together with the taxonomy info

**Usage**

```
data(profileWithTaxonomy)
```

**Format**

Dataframe

**Value**

A data frame with 20 rows and 12 variables:

- geneID Seed or ortholog group ID, e.g. "OG\_1017"
- ncbiID Taxon ID, e.g. "ncbi176299"
- orthoID Ortholog ID, e.g. "A.fabrum@176299@1582"
- var1 First additional variable
- var2 Second additional variable
- paralog Number of co-orthologs in the current taxon
- abbrName e.g. "ncbi176299"
- taxonID Taxon ID, e.g. "176299"
- fullName Full taxon name, e.g. "Agrobacterium fabrum str. C58"
- supertaxonID Supertaxon ID (only different than ncbiID in case working with higher taxonomy rank than input's)
- supertaxon Name of the corresponding supertaxon
- rank Rank of the supertaxon

---

|                    |                                   |
|--------------------|-----------------------------------|
| qualitativeColours | <i>Create qualitative colours</i> |
|--------------------|-----------------------------------|

---

**Description**

Create qualitative colours

**Usage**

```
qualitativeColours(n, light = FALSE)
```

**Arguments**

|       |                            |
|-------|----------------------------|
| n     | number of colors           |
| light | light colors TRUE or FALSE |

**Value**

list of n different colors

**Source**

Modified based on <https://gist.github.com/peterk87/6011397>

**Examples**

```
PhyloProfile::qualitativeColours(5)
```

---

|              |                                                        |
|--------------|--------------------------------------------------------|
| rankIndexing | <i>Indexing all available ranks (including norank)</i> |
|--------------|--------------------------------------------------------|

---

**Description**

Indexing all available ranks (including norank)

**Usage**

```
rankIndexing(rankListFile = NULL)
```

**Arguments**

rankListFile     Input file, where each row is a rank list of a taxon (see rankListFile in example)

**Value**

A dataframe containing a list of all possible ranks and their indexed values.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
rankListFile <- system.file(
  "extdata", "data/rankList.txt", package = "PhyloProfile", mustWork = TRUE
)
PhyloProfile::rankIndexing(rankListFile)
```

---

|          |                                                  |
|----------|--------------------------------------------------|
| rankList | <i>NCBI rank list for experimental data sets</i> |
|----------|--------------------------------------------------|

---

**Description**

Data frame, in which each row contains the complete taxonomy ranks from the lowest systematic level (strain/species) upto the taxonomy root for one taxon in the experimental data sets.

**Usage**

```
data(rankList)
```

**Format**

Dataframe

**Value**

A data frame with up to 41 columns and 95 rows corresponding to 95 taxa in the 2 experimental data sets

---

|               |                                                               |
|---------------|---------------------------------------------------------------|
| reduceProfile | <i>Reduce the filtered profile data into supertaxon level</i> |
|---------------|---------------------------------------------------------------|

---

**Description**

Reduce data of the processed phylogenetic profiles from input taxonomy rank into supertaxon level (e.g. from species to phylum)

**Usage**

```
reduceProfile(filteredProfile)
```

**Arguments**

`filteredProfile`  
dataframe contains the filtered profiles (see `?parseInfoProfile`, `?filterProfileData` and `?filteredProfile`)

**Value**

A reduced dataframe contains only profile data for the selected supertaxon rank. This dataframe contains only supertaxa and their value (mVar1 & mVar2) for each gene.

**Author(s)**

Vinh Tran [tran@bio.uni-frankfurt.de](mailto:tran@bio.uni-frankfurt.de)

**See Also**

[parseInfoProfile](#) for creating a full processed profile dataframe, [filterProfileData](#) for filter processed profile and [filteredProfile](#) for a demo filtered profile dataframe

**Examples**

```
data("filteredProfile", package="PhyloProfile")
reduceProfile(filteredProfile)
```

---

`resolveOverlapFeatures`*Modify domain dataframe to resolve overlapped domains/features*

---

**Description**

Modify domain dataframe to resolve overlapped domains/features

**Usage**

```
resolveOverlapFeatures(domainDf)
```

**Arguments**

domainDf            input domain dataframe

**Value**

Domain dataframe with modified feature names that join multiple domains of the same type that are not overlapped

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
# get domain data
seedID <- "101621at6656"
domainFile <- system.file(
  "extdata", "domainFiles/101621at6656.domains",
  package = "PhyloProfile", mustWork = TRUE
)
domainDf <- parseDomainInput(seedID, domainFile, "file")
# get seedDf and orthoDf
subDf <- domainDf[
  domainDf$seedID ==
  "101621at6656#101621at6656:AGRPL@224129@0:224129_0:001955:1",]
orthoDf <- subDf[subDf$orthoID == "101621at6656:DROME@7227@1:Q9VG04",]
# resolve overlapped features
PhyloProfile::resolveOverlapFeatures(orthoDf)
```

---

|                 |                             |
|-----------------|-----------------------------|
| runPhyloProfile | <i>Run PhyloProfile app</i> |
|-----------------|-----------------------------|

---

**Description**

Run PhyloProfile app

**Usage**

```
runPhyloProfile(configFile = NULL, host = NULL, port = NULL)
```

**Arguments**

|            |                                                                                                                   |
|------------|-------------------------------------------------------------------------------------------------------------------|
| configFile | Configuration file for specifying path to input files, taxonomy rank and reference taxon, and some other settings |
| host       | IP adress (e.g. host = "127.0.0.1")                                                                               |
| port       | Port (e.g. port = 8888)                                                                                           |

**Value**

A shiny application - GUI version of PhyloProfile

**Examples**

```
?runPhyloProfile
# runPhyloProfile()
```

---

|                      |                                                     |
|----------------------|-----------------------------------------------------|
| singleDomainPlotting | <i>Create architecure plot for a single protein</i> |
|----------------------|-----------------------------------------------------|

---

**Description**

Create architecure plot for a single protein

**Usage**

```
singleDomainPlotting(df, geneID, sep, labelSize, titleSize, minStart,
  maxEnd, colorPalette, showScore, showWeight, namePosition, firstDist,
  nameType, nameSize, segmentSize, nameColor, labelPos, font)
```

**Arguments**

|                           |                                                                                                                                                                                                                                                                                                                         |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>df</code>           | Domain dataframe for plotting containing the seed ID, ortholog ID, ortholog sequence length, feature names, start and end positions, feature weights (optional) and the status to determine if that feature is important for comparison the architecture between 2 proteins* (e.g. seed protein vs ortholog) (optional) |
| <code>geneID</code>       | ID of seed or orthologous protein                                                                                                                                                                                                                                                                                       |
| <code>sep</code>          | Separate indicator for title. Default = " "                                                                                                                                                                                                                                                                             |
| <code>labelSize</code>    | Label size. Default = 12                                                                                                                                                                                                                                                                                                |
| <code>titleSize</code>    | Title size. Default = 12                                                                                                                                                                                                                                                                                                |
| <code>minStart</code>     | The smallest start position of all domains                                                                                                                                                                                                                                                                              |
| <code>maxEnd</code>       | The highest stop position of all domains                                                                                                                                                                                                                                                                                |
| <code>colorPalette</code> | Color palette. Default = Paired"                                                                                                                                                                                                                                                                                        |
| <code>showScore</code>    | Show/hide E-values and Bit-scores. Default = NULL (hide)                                                                                                                                                                                                                                                                |
| <code>showWeight</code>   | Show/hide feature weights. Default = NULL (hide)                                                                                                                                                                                                                                                                        |
| <code>namePosition</code> | List of positions for domain names, choose from "plot", "legend" or "axis". Default: "plot"                                                                                                                                                                                                                             |
| <code>firstDist</code>    | Distance of the first domain to plot title. Default = 0.5                                                                                                                                                                                                                                                               |
| <code>nameType</code>     | Type of domain names, either "Texts" or "Labels" (default)                                                                                                                                                                                                                                                              |
| <code>nameSize</code>     | Size of domain names. Default = 3                                                                                                                                                                                                                                                                                       |
| <code>segmentSize</code>  | Height of domain segment. Default = 5                                                                                                                                                                                                                                                                                   |
| <code>nameColor</code>    | Color of domain names (for Texts only). Default = "black"                                                                                                                                                                                                                                                               |
| <code>labelPos</code>     | Position of domain names (for Labels only). Choose from "Above" (default), "Below" or "Inside" the domain bar                                                                                                                                                                                                           |
| <code>font</code>         | font of text. Default = Arial"                                                                                                                                                                                                                                                                                          |

**Value**

Domain plot of a single protein as a ggplot object.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[parseDomainInput](#)

**Examples**

```
seed <- "101621at6656"
ortho <- "101621at6656|AGRPL@224129@0|224129_0:001955|1"
ortho <- gsub("\\|", ":", ortho)
grepID <- paste(seed, "#", ortho, sep = "")
domainFile <- system.file(
```

```

      "extdata", "domainFiles/101621at6656.domains",
      package = "PhyloProfile", mustWork = TRUE
    )
    domainDf <- parseDomainInput(seed, domainFile, "file")
    domainDf$feature_id_mod <- domainDf$feature_id
    subdomainDf <- domainDf[grepl(grepID, domainDf$seedID), ]
    subdomainDf$feature <- as.character(subdomainDf$feature)
    orthoDf <- subdomainDf[subdomainDf$orthoID == ortho,]
    seedDf <- subdomainDf[subdomainDf$orthoID != ortho,]
    minStart <- min(subdomainDf$start)
    maxEnd <- max(c(subdomainDf$end, subdomainDf$length))
    # resolve overlapping domains
    seedDf <- PhyloProfile:::resolveOverlapFeatures(seedDf)
    orthoDf <- PhyloProfile:::resolveOverlapFeatures(orthoDf)
    # add feature colors
    featureColorDf <- PhyloProfile:::addFeatureColors(seedDf, orthoDf)
    seedDf <- featureColorDf[[1]]
    orthoDf <- featureColorDf[[2]]
    # do plot
    g <- PhyloProfile:::singleDomainPlotting(
      seedDf, seed, minStart = minStart, maxEnd = maxEnd, font = "sans"
    )
    grid::grid.draw(g)

```

---

sortDomains

---

Sort one domain dataframe based on the other domain dataframe

---

## Description

Sort domain dataframe of one protein (either seed or ortholog) based on the dataframe of the its paired protein, in order to bring the common domain feature in the same order which make it easy for comparing.

## Usage

```
sortDomains(seedDf, orthoDf)
```

## Arguments

|         |                          |
|---------|--------------------------|
| seedDf  | data of seed protein     |
| orthoDf | data of ortholog protein |

## Value

Dataframe contains sorted domain list.

## Author(s)

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
# get domain data
seedID <- "101621at6656"
domainFile <- system.file(
  "extdata", "domainFiles/101621at6656.domains",
  package = "PhyloProfile", mustWork = TRUE
)
domainDf <- parseDomainInput(seedID, domainFile, "file")
# get seedDf and orthoDf
subDf <- domainDf[
  domainDf$seedID ==
  "101621at6656#101621at6656:AGRPL@224129@0:224129_0:001955:1",]
orthoDf <- subDf[subDf$orthoID == "101621at6656:DROME@7227@1:Q9VG04",]
seedDf <- subDf[subDf$orthoID != "101621at6656:DROME@7227@1:Q9VG04",]
# sort
PhyloProfile::sortDomains(seedDf, orthoDf)
```

---

|                   |                                                                         |
|-------------------|-------------------------------------------------------------------------|
| sortDomainsByList | <i>Sort one domain dataframe based on list of ordered feature types</i> |
|-------------------|-------------------------------------------------------------------------|

---

**Description**

Sort domain dataframe of one protein based on a given list of ordered feature types

**Usage**

```
sortDomainsByList(domainDf = NULL, featureClassOrder = NULL)
```

**Arguments**

|                   |                                   |
|-------------------|-----------------------------------|
| domainDf          | domain dataframe                  |
| featureClassOrder | vector of ordered feature classes |

**Value**

Dataframe contains sorted domain list.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
# get domain data
seedID <- "101621at6656"
domainFile <- system.file(
  "extdata", "domainFiles/101621at6656.domains",
  package = "PhyloProfile", mustWork = TRUE
```

```
)
domainDf <- parseDomainInput(seedID, domainFile, "file")
# get seedDf and orthoDf
subDf <- domainDf[
  domainDf$seedID ==
  "101621at6656#101621at6656:AGRPL@224129@0:224129_0:001955:1",]
orthoDf <- subDf[subDf$orthoID == "101621at6656:DROME@7227@1:Q9VG04",]
featureClassOrder <- c("pfam", "smart", "tmhmm", "coils", "signalp", "seg",
  "flps")
# sort
PhyloProfile:::sortDomainsByList(orthoDf, featureClassOrder)
```

---

|               |                                                                            |
|---------------|----------------------------------------------------------------------------|
| sortInputTaxa | <i>Sort list of (super)taxa based on a selected reference (super)taxon</i> |
|---------------|----------------------------------------------------------------------------|

---

**Description**

Sort list of (super)taxa based on a selected reference (super)taxon

**Usage**

```
sortInputTaxa(taxonIDs = NULL, rankName, refTaxon = NULL,
  taxaTree = NULL, sortedTaxonList = NULL, taxDB = NULL)
```

**Arguments**

|                 |                                                                   |
|-----------------|-------------------------------------------------------------------|
| taxonIDs        | list of taxon IDs (e.g.: ncbi1234, ncbi9999, ...). Default = NULL |
| rankName        | working taxonomy rank (e.g. "species", "phylum",...)              |
| refTaxon        | selected reference taxon. Default = NULL                          |
| taxaTree        | taxonomy tree for the input taxa (optional). Default = NULL       |
| sortedTaxonList | list of sorted taxa (optional). Default = NULL                    |
| taxDB           | Path to the taxonomy DB files                                     |

**Value**

A taxonomy matrix for the input taxa ordered by the selected reference taxon. This matrix is sorted either based on the NCBI taxonomy info, or based on an user-defined taxonomy tree (if provided).

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[getNameList](#), [getTaxonomyMatrix](#), [createUnrootedTree](#), [sortTaxaFromTree](#), [getInputTaxaName](#), [getInputTaxaID](#), [createLongMatrix](#)

**Examples**

```
taxonIDs <- c(
  "ncbi10116", "ncbi123851", "ncbi3702", "ncbi13616", "ncbi9606"
)
sortInputTaxa(taxonIDs, "species", "Homo sapiens", NULL, NULL)
```

---

|                  |                                                                   |
|------------------|-------------------------------------------------------------------|
| sortTaxaFromTree | <i>Get sorted supertaxon list based on a rooted taxonomy tree</i> |
|------------------|-------------------------------------------------------------------|

---

**Description**

Get sorted supertaxon list based on a rooted taxonomy tree

**Usage**

```
sortTaxaFromTree(tree)
```

**Arguments**

tree                    an "phylo" object for a rooted taxonomy tree

**Value**

A list of sorted taxa obtained the input taxonomy tree.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[ppTaxonomyMatrix](#) for a demo taxonomy matrix data

**Examples**

```
data("ppTaxonomyMatrix", package = "PhyloProfile")
# create taxonomy tree rooted by ncbi10090
tree <- createUnrootedTree(ppTaxonomyMatrix)
rootedTree <- ape::root(tree, outgroup = "ncbi10090", resolve.root = TRUE)
# get taxon list sorted from tree
sortTaxaFromTree(rootedTree)
```

---

|           |                  |
|-----------|------------------|
| taxa2dist | <i>taxa2dist</i> |
|-----------|------------------|

---

**Description**

taxa2dist

**Usage**

```
taxa2dist(x, varstep = FALSE, check = TRUE, labels)
```

**Arguments**

|         |             |
|---------|-------------|
| x       | taxa matrix |
| varstep | var-step    |
| check   | check       |
| labels  | labels      |

**Value**

a distance matrix

**Author(s)**

function from taxize library

---

|                   |                                       |
|-------------------|---------------------------------------|
| taxonNamesReduced | <i>NCBI Taxonomy reduced data set</i> |
|-------------------|---------------------------------------|

---

**Description**

A list of NCBI taxonomy info (including taxon IDs, taxon names, their systematic taxonomy rank and IDs of their next rank - parent IDs) for 95 taxa in two experimental sets included in PhyloProfilData package.

**Usage**

```
data(taxonNamesReduced)
```

**Format**

Dataframe

**Value**

- A data frame with 4 columns:
- ncbiID e.g. "10090"
  - fullName e.g. "Mus musculus"
  - rank e.g. "species"
  - parentID e.g. "862507"

---

|                |                                                   |
|----------------|---------------------------------------------------|
| taxonomyMatrix | <i>Taxonomy matrix for experimental data sets</i> |
|----------------|---------------------------------------------------|

---

**Description**

Data frame containing the fully aligned taxonomy IDs of 95 taxa in the experimental data sets. By talking into account both the defined ranks (e.g. strain, This data is used for clustering and then creating a taxon tree. It is used also for cross-linking between different taxonomy ranks within a taxon.

**Usage**

data(taxonomyMatrix)

**Format**

Dataframe

**Value**

A data frame with up to 149 columns and 95 rows corresponding to 95 taxa in the 2 experimental data sets

---

|                      |                                                                         |
|----------------------|-------------------------------------------------------------------------|
| taxonomyTableCreator | <i>Align NCBI taxonomy IDs of list of taxa into a sorted rank list.</i> |
|----------------------|-------------------------------------------------------------------------|

---

**Description**

Align NCBI taxonomy IDs of list of taxa into a sorted rank list.

**Usage**

taxonomyTableCreator(idListFile = NULL, rankListFile = NULL)

**Arguments**

- |              |                                                                                     |
|--------------|-------------------------------------------------------------------------------------|
| idListFile   | a text file whose each row is a rank+ID list of a taxon (see idListFile in example) |
| rankListFile | a text file whose each row is a rank list of a taxon (see rankListFile in example)  |

**Value**

An aligned taxonomy dataframe which contains all the available taxonomy ranks from the id and rank list file. This dataframe can be used for creating a well resolved taxonomy tree (see ?createUnrootedTree) and sorting taxa based on a selected reference taxon (see ?sortInputTaxa).

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[rankIndexing](#), [createUnrootedTree](#), [sortInputTaxa](#)

**Examples**

```
idListFile <- system.file(
  "extdata", "data/idList.txt", package = "PhyloProfile", mustWork = TRUE
)
rankListFile <- system.file(
  "extdata", "data/rankList.txt", package = "PhyloProfile", mustWork = TRUE
)
taxonomyTableCreator(idListFile, rankListFile)
```

---

varDistTaxPlot

---

*Create variable distribution comparison plot*


---

**Description**

Create variable distribution plots between 2 groups of taxa for a selected gene.

**Usage**

```
varDistTaxPlot(data, plotParameters)
```

**Arguments**

|                |                                                                                                                                                                                                                                             |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| data           | dataframe for plotting. Last column indicates what type of taxon group (in- or out-group). The first (or first 2) column contains values of the variables. See ?dataVarDistTaxGroup                                                         |
| plotParameters | plot parameters, including size of x-axis, y-axis, legend and title; position of legend ("right", "bottom" or "none"); mean/median point; names of in-group and out-group; and plot title. NOTE: Leave blank or NULL to use default values. |

**Value**

Distribution plots as a grob (gtable) object. Use grid.draw to plot.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**See Also**

[dataVarDistTaxGroup](#)

**Examples**

```
data("mainLongRaw", package="PhyloProfile")
data <- mainLongRaw
inGroup <- c("ncbi9606", "ncbi10116")
variable <- colnames(data)[c(4, 5)]
plotDf <- dataVarDistTaxGroup(data, inGroup, "101621at6656", variable)
plotParameters <- list(
  "xSize" = 12,
  "ySize" = 12,
  "titleSize" = 15,
  "legendSize" = 12,
  "legendPosition" = "right",
  "mValue" = "mean",
  "inGroupName" = "In-group",
  "outGroupName" = "Out-group",
  "title" = "101621at6656"
)
g <- varDistTaxPlot(plotDf, plotParameters)
grid::grid.draw(g)
```

---

wideToLong

---

*Transform input file in wide matrix into long matrix format*


---

**Description**

Transform input file in wide matrix into long matrix format

**Usage**

```
wideToLong(inputFile = NULL)
```

**Arguments**

inputFile      input file in wide matrix format

**Value**

A data frame of input data in long-format containing seed gene IDs ( or orthologous group IDs), their orthologous proteins together with the corresponding taxonomy IDs and values of (up to) two additional variables.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
inputFile <- system.file(  
  "extdata", "test.main.wide", package = "PhyloProfile", mustWork = TRUE  
)  
wideToLong(inputFile)
```

---

xmlParser

*Parse orthoXML input file*

---

**Description**

Parse orthoXML input file

**Usage**

```
xmlParser(inputFile = NULL)
```

**Arguments**

inputFile      input file in xml format

**Value**

A data frame of input data in long-format containing seed gene IDs ( or orthologous group IDs), their orthologous proteins together with the corresponding taxonomy IDs and values of (up to) two additional variables.

**Author(s)**

Vinh Tran tran@bio.uni-frankfurt.de

**Examples**

```
inputFile <- system.file(  
  "extdata", "test.main.xml", package = "PhyloProfile", mustWork = TRUE  
)  
xmlParser(inputFile)
```

# Index

addDimRedTaxaColors, 4  
addFeatureColors, 5  
addRankDivisionPlot, 6  
  
calcPresSpec, 8, 78  
checkColorPalette, 9  
checkInputValidity, 9  
checkNewick, 10  
checkOmaID, 10, 11  
checkOverlapDomains, 11  
clusterDataDend, 12, 48  
compareMedianTaxonGroups, 13  
compareTaxonGroups, 14  
createArchiPlot, 15  
createDimRedPlotData, 5, 17, 80, 81  
createGeneAgePlot, 18  
createLongMatrix, 19, 27, 28, 39, 54, 78, 94  
createPercentageDistributionData, 20, 23  
createProfileFromOma, 21  
createUnrootedTree, 21, 94, 98  
createVarDistPlot, 22  
createVariableDistributionData, 23, 23, 25  
createVariableDistributionDataSubset, 23, 24  
  
dataCustomizedPlot, 25, 66–68  
dataFeatureTaxGroup, 26, 33  
dataMainPlot, 27, 66–68  
dataVarDistTaxGroup, 28, 99  
dimReduction, 5, 17, 29, 80, 81  
distributionTest, 30  
  
estimateGeneAge, 18, 30, 41  
  
fallbackUmap, 32  
fastaParser, 19, 32  
featureDistTaxPlot, 33  
filteredProfile, 34, 88  
  
filterProfileData, 26, 27, 35, 39, 88  
finalProcessedProfile, 37  
fromInputToProfile, 36, 38, 47  
fullProcessedProfile, 25, 31, 36, 40  
  
geneAgePlotDf, 18, 41  
generateSinglePlot, 42  
getAllDomainsOma, 43  
getAllFastaOma, 43  
getCommonAncestor, 44  
getCoreGene, 45  
getDataClustering, 13, 46, 49  
getDataForOneOma, 21, 43, 44, 47, 59  
getDendrogram, 48  
getDistanceMatrix, 13, 49  
getDomainFolder, 50, 77  
getFastaFromFasInput, 50  
getFastaFromFile, 51  
getFastaFromFolder, 52  
getIDsRank, 53  
getInputTaxaID, 10, 39, 54, 55, 94  
getInputTaxaName, 39, 54, 94  
getNameList, 31, 55, 55, 94  
getOmaDataForOneOrtholog, 56  
getOmaDomainFromURL, 56  
getOmaMembers, 57  
getQualColForVector, 58  
getSelectedFastaOma, 58  
getSelectedTaxonNames, 59  
getTaxHierarchy, 60  
getTaxonomyInfo, 61  
getTaxonomyMatrix, 7, 22, 31, 61, 94  
getTaxonomyRanks, 62  
gridArrangeSharedLegend, 63  
groupLabelDimRedData, 64  
  
hclust, 13  
heatmapPlotting, 7, 65, 68  
heatmapPlottingFast, 66  
highlightProfilePlot, 7, 68

id2name, [69](#)  
idList, [70](#)

joinPlotMergeLegends, [71](#)

linearizeArchitecture, [72](#)

mainLongRaw, [20](#), [23–25](#), [52](#), [54](#), [73](#), [78](#)  
mainTaxonomyRank, [74](#)  
modifyFeatureName, [74](#)

pairDomainPlotting, [16](#), [75](#)  
parseDomainInput, [16](#), [27](#), [76](#), [77](#), [91](#)  
parseInfoProfile, [25](#), [31](#), [36](#), [39](#), [46](#), [78](#), [88](#)  
performPCA, [79](#)  
performUmap, [79](#)  
plotDimRed, [80](#)  
plotDimRed3D, [81](#)  
ppTaxonomyMatrix, [22](#), [82](#), [95](#)  
ppTree, [10](#), [82](#)  
prepareDimRedData, [5](#), [17](#), [29](#), [64](#), [80](#), [81](#), [83](#)  
processNcbiTaxonomy, [84](#)  
processOrthoID, [85](#)  
profileWithTaxonomy, [8](#), [85](#)

qualitativeColours, [58](#), [86](#)

rankIndexing, [87](#), [98](#)  
rankList, [87](#)  
reduceProfile, [36](#), [39](#), [88](#)  
resolveOverlapFeatures, [89](#)  
runPhyloProfile, [90](#)

singleDomainPlotting, [16](#), [76](#), [90](#)  
sortDomains, [16](#), [76](#), [92](#)  
sortDomainsByList, [93](#)  
sortInputTaxa, [39](#), [78](#), [94](#), [98](#)  
sortTaxaFromTree, [94](#), [95](#)

taxa2dist, [22](#), [96](#)  
taxonNamesReduced, [96](#)  
taxonomyMatrix, [97](#)  
taxonomyTableCreator, [97](#)

varDistTaxPlot, [98](#)

wideToLong, [19](#), [99](#)

xmlParser, [19](#), [100](#)