

# Package ‘ROntoTools’

December 20, 2025

**Type** Package

**Title** R Onto-Tools suite

**Version** 2.39.0

**Author** Calin Voichita <calin@wayne.edu> and Sahar Ansari  
<saharansari@wayne.edu> and Sorin Draghici <sorin@advaitabio.com>

**Maintainer** Sorin Draghici <sorin@advaitabio.com>

**Description** Suite of tools for functional analysis.

**biocViews** NetworkAnalysis, Microarray, GraphsAndNetworks

**License** CC BY-NC-ND 4.0 + file LICENSE

**Depends** methods, graph, boot, KEGGREST, KEGGgraph, Rgraphviz

**Suggests** RUnit, BiocGenerics

**RoxygenNote** 5.0.1

**git\_url** <https://git.bioconductor.org/packages/ROntoTools>

**git\_branch** devel

**git\_last\_commit** 5a6e829

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.23

**Date/Publication** 2025-12-19

## Contents

|                             |   |
|-----------------------------|---|
| alpha1MR . . . . .          | 2 |
| alphaMLG . . . . .          | 3 |
| compute.fisher . . . . .    | 4 |
| compute.normalInv . . . . . | 5 |
| KEGGpathway2Graph . . . . . | 6 |
| keggPathwayGraphs . . . . . | 6 |
| keggPathwayNames . . . . .  | 7 |
| nodeWeights . . . . .       | 8 |
| pDis . . . . .              | 9 |

|                                         |           |
|-----------------------------------------|-----------|
| pDisPathway-class . . . . .             | 11        |
| pDisRes-class . . . . .                 | 12        |
| pe . . . . .                            | 13        |
| peEdgeRenderInfo . . . . .              | 15        |
| peNodeRenderInfo . . . . .              | 16        |
| pePathway-class . . . . .               | 18        |
| peRes-class . . . . .                   | 18        |
| plot,pePathway,missing-method . . . . . | 19        |
| plot,peRes,missing-method . . . . .     | 20        |
| setEdgeWeights . . . . .                | 21        |
| setNodeWeights . . . . .                | 22        |
| subGraphByNodeType . . . . .            | 23        |
| Summary,pDisRes-method . . . . .        | 24        |
| Summary,peRes-method . . . . .          | 24        |
| summary,pDisRes . . . . .               | 25        |
| summary,peRes . . . . .                 | 26        |
| <b>Index</b>                            | <b>28</b> |

---

|          |                              |
|----------|------------------------------|
| alpha1MR | <i>Compute alpha weights</i> |
|----------|------------------------------|

---

**Description**

Transform a vector of p-values into weights.

**Usage**

```
alpha1MR(pv, threshold = max(pv))
```

**Arguments**

- pv                      vector of p-values
- threshold              the threshold value that was used to select DE genes

**Details**

Computes a set of weights from p-values using the formula  $1-pv/threshold$ .

**Author(s)**

Calin Voichita and Sorin Draghici

**See Also**

[pe](#)

**Examples**

```
load(system.file("extdata/E-GEOD-21942.topTable.RData", package = "ROntoTools"))  
  
head(alpha1MR(top$adj.P.Val))
```

---

|          |                              |
|----------|------------------------------|
| alphaMLG | <i>Compute alpha weights</i> |
|----------|------------------------------|

---

**Description**

Transform a vector of p-values into weights.

**Usage**

```
alphaMLG(pv, threshold = max(pv))
```

**Arguments**

|           |                                                      |
|-----------|------------------------------------------------------|
| pv        | vector of p-values                                   |
| threshold | the threshold value that was used to select DE genes |

**Details**

Computes a set of weights from p-values using the formula  $-\log_{10}(pv/threshold)$ .

**Author(s)**

Calin Voichita and Sorin Draghici

**See Also**

[pe](#)

**Examples**

```
load(system.file("extdata/E-GEOD-21942.topTable.RData", package = "ROntoTools"))  
  
head(alphaMLG(top$adj.P.Val))
```

---

|                |                                                             |
|----------------|-------------------------------------------------------------|
| compute.fisher | <i>Combine independent p-values using the Fisher method</i> |
|----------------|-------------------------------------------------------------|

---

**Description**

Combine independent p-values using the Fisher method

**Usage**

```
compute.fisher(p, eps = 1e-06)
```

**Arguments**

|     |                                                                                 |
|-----|---------------------------------------------------------------------------------|
| p   | a vector of independent p-values                                                |
| eps | the minimal p-value considered (all p-values smaller will be set to this value) |

**Value**

the combined p-value

**Author(s)**

Calin Voichita and Sorin Draghici

**References**

Tarca AL., Draghici S., Khatri P., Hassan SS., Kim J., Kim CJ., Kusanovic JP., Romero R.: "A Signaling Pathway Impact Analysis for Microarray Experiments", 2008, Bioinformatics, 2009, 25(1):75-82.

**See Also**

[pe,compute.normalInv](#)

**Examples**

```
p <- c(.1, .01)
compute.fisher(p)
```

---

|                   |                                                                       |
|-------------------|-----------------------------------------------------------------------|
| compute.normalInv | <i>Combine independent p-values using the normal inversion method</i> |
|-------------------|-----------------------------------------------------------------------|

---

**Description**

Combine independent p-values using the normal inversion method

**Usage**

```
compute.normalInv(p, eps = 1e-06)
```

**Arguments**

|     |                                                                                 |
|-----|---------------------------------------------------------------------------------|
| p   | a vector of independent p-values                                                |
| eps | the minimal p-value considered (all p-values smaller will be set to this value) |

**Value**

the combined p-value

**Author(s)**

Calin Voichita and Sorin Draghici

**References**

Tarca AL., Draghici S., Romero R.: "A Mmore Specific Method To Combine Perturbation and Over-representation Evidence in Pathway Analysis", PSB 2010 poster.

**See Also**

[pe,compute.fisher](#)

**Examples**

```
p <- c(.1, .01)
compute.normalInv(p)
```

---

|                   |                                                             |
|-------------------|-------------------------------------------------------------|
| KEGGpathway2Graph | <i>Modified version of the same function from KEGGgraph</i> |
|-------------------|-------------------------------------------------------------|

---

**Description**

Modified version of the same function from KEGGgraph

**Usage**

```
KEGGpathway2Graph(pathway, genesOnly = TRUE, expandGenes = TRUE)
```

---

|                   |                                             |
|-------------------|---------------------------------------------|
| keggPathwayGraphs | <i>Download and parse KEGG pathway data</i> |
|-------------------|---------------------------------------------|

---

**Description**

Download and parse KEGG pathway data

**Usage**

```
keggPathwayGraphs(organism = "hsa", targRelTypes = c("GErel", "PCrel",
  "PPrel"), relPercThresh = 0.9, nodeOnlyGraphs = FALSE,
  updateCache = FALSE, verbose = TRUE)
```

**Arguments**

|                |                                                                                       |
|----------------|---------------------------------------------------------------------------------------|
| organism       | organism code as defined by KEGG                                                      |
| targRelTypes   | target relation types                                                                 |
| relPercThresh  | percentage of the number of relation types over all possible realtions in the pathway |
| nodeOnlyGraphs | allow graphs with no edges                                                            |
| updateCache    | re-download KEGG data                                                                 |
| verbose        | show progress of downloading and parsing                                              |

**Value**

A list of [graphNEL](#) objects encoding the pathway information.

**Author(s)**

Calin Voichita and Sorin Draghici

**See Also**

[keggPathwayNames](#)

## Examples

```
# The pathway cache provided as part of the pathway contains only the
# pathways that passed the default filtering. We recommend, re-downloading
# the pathways using the updateCache parameter
kpg <- keggPathwayGraphs("hsa")

# to update the pathway cache for human run:
# kpg <- keggPathwayGraphs("hsa", updateCache = TRUE)
# this is time consuming and depends on the available bandwidth.

head(names(kpg))

kpg[["path:hsa04110"]]
head(nodes(kpg[["path:hsa04110"]]))
head(edges(kpg[["path:hsa04110"]]))
```

---

|                  |                                   |
|------------------|-----------------------------------|
| keggPathwayNames | <i>Obtain KEGG pathway titles</i> |
|------------------|-----------------------------------|

---

## Description

Obtain KEGG pathway titles

## Usage

```
keggPathwayNames(organism = "hsa", updateCache = FALSE, verbose = TRUE)
```

## Arguments

|             |                                          |
|-------------|------------------------------------------|
| organism    | organism code as defined by KEGG         |
| updateCache | re-download KEGG data                    |
| verbose     | show progress of downloading and parsing |

## Value

A named vector of pathway titles. The names of the vector are the pathway KEGG IDs.

## Author(s)

Calin Voichita and Sorin Draghici

## See Also

[keggPathwayGraphs](#)

## Examples

```
kpn <- keggPathwayNames("hsa")

# to update the pathway cache for human run:
# kpn <- keggPathwayNames("hsa", updateCache = TRUE)
# this is time consuming and depends on the available bandwidth.

head(kpn)
```

---

|             |                                             |
|-------------|---------------------------------------------|
| nodeWeights | <i>Retrieve the node weights of a graph</i> |
|-------------|---------------------------------------------|

---

## Description

A generic function that returns the node weights of a graph. If index is specified, only the weights of the specified nodes are returned. The user can control which node attribute is interpreted as the weight.

## Usage

```
nodeWeights(object, index, ..., attr = "weight", default = 1)

## S4 method for signature 'graph,character'
nodeWeights(object, index, attr, default)

## S4 method for signature 'graph,numeric'
nodeWeights(object, index, attr, default)

## S4 method for signature 'graph,missing'
nodeWeights(object, index, attr, default)
```

## Arguments

|         |                                                                                                                                                                    |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| object  | A graph, any object that inherits the graph class.                                                                                                                 |
| index   | If supplied, a character or numeric vector of node names or indices.                                                                                               |
| ...     | Unused.                                                                                                                                                            |
| attr    | The name of the node attribute to use as a weight. You can view the list of defined node attributes and their default values using <code>nodeDataDefaults</code> . |
| default | The value to use if object has no node attribute named by the value of attr. The default is the value 1.                                                           |



## Details

The weights of all nodes identified by the `index` are returned. If `index` is not supplied, the weights of all nodes are returned.

By default, `nodeWeights` looks for a node attribute with name "weight" and, if found, uses these values to construct the node weight vector. You can make use of attributes stored under a different name by providing a value for the `attr` argument. For example, if `object` is a graph instance with a node attribute named "WTS", then the call `nodeWeights(object, attr="WTS")` will attempt to use those values.

If the graph instance does not have a node attribute with name given by the value of the `attr` argument, `default` will be used as the weight for all nodes. Note that if there is an attribute named by `attr`, then its default value will be used for nodes not specifically customized. See `nodeData` and `nodeDataDefaults` for more information.

## Value

A named vector with the node weights. The names of the vector are the names of the specified `index`, or all nodes if `index` was not provided.

## Author(s)

Calin Voichita and Sorin Draghici

## See Also

[nodes](#), [nodeData](#)

## Examples

```
library(graph)
V <- LETTERS[1:4]
g <- graphNEL(nodes = V, edgemode = "directed")
nodeWeights(g)
nodeWeights(g, "B")
nodeWeights(g, attr = "WT", default = 3)
```

---

pDis

*Primary dis-regulation: Pathway analysis approach based on the unexplained dis-regulation of genes*

---

## Description

Primary dis-regulation: Pathway analysis approach based on the unexplained dis-regulation of genes

**Usage**

```
pDis(x, graphs, ref = NULL, nboot = 2000, verbose = TRUE,
     cluster = NULL, seed = NULL)
```

**Arguments**

|         |                                                                                                                                                                                 |
|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x       | named vector of log fold changes for the differentially expressed genes; names(x) must use the same id's as ref and the nodes of the graphs                                     |
| graphs  | list of pathway graphs as objects of type graph (e.g., <a href="#">graphNEL</a> ); the graphs must be weighted graphs (i.e., have an attribute weight for both nodes and edges) |
| ref     | the reference vector for all genes in the analysis; if the reference is not provided or it is identical to names(x) a cut-off free analysis is performed                        |
| nboot   | number of bootstrap iterations                                                                                                                                                  |
| verbose | print progress output                                                                                                                                                           |
| cluster | a cluster object created by makeCluster for parallel computations                                                                                                               |
| seed    | an integer value passed to set.seed() during the bootstrap permutations                                                                                                         |

**Details**

See details in the cited articles.

**Value**

An object of class [pDisRes-class](#).

**Author(s)**

Calin Voichita, Sahar Ansari and Sorin Draghici

**References**

Voichita C., Donato M., Draghici S.: "Incorporating gene significance in the impact analysis of signaling pathways", IEEE Machine Learning and Applications (ICMLA), 2012 11th International Conference on, Vol. 1, p.126-131, 2012 Ansari, S., Voichita, C., Donato, M., Tagett, R., & Draghici, S. A Novel Pathway Analysis Approach Based on the Unexplained Disregulation of Genes.

**See Also**

[Summary](#), [keggPathwayGraphs](#), [setNodeWeights](#), [setEdgeWeights](#)

**Examples**

```
# load a multiple sclerosis study (public data available in Array Express
# ID: E-GEOD-21942)
# This file contains the top table, produced by the limma package with
# added gene information. All the probe sets with no gene associate to them,
# have been removed. Only the most significant probe set for each gene has been
# kept (the table is already ordered by p-value)
```

```

# The table contains the expression fold change and significance of each
# probe set in peripheral blood mononuclear cells (PBMC) from 12 MS patients
# and 15 controls.
load(system.file("extdata/E-GEOD-21942.topTable.RData", package = "ROntoTools"))
head(top)

# select differentially expressed genes at 1% and save their fold change in a
# vector fc and their p-values in a vector pv
fc <- top$logFC[top$adj.P.Val <= .01]
names(fc) <- top$entrez[top$adj.P.Val <= .01]

pv <- top$P.Value[top$adj.P.Val <= .01]
names(pv) <- top$entrez[top$adj.P.Val <= .01]

# alternatively use all the genes for the analysis
# NOT RUN:
# fc <- top$logFC
# names(fc) <- top$entrez

# pv <- top$P.Value
# names(pv) <- top$entrez

# get the reference
ref <- top$entrez

# load the set of pathways
kpg <- keggPathwayGraphs("hsa")

# set the beta information (see the cited documents for meaning of beta)
kpg <- setEdgeWeights(kpg)

# include the significance information in the analysis (see Voichita:2012
# for more information)
# set the alpha information based on the pv with one of the predefined methods
kpg <- setNodeWeights(kpg, weights = alphaMLG(pv), defaultWeight = 1)

# perform the pathway analysis
# in order to obtain accurate results the number of bootstraps, nboot, should
# be increase to a number like 2000
pDisRes <- pDis(fc, graphs = kpg, ref = ref, nboot = 100, verbose = TRUE)

# obtain summary of results
head(Summary(pDisRes))

```

---

pDisPathway-class

*Class that encodes the result of pDis analysis for a single pathway*


---

## Description

Class that encodes the result of pDis analysis for a single pathway

**Slots**

map: an object of type graph (e.g., [graphNEL](#)).  
 input: named vector of fold changes for genes on this pathway. The names of the genes are the original IDS used in the analysis  
 ref: vector of reference IDs on this pathway  
 boot: an object of class boot encoding the bootstrap information.  
 pDis: the gene primary dis-regulation for all genes on the pathway, as computed by primary dis-regulation.  
 asGS: pathway was considered as gene set

**Author(s)**

Calin Voichita, Sahar Ansari and Sorin Draghici

**See Also**

[pDis](#), [pDisRes-class](#)

---

pDisRes-class

*Primary dis-regulation (pDis) result class*

---

**Description**

This class is used to encode the results of the pathway analysis performed by the function [pDis](#).

**Details**

The slots input and ref record global information related to the whole analysis, while the pathways slot records the specific results as [pDisPathway-class](#) for each one of the pathways used in the analysis.

**Slots**

pathways: A list of [pDisPathway-class](#) objects.  
 input: named vector of fold changes used for the analysis. The names of the vector are the IDs originally used.  
 ref: character vector containing the IDs used as reference in the analysis.  
 cutOffFree: boolean value indicating if a cut-of-free analysis has been performed.

**Author(s)**

Calin Voichita, Sahar Ansari and Sorin Draghici

**See Also**

[pDis](#), [pDisPathway-class](#)

**Description**

Pathway-Express: Pathway analysis of signaling pathways

**Usage**

```
pe(x, graphs, ref = NULL, nboot = 2000, verbose = TRUE, cluster = NULL,
   seed = NULL)
```

**Arguments**

|         |                                                                                                                                                                                 |
|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| x       | named vector of log fold changes for the differentially expressed genes; names(x) must use the same id's as ref and the nodes of the graphs                                     |
| graphs  | list of pathway graphs as objects of type graph (e.g., <a href="#">graphNEL</a> ); the graphs must be weighted graphs (i.e., have an attribute weight for both nodes and edges) |
| ref     | the reference vector for all genes in the analysis; if the reference is not provided or it is identical to names(x) a cut-off free analysis is performed                        |
| nboot   | number of bootstrap iterations                                                                                                                                                  |
| verbose | print progress output                                                                                                                                                           |
| cluster | a cluster object created by makeCluster for parallel computations                                                                                                               |
| seed    | an integer value passed to set.seed() during the bootstrap permutations                                                                                                         |

**Details**

See details in the cited articles.

**Value**

An object of class [peRes-class](#).

**Author(s)**

Calin Voichita and Sorin Draghici

**References**

- Voichita C., Donato M., Draghici S.: "Incorporating gene significance in the impact analysis of signaling pathways", IEEE Machine Learning and Applications (ICMLA), 2012 11th International Conference on, Vol. 1, p.126-131, 2012
- Tarca AL., Draghici S., Khatri P., Hassan SS., Kim J., Kim CJ., Kusanovic JP., Romero R.: "A Signaling Pathway Impact Analysis for Microarray Experiments", 2008, Bioinformatics, 2009, 25(1):75-82.

Khatri P., Draghici S., Tarca AL., Hassan SS., Romero R.: "A system biology approach for the steady-state analysis of gene signaling networks". Progress in Pattern Recognition, Image Analysis and Applications, Lecture Notes in Computer Science. 4756:32-41, November 2007.

Draghici S., Khatri P., Tarca A.L., Amin K., Done A., Voichita C., Georgescu C., Romero R.: "A systems biology approach for pathway level analysis". Genome Research, 17, 2007.

### See Also

[Summary](#), [plot](#), [peRes](#), [missing-method](#), [keggPathwayGraphs](#), [setNodeWeights](#), [setEdgeWeights](#)

### Examples

```
# load a multiple sclerosis study (public data available in Array Express
# ID: E-GEOD-21942)
# This file contains the top table, produced by the limma package with
# added gene information. All the probe sets with no gene associate to them,
# have been removed. Only the most significant probe set for each gene has been
# kept (the table is already ordered by p-value)
# The table contains the expression fold change and significance of each
# probe set in peripheral blood mononuclear cells (PBMC) from 12 MS patients
# and 15 controls.
load(system.file("extdata/E-GEOD-21942.topTable.RData", package = "ROntoTools"))
head(top)

# select differentially expressed genes at 1% and save their fold change in a
# vector fc and their p-values in a vector pv
fc <- top$logFC[top$adj.P.Val <= .01]
names(fc) <- top$entrez[top$adj.P.Val <= .01]

pv <- top$P.Value[top$adj.P.Val <= .01]
names(pv) <- top$entrez[top$adj.P.Val <= .01]

# alternatively use all the genes for the analysis
# NOT RUN:
# fc <- top$logFC
# names(fc) <- top$entrez

# pv <- top$P.Value
# names(pv) <- top$entrez

# get the reference
ref <- top$entrez

# load the set of pathways
kpg <- keggPathwayGraphs("hsa")

# set the beta information (see the cited documents for meaning of beta)
kpg <- setEdgeWeights(kpg)

# include the significance information in the analysis (see Voichita:2012
# for more information)
# set the alpha information based on the pv with one of the predefined methods
```

```

kpg <- setNodeWeights(kpg, weights = alphaMLG(pv), defaultWeight = 1)

# perform the pathway analysis
# in order to obtain accurate results the number of bootstraps, nboot, should
# be increase to a number like 2000
peRes <- pe(fc, graphs = kpg, ref = ref, nboot = 100, verbose = TRUE)

# obtain summary of results
head(Summary(peRes))

```

---

|                  |                                                                      |
|------------------|----------------------------------------------------------------------|
| peEdgeRenderInfo | <i>Extract edge render information from a pePathway-class object</i> |
|------------------|----------------------------------------------------------------------|

---

## Description

Extract edge render information from a pePathway-class object

## Usage

```

peEdgeRenderInfo(x, pos.col = "black", pos.lty = "solid", pos.ah = "vee",
  neg.col = "black", neg.lty = "dashed", neg.ah = "tee",
  zero.col = "lightgray", zero.lty = "dotted", zero.ah = "none")

```

## Arguments

|          |                                                    |
|----------|----------------------------------------------------|
| x        | an object of class <a href="#">pePathway-class</a> |
| pos.col  | color of the edges with possitive weight           |
| pos.lty  | line type of the edges with possitive weight       |
| pos.ah   | arrow head of the edges with possitive weight      |
| neg.col  | color of the edges with negative weight            |
| neg.lty  | line type of the edges with negative weight        |
| neg.ah   | arrow head of the edges with negative weight       |
| zero.col | color of the edges with zero weight                |
| zero.lty | color of the edges with zero weight                |
| zero.ah  | color of the edges with zero weight                |

## Value

a named list as expected by [edgeRenderInfo](#)

## Author(s)

Calin Voichita and Sorin Draghici

**See Also**[edgeRenderInfo,par](#)**Examples**

```
# load experiment
load(system.file("extdata/E-GEOD-21942.topTable.RData", package = "ROntoTools"))
fc <- top$logFC[top$adj.P.Val <= .01]
names(fc) <- top$entrez[top$adj.P.Val <= .01]
ref <- top$entrez

# load the set of pathways
kpg <- keggPathwayGraphs("hsa")
kpg <- setEdgeWeights(kpg)
kpg <- setNodeWeights(kpg, defaultWeight = 1)

# perform the pathway analysis
peRes <- pe(fc, graphs = kpg, ref = ref, nboot = 100, verbose = TRUE)

p <- peRes@pathways[[50]]
g <- layoutGraph(p@map, layoutType = "dot")
graphRenderInfo(g) <- list(fixedsize = FALSE)
edgeRenderInfo(g) <- peEdgeRenderInfo(p)
nodeRenderInfo(g) <- peNodeRenderInfo(p)
# notice the different type of edges in the graph (solid/dashed/dotted)
renderGraph(g)
```

peNodeRenderInfo

*Extract node render information from a pePathway-class object***Description**

Extract node render information from a pePathway-class object

**Usage**

```
peNodeRenderInfo(x, y = "Pert", input.shape = "box",
  default.shape = "ellipse", pos.col = "red", neg.col = "blue",
  zero.col = "white")
```

**Arguments**

|               |                                                                                                               |
|---------------|---------------------------------------------------------------------------------------------------------------|
| x             | an object of class <a href="#">pePathway-class</a>                                                            |
| y             | a string representing the factor to be represented (Pert, Acc or input; see <a href="#">pePathway-class</a> ) |
| input.shape   | shape of nodes that have measured expression change                                                           |
| default.shape | shape of all other nodes                                                                                      |



|          |                                                |
|----------|------------------------------------------------|
| pos.col  | color of nodes with a positive y factor        |
| neg.col  | color of nodes with a negative y factor        |
| zero.col | color of nodes with the y factor equal to zero |

**Value**

a named list as expected by [nodeRenderInfo](#)

**Author(s)**

Calin Voichita and Sorin Draghici

**See Also**

[nodeRenderInfo](#), [par](#)

**Examples**

```
# load experiment
load(system.file("extdata/E-GEOD-21942.topTable.RData", package = "R0ntoTools"))
fc <- top$logFC[top$adj.P.Val <= .01]
names(fc) <- top$entrez[top$adj.P.Val <= .01]
ref <- top$entrez

# load the set of pathways
kpg <- keggPathwayGraphs("hsa")
kpg <- setEdgeWeights(kpg)
kpg <- setNodeWeights(kpg, defaultWeight = 1)

# perform the pathway analysis
peRes <- pe(fc, graphs = kpg, ref = ref, nboot = 100, verbose = TRUE)

p <- peRes@pathways[[50]]
g <- layoutGraph(p@map, layoutType = "dot")
graphRenderInfo(g) <- list(fixedsize = FALSE)
edgeRenderInfo(g) <- peEdgeRenderInfo(p)
nodeRenderInfo(g) <- peNodeRenderInfo(p)
# notice the different type of nodes in the graph (box/circle)
# the color of each node represents the perturbation (red = positive, blue = negative)
# the shade represents the strength of the perturbation
renderGraph(g)

nodeRenderInfo(g) <- peNodeRenderInfo(p, "Acc")
# now, the color of each node represents the accumulation (red = positive, blue = negative)
# notice that square nodes with no parents have no accumulation
renderGraph(g)
```

---

|                 |                                                                              |
|-----------------|------------------------------------------------------------------------------|
| pePathway-class | <i>Class that encodes the result of Pathway-Express for a single pathway</i> |
|-----------------|------------------------------------------------------------------------------|

---

### Description

Class that encodes the result of Pathway-Express for a single pathway

### Slots

**map:** an object of type graph (e.g., [graphNEL](#)).  
**input:** named vector of fold changes for genes on this pathway. The names of the genes are the original IDS used in the analysis  
**ref:** vector of reference IDs on this pathway  
**boot:** an object of class boot encoding the bootstrap information.  
**Pert:** the gene perturbation factors for all genes on the pathway, as computed by Pathway-Express.  
**Acc:** the gene accumulations for all genes on the pathway, as computed by Pathway-Express.  
**asGS:** pathway was considered as gene set

### Author(s)

Calin Voichita and Sorin Draghici

### See Also

[pe](#), [peRes-class](#)

---

|             |                                     |
|-------------|-------------------------------------|
| peRes-class | <i>Pathway-Express result class</i> |
|-------------|-------------------------------------|

---

### Description

This class is used to encode the results of the pathway analysis performed by the function [pe](#).

### Details

The slots **input** and **ref** record global information related to the whole analysis, while the **pathways** slot records the specific results as [pePathway-class](#) for each one of the pathways used in the analysis.

### Slots

**pathways:** A list of [pePathway-class](#) objects.  
**input:** named vector of fold changes used for the analysis. The names of the vector are the IDs originally used.  
**ref:** character vector containing the IDs used as reference in the analysis.  
**cutOffFree:** boolean value indicating if a cut-of-free analysis has been performed.

**Author(s)**

Calin Voichita and Sorin Draghici

**See Also**[pe](#), [pePathway-class](#)

---

plot,pePathway,missing-method*Plot pathway level statistics*

---

**Description**

Display graphical representation of pathway level statistic like: i) two way comparison between the measured expression change and one of the factors computed by Pathway-Express ([pe](#)) or ii) the bootstrap statistics of the same factors.

**Usage**

```
## S4 method for signature 'pePathway,missing'
plot(x, y, ..., type = "two.way", eps = 1e-06)

## S4 method for signature 'pePathway,character'
plot(x, y, main = "", ..., type = "two.way",
     eps = 1e-06)
```

**Arguments**

|      |                                                                                                            |
|------|------------------------------------------------------------------------------------------------------------|
| x    | an object of type <a href="#">pePathway-class</a>                                                          |
| y    | if provided, the factor to be plotted (either Acc (default) or Pert; see <a href="#">pePathway-class</a> ) |
| ...  | Arguments to be passed to methods, such as <a href="#">par</a>                                             |
| type | type of plot (either two.way (default) or boot)                                                            |
| eps  | any value smaller than this will be plotted as 0                                                           |
| main | title                                                                                                      |

**Author(s)**

Calin Voichita and Sorin Draghici

**See Also**[pe](#), [plot](#), [peRes](#), [missing-method](#), [peNodeRenderInfo](#), [peEdgeRenderInfo](#)

## Examples

```
# load experiment
load(system.file("extdata/E-GEOD-21942.topTable.RData", package = "ROntoTools"))
fc <- top$logFC[top$adj.P.Val <= .01]
names(fc) <- top$entrez[top$adj.P.Val <= .01]
ref <- top$entrez

# load the set of pathways
kpg <- keggPathwayGraphs("hsa")
kpg <- setEdgeWeights(kpg)
kpg <- setNodeWeights(kpg, defaultWeight = 1)

# perform the pathway analysis (for more accurate results use nboot = 2000)
peRes <- pe(fc, graphs = kpg, ref = ref, nboot = 100, verbose = TRUE)

plot(peRes@pathways[[50]])

plot(peRes@pathways[[50]], "Pert", main = "Perturbation factor")

plot(peRes@pathways[[50]], type = "boot")

plot(peRes@pathways[[50]], "Pert", type = "boot", main = "Perturbation factor")
```

---

plot,peRes,missing-method

*Plot Pathway-Express result*

---

## Description

Display a two-way plot using two of the p-values from the Pathway-Express analysis.

## Usage

```
## S4 method for signature 'peRes,missing'
plot(x, y, ..., comb.pv.func = compute.fisher,
      adjust.method = "fdr", threshold = 0.05, eps = 1e-06)

## S4 method for signature 'peRes,character'
plot(x, y, ..., comb.pv.func = compute.fisher,
      adjust.method = "fdr", threshold = 0.05, eps = 1e-06)
```

## Arguments

|     |                                                                                              |
|-----|----------------------------------------------------------------------------------------------|
| x   | an object of type <a href="#">peRes-class</a>                                                |
| y   | vector of two p-values names to be combined using comb.pv.func (default: c("pAcc", "pORA")). |
| ... | Arguments to be passed to methods, such as <a href="#">par</a> .                             |

comb.pv.func      the function to combine the p-values - takes as input a vector of p-values and returns the combined p-value (default: [compute.fisher](#)).

adjust.method    the name of the method to adjust the p-value (see [p.adjust](#))

threshold        corrected p-value threshold

eps               any value smaller than this will be considered as eps (default: 1e-6).

**Author(s)**

Calin Voichita and Sorin Draghici

**See Also**

[pe](#), [summary.peRes](#), [plot](#), [pePathway](#), [missing-method](#)

**Examples**

```
# load experiment
load(system.file("extdata/E-GEOD-21942.topTable.RData", package = "ROntoTools"))
fc <- top$logFC[top$adj.P.Val <= .01]
names(fc) <- top$entrez[top$adj.P.Val <= .01]
ref <- top$entrez

# load the set of pathways
kpg <- keggPathwayGraphs("hsa")
kpg <- setEdgeWeights(kpg)
kpg <- setNodeWeights(kpg, defaultWeight = 1)

# perform the pathway analysis (for more accurate results use nboot = 2000)
peRes <- pe(fc, graphs = kpg, ref = ref, nboot = 100, verbose = TRUE)

plot(peRes)

plot(peRes, c("pPert", "pORA"), comb.pv.func = compute.normalInv, threshold = .01)
```

---

|                |                                            |
|----------------|--------------------------------------------|
| setEdgeWeights | <i>Set gene weights based on edge type</i> |
|----------------|--------------------------------------------|

---

**Description**

setEdgeWeights

**Usage**

```
setEdgeWeights(graphList, edgeTypeAttr = "subtype",
  edgeWeightByType = list(activation = 1, inhibition = -1, expression = 1,
    repression = -1), defaultWeight = 0, combineWeights = sum,
  nodeOnlyGraphs = FALSE)
```

Arguments

- graphList      a list of graphNEL objects
- edgeTypeAttr   edge attribute to be considered as the edge type. If the edge has multiple types, the edge type attribute is considered as a comma separated list of types
- edgeWeightByType   named list of weights, where the names of the list are the edge type (values of the attribute defined by edgeTypeAttr)
- defaultWeight   default value for an edge with a type not defined in edgeWeightByType
- combineWeights   for the edges with multiple types, the function to be applied on the vector of weights
- nodeOnlyGraphs   boolean value marking if graphs with no edges should be returned or not; note that graphs with all edge weights equal to 0 are considered node only graphs

Value

The graphList with the edge weights set.

Author(s)

Calin Voichita and Sorin Draghici

Examples

```
# load the set of pathways
kpg <- keggPathwayGraphs("hsa")

kpg <- setEdgeWeights(kpg)

edgeWeights(kpg[["path:hsa04110"]])
```

---

|                |                         |
|----------------|-------------------------|
| setNodeWeights | <i>Set node weights</i> |
|----------------|-------------------------|

---

Description

Set node weights

Usage

```
setNodeWeights(graphList, weights = NULL, defaultWeight = 1)
```

**Arguments**

|               |                                                                                                                                                                                                                                  |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| graphList     | a list of graph (e.g., <a href="#">graphNEL</a> ) objects                                                                                                                                                                        |
| weights       | named vector or matrix; if vector, the node is going to have the same weight in all graphs it appears; if matrix, the rows represent nodes and columns represent graphs and the node will have different weights in each pathway |
| defaultWeight | the default weight for all nodes not set by the parameter weights                                                                                                                                                                |

**Value**

The graphList with the node weights set.

**Author(s)**

Calin Voichita and Sorin Draghici

**Examples**

```
# load the set of pathways
kpg <- keggPathwayGraphs("hsa")

kpg <- setNodeWeights(kpg)

nodeWeights(kpg[["path:hsa04110"]])
```

---

|                    |                                                             |
|--------------------|-------------------------------------------------------------|
| subGraphByNodeType | <i>Modified version of the same function from KEGGgraph</i> |
|--------------------|-------------------------------------------------------------|

---

**Description**

Modified version of the same function from KEGGgraph

**Usage**

```
subGraphByNodeType(graph, type = "gene")
```

---

Summary,pDisRes-method

*Summarize the results of a Pathway-Express analysis*

---

### Description

Summarize the results of a Pathway-Express analysis

### Usage

```
## S4 method for signature 'pDisRes'  
Summary(x, ..., na.rm = FALSE)
```

### Arguments

|       |                                                                                   |
|-------|-----------------------------------------------------------------------------------|
| x     | Primary dis-regulation analysis result object obtained using <a href="#">pDis</a> |
| ...   | see <a href="#">summary.pDisRes</a>                                               |
| na.rm | ignored                                                                           |

---

Summary,peRes-method    *Summarize the results of a Pathway-Express analysis*

---

### Description

Summarize the results of a Pathway-Express analysis

### Usage

```
## S4 method for signature 'peRes'  
Summary(x, ..., na.rm = FALSE)
```

### Arguments

|       |                                                                          |
|-------|--------------------------------------------------------------------------|
| x     | Pathway-Express analysis result object obtained using <a href="#">pe</a> |
| ...   | see <a href="#">summary.peRes</a>                                        |
| na.rm | ignored                                                                  |



---

|                 |                                                                          |
|-----------------|--------------------------------------------------------------------------|
| summary.pDisRes | <i>Summarize the results of a primary dis-regulation (pDis) analysis</i> |
|-----------------|--------------------------------------------------------------------------|

---

## Description

Summarize the results of a primary dis-regulation (pDis) analysis

## Usage

```
summary.pDisRes(object, ..., pathNames = NULL, totalpDis = TRUE, normalize = TRUE,
  ppDis = TRUE, pORA = TRUE,
  comb.pv = c("ppDis", "pORA"), comb.pv.func = compute.fisher,
  order.by = "pComb", adjust.method = "fdr")
```

## Arguments

|               |                                                                                                                                              |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| object        | pDis analysis result object obtained using <a href="#">pDis</a>                                                                              |
| ...           | ignored                                                                                                                                      |
| pathNames     | named vector of pathway names; the names of the vector are the IDs of the pathways                                                           |
| totalpDis     | boolean value indicating if the total primary dis-regulation should be computed                                                              |
| normalize     | boolean value indicating if normalization with regards to the bootstrap simulations should be performed on totalpDis                         |
| ppDis         | boolean value indicating if the significance of the total primary dis-regulation in regards to the bootstrap permutations should be computed |
| pORA          | boolean value indicating if the over-representation p-value should be computed                                                               |
| comb.pv       | vector of the p-value names to be combine (any of the above p-values)                                                                        |
| comb.pv.func  | the function to combine the p-values; takes as input a vector of p-values and returns the combined p-value                                   |
| order.by      | the name of the p-value that is used to order the results                                                                                    |
| adjust.method | the name of the method to adjust the p-value (see <a href="#">p.adjust</a> )                                                                 |

## See Also

[pDis](#)

## Examples

```
# load experiment
load(system.file("extdata/E-GEOD-21942.topTable.RData", package = "ROntoTools"))
fc <- top$logFC[top$adj.P.Val <= .01]
names(fc) <- top$entrez[top$adj.P.Val <= .01]
ref <- top$entrez

# load the set of pathways
```

```

kpg <- keggPathwayGraphs("hsa")
kpg <- setEdgeWeights(kpg)
kpg <- setNodeWeights(kpg, defaultWeight = 1)

# perform the pathway analysis
pDisRes <- pDis(fc, graphs = kpg, ref = ref, nboot = 100, verbose = TRUE)

# obtain summary of results
head(summary(pDisRes))

kpn <- keggPathwayNames("hsa")

head(summary(pDisRes))

head(summary(pDisRes, pathNames = kpn, totalpDis = FALSE,
              pORA = FALSE, comb.pv = NULL, order.by = "pDis"))

```

summary.peRes

*Summarize the results of a Pathway-Express analysis***Description**

Summarize the results of a Pathway-Express analysis

**Usage**

```

summary.peRes(object, ..., pathNames = NULL, totalAcc = TRUE, totalPert = TRUE, normalize = TRUE,
               pPert = TRUE, pAcc = TRUE, pORA = TRUE,
               comb.pv = c("pPert", "pORA"), comb.pv.func = compute.fisher,
               order.by = "pComb", adjust.method = "fdr")

```

**Arguments**

|           |                                                                                                                                    |
|-----------|------------------------------------------------------------------------------------------------------------------------------------|
| object    | Pathways-Express result object obtained using <a href="#">pe</a>                                                                   |
| ...       | ignored                                                                                                                            |
| pathNames | named vector of pathway names; the names of the vector are the IDs of the pathways                                                 |
| totalAcc  | boolean value indicating if the total accumulation should be computed                                                              |
| totalPert | boolean value indicating if the total perturbation should be computed                                                              |
| normalize | boolean value indicating if normalization with regards to the bootstrap simulations should be performed on totalAcc and totalPert  |
| pPert     | boolean value indicating if the significance of the total perturbation in regards to the bootstrap permutations should be computed |
| pAcc      | boolean value indicating if the significance of the total accumulation in regards to the bootstrap permutations should be computed |

|               |                                                                                                            |
|---------------|------------------------------------------------------------------------------------------------------------|
| pORA          | boolean value indicating if the over-representation p-value should be computed                             |
| comb.pv       | vector of the p-value names to be combine (any of the above p-values)                                      |
| comb.pv.func  | the function to combine the p-values; takes as input a vector of p-values and returns the combined p-value |
| order.by      | the name of the p-value that is used to order the results                                                  |
| adjust.method | the name of the method to adjust the p-value (see <a href="#">p.adjust</a> )                               |

### See Also

[pe](#)

### Examples

```
# load experiment
load(system.file("extdata/E-GEOD-21942.topTable.RData", package = "ROntoTools"))
fc <- top$logFC[top$adj.P.Val <= .01]
names(fc) <- top$entrez[top$adj.P.Val <= .01]
ref <- top$entrez

# load the set of pathways
kpg <- keggPathwayGraphs("hsa")
kpg <- setEdgeWeights(kpg)
kpg <- setNodeWeights(kpg, defaultWeight = 1)

# perform the pathway analysis
peRes <- pe(fc, graphs = kpg, ref = ref, nboot = 100, verbose = TRUE)

# obtain summary of results
head(summary(peRes))

kpn <- keggPathwayNames("hsa")

head(summary(peRes))

head(summary(peRes, pathNames = kpn, totalAcc = FALSE, totalPert = FALSE,
              pAcc = FALSE, pORA = FALSE, comb.pv = NULL, order.by = "pPert"))
```

# Index

## \* **internal**

- KEGGpathway2Graph, [6](#)
- subGraphByNodeType, [23](#)
- alpha1MR, [2](#)
- alphaMLG, [3](#)
- compute.fisher, [4](#), [5](#), [21](#)
- compute.normalInv, [4](#), [5](#)
- edgeRenderInfo, [15](#), [16](#)
- graphNEL, [6](#), [10](#), [12](#), [13](#), [18](#), [22](#), [23](#)
- KEGGpathway2Graph, [6](#)
- keggPathwayGraphs, [6](#), [7](#), [10](#), [14](#)
- keggPathwayNames, [6](#), [7](#)
- nodeData, [9](#)
- nodeRenderInfo, [17](#)
- nodes, [9](#)
- nodeWeights, [8](#)
- nodeWeights, graph, character-method  
(nodeWeights), [8](#)
- nodeWeights, graph, missing-method  
(nodeWeights), [8](#)
- nodeWeights, graph, numeric-method  
(nodeWeights), [8](#)
- p.adjust, [21](#), [25](#), [27](#)
- par, [16](#), [17](#), [19](#), [20](#)
- pDis, [9](#), [12](#), [24](#), [25](#)
- pDisPathway-class, [11](#)
- pDisRes-class, [12](#)
- pe, [2–5](#), [13](#), [18](#), [19](#), [21](#), [24](#), [26](#), [27](#)
- peEdgeRenderInfo, [15](#), [19](#)
- peNodeRenderInfo, [16](#), [19](#)
- pePathway-class, [18](#)
- peRes-class, [18](#)
- plot, pePathway, character-method  
(plot, pePathway, missing-method),  
[19](#)
- plot, pePathway, missing-method, [19](#)
- plot, peRes, character-method  
(plot, peRes, missing-method), [20](#)
- plot, peRes, missing-method, [20](#)
- setEdgeWeights, [10](#), [14](#), [21](#)
- setNodeWeights, [10](#), [14](#), [22](#)
- subGraphByNodeType, [23](#)
- Summary, [10](#), [14](#)
- Summary, pDisRes-method, [24](#)
- Summary, peRes-method, [24](#)
- summary.pDisRes, [24](#), [25](#)
- summary.peRes, [21](#), [24](#), [26](#)