

Package ‘Prostar’

December 16, 2025

Type Package

Title Provides a GUI for DAPAR

Version 1.42.0

Date 2024-01-17

Description This package provides a GUI interface for the DAPAR package. The package Prostar (Proteomics statistical analysis with R) is a Bioconductor distributed R package which provides all the necessary functions to analyze quantitative data from label-free proteomics experiments. Contrarily to most other similar R packages, it is endowed with rich and user-friendly graphical interfaces, so that no programming skill is required.

biocViews Proteomics, MassSpectrometry, Normalization, Preprocessing, Software, GUI

License Artistic-2.0

Depends R (>= 4.4.0)

Suggests BiocStyle, BiocManager, testthat, knitr

Imports DAPAR (>= 1.35.1), DAPARdata (>= 1.30.0), rhandsontable, data.table, shiny, shinyBS, shinyAce, highcharter, htmlwidgets, webshot, shinythemes, later, shinycssloaders, future, promises, shinyjs, tibble, ggplot2, gplots, shinyjs, vioplot, Biobase, DT, R.utils, RColorBrewer, XML, colourpicker, gtools, markdown, rclipboard, sass, shinyTree, shinyWidgets

NeedsCompilation no

RoxygenNote 7.3.2

Encoding UTF-8

URL <http://www.prostar-proteomics.org/>

BugReports <https://github.com/edyp-lab/Prostar/issues>

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/Prostar>

git_branch RELEASE_3_22

git_last_commit d48b236

git_last_commit_date 2025-10-29

Repository Bioconductor 3.22

Date/Publication 2025-12-15
Author Thomas Burger [aut],
 Florence Combes [aut],
 Samuel Wieczorek [cre, aut]
Maintainer Samuel Wieczorek <samuel.wieczorek@cea.fr>

Contents

BuildColorStyles	2
getDataForExprs	2
Prostar	3

Index	4
--------------	----------

BuildColorStyles	xxx
------------------	-----

Description

xxx

Usage

BuildColorStyles(obj)

Arguments

obj	xx
-----	----

getDataForExprs	xxx
-----------------	-----

Description

xxx

Usage

getDataForExprs(obj, digits = NULL)

Arguments

obj	xx
digits	xxx

Prostar	<i>Prostar</i>
---------	----------------

Description

Prostar

Usage

Prostar()

Value

A new window in the default internet browser

Author(s)

Samuel Wieczorek

Examples

```
## Not run:  
  Prostar()  
  
## End(Not run)
```

Index

BuildColorStyles, [2](#)

getDataForExprs, [2](#)

Prostar, [3](#)